









Hydraulic Hoses, Fittings and Equipment

Catalogue



Parker

ENGINEERING YOUR SUCCESS.

Detailed Table of Contents

Introduction	2 – 31

Technical Handbook

Crimp Systems You Can Trust	A-2 – A-5
Hoses and Fittings Terminology – The basics	Aa-2 – Aa-8
Safe Hose Assemblies – Working Steps	Aa-9 – Aa-19
How to Order (Part Number Description)	Aa-20 – Aa-21
Identifying Fitting Types	Aa-22 – Aa-33
Storage – Hoses and Hose Fittings	Aa-34 – Aa-35
Safety First! – Parker Safety Guide	Aa-36 – Aa-41
Technical Data	Ab-2 – Ab-34

Low Pressure Push-Lok

Push-Lok Hoses	B1a-1 – B1a-9
Fittings 82 series	B1b-1 – B1b-18
Assembly Instructions / Assembly Tools	B1b-19

Low Pressure Transportation + Hydraulic

Low Pressure Hoses	B2a-1 – B2a-10
Fittings 26 series	B2b-1 – B2b-9

Medium Pressure

GlobalCore Parkrimp No-Skive Hoses	Caa-1 – Caa-6
Parkrimp No-Skive Hoses	Cab-1 – Cab-31
Fittings 43 series	Cb-1 – Cb-17
Fittings 46 and 48 series	Cc-1 – Cc-50
Fittings 2piece 48 series	Cd-1 – Cd-2
Fittings 2piece IF series	Ce-1 – Ce-3

High Pressure


GlobalCore Parkrimp No-Skive Hoses	Daa-1 – Daa-7
Parkrimp No-Skive and ParLock Skive Hoses	Dab-1 – Dab-28
Fittings 70 series	Db-1 – Db-20
Fittings 73 series	Dc-1 – Dc-19
Fittings 77 series	Dd-1 – Dd-27
Fittings VS series	De-1 – De-16
Fittings V4/V6 series	Df-1 – Df-27
Fittings V5 series	Dg-1 – Dg-3
Fittings WB series	Dh-1 – Dh-4

Machines, Tooling, Accessories

Machines	Ea-1 – Ea-29
Accessories	Eb-1 – Eb-24
Assembly Instructions	Ec-1 – Ec-2
Your Crimp Source online	Ed-1

SOLVING THE WORLD'S GREATEST ENGINEERING CHALLENGES.

Our focus on solving some of the world's greatest engineering challenges sparks our passion for innovation and secures our future growth.



The development of more efficient energy sources; the desire to produce and distribute clean water; new drug discovery and medical advances; the building of infrastructure and transportation to support a growing population; the safe cultivation, transportation and preservation of food sources; emerging developments in defense; and the protection of our environment – all of these challenges drive Parker people forward, seeking new ways to innovate, combine technologies, collaborate, develop systems and partner with our customers to solve problems.

ENGINEERING **YOUR** SUCCESS.

If you view the world as we do, through the lens of our broad range of motion and control technologies, you can see a vast number of engineering challenges that are yet to be solved and can make a meaningful difference in the lives of people everywhere.

Our focus is on our customers. By improving their productivity and profitability we create a cleaner, more efficient future for everyone.








PARKER HANNIFIN – THE GLOBAL LEADER AND YOUR PARTNER

Parker Hannifin is the world's leading diversified manufacturer of motion and control technologies and systems, providing precision-engineered solutions for a wide variety of mobile, industrial and aerospace markets. Our products are vital to virtually everything that moves or requires control, including the manufacture and processing of raw materials, durable goods, infrastructure development and all forms of transport.

Our engineering expertise spans the core motion and control technologies – electromechanical, hydraulic and pneumatic – as well as a full complement of fluid control systems; software and electronic controls; filtration systems; and refrigeration, instrumentation and sealing technologies.

Dry Technology

The leader in "dry technology" for the fluid power industry, Parker's Fluid Connectors Group is your single source for high-quality tube fittings, hose and hose fittings, thermoplastic tubing, brass fittings and valves, quickdisconnect couplings and assembly tools.

Markets

The Fluid Connectors Group serves customers in a broad range of markets, including Aerial Lift, Agriculture, Bulk Chemical Handling, Construction Machinery, Food & Beverage, Fuel & Gas Delivery, Industrial Machinery, Medical, Mining, Mobile, Oil & Gas and Transportation.

Customer Services

Products are available for shipment 24 hours a day, supported by 49 manufacturing facilities throughout the world, a global distribution network and 25 company-owned stocking service centers. Our commitment to you is impeccable customer service. To meet your specific requirements, we offer a broad range of programs designed to reduce your overall operating costs, streamline manufacturing, improve productivity, manage inventory, enhance delivery and address safety and environmental issues. For value-added services that generate value-added solutions, team up with Parker!

PARKER HANNIFIN – OPPORTUNITY THROUGH INNOVATION IN THE WORLD'S MOST DEMANDING MARKETS



Worldwide availability

With more than 55,000 employees serving our valued customers in almost 50 countries, Parker is literally everywhere you need us to be. By working with us, you have access to an integrated network of 300+ manufacturing plants, as well as 13,000 distributors and MRO outlets, and over 2,000 ParkerStores™. That's the kind of global network for global businesses demand.

Flexibility

As the world's motion control expert, Parker offers you a complete range of proven, off-the-shelf products. These products deliver exceptional quality and durability, reducing costs and advancing performance.

Innovation

It's what drives us. Our mandate for continuous improvement leads us to partner with our customers to create solutions that are smaller, lighter, sustainable, more energy efficient, and highly reliable.

Hose Products Division Europe

The market leader and your supplier of choice.

Put a bite on the braid.

Parker's world-recognized tiger mascot has represented the Parkrimp No-Skive hose assembly program since its introduction in 1980. In a contest originally held by our marketing department, the tiger was the winning suggestion over three others: a turtle (deemed "too slow"), an alligator ("not very good looking") and a shark ("too intimidating" particularly at the time of the release of the movie Jaws).

More than three decades later, the tiger graphic still supports the Parkrimp message everywhere, clearly symbolizing our unique, patented Parkrimp fittings with tapered steel teeth and our Parkrimp crimping machines. Their ability to eliminate hose cover skiving and achieve the metal-to-metal grip of factory assemblies revolutionized the process for markets worldwide. And today, it's the industry standard.


Pride in our products: At Parker, we believe the best fluid connector products for your operation are the ones that get the job done right. We offer the most comprehensive line of hoses, fittings, equipment and accessories you'll need. And if there's something you need that's not a standard product, we're able to design and manufacture it for you with ease.

You'll also benefit from our ultimate competitive advantage – our network of distribution outlets that can provide our products nearly anytime and anywhere. We strive to provide customers with local engineering, local products and local service.

Parker offers the largest selection of hoses plus more fitting sizes than any other manufacturer. You'll find a wide variety of hoses including braided, spiral and multi-purpose, and more than 4,500 Parkrimp fittings. Parker products have been designed, tested and approved to meet and exceed global standards.



The right product is available for your application, including hose that features a variety of abrasion resistant cover choices, flexibility, a wide range of media compatibility and more – characteristics that make Parker the hose supplier of choice for customers that demand the most from their equipment.



A long history of providing premier customer service.

Our European division headquarters in Veniano, Italy is our precision-engineered-solution center for products, materials and processes, and is equipped with state-of-the-art development, testing and performance technology. Hose Products Division Europe has 5 manufacturing locations dedicated to provide a quality product on time. Knowing that uptime and productivity are major drivers in your business success, we proudly present this catalog outlining Parker's best-in-class hose products and services.



Low, Medium, High and Ultra Pressure Hose



Parkrimp® Hose Fittings



Parkrimp® Assembly Equipment

Parker

Parker HoseFinder

Parker Hose Selection Guide

Mobile Phone Applications





Parker Tracking System



ParkerStore™ Onsite Container Program and Hose Doctor Service



Custom Hose Assemblies and Hose Fittings



Accessories

GlobalCore™

The world's first high-performance, cohesive hose and fitting system.

Providing a simple solution of robust hydraulic hoses designed to endure the tough conditions where work gets done, GlobalCore is the future that OEMs and end users around the world have been asking for.

You know Parker as the global leader in providing unprecedented performance and value for hydraulic systems with high-pressure applications. With our GlobalCore solution, you can significantly reduce your inventory and part number complexity by using just five hoses and two fittings.

Designed to meet the most common working pressures in industry, GlobalCore stands above the competition and serves customers around the world with a simple family of constant working pressure hoses.

Designed, built and tested to the ISO 18752 specification, GlobalCore reduces engineering and service complexity by providing the first comprehensive product family across the most commonly used constant working pressure classes.

Hoses	-4	-6	-8	-10	-12	-16	-20	-24	-32
21 MPa / 3,000 psi	387	387	387	387	387	387	387	387	387
28 MPa / 4,000 psi	487	487/722	487/722	487/722	487/722	487/722	487	487	487
35 MPa / 5,000 psi	–	–	787	787	787	787	787	787	787
42 MPa / 6,000 psi	–	–	797	797	797	797	797	797	797

Fittings	-4	-6	-8	-10	-12	-16	-20	-24	-32
21 MPa / 3,000 psi	43/48	43/48	43/48	43/48	43/48	43/48	43/48	77	77
28 MPa / 4,000 psi	43/48	43/48	43/48	43/48	43/48	43	77	77	77
35 MPa / 5,000 psi	–	–	77	77	77	77	77	77	77
42 MPa / 6,000 psi	–	–	77	77	77	77	77	77	77

High Performance

Because challenges can emerge anytime and anywhere, your solution should endure the tough conditions of your work environment.
The high-performance standards designed, engineered and manufactured into GlobalCore provide the longest service life possible.
With GlobalCore hoses tested to twice the ISO 18752 standard, high performance in rugged environments and high-impulse applications is ensured.

Additional value is realized through:

- 100 °C / 125 °C temperature ratings
- Standard, ToughCover and SuperTough cover technologies for abrasion resistance
- ½ minimum bend radius
- Low force to flex for ease of installation
- Advanced inner tube chemistry





Five Hoses. Two Fittings. One Solution.

Cohesive

GlobalCore is a unified system that delivers hoses designed, built and tested to the ISO 18752 specification.
GlobalCore expands our range of ISO 18752 hoses and provides options for the most critical sizes and pressure ranges - 21.0 MPa (3,000 psi) to 42.0 MPa (6,000) psi in sizes -4 through -32.

Simple

The GlobalCore system is simple. With only five hoses, OEM and MRO customers alike will enjoy selecting the right hose based on working pressure. Selecting the fitting is even simpler. Choose the world renowned 43/48 Series, with more than 2,500 configurations, or the 77 Series, designed specifically for higher pressure applications and available in more than 500 configurations.

Cover Options

GlobalCore hoses come with a variety of cover options so you can match the right cover to your application.

Standard | Tough (TC) | Super Tough (ST)

Global

A single cohesive family of complimentary products so qualified has never before been offered globally.
Produced with the same performance and manufacturing specification in production plants located in all the continents, GlobalCore can support your hydraulic hose needs regardless of where your equipment was originally manufactured or is today.

Global Approvals

GlobalCore will carry the most common international classification body type approvals as requested by our customers. ABS, DNV, Lloyd's, MSHA and USCG will be comprehensive approvals, while other certifications will be specific to designated hoses or sizes.

Visit parkerglobalcore.com for the latest list of hose and classification body type approvals.



It's so easy to crimp your own hose assemblies whenever YOU need them

Parkrimp® *No-Skive*

The system for fast and leak-free hose assemblies with No-Skive one-piece fittings

Hose fittings have an impact on the overall efficiency and safety of a hydraulic system. The No-Skive concept was launched by Parker Hannifin some 30 years ago but continuous development and the use of modern materials and production techniques have resulted in a state-of-the-art hose to fitting connection. Much easier handling and a high level of safety are available with No-Skive crimp fittings. Parker offers No-Skive fittings in one and two pieces as part of a package consisting of quality hose, No-Skive fittings, hose crimpers and tooling.

- No skiving tool needed
- No need to remove the cover
- Crimps one-piece fittings
- Parkalign positions the fittings in the dies perfectly every time
- Quick and easy: no gauges to set on the machine
- Portable machines for field repair
- Meets EN safety regulationson



KarryKrimp® 1
82CE-061L



KarryKrimp® 2
85CE-061L



Parkrimp® 2
83CE-083U

Modular crimpers with Bench Power Unit for workshops

The modular design enables the customer to choose between the portability that Parker KarryKrimp crimpers have always offered, and the option to make these same crimpers bench mount units.

In addition to the portable versions, the sole crimping units can be used with the Bench Power Unit for workshop versions for faster cycle times, increased productivity and increased height for longer elbows or bent tube fittings.



KarryKrimp® 2 Bench Mount
85CE-061L + 85CE-1PE

Please visit us also at
www.easy-crimping.com

ParLock – the complete Big Bore solution

No-Skive™ and ParLock Skive technology

In addition to the new R35TC-40, already launched and very well accepted in the market, Hose Products Division Europe follows its strategy to develop a complete Big Bore hydraulic hose range. Four different hose types are available to fulfil all high flow rate hydraulic needs for markets like oil & gas, mining and heavy duty constructions.



R35TC-40 and RS35TC-48

R35TC-40 and RS35TC-48

- Very high working pressure of 35.0 MPa (5000 psi)
- High abrasion resistant TOUGH COVER prolongs hose life, minimizes downtime and eliminates extra cost for additional protection sleeves – MSHA approved
- Approved with Interlock V6 series fittings, connection types: ISO 6162-2 (42.0 MPa/6000 psi)

R35TC-40

- Design factor of 4:1
- Impulse tested to more than 1.5 million cycles at +120 °C
- Extra strong 6-spiral construction for high-flex-impulse and high-vibration applications
- **NEW:** ISO 6162-2 (42.0 MPa/ 6000 psi) flange

RS35TC-48

- Design factor of 2.5:1 according ISO 6708-D
- Extra strong 6-spiral construction for high-vibration applications

For heavy duty applications, both sizes -40 (63.5 mm) and -48 (76 mm), based on Interlock technology, will complete the existing ParLock range and is now available from size -4 to -48.
Due to the severe applications, both hoses are coming with TC cover for best abrasion resistance and MSHA approved. Due to the enhanced hose diameters and in combination with very high pressures, flow rates can be increased – this eliminates the need of numerous pressure lines and results in a cost reduction for connectors. Today, all 6000 psi flanges are available and SteckO® fittings can be used for mining applications.



462TC-40/462TC-48

For low pressure and return lines, Parker extended the very well known Elite Compact range with the new 2SC hose type 462TC – available ***now*** from size -4 to -48.
In order to reach a 7.0 MPa working pressure with Elite Compact hose 462TC in both sizes -40 and -48, Parker developed a brand new Big Bore fitting which will complete the well known 48 series.

462TC-40 and 462TC-48

- No-Skive hose construction – Compact design
- Nitrile (NBR) inner tube – extended fluid compatibility
- Exceeding EN/ISO specifications for pressure, bend radius and abrasion resistance
- Highly abrasion resistant TOUGH COVER, MSHA approved
- WP 7.0 MPa with 4:1 design factor – Dynamic application, impulse tested
- High flexibility in spite of big size
- 2piece fittings for use with adjustable crimper only (47 series nipple and 10048 shell)

Blowout Preventer hose system

for exploration and deep drilling in the oil & gas industry

The Parker Blowout Preventer (BOP) Hose System is a vital part of exploration and drilling equipment in the very demanding oil & gas market. Optimum performance with the highest safety is the main aspect. Especially the high quality components of BOP hoses – all made in Europe – and the assembly process of the components guarantees our customers the highest flexibility and the easiest installation on site. Parker BOP Hose System has been tested and approved to API16D standard by Lloyds Register.
Together with the new BOP Hose System, Parker Hose Products Division Europe offers a wide range of hose and fittings for drilling applications such as hose type R35TC (big bore spiral hose). Our offer is completed by the No-Skive Elite hose range with outstanding technical performance. All these matching systems, certified by international certification bodies let you work safer, smarter, faster and better.

Blowout preventer (BOP) hose range:

- from size -8 up to size -32 (DN 12 to DN 51)
- Variable length up to 40 m max
- 5,000 psi (35.0 MPa) and 6,000 psi (42.0 MPa) range with a design factor 4:1
- Glass fibre fire sleeve protection – in compliance with RoHS directive 2002/95/EC
- Protected by square-locked metal flexible hose
- Material: hose fittings and metal protection available in steel and stainless steel
- Available as complete assemblies certified and approved to API16D specification and MSHA
- Accessories and hammer union adaptors type 1502 and 602 available on request



Tested according to API16D by Lloyds Register

Complete system, assembled and tested

Assemblies made to order according to customers requirements

Full range, from 1/2“ to 2“, working at 5,000 psi and 6,000 psi

Great flexibility, assured by Parker specific system design and assembly

Available in variable length up to 40 m

Steel and stainless steel fittings and armour

NPT, BSP male and female and integral hammer union in 2”

Parker Blastopak

New Hose Range for Water-Blasting Applications

Choose the improved performance of Parker Blastopak Hose

Parker's Blastopak range BPK-XX is the new offer of hoses with four or six spirals that better meets the requirements of water-jetting and blasting applications.
High-pressure water-blasting hoses are widely used for many industrial applications like water cutting, cleaning and removal of corrosion or paint or other kinds of materials.
In water-blasting applications, ultra-high pressure systems are commonly used, where the safety and robustness of a product are essential.
Parker's range of Blastopak hoses is the ideal solution for these kinds of applications. With its high working pressure from 800 bar (80 MPa) in size -16 up to 1100 bar (110 MPa) in size -4 to -12, good flexibility combined with dedicated interlock fittings is the right choice to ensure better performance and safety at the same time.
Design factor burst/working pressure of 2.5:1; the product meets the requirements of global specification DIN EN 1829/2 (impulse) in all common hydraulic applications.



Parker Hose Products Division Europe
DIN EN
1829-2
APPROVED
Best Performance & High Safety



EO-3®

Potential assembly errors are eliminated with the innovative fitting system for hose and tube applications.

As a connector component, any fitting is only as good as the effectiveness of the assembly process and therefore depends on how it has been assembled. New end-configurations and material compositions have increasingly improved performance, reliability and ease of assembly. In this field Parker has constantly set new standards in the marketplace.
With the development of the EO-3® fitting, Parker now introduces another very important milestone in the history of connector technology. Our customers practical experience provided the impetus for the development of the EO-3® system with the message that potential assembly errors, such as over- or under-tightening, should be eliminated. Practical experience often shows that fittings are in large part not expertly assembled. Changing personnel, a shortage of skilled workers and increasingly difficult installation conditions lead to failed assemblies. The consequences are leakage, costly downtime and expensive reworking – or even accidents.
The advantages of the new fitting are clearly apparent with its greater simplicity, speed and safety. With its new thread technology, EO-3® can be assembled more easily and faster than other commercially available fittings systems and the assembly outcome of EO-3® is, for the first time ever, easily discernible from the outside; every user is now in a position to directly control work safety and machine reliability.





Users can secure a whole raft of money – saving advantages when they install EO-3® fittings.

- Leakage can be prevented with the help of unambiguous assembly inspection
- Distinctly increased machine performance and reliability
- EO-3® meets the increased safety and quality requirements now in force
- Additional costs of reworking are substantially avoided
- EO-3® increases the quality of the end-product
- Company image is enhanced due to better products
- No oil loss –an important contribution to environmental protection

This arguments support the immediate installation of EO-3® in a very wide range of operating conditions - whether energy, agriculture, paper machinery or oil and gas extraction; the EO-3® system will satisfy the highest requirements for quality and function.
„Fit and forget“ sums it all up.

692PU Hose

for heavy-duty materials handling applications

Off-highway manufacturers involved in the design and manufacture of heavy lifting and materials handling vehicles such as aerial lifts, telehandlers, truck-mounted cranes and roughterrain forklifts, are coming up against ever-more stringent customer demands. Sure enough, price will always have an influence on product selection but, more and more often, the market is also requesting increased operating efficiency, greater compliance with standards to ensure safety for operators and equipment, and the minimisation of costly downtime. Fortunately, increasing numbers of OEM engineers are discovering that the humble braided hydraulic hose has a significant role to play in helping meet such requirements.

The requirement to improve productivity is paramount in a market that is governed by rapid transportation and delivery. Productivity is linked directly to the speed of moving parts, which in turn implicates factors such as higher flows and the necessity to maximise pressure rates while retaining the same size of tubing in the hydraulic circuit.






- Suitable for all forklift and materials handling applications
- Constant working pressure of 21.0 MPa
- Design factor of 4:1
- Smaller outside diameter
- Thinner lightweight cover
- Special abrasion resistance
- Tight bend radius enables smaller pulleys
- Addresses critical factors of modern hydraulic circuits

Parker rubber compounds

assuring superior ozone resistance and performance

Ozone – O_3

A molecule consisting of three oxygen atoms is called OZONE (O3). In the ozone layer this gas protects living organisms against harmful UV-radiation, but also it is a strong oxidant, harmful against the respiratory system of humans and animals.



Ozone is highly impacting the degeneration of rubber

Ozone is one of the strongest oxidants. Beside the harms to all organic material it also applies to elastomer compounds, e.g. NBR, CR. Already small concentrations impacting product quality and service life. Moisture intensifies ozone cracking.

The concentration of ozone is rising

Ozone is generated by UV-rays, electrical discharge and air pollution. The natural ozone concentration is highly influenced by local conditions. Since 1971, the beginning of ozone measurements, the values continuously raised by 30% up to now.


Ozone resistance is a must

The polymer chains are split by ozone, leading to cracks growing vertical to the direction of elongation. Even a small amount of elongation (≤10%) is required to provoke cracks and increases rapidly with increasing elongation. The cracks, finally reaching the reinforcement of the hose, will cause corrosion and ending up in severe damage. In order to increase hose life, Parker developed a new series of rubber compounds for Standard cover, Tough cover (TC) and low temperature (LT) hoses.

Parker Elite and multispiral **400 hours** hoses are able to withstand more than 400 hour ozone resistance, following the ISO7326 Ozone Resistance Test. Super Tough (ST) cover hoses pass even more than 800 hours ozone resistance.



ISO 7326 Ozone Resistance Test



Attention

Ozone resistance is highly influenced by the bending radius (short bend radius = less ozone resistance)

Additional environmental conditions such as chemicals and temperatures may also shorten the hose life!

If your application requires corrosion resistance

state of the art surface protection for hose fittings is the solution

400 hours

Our mandate for continuous improvement leads us to partner with our customers to create smaller, lighter, sustainable, more energy efficient and finally highly reliable solutions. Our goal is thus to provide you with state of the art surface protection for our standard hydraulic hose fittings in order to withstand the world's most demanding application requirements.

In terms of corrosion resistance properties, we decided to follow the needs of our customers and the market and chose improved red corrosion resistance four standard hose fittings.

Parker hose fittings with our chromium 6 free standard plating show a red corrosion resistance of at least **400 hours** of salt spray in a test carried out in accordance with DIN EN 9227.

Chromium-6 Free

Fittings with XTR coating for extreme resistance to corrosion

720 hours

An outstanding advantage for equipment used in highly caustic applications and environments, are Parker fittings with XTR (Extreme-Resistance) coating. This coating withstands corrosion more than seven times longer than the SAE standard of 96 hours. In fact, Parker's proprietary formulation has been tested to resist corroding for more than **720 hours**. In addition, Parker XTR coating is compliant with environmental restrictions worldwide, including RoHS, ELV and REACH.

Parker products with XTR coating guarantee all the leak-free performance and installation advantages that our customers expect. If your application requires highly-resistant coating, you can order hose fittings with the extension "ZJ" e. g. **1C348-12-12ZJ**



For special applications in demanding environments stainless steel is the preferred selection

For pneumatic and hydraulic applications in demanding environments, your connection requirements will be met by Parker's range of stainless steel products.
Parker offers a complete system of stainless steel products such as tubes, tube fittings or 1- or 2-piece hose fittings for low, medium and high-pressure hydraulic hoses – everything from one source and approved by well known international classification bodies. It goes without saying that Parker's stainless steel components are produced using superior quality stainless steel grade 1.4571, 1.4404, or 1.4401. Thanks to their resistance to corrosion and acids, all components are suitable for tough environments. However, some special applications require special materials and here you can rely on Parker as well – we have the resources to produce customised hose fittings for even the most demanding customer requirements.


Power in Stainless Steel

- Premier customer service
- Single-source solution
- Worldwide availability
- One team for all requirements
- Customized products
- Special materials
- Complementary design of tube & hose fittings



The benefits of working with Parker hose

Bring the power of Parker to the palm of your hand.



1 **Browse it.** It's easy to use.
2 **STAMP it.** Use the STAMP search or browse the catalog to find the product you are looking for.
3 **Search it.** Results include all the details you need to make an informed decision.
4 **Find it.** Choose the "Find It" link and you'll be directed to one of Parker's 12,000 worldwide distributor locations.



Parker is committed to delivering customer service options to help you work smarter, faster, and better.

Need the latest? Go online. From complete product information on hose, to 3D-CAD models of our complete fitting line, you'll find everything you need at www.parkerhose.com.

And HoseFinder, our mobile app, makes it fast and convenient to search for hydraulic hose products and information on the go. The app features an abbreviated STAMP selection process to help you find what you need quickly and easily. Download yours today at **www.hosefinder.com**.

Whatever you do, visit our site often. It's the fastest and easiest way to keep up with changing technology and our ever expanding product offering.

Save valuable time

HoseFinder
Parker Hose Selection Guide

HoseFinder is currently available for iPhone®, Blackberry® and Android™ mobile phones... and at no charge.

Parker Crimpsource™

Crimpsource is the industry's most complete resource for crimper technical information. It contains all of the crimp specifications approved for Parker's hose:

- **Crimp specs**
- **PDFs of technical manuals**
- **Parts lists**
- **Troubleshooting advice**
- **PDFs of crimper decals**


PTS
Parker Tracking System

Global asset tagging and identification system

The Parker® Tracking System Enterprise (PTS) is designed to help customers reduce vehicle or asset downtime through increases in the speed, timing and accuracy of necessary repairs. PTS provides a unique 8 digit identification code and bar code printed on a durable label for each hose assembly.
PTS labels are specifically engineered to withstand harsh chemicals, temperatures, UV exposure and other challenging conditions.



- PTS captures, records and recalls unique hose assembly information – on demand
- Provides fast and accurate product indentification to speed up replacement regardless of where the original assembly was made.
- Assembly can be replaced with only the 8 digit PTS ID number/bar code eliminating the need to remove hoses prior to replacement. This can provide critical machine uptime and enable more conveniently scheduled repair.
- PTS includes additional reporting tools to assist in continuous improvement programmes and preventative maintenance initiatives.



Save valuable time
Parker Tracking System
www.Parker.com/PTS

Crimpsource provides easy access to all the specifications necessary to correctly fabricate a factory quality hose assembly.

You can also print a simple-to-follow data specification sheet or crimper decal. Crimpsource is available at **www.parker.com/crimpsource-euro**


PTS Mobile
Parker Tracking System

Get your next replacement faster. Use PTS Mobile.

PTS is one of the industry's most comprehensive and widely distributed asset-tagging and tracking systems, and the mobile app is the perfect jobsite companion. With millions of tagged assemblies worldwide, you're only a few clicks away to a faster, easier, and more accurate replacement experience.

With you wherever you go

Identifying and replacing faulty hose assemblies can be a frustrating process. Lost or outdated manuals and complex hose routings can make identification difficult and time-consuming. Usually, the only solution is to remove the product and take it to a distributor for a replacement.
PTS makes getting replacement hose assemblies and components fast, easy, and exact. And now that convenience is available wherever you go with the PTS Mobile app.





Scan it

Scan the barcode of any PTS tag and quickly find your record in Parker's global database.



Order it

With exact replacement details provided to a local distributor, arrange for pick up or delivery of replacement parts.



Get it

PTS Mobile provides mapping and directions to any nearby distributor using your smartphone's built-in GPS.

Available on popular platforms

PTS Mobile is available for download to Apple and Android devices. This free application from Parker makes it faster and easier than ever before to accurately order the replacement hoses and other components that you need.

PTS Mobile can also be paired with our OEM or Enterprise application to provide a complete asset management solution for your operation.

Find out more
Parker Tracking System
www.Parker.com/PTSmobile

Want to see how PTS Mobile works? Scan the code and view our video.

PTS Pro
Parker Tracking System

Track and manage critical assets with ease.

PTS Pro is a powerful new offering from Parker Tracking System. It brings together advanced asset tracking/management capabilities with Parker's global network of distributors and service partners to provide comprehensive asset management solutions.

Fix when fail is not a strategy

Managing equipment or machinery maintenance can be a challenge for even the most capable and well resourced organizations.

With hundreds or thousands of individual parts or components that require maintenance, keeping detailed records or maintenance logs can be a burden. Most asset management systems do not break capital assets down into the detailed components that comprise them. PTS can help.


PTS Pro is an asset identification and management tool from Parker designed specifically to address the parts that can wear or fail unexpectedly.

Global service partner

Parker employs a team of dedicated support staff worldwide to make installing PTS fast and easy. Through more than 13,000 service partners and OEMs, Parker can work with customers to provide advanced, on-site audit and maintenance planning services.

These services include:

- On-site asset identification and tagging
- Inspection, maintenance, and replacement
- Site or computer-based training programs



With PTS Pro, you can:

- Establish detailed asset location data
- Create and deploy custom inspection templates
- Schedule inspections and replacements
- Apply application and related data to an asset group
- Transfer record ownership between PTS accounts
- Store and retrieve historical inspection results
- Export asset details into Excel reports
- Create custom asset books for audits or inspections
- Schedule and personalize MRO alerts and notifications

Preventive Maintenance Program

Be preventive ... not reactive!


Hydraulic hose assemblies are essential components in hydraulic systems and each hose assembly will eventually fail: it's just a matter of when!

Broken hose assemblies often cause loss of earning, downtime and serious personal injuries.

Avoiding failures, losses and risks is definitely your first priority.

Preventive maintenance is needed whenever your hose assemblies show:

- Damaged, cracked, cut or abraded cover
- Exposed reinforcement
- Cracked, damaged or corroded fittings
- Leaks in fitting, sweating hose cover close to fitting
- Kinked, crushed, flattened or twisted hose
- Hard, stiff, cracked or burnt hose
- Blistered, soft, degraded or loose cover
- Fitting slippage on hose



Despite that, hose assemblies are generally underrated overlooked during machine servicing and the need of their preventive maintenance and timely replacement is ignored. This is simple a fact which we can hardly change. But what we can do, however is to help you to provide a hose assembly in the right place and at the right time whenever and wherever you'll need it.





Hint

A good analogy is automobile tyres. Just like hose, tyres are made of rubber, age with time and experience a lot of strain from the conditions they work in. Most drivers are cautious to replace tyres once they show signs of wear, not leaving it to destiny when they break on the road! So why don't they do it with hydraulic hoses?

As there are countless factors influencing the hose life, there cannot be and are not any exact guidelines to determine when a hose assembly has to be replaced or to judge how long it will work. Yet, we do have a tool to influence and determine the hose life:

Visual Inspections + Preventive Replacement = Preventive Maintenance Program!

Save valuable time

Parker Tracking System

www.Parker.com/PTS

Parker Rapid Service Unit

Non standard and customized hose fittings

The Rapid Service Unit (RSU) can provide:

- **Jump sizes**
- **Specific end configurations**
- **Specific drop lengths**
- **Fitting/tube combinations**
- **Customised prototypes**
- **Any batch size upwards from a single piece**

Material options include steel, stainless steel, brass and special materials on request.



Hose Fitting Design Center of Excellence



Flexible brazing in terms of design and process

The Rapid Service Unit (RSU) is part of the Manufacturing Unit Fittings of Hose Products Division Europe and is a dedicated unit for the manufacture of customised and prototype hose fittings.
The unit is reponsible for both checking the technical possibilities of the customer request from an engineering perspective as well as establishing the most economic production process. Because of close cooperation between Parker's Manufacturing Units and the Parker Sales Companies (PSC) the Rapid Service Unit (RSU) can live up to its name by reacting, quoting and supplying rapidly.
After receiving the order, the RSU team will promptly and carefully process the order – from its receipt to the shipping of the fittings. For the production of such fittings, we have dedicated resources in a state-of-the-art manufacturing cell with CNC machinery and tools.



24 Hours Turn-Around Capability with access to 19 modern CNC

Where corrosion resistance is vital,

we have the best solution in stainless steel





For more information about Parker's Stainless Steel Products please refer to our catalogue 4400.1 "Hydraulic Hose Fittings in Stainless Steel"



Mining hose, fittings and equipment



Parker's mining hoses, fittings and adaptors provide a complete, reliable hydraulic package to connect and support the mining equipment. All Parker mining hose products combine international approvals with total system integrity and long service life in hostile conditions. Special coatings and carefully selected materials ensure reliability in corrosive environments.

For more information about Parker's Mining Products please refer to our catalogue 4410 "Mining Hose, Fittings and Equipment"



We offer more

than just innovative products and solutions



We're constantly updating our customer service options to help you work smarter, faster, and better.

Parker offers concrete knowledge of respective products where selection criteria, scope of application and breadth of operation are invaluable. It is the goal of Parker to offer the possibility to our customers to always acquire and regularly refresh this expertise for daily implementation. In this respect, Parker's Hose Products Division Europe extensive training program offers valuable support.

The program incorporates product and target group training for acquiring not only basic knowledge, but also extensive familiarisation through practical experience with the products, incorporating identification and demonstration of application-specific operational advantages. To ensure that all participants enter the classroom with a fundamental product knowledge, Hose Products Division Europe has developed a complete training concept, including a training sample case.

News for business

This training is ideal for an audience who is interested on all kind of hose products/business news and their benefits for the customers.

- In addition to the regular training offerings, Parker Hose Products Division is offering customised in-house training sessions.
- To support all training activities, a sample case with the part number **HPDE-SAMPLE-CASE** has been developed with a comprehensive product selection to
  - provide you the tools allowing you to run and lead training sessions
  - improve your knowledge of the Division and its products
  - improve your knowledge of the hose market

Hose assembly workshop training

In this training the participant will get familiar with all major aspects (facility + equipment/operational steps/safety requirements) to produce a proper hydraulic hose assembly. This training supports all activities around a certified hose workshop.

Qualified person – hydraulic hose technology

The participants will learn about international safety standards and requirements for hydraulic hose products. The training course includes guidance to select the right product depend on application conditions and Parker instructions to produce a proper hose assembly. The training will convey also knowledge about potential failure and aging affects and how to avoid them.



Part Number HPDE-SAMPLE-CASE

Basic product training

The scope of this training is for beginners in hydraulic hose business and helps to acquire basic knowledge about hose products incl. workshop equipment . The participant is able to identify all hydraulic hose products and to answer application related questions based on catalogue knowledge, the product range and production selection criteria.



ParkerStore™

At Parker Hannifin, we're continually looking for ways to deliver more products, more efficiently.

The Global ParkerStore™ network enables Parker to provide:

- Prompt, efficient, professional in-store services while you wait
- Expert local services and support
- A safe, friendly and convenient shopping environment
- A greater range of parts options so you get exactly what you're looking for


Customers trust ParkerStores to provide OEM and MRO customers with direct access to:

- Custom-made hydraulic hose assemblies and complementary products to support their applications and decrease their downtime
- Expert technical support
- Professional, personalized services, including 24/7/365 support
- The convenience, comfort and amenities of a local service provider.



ParkerStore™ Container Service




Cargo Doors


Storage Racks and Cabinets


Full Electrical Service


Security Doors


Heating/Cooling


Rugged Lighting Service

The ParkerStore container is a transportable workshop, providing on-site maintenance and product support for large construction projects such as roadworks, tunnels, railways, underground systems, etc. Provides an on-site product and hose replacement service. With this service on your site, you can reduce your downtime keeping your project on time and on budget!

HOSE DOCTOR®

Parker HOSE DOCTORS® are a network of independently-owned, mobile service technicians built around the commitment to identify and replace hose assemblies wherever their customers need them, with the fastest response times possible.

HOSE DOCTORS® are an extension of the worldwide Parker distribution network, coupling their service commitment with Parker products – the highest quality hoses and fittings available in the market today.









Value Added Services

Kitting

Multiple components are supplied under a single part number



- Reduced number of suppliers
- Reduced stocks and no obsolete items
- Optimized management (stock and supplies)
- Simplified and optimised order handling
- Reduced assembly costs
- Greater productivity

Tech Services

Optimises the performance of your hydraulic and pneumatic circuits



- With Parker Tech Services involved, your time to market is shorter, which saves on development costs
- The 3 year no-leak guarantee enhances your reputation and lowers your warranty costs
- More reliable operation lowers your customer's operating costs
- More efficient performance and no-leak guarantee is beneficial to the environment
- Parker worldwide coverage ensures you can use the service and save costs wherever you are

Breadman Vendor Managed Inventory

Lean logistics and delivery of Parker products and kits directly to the customer's assembly line, work stations or warehouse



- 100 % parts availability minimises downtime, increases production and reduces costs
- Elimination of stock checking reduces manpower and maintains production levels
- Daily delivery reduces inventory and overheads
- Electronic order processing eliminates paperwork and reduces administration costs
- Enjoy a customized program where Parker personnal can manage your inventroy in person or remotely
- Reduce overall inventroy, increase your inventory turns and increase your efficiency

Parker Tracking System (PTS)

designed to help customers reduce vehicle or asset downtime through increases in the speed, timing and accuracy of necessary repairs.



PTS provides a unique identification code for each hose assembly which is printed on a durable bar code or RFID label.

PTS can eliminate costly hours of equipment downtime, helping customers achieve greater productivity and profitablity.

www.parker.com/pts

It's so easy to crimp a hose

Make your own safe and reliable hose assemblies with a Parkrimp hose crimper, whenever and wherever you need them. Easy, fast and safe – the problem solver for your downtime.



Please visit us also at
www.easy-crimping.com

Mobile APPs

Bring the power of Parker to the palm of your hand.

Our mobile apps, makes it fast and convenient to search for hydraulic hose products and information on the go.

Save valuable time

HoseFinder
Parker Hose Selection Guide

Find out more

Parker Tracking System

www.Parker.com/PTSmobile

Crimpsource

The industry's most complete resource for crimper technical information.

- Crimp specs
- PDFs of technical manuals
- Parts lists
- Troubleshooting advice
- PDFs of crimper decals

Crimpsource provides easy access to all the specifications necessary to correctly fabricate a factory quality hose assembly.

You can also print a simple-to-follow data specification sheet or crimper decal.
www.parker.com/crimpsource-euro

Whatever application you have

we have the best solution

Hose Products Division Europe supplies premier customer service by focussing on customer needs and analysing the entire business environment in which our customers operate.

Our expertise spans the core motion and control technologies, and we apply it to make a meaningful difference in the lives of people everywhere. Parker can be found on and around everything that moves!
We engineer and manufacture high quality hoses and hose fittings to help our customers to achieve a higher level of profitability by considering

- our customers' needs and desires
- what hose and fitting technology our customers prefer
- how to advance customer's brand loyalty

By working with us, you have access to an integrated network of global manufacturing plants as well as sales and service offices in 49 countries.


Transportation


Military


Agriculture


Forestry


Utility Equipment


Machine Tool


Waste & Refuse


Marine


Ground Support Equipment


Mining


RV & Bus


Construction


Grounds & Building Maintenance


Railroad


Personnel Lift Equipment


Oil Field Service


Material Handling


Paving & Road Maintenance


Industrial


Inplant Automotive

Contents

Technical Handbook

Low Pressure Push-Lok
The intelligent Push-Lok System covering different types of rubber, thermoplastic as well as a hybrid hose version and a wide selection of reusable fittings made of steel, brass and stainless steel.
Pressure range up to 2.4 MPa

Low Pressure Transportation and Hydraulics
This low pressure range follows the No-Skive concept and the majority can be assembled on Parkrimp machines.
Pressure range up to 20.7 MPa

Medium Pressure Hydraulics
Hose and fitting product range for applications in mobile and industrial hydraulics.
The perfect range for the more demanding market requirements with a broad selection of Parkrimp No-Skive fittings, with over sixty end configurations, combined with Parker hoses and crimpers allows simple and safe assembly – whenever and wherever needed.
Pressure range up to 45.0 MPa

High Pressure Hydraulics
Heavy-duty products for heavy-duty applications with a full range of Parkrimp No-Skive multispiral hoses and fittings and ParLock skive type hoses and fittings.
Pressure range up to 56.0 MPa

Machines, Tooling, Accessories
The perfect complement to the largest range of hoses and fittings in the market. Parker crimping technology is recognised throughout the industry as the easiest and most accurate crimping system available.





aerospace
climate control
electromechanical
filtration
fluid & gas handling
hydraulics
pneumatics
process control
sealing & shielding





Hydraulic Hoses, Fittings and Equipment

Technical Handbook



Parker


ENGINEERING YOUR SUCCESS.

Crimp Systems you can trust

Along with the ever-growing power and efficiency of each type of machinery and increasing working pressures and flow rates of their hydraulic systems, multispiral hose is gaining an increasingly important role in machine design. Parker Hannifin, as the world leader in the hydraulic hose market, responds to these highly demanding requirements with 3 comprehensive systems – Parkrimp No-Skive, Interlock No-Skive and Parlock Skive type.


Parkrimp *No-Skive* system

is based on no-skiving technology (without removing the rubber cover before assembling)




Interlock *No-Skive*™ system

for Compact Spiral™ hoses



ParLock system

uses external or internal and external skiving (Interlock) technology



Each of the systems consists of integrated ranges of hose, fittings and assembling equipment and know-how, all of which are:

- Designed and developed together
- Tested and approved together
- Produced and supplied together

This way Parker Hannifin can guarantee:

- The highest quality and safety and the longest service life of the final product – to the end users,

and at the same time:

- The easiest, most efficient and safe production process – to the assemblers.

In this way Parker Hannifin also meets the requirements of SAE J1273 and ISO 17165-2, which pay particular attention to matching the hose with the fittings and to their compatibility proven by the manufacturer.

Parkrimp *No-Skive*


The easy to operate crimp system from textile to 6 spiral high tensile steel wire

Parkrimp No-Skive is synonymous with the best solution for assembling hydraulic and related hose and fittings from both the technical and the manufacturing points of view!
Throughout the progressive rubber and metal compression during the crimping process the reinforcement always remains intact. The meticulous design, testing and manufacturing processes of Parkrimp No-Skive hose and fittings, combined with the approved crimping diameters provide an excellent mechanical connection between the hose and the fitting. This absolutely leak-free connection gives long service life even with the highest pressures associated with 4- and 6-spiral hose assemblies.


The smartly designed and time-tested Parkrimp No-Skive assembling equipment combined with Parker's assembling know how allow the safest, most efficient and mistake-proof assembly process. The Parkrimp equipment allows cost and time savings to the assembler and guarantees a defect-free, reliable and durable final product to the end-user.

Parkrimp *No-Skive* hose and fittings
the system for fast
and leak-free assemblies


- For crimping Parkrimp No-Skive fittings only
- No skiving tool needed
- No need to remove the cover
- Quick and easy: no gauges to set on the machine
- Portable machines for field repair
- Meets EN safety regulations




Parkrimp *No-Skive* hose and fittings the system with the perfect match



The perfect match
The complete system from one source. No-Skive hose, No-Skive fitting and crimping machine with world-wide guarantee and availability.



Parker's colour-coded die sets
No loose parts to mismatch or misplace – die set segments linked together. Die sets provide 360° evenly applied crimping forces for an ideal crimp result.



Parkalign®
Parker's exclusive Parkalign® positions the fitting in the dies perfectly every time.

Interlock *No-Skive*™


The system for Compact Spiral™ hoses

For applications with extremely dynamic pressure profiles, pressure surges and peaks, as well as applications with intense vibrations and hose flexing (bending), especially when close to the fitting, a strong mechanical grip by the fitting onto the hose is paramount.
A popular method accepted by the market of achieving this mechanical grip in such applications is to use hose fittings that „lock“ the metal reinforcement of the hose directly between the metal shell and nipple (a concept generally called „Interlock“).
As a response to the market requirement for an „Interlock“ hose fitting system, Parker has developed the Parlock and Interlock No-Skive program. This range consists of a specific range of hose, fittings and assembly equipment combined with Parker crimping know-how.

1piece No-Skive 77 series fitting covers the full range of sizes for both Compact Spiral™ hoses 787TC and 797TC hoses – designed to engage the inside of the tube into the spiral wire reinforcement

Parker’s exclusive Interlock No-Skive design, with both internal and external “Bite the Wire” technology for assured connection strength and for better hose to fitting connection which reduces leaks and increases holding power.

- Superior holding power
- Reduced „push- in“ force
- Smart sealing geometry to improve the cool down leakage performance
- Approved by the German DGUV (German Accident Prevention & Insurance Association) for applications requiring Interlock connection e. g. injection moulding machines (design standards EN 201).






ParLock

The system for extremely dynamic pressure applications

Applications requiring the ParLock system

- Hydrostatic transmissions (combine harvesters, large tractors, excavators, etc.)
- Vibratory hammers
- Large injection moulding machines
- Tunnelling machines
- Forestry machines
- Large material handling machines (container handling)
- Excavator booms
- Blow-out preventers in oil and gas



Gripping zone
- superb mechanical grip for safety and impulse life

Sealing zone
- superb sealing performance
- high compression
- rubber friendly shapes

Transition zone
- gradual take-up of bending forces and reinforcement and hose movements
- weather seal

For manufacturing the ParLock hose assemblies Parker Hannifin offers

- Skiving machines for external and internal skiving
- Universal crimping machines with adjustable crimping diameter
- Detailed assembling instructions (see further in this catalogue)









Hydraulic Hoses and Fittings

Hoses and Fittings Terminology – The basics	Aa-2 – Aa-8
Safe Hose Assemblies Working steps	
1 STAMP	Aa-9 – Aa-11
2 ASSEMBLY – 1piece Parkrimp No-Skive Fittings	Aa-12 – Aa-14
– 2piece ParLock Fittings	Aa-15 – Aa-16
3 INSTALLATION	Aa-17 – Aa-19
How to Order (Part number description)	Aa-20 – Aa-21
Identifying Fitting Types Hoses and Fittings	Aa-22 – Aa-33
Storage	Aa-34 – Aa-35
Safety First!	Aa-36 – Aa-37
Parker Safety Guide	Aa-38 – Aa-41

Technical Data	
Hose Overview	Ab-2 – Ab-4
Hose Fittings Overview	Ab-5 – Ab-8
Hose Fittings Pressure Ratings	Ab-9 – Ab-11
Hose Fittings Nomenclature	Ab-12 – Ab-15
Classification Bodies	Ab-16
Approvals for Parker Hydraulic Hoses	Ab-17 – Ab-19
Conversion Chart	Ab-20
Temperature / Pressure Chart	Ab-21
Flow Capacity Nomogram	Ab-22
The Correct Method to Fit Female Swivel Ends	Ab-23
The Correct Method to Fit ISO 6162-1 and ISO 6162-2 Flanges	Ab-24 – Ab-25
Chemical Resistance Table	Ab-26 – Ab-34

Hoses and fittings terminology
The basics!



Hydraulic hose is a full-value part of the hydraulic system transmitting the hydraulic power – not just conveying a fluid – and deserves adequate attention, just like the other hydraulic components which generate, consume or control that power. Furthermore, it is just hydraulic hose assemblies that are usually most exposed to various extreme conditions in which they have to retain full functionality and assure serviceability of the hydraulic system and safety of the operators.

In spite of that, the importance of the hydraulic hose is often overlooked and underestimated.


This catalogue is to provide guidelines to correct hoses and fittings selection and hose assembly manufacturing and to highlight the most important safety aspects for its service in the field.

Hydraulic rubber hoses

Tube – inner layer of rubber compound with chemical and physical properties to be long-term resistant to the fluid and working conditions.

Reinforcement – 1 or 2 (exceptionally 3) layers of braided textile fibre or highly tensile steel wire or 4 or 6 layers of spiralled very highly tensile steel wire to bear high pressure but allow flexibility of the hose.

Cover – outer layer of rubber compound with chemical and physical properties to protect the reinforcement against ambient conditions and mechanical damage.





Depending on the pressure level we classify the hydraulic hoses in this catalogue into 4 groups:

- **Push-Lok**
  – low-pressure hoses with self-grip connection to fittings
- **Low pressure** and **Transportation**
  – 1 and 2 textile yarn braided and 1 steel wire braided hoses
- **Medium pressure**
  – 1 and 2 steel wire braided hoses and suction hoses
- **High pressure**
  – 3 steel wire braided hoses and 4 or 6 steel wire spiral hoses

Depending on the method of hose and fittings assembling we offer 2 basic product concepts (integrated product lines of hoses, fittings, assembling equipment and know-how):

- **Parkrimp** *No-Skive*
  – complete range of braided and spiralled hose, not needing removing (skiving) of the hose cover before assembling.
  – Compact Spiral hose with patented internal and external "Bite the Wire" *No-Skive* technology.
- **ParLock**
  – specific range of 4 and 6 spiral hose for extreme applications which require skiving of the cover and for bigger sizes also of the inner tube.

Hose fittings



Nipple (insert etc.) – the body of the fitting whereof one end is coupled to the counterpart of a hydraulic component (termination end), while the other end is inserted into the hose (tail end).

To assure compatibility with the counterpart, the designs of termination ends are specified by international standards.

The main role of the tail end is to provide durable sealing between fitting and hose.

Shell (socket, ferrule etc.) – the outer part of the fitting provides mechanical connection of the fitting with the hose. To assure a strong hold of the hose reinforcement, shells are generally crimped on to the hose during assembly.

The designs of tails and shells are not standardized but they are in the sole responsibility of the manufacturer.

Due to this reason fittings of various manufacturers are not automatically compatible with hoses of other manufacturers - unless the combination is fully tested acc. to the relevant international hose standards! This is also imposed by all international standards for hydraulic hose usage practices and fluid power systems safety!

Note
Parker Hannifin also offers a limited range of 2piece Parkrimp No-Skive fittings but being special products they are not included in this catalogue. For more information about 2piece fittings, please contact our Division Helpdesk (HPDE_Helpdesk@parker.com)

Note
Parker hoses have to be assembled with Parker fittings only! Crimping Parker hoses with fittings of other manufacturers may have serious impact on the hose assembly functionality and safety!

In this catalogue we offer 3 kinds of fittings:

- **Push-Lok**
  – special nipples connectable to Push-Lok hose without any shells.
- **1piece fittings**
  – pre-crimped shells on nipples make the assembling of hose with fittings easier, more effective and reliable.
- **2piece fittings** (for **ParLock hoses**)
  – for extreme applications requiring full metal-to-metal connection of the hose reinforcement with the shell or even with the nipple (external or external plus internal skiving).
- **2piece fittings** (for **Parkrimp** *No-Skive* **hoses size -40 and -48**)
  – for big bore applications
  Please use adjustable crimpers only (47 series nipple and 10048 shell)



Except Push-Lok, all fittings in this catalogue are crimped and include:

- All Parker 1piece fittings
  – suitable for the
  Parkrimp *No-Skive* product line
  Interlock *No-Skive* product line
- All 2piece fittings in this catalogue
  – suitable for the
  ParLock product line and
  Parkrimp *No-Skive* product line
  (size -40 and -48 only)





Hose assembly

It is the interplay between the fitting tail and shell designs and the hose design with its material properties that primarily determine performance, service, durability and safety of the final hose assembly. Yet compatibility of hose and fitting cannot be just theoretically projected. It requires exhaustive and repetitive laboratory and field tests and further tuning of the designs.

Non-compatibility of hose with fittings or combination of hose and fittings from different manufacturers, do not only influence performance of the hose assembly, they often lead to hose failure with serious health or life-threatening consequences! For this reason the main international standards for hydraulic hose usage practices and fluid power systems safety strictly warn not to mix hose with fittings from different manufacturers!

Parker Hannifin has not approved products of any other manufacturer for combination with Parker hoses and/ or Parker fittings and guarantees full compatibility, reliability and safety only for combinations of genuine Parker parts selected and assembled in accordance with the guidelines included in this catalogue!

Hose Hint
Never mix & match one manufacturer's fittings with hoses from another manufacturer!
Parker hoses, fittings, assembling equipment and know-how are designed as an integrated system, guaranteeing the utmost product performance, reliability and safety!



Pressure rating


Hydraulic hose is a component transmitting hydraulic power and the pressure is obviously the main physical quantity determining the hydraulic power. For hydraulic hoses the following pressure ratings are used:

Working Pressure – the pressure for which the hose assembly is designed to operate over its whole service life - provided the other parameters (temperature in particular) stay within reasonable limits.



For apparently static applications (e.g. with hand pumps or water jetting) consult the Working Pressure with your Parker Field Representative or with our Technical Support (HPDE_Helpdesk@parker.com).

Burst Pressure – the pressure which statically applied causes destruction of the hose. Technical standards for hydraulic hoses define the burst pressure to be equal to or higher than **4 times the working pressure** (design factor 4). This rule and the burst pressure in general serve to hose manufacturers for design and testing of the hose only! If you happen to know the burst pressure of certain hose, never use this rule backwards to deduce its working pressure!



Pressure rating

Remember the working pressure

1. The **hose assembly working pressure** is given by the weakest "link in the chain" - i.e. by the lowest of the working pressures of the hose and of both fittings. Do not forget to check the working pressure of the fittings when selecting components for a hose assembly (see pages ***Ab-9*** to ***Ab-11*** of this catalogue)!
2. The **real hydraulic system operating pressure** is not given by the system components setup but by the application which introduces into the system peaks and surges or by the functioning of the system itself (rapid closing or opening) which induces spikes and pulses. Such occurrences are detectable only by sensitive electronic pressure gauges and are usually not fully or not at all filtered out by safety or relief valves and exert excessive strain on the hydraulic system – hoses and tubes first of all!
3. **The hose assembly working pressure must always be equal to or higher than the real hydraulic system operating pressure incl. all peaks, surges, spikes and pulses!**



Unit of measure

The most commonly used unit of measure for hydraulic pressure worldwide is MPa (Mega Pascal) – used also in this catalogue. In the US and in Anglo-Saxon markets also psi (pounds per square inch) is officially used and many European producers, users and even technical standards still also use bar.

For the conversion chart of various units of measure see page ***Ab-20.***

Hose Hint
Working pressure is a dynamic parameter, burst pressure is a static parameter. High burst pressure does not mean high working pressure!

In order to assure mutual compatibility, producers of hydraulic equipment, producers of machines and also international technical standards profess certain preferred pressure levels:

MPa	21	28	35	42
bar	210	280	350	420
psi	3000	4000	5000	6000





Hose Hint
For highly demanding applications (dynamic pressure, high number of pressure cycles, high temperature etc.):
- *Select hose with much higher working pressure than officially requested*
- *Select multispiral hose instead of braided or ParLock instead of Parkrimp No-Skive*
- *Select all of that in order to increase service life and safety!*

Hose size


The other parameter determining the hydraulic power in direct proportion is the flow rate – i.e. the fluid velocity. However, too high fluid velocity gives rise to turbulence, pressure drops and heating up of the fluid, causing excessive ageing of hoses and other components or even their damage. To keep the fluid velocity below certain limits but achieve the required flow rate, the size of the hose has to be defined appropriately (see Flow Capacity Chart on page ***Ab-22***).

As the first technical standards for hose came from the USA, dimensions of hose are defined in inches and hose sizes are expressed in inches or from inch-derived units. Global companies – such as Parker – use **dash sizes** (-1 = 1/16"), while the European standards use DIN-based DN (diameter nominal) sizes.




dash	inch	DN	mm
-3	3/16	5	4.8
-4	1/4	6	6.4
-5	5/16	8	7.9
-6	3/8	10	9.5
-8	1/2	12	12.7
-10	5/8	16	15.9
-12	3/4	19	19.1
-16	1	25	25.4
-20	1 1/4	31	31.8
-24	1 1/2	38	38.1
-32	2	51	50.8
-40	2 1/2	63	63.5
-48	3	76	76.2

Note
SAE 100 R5 hydraulic hose, SAE J1402 air-brake hose and SAE J2064 air-conditioning hose use sizes equivalent to corresponding metal tube I.D. – different from the other hydraulic hoses (see datasheets of these hoses in this catalogue).



Ambient and fluid temperature




Temperature is one of the factors which most negatively affect rubber characteristics and so it deserves particular attention of the hydraulic system designers and hose users!

High temperature causes degradation of rubber and accelerated ageing of the hose – an effect which can be yet further intensified by the chemical impact of the fluid. That is why the upper temperature limits specified in this catalogue refer to the fluid temperature and why they differ for various media. However, permanent or long-term use at temperatures close to the upper limit would considerably shorten the hose service life in any case and if it cannot be avoided the hose should be replaced more frequently once it shows first symptoms of deterioratioin (stiffness, hard cover and cracks).

Low temperature, on the other hand, affects mainly physical properties of rubber – making it more fragile – and so at extremely low temperatures hose being bent may crack in tube or cover which can cause immediate or later leakage, burst or reinforcement damage. As there are not many hydraulic fluids which flow at or below -40 °C, the lower temperature limits specified in this catalogue refer rather to ambient temperature below which the hose should not be bent or otherwise hit from outside (while staying passively in it does not cause serious problems).

Hose Hint
The combination of high temperature and high pressure reduces the hose service life. Pay attention to regular inspection of such hoses and their preventive replacement if the cover is brittle or cracked!

Hose bend radius



The role of hydraulic hose is to provide a connection of relatively movable parts of the circuit and so its bending is a natural state the hose is designed for. However, the lay-out of the reinforcement wire or fibre inside a bent hose **may** shift to less appropriate positions.The tube and cover are stretched and become thinner and so the pressure resistance of a bent hose considerably decreases. For this reason working pressure and bend radius are negatively interdependent parameters and the max. working pressures specified in this catalogue are conditioned by respecting the min. bend radii.

Hose Hint
Bend radius and bending force are two different things! Not even apparently "flexible" hose (with low bending force) may be bent below the min. allowed radius!

Recommended fluids

As the power transmitting – not fluid conveying – element, hydraulic hose should be first of all used for the primary applications and with the recommended fluids specified in this catalogue!


For low pressure applications with various non-hydraulic fluids see our catalogue **"4401 Industrial Hoses"**.
If for required higher pressure or for any other reason you cannot use industrial hoses, follow the instructions in this catalogue (pages ***Aa-10*** – Application, ***Aa-11*** – Media and ***Ab-26*** to ***Ab-34*** – Chemical Resistance Table).

1 Before you spec it, STAMP it.

S	T	A	M	P
SIZE	TEMPERATURE	APPLICATION	MEDIA	PRESSURE

SIZE

Parker uses a system of measurement called Dash Numbers to indicate hose and fitting size. The dash number, or dash size, is the measure of a hose's Inner Diameter (I.D.) in sixteenths of an inch.
This measuring system of the inside diameter of the hose is universally used by the fluid power industry today. Don't know the hose size? Check the layline. If the original printing has worn off, the original hose must be cut and the inside diameter measured. Be sure to measure the overall assembly length and fitting orientation before cutting the hose.
The hose I.D. must be sized accurately to obtain the proper flow velocity. A flow that's too slow results in sluggish system performance, while a flow that's too high causes excessive pressure drops, system damage, and leaks.
Use the Flow Capacity Nomogram page ***Ab-22*** to determine the proper hose I.D. for an application's flow rate requirements.




The hose size is determined by the inside diameter which can be measured or found on the layline.

Max. recommended fluid velocity:

- Pressure lines – ca. 6.1 m/sec
- Return lines – ca. 3 m/sec
- Suction lines – ca. 1.2 m/sec

Hose Hint
Don't try to save your own or your customer's money by downsizing the hose! It would cost your customer more to replace damaged hoses, other components and oil, and it will cost you more as you may lose your customer!

TEMPERATURE



High Temperature
For high temperature hoses choose the part numbers ending in **"6"** – e.g. **436**

Low Temperature
For low temperature hoses choose the part numbers ending in **"LT"** – e.g. **461LT**

When specifying hose, there are two temperatures you need to identify. One is the **ambient temperature,** which is the temperature that exists outside the hose where it is being used; the other is the **media temperature,** which is the temperature of the media conveyed through the hose.
Very high or low ambient temperatures can have adverse affects on the hose cover and reinforcement materials, resulting in reduced service life.

Media temperatures can have a much greater impact on hose life. For example, rubber loses flexibility if operated at high temperatures for extended periods.
Parker hoses carry different temperature ratings for different fluids. For example, 611HT hose has a temperature range of -40 °C to +150 °C for petroleum-based hydraulic fluids. However for water, water/glycol, and water/oil emulsion hydraulic fluids, the range drops to a rating of up to + 85 °C. Air is rated even lower at up to + 100 °C.
Some media can increase or decrease the effects of temperature on the hose. The maximum rated temperature of a hose is specific to the media.

Working steps

STAMP (SIZE, TEMPERATURE, APPLICATION, MEDIA, PRESSURE)

APPLICATION

Before selecting a hose, it is important to consider how the hose assembly will be used.
Answering the following questions may help:

- **What type of equipment is involved?**
- **What are the environmental factors?**
- **Are mechanical loads applied to the assembly?**
- **Will the routing be confined?**
- **What about hose fittings – No-Skive or ParLock?**
- **Will the assembly be subjected to abrasion?**




Hose Hint
You do not always need additional sleeve to protect the hose against abrasion!
Parker high and extremely high abrasion resistant TOUGH COVER *and* SUPER TOUGH *versions with 80-times and 450-times higher abrasion resistance do the same, but better and cheaper!*

Sometimes specific applications require specific hoses. For example, applications where hoses will encounter rubbing or abrasive surfaces, would be best handled by our family of abrasion-resistant hose with both Tough and Super Tough covers.
When application space is tight, bend radius is another important consideration. Parker offers a full line of hoses designed for one-half SAE bend radius at full SAE-rated pressures. We ofer hoses with increased flexibility and smaller outer diameters enabling faster, easier routing in small spaces, reducing both hose length and inventory requirements.
Industry standards set specific requirements concerning construction type, size, tolerances, burst pressure, and impulse cycles of hoses. Parker hydraulic hoses meet or exceed standards such as:

- **ISO (International Organization for Standardization)**
- **EN (European Norm)**
- **SAE (Society of Automotive Engineers)**
- **DIN (Deutsches Institut für Normung)**

Governmental agencies control additional standards for particular industries such as U.S.C.G. and ABS. You must select a hose that meets the legal requirements as well as the functional requirements of the application.



MEDIA

What will the hose convey?
Some applications require the use of specialized oils or chemicals. The hose you order must be compatible with the medium being conveyed.
Compatibility must cover the inner tube, the cover, hose fittings, and o-rings as well. Use a Chemical Resistance Chart to select the correct components of the hose assembly that will be compatible with your system's media. The chart contains the chemical resistance rating of a variety of fluids.
See pages ***Ab-26*** to ***Ab-34.***



PRESSURE

When considering hose pressure, it's important to know both the system working pressure and any surge pressures and spikes. Hose selection must be made so that the published maximum working pressure of the hose is equal to or greater than the maximum system pressure.
Surge pressures or peak transient pressures in the system must be below the published maximum working pressure for the hose.
Each Parker hose has a pressure rating which can be found on the hose table. All Parker hydraulic hoses have passed the industry rated specifications for burst pressure and carry a 4:1 design factor unless otherwise noted. Burst pressure ratings for hose are for manufacturing test purposes only. They are not an indication that the product can be used above the published maximum working pressure.
Care must also be taken when looking at the "weakest link" of the hose assembly. A hose assembly is rated at the maximum working pressure of the hose and the fitting component. Therefore the maximum working pressure of the hose assembly is the lesser of the rated working pressure of the hose and the end connections used.

Always check the fitting working pressure – see pages ***Ab-9*** to ***Ab-11***.




Hose Hint
Although fittings are made of steel, their working pressure is often lower than that of hose!
Don't forget to check the working pressures of both fittings when selecting components for your hose assembly!

Working steps

2.1 ASSEMBLY
1piece Parkrimp *No-Skive* Fittings


Cutting






Hose is cut to the desired length according to specifications. The correct hose cutting tool ensures a square, clean cut without damaging the pressure reinforcement. Depending on the hose type, different kinds of cutting blades must be used:


1) Smooth cutting blade:
   for high tensile textile layer, return line hoses and steel wire braided hoses
2) Serrated cutting blade:
   for hoses with 4 or 6 spiral layer of high tensile steel wire




All male threads are measured up to the end of the fitting.




US fittings (JIC, SAE, NPSM), except ORFS fittings, are measured up to the end of the nut.




Flange elbows are measured up to the centre line of the face.



All DIN, BSP and ORFS fittings are measured up to the end of the sealing head.



Straight flange fittings are measured up to the face.




All elbow fittings with swivel nuts are measured up to the summit of the head/centre line.

Tolerances for hose assemblies
Length tolerance according to DIN 20066 Tabelle 6

Hose assembly length (mm)	Diameter (mm) ≤ 25	Diameter (mm) > 25
up to 630	+7 -3	+12 -4
over 630 up to 1250	+12 -4	+20 -6
over 1250 up to 2500	+20 -6	+25 -6
over 2500 up to 8000	+1,5 % -0,5 %	
over 8000	+3 % -1 %	

According to EN ISO 4413, hose assemblies are not permitted to be manufactured from any components that have already been in use in other hose assemblies.

Cleaning after cutting




After cutting it is recommended to clean the hose with compressed air from both sides.
Please make use of Parker's Cleaning System TH6-7
– A quick and simple system
– Delivered with two plastic nozzles for hoses from size -4 up to -32.
The hose is pressed against the nozzle and thereby opens a valve to allow the compressed air to blow through the hose and blow out loose particles.

Working steps

Marking


According to EN and ISO standards, hose assemblies must be clearly and permanently marked. They must bear the following information:

– Manufacturer's identification
– Date of production (year and month)
– Maximum permissible working pressure of the whole hose assembly



Crimping 1piece Parkrimp No-Skive Fittings


Crimping is the safest, fastest and most commonly used method of making a hose assembly. The Parker crimping systems ensure precise, leak-free and tear-proof assembly of hose and fitting. Reaching the exact crimping diameter is possible with Parkrimp crimping tools or adjustable crimping tools. When crimping, it is essential that hose, fitting and crimping tool (dies) match precisely. For crimping dimensions please refer www.parker.com/crimpsource-euro.



Furthermore, the insertion depth, a square cut hose, correct, burr-free and clean crimping are important to ensure a correctly formed and leak-free connection of hose and fitting. Using the Parkrimp hose crimpers or adjustable crimpers, the fitting is crimped onto the hose in one slow and smooth crimping procedure. A depth stop with automatic function ensures safe positioning of the fitting. This guarantees the correct crimping of hydraulic hose assemblies.


Find the correct crimp specification on the push of a button!
www.parker.com/crimpsource-euro


26, 43, 46, 48, 70, 73, 77 series:
Push the hose all the way into the coupling. Place the hose next to the fitting shell and mark the insertion depth or the length of the fitting onto the hose, push the hose into the fitting until the mark on the hose is even with the end of the shell.
If necessary simply wet the fitting end with a drop of hoze oil. Do not lubricate if using spiral hose.






Angle setting
The displacement angle of a hose assembly is indicated only when two elbow fittings are assembled in a displaced way.
The angle always has to be indicated clockwise looking from the elbow fitting at the back to the one in the front. Please also consider the natural bending of the hose.





Working steps

Testing (optional)




Static test pressure depending on the hose type and application is applied to the finished hose assembly for a pre-defined period of time. The test procedure can be documented using a test logging unit. The test pressure for Parker hydraulic hose assemblies is 2 times the value of the dynamic operating overpressure.

Proof Pressure Test
This test is typically carried out on customer request according to a method defined by the ISO 1402 standard. The test should be done at normal ambient temperature with a proof test bench using water or another suitable liquid. The hose assembly should be pressurised for between 30 to 60 seconds at twice the working pressure of the hose assembly. There should be no leakage or pressure drop. A complete test report should be provided together with the hose assembly to the customer.

Cleaning

Hydraulic systems have to reach a defined degree of cleanliness. To ensure that and to achieve certain cleanliness classes you can use different cleaning devices for a fast and efficient cleaning of hose assemblies.
The TH6-6 cleaning device first flushes the hose assembly with an anticorrossive emulsion and dries it afterwards with compressed air.



The dry-cleaning systems TH6-10-EL-7 or TH6-10-HL-9-2 fire a Ultra Clean projectile through the length of the hose assembly. In the end protect the finished hose assembly against impurities with plastic caps.

ISO 4406	NAS 1638	SAE 749
11/8	2	
12/9	3	0
13/10	4	1
14/11	5	2
15/12	6	3
16/13	7	4
17/14	8	5
18/15	9	6
19/16	10	
20/17	11	
21/18	12	



Working steps


2.2 ASSEMBLY
2piece ParLock Fittings

Cutting, cleaning after cutting and marking
please see “Working Steps for 1piece Parkrimp No-Skive”

Skiving


For the skiving of hydraulic hose, one distinguishes between internal skiving and external skiving. This system is applied for hose types with 4 or 6 spiral reinforcement layers, the so-called Parker ParLock System or Interlock.






External skiving tool
A: External skiving tool with two arms
B: Mandrel for external skiving
C: Supporting arm for skiving knife (short/long arm)
D: External skiving knife

Internal skiving tool
a: Skiving knife






Skiving tool
A: Complete tool holder
B: Skiving mandrel for internal skiving
C: Supporting arm for skiving knife (short/long arm)
D: Skiving knife for external skiving (2x)
E: Skiving knife for internal skiving

Adjustment of tools for internal skiving
Select the skiving tool according to the manufacturing documents and the hose size. Insert the knife for the internal skiving mandrel into the borehole of the mandrel provided for this purpose and mark it with a lock collar at the straight surface. When adjusting the knife, observe the marking on the internal skiving knife and insert the mandrel into the tool holder.

Adjustment of tools for external skiving
Attach the knives in the supporting arm. Select the supporting arm (long or short) depending on the hose size.
Adjust the knives according to the Parker working instructions and insert the tools into the machine. Push the mandrel onto the hose until it is close to the tool (external or internal skiving knife).

Adjustment of the sense of rotation of the machine
Always skive into the direction of the spiral layers. Please observe the operation instructions of the machine.




Cleaning after skiving

All hose types which have been skived externally or internally should be cleaned immediately after skiving. For this purpose we recommend using cleaning plugs which are shot through the hose using compressed air.
(e.g. TH6-10-EL-7 or TH6-10-HL-9-2)

In addition to this working step, the finished hose assembly must be cleaned from both ends using pressurised air after the completion of this working step.

Working steps

Crimping 2piece ParLock Fittings




For crimping ParLock fittings V4 series a minimum of 320 tons crimping force is recommended. Min. of 340 tons for V6 series.

1) Select the appropriate crimping dies using the crimping diameter chart.
2) Before crimping hoses and fittings it must be ensured that you have the most recent crimping dimensions. For crimping dimensions please refer our crimp charts on page ***Ed-15*** to ***Ed-16*** or online at ***www.parker.com/crimpsource-euro***
3) Insert the dies into the crimping press and set the crimping diameter.
4) Place the pre-assembled hose assembly into the crimper and perform the crimping procedure.
5) Please observe the operating instructions of the crimper.


2piece fittings must not be crimped on Parkrimp crimpers **– only with adjustable crimpers.**



Make sure that the hose ends are cut squarely. Push the ferrule onto the hose. The cut end of the hose must be clearly visible.




Push the nipple down into the hose until it reaches the stop on the lower groove (plastic ring, fitting shoulder or metal stop). Use Hoze-Oil, if required.



The ferrule must bottom up against the plastic ring or metal stop.

Angle setting
please see “Working Steps for 1piece Parkrimp No-Skive”



After crimping, the ferrule must be located precisely in the groove of the nipple.

Checking for the correct crimping diameter

In case of the ParLock System, the conicity is measured. It is measured at the beginning and the end of the ferrule in 2 measuring planes.

The conicity must be within the tolerance range specified in the Parker specification.



Measurement 1
in the plane of force



Measurement 2
displaced by 90°





Measurement 1
at the beginning and the end of the ferrule




Measurement 2
at the beginning and the end of the ferrule (displaced by 90°)

Testing and cleaning please see “Working Steps for 1piece Parkrimp No-Skive Fittings”

Find the correct crimp specification on the push of a button!
www.parker.com/crimpsource-euro

Working steps

3 INSTALLATION



The **routing** of the hose assembly and the environment in which the hose assembly operates directly influence the service life of the hose assembly. The following diagrams indicate the correct routing of hose assemblies that will maximise its service life and assure a safe working functionality.

When hose installation is straight, it must be assured that there is enough slack in the hose to allow for changes in length that occur when pressure is applied. When pressurized, hose that is too short may pull loose from its hose fittings or stress the hose fitting connections, causing premature metallic or seal failures.


The **hose length** must be determined so that the hose assembly has enough slack to allow the system components to move or vibrate without creating tension in the hose.

However, care needs to be taken not to allow too much slack and therefore introduce the risk of the hose snagging on other equipment or rubbing on other components.


Mechanical straining of the hoses needs to be avoided, so the hose must not be bent below its minimum bend radius or twisted during installation. The minimum bending radii for each hose is stated in the hose tables in the catalogue.

The plane of movement must also be considered and the hose routing selected accordingly.

Hose routing also plays an important role on the selection of the hose fittings, as the correct fittings can avoid straining the hoses, unnecessary hose length or multiple threaded joints.



Working steps




Correct clamping (holding/supporting) of the hose should be exercised to securely route the hose or to avoid the hose contacting surfaces that will cause the hose damage.
It is however, vital that the hose be allowed to keep its functionality as a “flexible-pipe” and not be restricted from changing in length when under pressure.


It should also be noted that hoses for high- and low-pressure lines shall not be crossed or clamped together, as the difference in changes in length could wear the hose covers.
Hose should not be bent in more than one plane. If hose follows a compound bend, it shall be coupled into separate segments or clamped into segments that each flex in only one plane.

Hoses should be kept away from hot parts as high ambient temperatures shorten hose life. Protective insulation may need to be used in unusually high ambient temperature areas.

Whilst the importance of the functionality is primate the aesthetics and practicality of the installation should also be considered in the design.
It should be considered that maintenance might be necessary at some stage in the future, so prohibitive design routings should be avoided.




Working steps



Abrasive influences

In general care should be taken that the hose is not exposed to direct surface contact that will cause abrasive wearing of the outer cover (either hose to object or hose to hose contact). If however, the application is such that this cannot be avoided, either a hose with a higher abrasion resistant hose cover or a protective sleeve need to be used.

Parker TOUGH COVER (TC) or SUPER TOUGH (ST) covers offer 80 times or respectively 450 times the abrasion resistance of standard rubber covers.



Pollution of hydraulic circuits

Modern hydraulic equipment is becoming highly precise and as such more sensitive, so as a result the importance of a clean working fluid in the system is growing. Because as many as 75 % of hydraulic system failures are caused by contamination of the fluid by solid particles, the initial cleanliness of hydraulic components, as the main source of these contaminates, is vital.

With hose assemblies most of the pollution/ contaminates enter the hose assembly during its production and mainly during the cutting (or skiving) process.

In order to avoid system failures, all hose assemblies should be cleaned before use (cleaned and plugged before shipping) with suitable cleaning equipment; please see also page ***Ea-15*** up to ***Ea-18***.

The level of contamination is defined in three popular norms: ISO4406, ISO4405 or NAS 1638. Most common however, is the ISO 4406, which describes the number and size of solid particles in the hydraulic system by means of a classification value e.g. 16/13.



How to order

Hose and hose fittings

To make ordering Parker products easier, we have itemized the order numbers on this page. This will be especially helpful when you order hose assemblies.

Hose

Example:
462TC-6


462TC-6 → Hose type
462TC-**6** → Hose inside diameter in size



Hose Fittings

Example:
1CA48-12-6

1CA48-12-6 → Fitting
1**CA**48-12-6 → End configuration
1CA**48**-12-6 → Parker Fitting series
1CA48-**12**-6 → Thread or tube size
1CA48-12-**6** → Hose / fitting size



Material and specification:

Without suffix:	steel, zinc plated, Cr6-free
B:	brass
C:	stainless steel
K:	without a plastic ring
SM:	metric hexagon dimension

The content of the hose crimping tables shows the standard part numbers.
For the availability of non standard parts and materials please contact your local Parker service centre.

Hose assemblies



Hose Assemblies

Example:
P462TCCACF12106-1000-0-SG900

P462TCCACF12106-1000-0-SG900 → **R** → Low Pressure Push-Lok Fittings Series 82
P → Parkrimp No-Skive Fittings Series 26, 48
D → Parkrimp No-Skive Fittings Series 46
F → Parkrimp No-Skive Fittings Series 43, 70, 73, 77
E → Parlock Skive Fittings Series VS
V → Parlock Skive Fittings Series V4, V5, WB
S → Parlock Skive Fittings Series V6
T → Parkrimp No-Skive Fittings Series IF

P**462TC**CACF12106-1000-0-SG900 → Hose type

P462TC**CA**CF12106-1000-0-SG900 → Fitting 1 end configuration

P462TCCA**CF**12106-1000-0-SG900 → Fitting 2 end configuration


P462TCCACF**12**106-1000-0-SG900 → Fitting 1 thread or tube size

P462TCCACF12**10**6-1000-0-SG900 → Fitting 1 thread or tube size

P462TCCACF1210**6**-1000-0-SG900 → Hose / fitting size

P462TCCACF12106-**1000**-0-SG900 → Hose assembly length in mm

P462TCCACF12106-1000-**0**-SG900 → Displacement angle is relevant when the hose assembly has bent fittings



P462TCCACF12106-1000-0-**SG900** → **Accessory** (e.g. spring guard 900 mm length)
SG → Spring Guard
AG → Armour Guard
AS/PS → Partek Nylon protective sleeve
FS → Fire Sleeves
HG → PolyGuard-Hose Protector
PG → ParKoil-Hose Protector
DM → Minesleeve

Explanation of the example
Hose assembly with hose 462TC in size -6 and fitting series 48.
Hose assembly length 1000 mm.
Fitting 1: end configuration CA has a 12 mm pipe diameter and has a size -6 hose nipple
Fitting 2: end configuration CF has a 10 mm pipe diameter and has a size -6 hose nipple
The displacement angle for this combination is 0 degrees. On request a displacement angle can be specified for the bent fitting in relation with the hose curvature. A protection sleeve as a spring guard in length 900 mm is on the hose assembly.


Identifying fitting types

Determining sealing mechanisms

In general fittings can be identified by their visual appearance, their sealing surface/sealing type or by their thread type/form. Viewing the following pages, the visual identification will be self explanatory. The sealing mechanism and the method of thread identification, however, needs further explanation


Thread interface

The sealing is assured by the flattening of the edges of the threads when the male is screwed into the female fitting. Typically the front of the male fittings is narrower than the back of the fittings – often referred to as tapered threads.




O-ring

The O-ring on the male is compressed against the corresponding female and assures the seal. This type of sealing mechanism should be the preferred choice for high-pressure applications.
be convex or concave (seat) on the male or in the head of the pipe of the female as shown.




Matching angle or metal-to-metal joint

Sealing takes place where the two angled faces of the male and corresponding female meet and are wedged into one another by the tightening of the threaded nut. The sealing surfaces can either be convex or concave (seat) on the male or in the head of the pipe of the female as shown.



Matching angle with O-ring

These fittings combine the functionality of both the matching angle seal with the O-ring. The O-ring is in the angled sealing surface of the fitting so that when the threaded male and female are screwed together the sealing surfaces wedge together and at the same time deform the O-ring between them.





Determining the thread type

In general of the threads of various fittings look similar and hinder the easy identification of the thread. To assure the correct identification, the threads must be measured and compared to the tables listed in the following section.

Thread gauge


Using a thread gauge, the number of threads per inch can be determined.
Holding the gauge and coupling threads in front of a lighted background helps to obtain an accurate measurement.






Caliper measure

A vernier caliper should be used to measure the thread diameter of the largest point. (Outside diameter (O.D.) of male threads – Inside Diameter (I.D.) of female threads.)








DIN (DIN – Deutsches Institut für Normung)

Often referred to as metric fittings, these fittings seal using the angled sealing surfaces (metal-to-metal) or the combination of metal-to-metal with O-rings. They are available in **very light (LL), light (L) or heavy series (S)**. The sealing face angles are either 24° with or without O-rings, or 24°/60° universal cones. Identification is made by measuring the thread size and also the tube outside diameter.


Thread
Defined by the outside diameter and the pitch (distance between 2 crests of the thread) example: M22x1.5 - pitch of 1.5mm.




DIN very light series (LL)

The male 60° cone will mate with the female 60° cone only.
The male has a 60° sealing angle (seat) and straight metric thread.
The female has a 60° seat and straight metric thread.

Standard: **DIN 20078 Part 3** [1)]
Parker end configurations: **C0**






Tube O.D. (DN)	Thread metric	ØA (mm)	ØB (mm)
20	M30x1.5	30.00	28.50
25	M38x1.5	38.00	36.50
32	M45x1.5	45.00	43.50
40	M52x1.5	52.00	50.50
50	M65x2	65.00	63.00

DIN light (L) and heavy series (S) without O-ring

The male 60° cone will mate with the female universal 24° or 60° cone only.
The male has a 60° sealing angle (seat) and straight metric threads.
The female has a 24° and 60° universal seat and straight metric threads.

Standard: **DIN 20078 Part 2** [1)]
(previously DIN 20078 A, D & E)

Light series Parker end configurations: **C3, C4, C5, C6**
(Often also referred to as "Ball nose cones")



without O-ring

[1)] obsolete standard, no exact replacement

DIN (DIN – Deutsches Institut für Normung)


DIN 24° light (L) and heavy series (S) with O-ring

The male has a 24° sealing angle cone seat with straight metric threads.
The female has a 24° convex cone with O-ring and a swivel straight metric threaded nut.

Standard: **ISO 12151-2, ISO 8434-1, ISO 8434-4**
(Previously DIN 20 078 Part 4, 5, 8, 9)

Light series Parker end configurations: **CA, CE, CF, D0**

Heavy series Parker end configurations: **C9, 0C, 1C, D2**




with O-ring

Tube O.D. (mm)	Spec.	Thread metric	ØA (mm)	ØB (mm)	C (mm)	ØD (mm)
6.00	6L	M12X1.5	10.50	12.00	7.00	6.20
6.00	6S	M14X1.5	12.50	14.00	7.00	6.20
8.00	8L	M14x1.5	12.50	14.00	7.00	8.20
8.00	8S	M16x1.5	14.50	16.00	7.00	8.20
10.00	10L	M16x1.5	14.50	16.00	7.00	10.20
10.00	10S	M18x1.5	16.50	18.00	7.50	10.20
12.00	12L	M18x1.5	16.50	18.00	7.00	12.20
12.00	12S	M20x1.5	18.50	20.00	7.50	12.20
14.00	14S	M22x1.5	20.50	22.00	8.00	14.20
15.00	15L	M22x1.5	20.50	22.00	7.00	15.20
16.00	16S	M24x1.5	22.50	24.00	8.50	16.20
18.00	18L	M26x1.5	24.50	26.00	7.50	18.20
20.00	20S	M30x2	27.90	30.00	10.50	20.20
22.00	22L	M30x2	27.90	30.00	7.50	22.20
25.00	25S	M36x2	33.90	36.00	12.00	25.20
28.00	28L	M36x2	33.90	36.00	7.50	28.20
30.00	30S	M42x2	39.90	42.00	13.50	30.20
35.00	35L	M45x2	42.90	45.00	10.50	35.30
38.00	38S	M52x2	49.90	52.00	16.00	38.30
42.00	42L	M52x2	49.90	52.00	11.00	42.30

BSP (British Standard Pipe)


Also referred to as Whitworth threads, the BSP thread type fittings seal use metal-to-metal angled surfaces or a combination of metal-to-metal and an O-ring. The angle of the sealing surfaces is 60° for both forms.
There are two popular thread forms: British Standard Pipe Parallel (BSPP) and British Standard Pipe Tapered (BSPT).

Thread
Identification is made by measuring the outside diameter of the thread and the number of threads per inch (25.4 mm)



BSPP
metal-to-metal without O-ring

Standard: **BS5200**
Parker end configurations:
92, B1, B2, B4, D9




Tube I.D./O.D. (mm)	Size	Thread BSP	ØA (mm)	ØB (mm)
6/10	-2	1/8x28	8.60	9.70
8/13	-4	1/4x19	11.50	13.20
12/17	-6	3/8x19	14.90	16.70
15/21	-8	1/2x14	18.60	20.90
18/23	-10	5/8x14	20.60	22.90
20/27	-12	3/4x14	24.10	26.40
26/34	-16	1x11	30.30	33.20
33/42	-20	1-1/4x11	38.90	41.90
40/49	-24	1-1/2x11	44.90	47.80
50/60	-32	2x11	56.70	59.60

BSPP
metal-to-metal with O-ring

Standard: **ISO 12151-6**
Parker end configurations:
EA, EB, EC, EE, D9

BSPT
fittings seal through the thread interface mechanism. Care should be taken not to confuse the BSPT fitting with the NPTF male fitting. BSPT has a 55° thread angle. NPTF has 60° thread angle.


Parker end configurations: **91**



Tube I.D./O.D. (mm)	Size	Thread BSP	ØA (mm)
5/10	-2	1/8x28	9.73
8/13	-4	1/4x19	13.16
12/17	-6	3/8x19	16.66
15/21	-8	1/2x14	20.96
20/27	-12	3/4x14	26.44
26/34	-16	1x11	33.25
33/42	-20	1-1/4x11	41.91
40/49	-24	1-1/2x11	47.80
50/60	-32	2x11	59.61

BSP flat seal
These fittings have BSP parallel threads but the sealing surface is flat. The seal is made when the composite seal is compressed against the female flat face.

Parker end configurations:
B5, B6, B7



Tube I.D./O.D. (mm)	Size	Thread BSP	ØA (mm)
6/10	-2	1/8x28	8.6
8/13	-4	1/4x19	11.5
12/17	-6	3/8x19	14.9
15/21	-8	1/2x14	18.6
18/23	-10	5/8x14	20.6
20/27	-12	3/4x14	24.1
26/34	-16	1x11	30.3

French gas fittings


Typical to the French market the French Gas fittings have a 24° sealing surfaces seat with metric straight threads. Although similar to German DIN fittings the threads differ in some sizes as the French Gas fittings have fine threads in all sizes whereas the German DIN fittings use standard threads in the larger sizes.

French metric 24° cone gas fittings

The sealing mechanism is metal-to-metal.
The fittings are not specified in any international standard.

Metric tube Parker end configurations: **F6, F9**

Gas tube Parker end configurations: **FG, F2, F4**



Tube O.D. (mm)	Spec.	Thread metric	ØA (mm)	ØB (mm)	ØC (mm)	D (mm)
6.00	6N	M12x1	11.00	12.00	6.20	9.00
8.00	8N	M14x1.5	12.50	14.00	8.15	9.00
10.00	10N	M16x1.5	14.50	16.00	10.20	9.00
12.00	12N	M18x1.5	16.50	18.00	12.15	9.00
13.25	13G	M20x1.5	18.50	20.00	13.50	9.00
14.00	14N	M20x1.5	18.50	20.00	14.15	9.00
15.00	15N	M22x1.5	20.50	22.00	15.15	9.00
16.00	16N	M24x1.5	22.50	24.00	16.15	9.00
16.75	17G	M24x1.5	22.50	24.00	17.00	9.00
18.00	18N	M27x1.5	25.50	27.00	18.15	9.00
20.00	20N	M27x1.5	25.50	27.00	20.15	9.00
21.25	21G	M30x1.5	28.50	30.00	21.50	9.00
22.00	22N	M30x1.5	28.50	30.00	22.15	9.00
25.00	25N	M33x1.5	31.50	33.00	25.15	9.00
26.75	27G	M36x1.5	34.50	36.00	27.00	9.00
28.00	28N	M36x1.5	34.50	36.00	28.25	9.00
30.00	30N	M39x1.5	37.50	39.00	30.25	9.00
32.00	32N	M42x1.5	40.50	42.00	32.25	9.00
33.25	34G	M45x1.5	43.50	45.00	33.80	9.00
35.00	35N	M45x1.5	43.50	45.00	35.25	9.00
38.00	38N	M48x1.5	46.50	48.00	38.25	9.00
40.00	40N	M52x1.5	50.50	52.00	40.35	9.00
42.25	42G	M52x1.5	50.50	52.00	42.55	9.00
48.25	49G	M58x2	55.90	58.00	49.00	11.00


NPTF / SAE JIC 37°

This type of fitting uses the thread interface to seal and as such has a tapered thread that deforms and forms the seal. They have 30° sealing angle surfaces, forming a 60° inverted (concave) seat. The fittings are most frequently seen on machines of US origin.

Dryseal American standard taper pipe thread (NPTF)

The NPTF male will mate with the NPTF, NPSF, or NPSM females. Care should be taken not to confuse the NPTF fitting with the BSPT male fitting. NPTF fittings have a 60° thread angle. BSPT has a 55° thread angle.

Standard: **SAE J516**
Parker end configurations: **01**




ØA dimension is measured on the 4th pitch of the thread


Size	Thread NPTF	ØA (mm)	ØB (mm)
-2	1/8x27	10.24	8.73
-4	1/4x18	13.61	11.90
-6	3/8x18	17.05	15.90
-8	1/2x14	21.22	19.05
-12	3/4x14	26.56	24.60
-16	1x11.5	33.22	30.95
-20	1-1/4x11.5	41.98	39.69
-24	1-1/2x11.5	48.05	45.24
-32	2x11.5	60.09	57.15

SAE JIC 37°

Commonly referred to as JIC fittings, these metal-to-metal sealing type fittings have a 37° flare (sealing surface angle) and straight United National Fine Threads (UNF).
The original design specification for the fittings comes from the Society of Automotive Engineers (SAE) and these fittings are the most common American fitting types in Europe. Parker JIC hose fittings are fully compatible with Parker Triple-Lok Tube Fittings and adapters.

Standard: **ISO 12151-5, ISO8434-2, SAE J516**
Parker end configurations: **03, 06/68, 37/3V, 39/3W, 41/3Y, L9**






Tube O.D. (inch)	Tube O.D. (mm)	Thread UNF	Size	ØA (mm)	ØB (mm)
3/16		3/8x24	-3	8.60	9.50
1/4	6	7/16x20	-4	10.00	11.10
5/16	8	1/2x20	-5	11.60	12.70
3/8	10	9/16x18	-6	13.00	14.30
1/2	12	3/4x16	-8	17.60	19.10
5/8	14-15-16	7/8x14	-10	20.50	22.20
3/4	18-20	1-1/16x12	-12	24.60	27.00
7/8	22	1-3/16x12	-14	28.30	30.10
1	25	1-5/16x12	-16	31.30	33.30
1-1/4	30-32	1-5/8x12	-20	39.20	41.30
1-1/2	38	1-7/8x12	-24	45.60	47.60
2		2-1/2x12	x32	61.50	63.50

SAE 45° flare / Male ISO 11926

SAE 45° flare

The angle of the flare is commonly used as a name when referring to these metal-to-metal sealing fittings.
The female fittings have a 90° concave inverted seat, created by the 45° angle sealing surfaces.
The SAE 45° flare male will mate with an SAE 45° flare female only or a dual seat JIC 37°/SAE45°.

Standard: **SAE J516**
Parker end configurations:
04, 08/68, 37/3V, 39/3W, 41/3Y




Tube O.D. (inch)	Size	Thread UNF	ØA (mm)	ØB (mm)
1/4	x4	7/16x20	9.90	11.10
5/16	-5	1/2x20	11.50	12.70
3/8	-6	5/8x18	14.30	15.90
1/2	-8	3/4x16	17.50	19.10
5/8	-10	7/8x14	20.60	22.20
3/4	-12	1-1/16x14	25.00	27.00

Male ISO 11926

This male fitting has straight threads, a sealing face and an O-ring. It is compatible only with female boss type fittings generally found in the ports of machines. Sealing is achieved through the O-ring of the male and through the sealing face of the female.

Parker end configurations: **05**



Thread UNF	Size	ØA (mm)
5/16x24	-2	7.93
3/8x24	-3	9.52
7/16x20	-4	11.11
1/2x20	-5	12.70
9/16x18	-6	14.28
3/4x16	-8	19.10
7/8x14	-10	22.22
1-1/16x12	-12	27.00
1-3/16x12	-14	30.10
1-5/16x12	-16	33.30
1-5/8x12	-20	41.30
1-7/8x12	-24	47.60
2-1/2x12	-32	63.50

ORFS


O-ring face seal (ORFS)

ORFS fittings are becoming the most popular international fitting type used on global OEM machines due to their high level of sealing and their good vibration resistance. The fittings use the O-ring compression mechanism to seal.

The female fittings have flat faces and straight threaded UNF swivel nuts. The male fittings have the O-ring in a groove in the flat face. Seen as a major advantage, these fittings offer the possibility to build the hose assemblies into fixed distances/spaces, without having to move back other system components due the flat faces of the male and female fittings – the hose assembly can be slotted in.

Standard: **ISO 12151-1, ISO8434-3, SAE J516**

Parker end configurations: **JC, JM/J0, JS, JU, J1, J3, J5, J7, J9**



Tube O.D. (inch)	Tube O.D. (mm)	Thread UNF	Size	ØA (mm)	ØB (mm)
1/4	6	9/16x18	-4	13.00	14.20
3/8	10	11/16x16	-6	15.90	17.50
1/2	12	13/16x16	-8	19.10	20.60
5/8	16	1x14	-10	23.80	25.40
3/4	20	1-3/16x12	-12	28.20	30.10
1	25	1-7/16x12	-16	34.15	36.50
1-1/4	32	1-11/16x12	-20	40.50	42.90
1-1/2	38	2x12	-24	48.80	50.80

Flanges ISO 6162-1 and ISO 6162-2

Flange fittings

ISO 6162-1 and ISO 6162-2

The 4-bolt split flange (or full flange) fitting is used worldwide for connecting high-pressure hoses typically to pumps, motors and cylinders, where the hose assemblies are subjected to large pressure loadings.
The sealing mechanism is through compression of the O-ring in the face of the flange head against the surface of the port/ connection.
The flange fittings are generally separated into two pressure classes referred to as 21.0 MPa/ 3000 psi (SFL) or 42.0 MPa/ 6000 psi (SFS).
ISO 12151-3 refers to the flange fittings to as 21.0 MPa/ 3000 psi (SFL) or 42.0 MPa/ 6000 psi (SFS).
In addition to these flanges, customer-specific Komatsu® and CATERPILLAR® flanges can also be found in the market.

ISO 6162-1 (21.0 MPa/ 3000 psi) Parker end configurations:
15, 16, 17, 19, P5, P7, P9

ISO 6162-1 (35.0 MPa/ 5000 psi) Parker end configurations:
4A, 4F, 4N


ISO 6162-2 (42.0 MPa/ 6000 psi) Parker end configurations:
6A, 6F, 6N, PA, PF, PN, 89

Caterpillar flange Parker end configurations: **XA, XF, XG, XN**

- Standard ISO 6162-1 for 21.0 MPa/ 3000 psi to 35.0 MPa/ 5000 psi max., depending on size
- High Pressure ISO 6162-2 for 42.0 MPa/ 6000 psi max. regardless of size

Flange (inch)	Size	ISO 6262-1 MPa / psi	ISO 6162-2 MPa / psi
1/2	-8	34.5 / 5000	41.3 / 6000
3/4	-12	34.5 / 5000	41.3 / 6000
1	-16	34.5 / 5000	41.3 / 6000
1-1/4	-20	27.5 / 4000	41.3 / 6000
1-1/2	-24	20.7 / 3000	41.3 / 6000
2	-32	20.7 / 3000	41.3 / 6000

Note: 35.0 MPa/ 5000 psi in size -20/-24/-32 with 4A,4F and 4N fittings and 50H flange halves.



ISO 6162-1 – 21.0 MPa/ 3000 psi

Flange (inch)	Size	ØA (mm)	B (mm)	O-Ring
1/2	-8	30.18	6.73	18.64x3.53
3/4	-12	38.10	6.73	24.99x3.53
1	-16	44.45	8.00	32.92x3.53
1-1/4	-20	50.80	8.00	37.69x3.53
1-1/2	-24	60.33	8.00	47.22x3.53
2	-32	71.42	9.53	56.74x3.53
2-1/2	-40	84.12	9.53	69.44x3.53
3	-48	101.60	9.53	85.32x3.53

ISO 6162-2 – 42.0 MPa/ 6000 psi

Flange (inch)	Size	ØA (mm)	B (mm)	O-Ring
1/2	-8	31.75	7.75	18.64x3.53
3/4	-12	41.28	8.76	24.99x3.53
1	-16	47.63	9.53	32.92x3.53
1-1/4	-20	53.98	10.29	37.69x3.53
1-1/2	-24	63.50	12.57	47.22x3.53
2	-32	79.38	12.57	56.74x3.53

CATERPILLAR®

Flange (inch)	Size	ØA (mm)	B (mm)	O-Ring
3/4	-12	41.28	14.22	25.40x5.00
1	-16	47.63	14.22	31.90x5.00
1-1/4	-20	53.98	14.22	38.20x5.00
1-1/2	-24	63.50	14.22	44.70x5.00

Komatsu®

Flange (inch)	Size	ØA (mm)	B (mm)	O-Ring
5/8	-10	34.25	6.00	21.7x3.5


Although not in the SAE or the ISO standard the size -10 (5/8) flange head is gaining popularity. This flange is often found on Komatsu equipment or hydrostatic drives in agricultural machines.

4-bolt split flange

4-bolt split flange

A 4-bolt split flange is used to attach the flange fittings to their ports.

- Standard ISO 6162-1 for 21.0 MPa (3000 psi) to 35.0 MPa (5000 psi) max., depending on size
- High Pressure ISO 6162-2 for 42.0 MPa (6000 psi) max., regardless of size



port dimensions

ISO 6162-1 – 21.0 MPa (3000 psi)

Flange (inch)	Size	A (mm)	B (mm)	C (inch)	C (metr.)
1/2	-8	38.1	17.5	5/16x18	M8x1.25
3/4	-12	47.6	22.3	3/8x16	M10x1.5
1	-16	52.4	26.2	3/8x16	M10x1.5
1-1/4	-20	58.7	30.2	7/16x14	M10x1.5
1-1/2	-24	69.9	35.7	1/2x13	M12x1.75
2	-32	77.8	42.8	1/2x13	M12x1.75*

ISO 6162-2 – 42.0 MPa (6000 psi)

Flange (inch)	Size	A (mm)	B (mm)	C (inch)	C (metr.)
1/2	-8	40.5	18.2	5/16x18	M8x1.25
3/4	-12	50.8	23.8	3/8x16	M10x1.5
1	-16	57.2	27.8	7/16x14	M12x1.75
1-1/4	-20	66.7	31.8	1/2x13	M12x1.75*
1-1/2	-24	79.4	36.5	5/8x11	M16x2
2	-32	96.8	44.4	3/4x10	M20x2.5

*M14x2 still used in the market but no longer in accordance with ISO 6162

JIS (Japanese Industrial Standard)


The Japanese Industrial Standard (JIS) is seen on most Japanese equipment and uses a 30° sealing angle seat and either British Standard Pipe Parallel or metric threads. Care must be taken not to confuse the JIS fittings with BSP or JIC fittings.

JIS

The sealing mechanism of the fittings is the 30° metal-to-metal angled surfaces

Metric Parker end configurations:
MU, XU

BSP Parker end configurations:
FU



JIS 30° metric

Symbol	Thread metric	ØA (mm)	ØB (mm)
MU-6	M14x1.5	12.50	14.00
MU-9	M18x1.5	16.50	18.00
MU-12	M22x1.5	20.50	22.00
MU-15	M27x2	25.00	27.00
MU-19	M27x2	25.00	27.00
MU-25	M33x2	31.00	33.00
MU-32	M42x2	40.00	42.00
MU-38	M50x2	48.00	50.00
MU-50	M60x2	58.00	60.00

JIS 30° BSP

Symbol	Thread BSP	ØA (mm)	ØB (mm)
GUI-3	1/8x28	8.60	9.70
GUI-5/-6	1/4x19	11.50	13.20
GUI-8/-9	3/8x19	14.90	16.70
GUI-12	1/2x14	18.60	20.90
GUI-15/-19	3/4x14	24.10	26.40
GUI-25	1x11	30.30	33.20
GUI-32	1-1/4x11	38.90	41.90
GUI-38	1-1/2x11	44.90	47.80
GUI-50	2x11	56.70	59.60


It is a well-known fact that rubber properties deteriorate during the time of storage and service. A system of hose age control should be maintained to ensure that hose is used as long as it retains full capabilities for rendering the intended service.
However, it is impossible to advise the ideal storage period and service life of rubber hose as it is subject to a variety of factors which may affect the rubber characteristics and the suitability for use.
That is also why various standardization committees take very different approaches to rubber hose storage period and service life. The main national and international standards defining rules for rubber hose storage are the following:

DIN 20066

Fluid power systems – Hose assemblies – Dimensions, requirements

Specifies bulk hose shelf life and hose assembly storage period and service life:

- The shelf life of bulk hose before assembling must not exceed 4 years.
- The service life of a hose assembly, incl. any period of storage, should not exceed 6 years.
- The period of storage of a hose assembly must not exceed 2 years.



ISO 17165-2 / SAE J1273

Hydraulic fluid power – Hose assemblies – Recommended practices for hydraulic hose assemblies

The specified max. shelf life of bulk hose or a hose assembly is 10 years (40 quarters) from the date of manufacture (vulcanization) of the hose, provided it has been stored in accordance with ISO 2230 (Rubber products - Guidelines for storage) and passes visual inspection and if need be also a proof pressure test.
If visual inspection gives rise to any doubts as to the functionality of the hose (cracks in the cover or tube after hose flexing, excessive stiffness, reinforcement rust etc.), a proof pressure test should be carried out before use or the hose should be scrapped.

BS 5244

Recommendations for application, storage and life expiry of hydraulic rubber hoses and hose assemblies

Specifies tests needed for various storage periods of hose (in bulk or hose assembly):

- Storage period does not exceed 3 years – no tests needed.
- Storage period is between 3 and 5 years – proof pressure test needed.
- Storage period is between 5 and 8 years – proof pressure, burst, impulse, cold flexibility and electrical tests needed.
- Bulk hose or a hose assembly older than 8 years – must be scrapped.

For hose assembly service life no explicit limits are specified, whereas it is recommended to establish rules for each particular equipment and application on the basis of records taken from the real service.

Hint
German and the British standards are the most rigorous.

ISO 8331

Rubber and plastic hoses and hose assemblies – Guide to selection, storage, use and maintenance

Specifies storage periods similar to DIN 20066 – bulk hose max. 4 years, a hose assembly max. 2 years. If the storage exceeds these limits the hose must be inspected and tested (tests are not specified). Hose assembly service life is not specified.

OEM regulations

In addition to these national and international standards, also some Original Equipment Manufacturers (OEMs) have their own regulations for age of hose used for production of hose assemblies.
We recommend generally observe the regulations relevant for your country or ISO 17165-2 (if there is no domestic regulation), plus the regulation of your customer's country or of your OEM customer in the extent in which they are more demanding.

Hoses storage – best practices

Store hoses and hose assemblies in a cool, dark and dry room with capped ends in closed boxes (preferably in the original Parker packaging) and in the manner facilitating inspection of the hose condition and the first-in first-out (FIFO) inventory control system.
The main factors determining the hose storage are:

a) Temperature
Preferably between 15 °C and 25 °C, without rapid and frequent fluctuation.

b) Humidity
Preferably not higher than 65 %, protect hose against moisture and avoid atmospheric humidity condensation.

c) Heat
Store hose away from heat sources.

d) Light
Protect hose against direct sun light, light of discharge lamps and other ultraviolet sources.

e) Corrosive liquids and fumes
Do not store in the same room with corrosive chemicals.

f) Ozone
Avoid using high power electrical equipment and electrical spark sources in the storage room.

g) Oils and greases
Avoid direct contact.

h) Space and bends
Keep hose in stress-free shape never bent below the min. bend radius.

i) Electrical and magnetic fields
Store hose away from powerful electric transformers, motors and generators that could induce current in the hose metal reinforcement.

j) Rodents and insects
Protect against rodents and insects.

Fittings storage – best practices

For storing fittings the same rules as for hose are applicable (especially for fittings with rubber sealing), in addition:

a) Mismatching and confusing
Avoid unnecessary repacking and store fittings in clearly marked closed containers (preferably in the original Parker packaging).

b) Damage of threads and sealing surfaces
Avoid unnecessary reloading and handling.

c) Fittings with O-rings
Assure that storage period of fittings with O-rings or other rubber sealing does not exceed 2 years (remember: first in-first out) and make sure that hose assemblies or hose fittings with O-rings will be stored in a cool, dry and dark room.

d) Caps
Hose assemblies fittings should be capped against damage and contamination.






Safety First!

A hydraulic hose assembly is a power component and may cause property damage, personal injury or death!

WARNING: Injuries in which hydraulic or other liquid is involved must be treated without delay and not the same way as an ordinary injury!

1. High pressure fluid injection can be almost invisible, leaking from a pinhole, but it can pierce the skin deep into the muscle!
2. If a fluid-injection accident occurs, search immediately for a medical treatment by a doctor!
3. Don't touch pressurized hydraulic hose assemblies and don't look at them from a short distance – especially not close to fittings!
4. Secure ends of hydraulic assemblies with high pulsing pressure and all high pressure air hose assemblies against blow-off of the hose from the fitting with appropriate whip restraints!
5. Stay out of hazardous areas while testing hose assemblies under pressure and wear proper protective clothing and goggles!

We in Parker are making all efforts to develop, manufacture and deliver defect-free, durable and safe products and services – starting from integrated design and testing of all components through sharing our know-how with our customers and providing them with comprehensive support and training.



Please also make all efforts on your side to provide reliable and safe hose assemblies to your customers and forward to them the know-how you acquired, whether from us or due to your own unique experience, especially as regards the proper use and maintenance of hose assemblies.



Avoid injury to yourself and others by following these important rules

Carefully read and observe especially the following sections of this catalogue

- For selection of proper hose and fittings:
  - Safe Hose Assembly Working Steps (pages ***Aa-9*** ff)
  - Technical Data (pages ***Aa-2*** ff)

- For manufacturing of hose assemblies:
  - Working Steps for 1piece **Parkrimp** *No-Skive* Fittings (pages ***Aa-12*** ff)
  - Working Steps for 2piece **ParLock** Fittings (pages ***Aa-15*** ff)
  - Crimp Source (page ***Ed-1***)

- For storing, packing and handling:
  - Hose and Fittings Storage (pages ***Aa-34*** ff)

- For installation on machines:
  - Routing / Installation / Environmental Influences (pages ***Aa-17*** ff)

- Inspection, maintenance and replacement:
  - Preventive Maintenance Program (page ***Aa-26***)

Hose Hint
There are several analogies between hydraulic and electric systems and it is not inappropriate to compare high-pressure hydraulic hoses to high-voltage electrical cables and to advise to regard and handle them with similar caution and care!

- **READ CAREFULLY AND OBSERVE:**
  - **Parker Safety Guide** for Selecting and Using Hose, Tubing, Fittings and Related Accessories (pages ***Aa-38*** ff)

- **INVESTIGATE, STUDY AND OBSERVE all relevant international and national standards and directives** of your local trade, technical and work safety associations, such as:
  - **ISO 17165-1** *Hydraulic Fluid Power – Hose Assemblies*
  - **ISO 17165-2** *Hydraulic Fluid Power – Hose Assemblies*
  - **ISO 4413** *Hydraulic fluid power – General rules and safety requirements for systems and their components*
  - **SAE J1273** *Recommended Practices for Hydraulic Hose Assemblies*

  In Germany
  - **BGR 237** *Hydraulik-Schlauchleitungen – Regeln für den sicheren Einsatz*
  - **FA 015** *Hydraulik-Schlauchleitungen Prüfen und Auswechseln*
  - **BGI 5100** *Sicherheit bei der Hydraulik-Instandhaltung*

  In UK
  - **BFPDA D8** *Quality Control Procedures and Requirements for BFPDA Distributors*
  - **BFPDA D14** *A Simple Rule for Re-ending Hydraulic Hose Assemblies – Don't*
  - **BFPDA P47** *Guidelines for the Use of Hydraulic Fluid Power Hose and Hose Assemblies*

Parker Safety Guide for Selecting and Using Hose, Tubing, Fittings and Related Accessories

Parker Publication No. 4400-B.1 / Revised: September, 2015

WARNING

Failure or improper selection or improper use of hose, tubing, fittings, assemblies, valves, connectors, conductors or related accessories ("Products") can cause death, personal injury and property damage. Possible consequences of failure or improper selection or improper use of these Products include but are not limited to:

- **Fittings thrown off at high speed.**
- **High velocity fluid discharge.**
- **Explosion or burning of the conveyed fluid.**
- **Electrocution from high voltage electric powerlines.**
- **Contact with suddenly moving or falling objects that are controlled by the conveyed fluid.**
- **Injections by high-pressure fluid discharge.**
- **Dangerously whipping Hose.**
- **Tube or pipe burst.**
- **Weld joint fracture.**
- **Contact with conveyed fluids that may be hot, cold, toxic or otherwise injurious.**
- **Sparking or explosion caused by static electricity buildup or other sources of electricity.**
- **Sparking or explosion while spraying paint or flammable liquids.**
- **Injuries resulting from inhalation, ingestion or exposure to fluids.**

Before selecting or using any of these Products, it is important that you read and follow the instructions below. No product from any division in Fluid Connector Group is approved for in-flight aerospace applications. For hoses and fittings used in in-flight aerospace applications, please contact Parker Aerospace Group

1.0 GENERAL INSTRUCTIONS

Scope: This safety guide provides instructions for selecting and using (including assembling, installing, and maintaining) these Products. For convenience, all rubber and/or thermoplastic products commonly called "hose" or "tubing" are called "Hose" in this safety guide. Metallic tube or pipe are called "tube". All assemblies made with Hose are called "Hose Assemblies". All assemblies made with Tube are called "Tube Assemblies". All products commonly called "fittings", "couplings" or "adapters" are called "Fittings". Valves are fluid system components that control the passage of fluid. Related accessories are ancillary devices that enhance or monitor performance including crimping, flaring, flanging, presetting, bending, cutting, deburring, swaging machines, sensors, tags, lockout handles, spring guards and associated tooling. This safety guide is a supplement to and is to be used with the specific Parker publications for the specific Hose, Fittings and Related Accessories that are being considered for use. Parker publications are available at www.parker.com. SAE J1273 (www.sae.org) and ISO 17165-2 (www.ansi.org) also provide recommended practices for hydraulic Hose Assemblies, and should be followed.

1.1 Fail-Safe: Hose, Hose Assemblies, Tube, Tube Assemblies and Fittings can and do fail without warning for many reasons. Design all systems and equipment in a fail-safe mode, so that failure of the Hose, Hose Assembly, Tube, Tube Assembly or Fitting will not endanger persons or property.

1.2 Distribution: Provide a copy of this safety guide to each person responsible for selecting or using Hose, Tube and Fitting products. Do not select or use Parker Hose, Tube or Fittings without thoroughly reading and understanding this safety guide as well as the specific Parker publications for the Products.

1.3 User Responsibility: Due to the wide variety of operating conditions and applications for Hose, Tube and Fittings. Parker does not represent or warrant that any particular Hose, Tube or Fitting is suitable for any specific end use system. This safety guide does not analyze all technical parameters that must be considered in selecting a product. The user, through its own analysis and testing, is solely responsible for:

- Making the final selection of the Products.
- Assuring that the user's requirements are met and that the application presents no health or safety hazards.
- Following the safety guide for Related Accessories and being trained to operate Related Accessories.
- Providing all appropriate health and safety warnings on the equipment on which the Products are used.
- Assuring compliance with all applicable government and industry standards.

1.4 Additional Questions: Call the appropriate Parker technical service department if you have any questions or require any additional information. See the Parker publication for the Products being considered or used, or call 1-800-CPARKER, or go to www.parker.com, for telephone numbers of the appropriate technical service department.

2.0 HOSE, TUBE AND FITTINGS SELECTION INSTRUCTIONS

2.1 Electrical Conductivity: Certain applications require that the Hose be nonconductive to prevent electrical current flow. Other applications require the Hose and the Fittings and the Hose/Fitting interface to be sufficiently conductive to drain off static electricity. Extreme care must be exercised when selecting Hose, Tube and Fittings for these or any other applications in which electrical conductivity or nonconductivity is a factor. The electrical conductivity or nonconductivity of Hose, Tube and Fittings is dependent upon many factors and may be susceptible to change. These factors include but are not limited to the various materials used to make the Hose and the Fittings, Fitting finish (some Fitting finishes are electrically conductive while others are nonconductive), manufacturing methods (including moisture control), how the Fittings contact the Hose, age and amount of deterioration or damage or other changes, moisture content of the Hose at any particular time, and other factors. The following are considerations for electrically nonconductive and conductive Hose. For other applications consult the individual catalog pages and the appropriate industry or regulatory standards for proper selection.

2.1.1 Electrically Nonconductive Hose: Certain applications require that the Hose be nonconductive to prevent electrical current flow or to maintain electrical isolation. For applications that require Hose to be electrically nonconductive, including but not limited to applications near high voltage electric lines, only special nonconductive Hose can be used. The manufacturer of the equipment in which the nonconductive Hose is to be used must be consulted to be certain that the Hose, Tube and Fittings that are selected are proper for the application. Do not use any Parker Hose or Fittings for any such application requiring nonconductive Hose, including but not limited to applications near high voltage electric lines or dense magnetic fields, unless (i) the application is expressly approved in the Parker technical publication for the product, (ii) the Hose is marked "nonconductive", and (iii) the manufacturer of the equipment on which the Hose is to be used specifically approves the particular Parker Hose, Tube and Fittings for such use.

2.1.2 Electrically Conductive Hose: Parker manufactures special Hose for certain applications that require electrically conductive Hose. Parker manufactures special Hose for conveying paint in airless paint spraying applications. This Hose is labeled "Electrically Conductive Airless Paint Spray Hose" on its layline and packaging. This Hose must be properly connected to the appropriate Parker Fittings and properly grounded in order to dissipate dangerous static charge buildup, which occurs in all airless paint spraying applications. Do not use any other Hose for airless paint spraying, even if electrically conductive. Use of any other Hose or failure to properly connect the Hose can cause a fire or an explosion resulting in death, personal injury, and property damage. All hoses that convey fuels must be grounded. Parker manufactures a special Hose for certain compressed natural gas ("CNG")

applications where static electricity buildup may occur. Parker CNG Hose assemblies comply with the requirements of ANSI/IAS NGV 4.2; CSA 12.52, “Hoses for Natural Gas Vehicles and Dispensing Systems” (www.ansi.org). This Hose is labeled “Electrically Conductive for CNG Use” on its layline and packaging. This Hose must be properly connected to the appropriate Parker Fittings and properly grounded in order to dissipate dangerous static charge buildup, which occurs in, for example, high velocity CNG dispensing or transfer. Do not use any other Hose for CNG applications where static charge buildup may occur, even if electrically conductive. Use of other Hoses in CNG applications or failure to properly connect or ground this Hose can cause a fire or an explosion resulting in death, personal injury, and property damage. Care must also be taken to protect against CNG permeation through the Hose wall. See section 2.6, Permeation, for more information. Parker CNG Hose is intended for dispenser and vehicle use within the specified temperature range. Parker CNG Hose should not be used in confined spaces or unventilated areas or areas exceeding the specified temperature range. Final assemblies must be tested for leaks. CNG Hose Assemblies should be tested on a monthly basis for conductivity per ANSI/IAS NGV 4.2; CSA 12.52. Parker manufactures special Hose for aerospace in-flight applications. Aerospace in-flight applications employing Hose to transmit fuel, lubricating fluids and hydraulic fluids require a special Hose with a conductive inner tube. This Hose for in-flight applications is available only from Parker's Stratoflex Products Division. Do not use any other Parker Hose for in-flight applications, even if electrically conductive. Use of other Hoses for in-flight applications or failure to properly connect or ground this Hose can cause a fire or an explosion resulting in death, personal injury and property damage. These Hose assemblies for in-flight applications must meet all applicable aerospace industry, aircraft engine and aircraft requirements.

2.2 Pressure: Hose, Tube and Fitting selection must be made so that the published maximum working pressure of the Hose, Tube and Fittings are equal to or greater than the maximum system pressure. The maximum working pressure of a Hose, or Tube Assembly is the lower of the respective published maximum working pressures of the Hose, Tube and the Fittings used. Surge pressures or peak transient pressures in the system must be below the published maximum working pressure for the Hose, Tube and Fitting. Surge pressures and peak pressures can usually only be determined by sensitive electrical instrumentation that measures and indicates pressures at millisecond intervals. Mechanical pressure gauges indicate only average pressures and cannot be used to determine surge pressures or peak transient pressures. Published burst pressure ratings for Hose is for manufacturing test purposes only and is no indication that the Product can be used in applications at the burst pressure or otherwise above the published maximum recommended working pressure.

2.3 Suction: Hoses used for suction applications must be selected to insure that the Hose will withstand the vacuum and pressure of the system. Improperly selected Hose may collapse in suction application.

2.4 Temperature: Be certain that fluid and ambient temperatures, both steady and transient, do not exceed the limitations of the Hose, Tube, Fitting and Seals. Temperatures below and above the recommended limit can degrade Hose, Tube, Fittings and Seals to a point where a failure may occur and release fluid. Tube and Fittings performances are normally degraded at elevated temperature. Material compatibility can also change at temperatures outside of the rated range. Properly insulate and protect the Hose Assembly when routing near hot objects (e.g. manifolds). Do not use any Hose in any application where failure of the Hose could result in the conveyed fluids (or vapors or mist from the conveyed fluids) contacting any open flame, molten metal, or other potential fire ignition source that could cause burning or explosion of the conveyed fluids or vapors.

2.5 Fluid Compatibility: Hose, and Tube Assembly selection must assure compatibility of the Hose tube, cover, reinforcement, Tube, Plating and Seals with the fluid media used. See the fluid compatibility chart in the Parker publication for the product being considered or used. This information is offered only as a guide. Actual service life can only be determined by the end user by testing under all extreme conditions and other analysis. Hose, and Tube that is chemically compatible with a particular fluid must be assembled using Fittings and adapters containing likewise compatible seals. Flange or flare processes can change Tube material properties that may not be compatible with certain requirements such as NACE

2.6 Permeation: Permeation (that is, seepage through the Hose or Seal) will occur from inside the Hose or Fitting to outside when Hose or Fitting is used with gases, liquid and gas fuels, and refrigerants (including but not limited to such materials as helium, diesel fuel, gasoline, natural gas, or LPG). This permeation may result in high concentrations of vapors which are potentially flammable, explosive, or toxic, and in loss of fluid. Dangerous explosions, fires, and other hazards can result when using the wrong Hose for such applications. The system designer must take into account the fact that this permeation will take place and must not use Hose or Fitting if this permeation could be hazardous. The system designer must take into account all legal, government, insurance, or any other special regulations which govern the use of fuels and refrigerants. Never use a Hose or Fitting even though the fluid compatibility is acceptable without considering the potential hazardous effects that can result from permeation through the Hose or Tube Assembly. Permeation of moisture from outside the Hose or Fitting to inside the Hose or Fitting will also occur in Hose or Tube assemblies, regardless of internal pressure. If this moisture permeation would have detrimental effects (particularly, but not limited to refrigeration and air conditioning systems), incorporation of sufficient drying capacity in the system or other appropriate system safeguards should be selected and used. The sudden pressure release of highly pressurized gas could also result in Explosive Decompression failure of permeated Seals and Hoses.

2.7 Size: Transmission of power by means of pressurized fluid varies with pressure and rate of flow. The size of the components must be adequate to keep pressure losses to a minimum and avoid damage due to heat generation or excessive fluid velocity. .

2.8 Routing: Attention must be given to optimum routing to minimize inherent problems (kinking or flow restriction due to Hose collapse, twisting of the Hose, proximity to hot objects or heat sources). For additional routing recommendations see SAE J1273 and ISO 17165-2. Hose Assemblies have a finite life and should be installed in a manner that allows for ease of inspection and future replacement. Hose because of its relative short life, should not be used in residential and commercial buildings inside of inaccessible walls or floors, unless specifically allowed in the product literature. Always review all product literature for proper installation and routing instructions.

2.9 Environment: Care must be taken to insure that the Hose, Tube and Fittings are either compatible with or protected from the environment (that is, surrounding conditions) to which they are exposed. Environmental conditions including but not limited to ultraviolet radiation, sunlight, heat, ozone, moisture, water, salt water, chemicals and air pollutants can cause degradation and premature failure.

2.10 Mechanical Loads: External forces can significantly reduce Hose, Tube and Fitting life or cause failure. Mechanical loads which must be considered include excessive flexing, twist, kinking, tensile or side loads, bend radius, and vibration. Use of swivel type Fittings or adapters may be required to insure no twist is put into the Hose. Use of proper Hose or Tube clamps may also be required to reduce external mechanical loads. Unusual applications may require special testing prior to Hose selection.

2.11 Physical Damage: Care must be taken to protect Hose from wear, snagging, kinking, bending smaller that minimum bend radius and cutting, any of which can cause premature Hose failure. Any Hose that has been kinked or bent to a radius smaller than the minimum bend radius, and any Hose that has been cut or is cracked or is otherwise damaged should be removed and discarded. Fittings with damages such as scratches on sealing surfaces and deformation should be replaced.

2.12 Proper End Fitting: See instructions 3.2 through 3.5. These recommendations may be substantiated by testing to industry standards such as SAE J517 for hydraulic applications, or MIL-A-5070, AS1339, or AS3517 for Hoses from Parker's Stratoflex Products Division for aerospace applications.

2.13 Length: When determining the proper Hose or Tube length of an assembly, be aware of Hose length change due to pressure, Tube length change due to thermal expansion or contraction, and Hose or Tube and machine tolerances and movement must be considered. When routing short hose assemblies, it is recommended that the minimum free hose length is always used. Consult the hose manufacturer for their minimum free hose length recommendations. Hose assemblies should be installed in such a way that any motion or flexing occurs within the same plane.

2.14 Specifications and Standards: When selecting Hose, Tube and Fittings, government, industry, and Parker specifications and recommendations must be reviewed and followed as applicable.

2.15 Hose Cleanliness: Hose and Tube components may vary in cleanliness levels. Care must be taken to insure that the Hose and Tube Assembly selected has an adequate level of cleanliness for the application.

2.16 Fire Resistant Fluids: Some fire resistant fluids that are to be conveyed by Hose or Tube require use of the same type of Hose or Tube as used with petroleum base fluids. Some such fluids require a special Hose, Tube, Fitting and Seal, while a few fluids will not work with any Hose at all. See instructions 2.5 and 1.5. The wrong Hose, Tube, Fitting or Seal may fail after a very short service. In addition, all liquids but pure water may burn fiercely under certain conditions, and even pure water leakage may be hazardous.

2.17 Radiant Heat: Hose and Seals can be heated to destruction without contact by such nearby items as hot manifolds or molten metal. The same heat source may then initiate a fire. This can occur despite the presence of cool air around the Hose or Seal. Performance of Tube and Fitting subjected to the heat could be degraded.

2.18 Welding or Brazing: When using a torch or arc welder in close proximity to hydraulic lines, the hydraulic lines should be removed or shielded with appropriate fire resistant materials. Flame or weld spatter could burn through the Hose or Seal and possibly ignite escaping fluid resulting in a catastrophic failure. Heating of plated parts, including Hose Fittings and adapters, above 450°F (232°C) such as during welding, brazing or soldering may emit deadly gases. Any elastomer seal on fittings shall be removed prior to welding or brazing, any metallic surfaces shall be protected after brazing or welding when necessary. Welding and brazing filler material shall be compatible with the Tube and Fitting that are joined.

2.19 Atomic Radiation: Atomic radiation affects all materials used in Hose and Tube assemblies. Since the long-term effects may be unknown, do not expose Hose or Tube assemblies to atomic radiation. Nuclear applications may require special Tube and Fittings.

2.20 Aerospace Applications: The only Hose, Tube and Fittings that may be used for in-flight aerospace applications are those available from Parker's Stratoflex Products Division. Do not use any other Hose or Fittings for in-flight applications. Do not use any Hose or Fittings from Parker's Stratoflex Products Division with any other Hose or Fittings, unless expressly approved in writing by the engineering manager or chief engineer of Stratoflex Products Division and verified by the user's own testing and inspection to aerospace industry standards.

2.21 Unlocking Couplings: Ball locking couplings or other Fittings with quick disconnect ability can unintentionally disconnect if they are dragged over obstructions, or if the sleeve or other disconnect member, is bumped or moved enough to cause disconnect. Threaded Fittings should be considered where there is a potential for accidental uncoupling.

3.0 HOSE AND FITTINGS ASSEMBLY AND INSTALLATION INSTRUCTIONS

3.1 Component Inspection: Prior to assembly, a careful examination of the Hose and Fittings must be performed. All components must be checked for correct style, size, catalog number, and length. The Hose must be examined for cleanliness, obstructions, blisters, cover looseness, kinks, cracks, cuts or any other visible defects. Inspect the Fitting and sealing surfaces for burrs, nicks, corrosion or other imperfections. Do NOT use any component that displays any signs of nonconformance.

3.2 Hose and Fitting Assembly: Do not assemble a Parker Fitting on a Parker Hose that is not specifically listed by Parker for that Fitting, unless authorized in writing by the engineering manager or chief engineer of the appropriate Parker division. Do not assemble a Parker Fitting on another manufacturer's Hose or a Parker Hose on another manufacturer's Fitting unless (i) the engineering manager or chief engineer of the appropriate Parker division approves the Assembly in writing or that combination is expressly approved in the appropriate Parker literature for the specific Parker product, and

(ii) the user verifies the Assembly and the application through analysis and testing. For Parker Hose that does not specify a Parker Fitting, the user is solely responsible for the selection of the proper Fitting and Hose Assembly procedures. See instruction 1.4. To prevent the possibility of problems such as leakage at the Fitting or system contamination, it is important to completely remove all debris from the cutting operation before installation of the Fittings. The Parker published instructions must be followed for assembling the Fittings on the Hose. These instructions are provided in the Parker Fitting catalog for the specific Parker Fitting being used, or by calling 1-800-CPARKER, or at www.parker.com.

3.3 Related Accessories: Do not crimp or swage any Parker Hose or Fitting with anything but the listed swage or crimp machine and dies in accordance with Parker published instructions. Do not crimp or swage another manufacturer's Fitting with a Parker crimp or swage die unless authorized in writing by the engineering manager or chief engineer of the appropriate Parker division.

3.4 Parts: Do not use any Parker Fitting part (including but not limited to socket, shell, nipple, or insert) except with the correct Parker mating parts, in accordance with Parker published instructions, unless authorized in writing by the engineering manager or chief engineer of the appropriate Parker division.

3.5 Field Attachable/Permanent: Do not reuse any field attachable Hose Fitting that has blown or pulled off a Hose. Do not reuse a Parker permanent Hose Fitting (crimped or swaged) or any part thereof. Complete Hose Assemblies may only be reused after proper inspection under section 4.0. Do not assemble Fittings to any previously used hydraulic Hose that was in service, for use in a fluid power application.

3.6 Pre-Installation Inspection: Prior to installation, a careful examination of the Hose Assembly must be performed. Inspect the Hose Assembly for any damage or defects. DO NOT use any Hose Assembly that displays any signs of nonconformance.

3.7 Minimum Bend Radius: Installation of a Hose at less than the minimum listed bend radius may significantly reduce the Hose life. Particular attention must be given to preclude sharp bending at the Hose to Fitting juncture. Any bending during installation at less than the minimum bend radius must be avoided. If any Hose is kinked during installation, the Hose must be discarded.

3.8 Twist Angle and Orientation: Hose Assembly installation must be such that relative motion of machine components does not produce twisting.

3.9 Securement: In many applications, it may be necessary to restrain, protect, or guide the Hose to protect it from damage by unnecessary flexing, pressure surges, and contact with other mechanical components. Care must be taken to insure such restraints do not introduce additional stress or wear points.

3.10 Proper Connection of Ports: Proper physical installation of the Hose Assembly requires a correctly installed port connection insuring that no twist or torque is transferred to the Hose when the Fittings are being tightened or otherwise during use.

3.11 External Damage: Proper installation is not complete without insuring that tensile loads, side loads, kinking, flattening, potential abrasion, thread damage or damage to sealing surfaces are corrected or eliminated. See instruction 2.10.

3.12 System Checkout: All air entrapment must be eliminated and the system pressurized to the maximum system pressure (at or below the Hose maximum working pressure) and checked for proper function and freedom from leaks. Personnel must stay out of potential hazardous areas while testing and using.

3.13 Routing: The Hose Assembly should be routed in such a manner so if a failure does occur, the escaping media will not cause personal injury or property damage. In addition, if fluid media comes in contact with hot surfaces, open flame or sparks, a fire or explosion may occur. See section 2.4.

3.14 Ground Fault Equipment Protection Devices (GFEPDs): WARNING! Fire and Shock Hazard. To minimize the danger of fire if the heating cable of a Multitube bundle is damaged or improperly installed, use a Ground Fault Equipment Protection Device. Electrical fault currents may be insufficient to trip a conventional circuit breaker. For ground fault protection, the IEEE 515: (www.ansi.org) standard for heating cables recommends the use of GFEPDs with a nominal 30 milliampere trip level for "piping systems in classified areas, those areas requiring a high degree of maintenance, or which may be exposed to physical abuse or corrosive atmospheres".

4.0 TUBE AND FITTINGS ASSEMBLY AND INSTALLATION INSTRUCTIONS

4.1 Component Inspection: Prior to assembly, a careful examination of the Tube and Fittings must be performed. All components must be checked for correct style, size, material, seal, and length. Inspect the Fitting and sealing surfaces for burrs, nicks, corrosion, missing seal or other imperfections. Do NOT use any component that displays any signs of nonconformance.

4.2 Tube and Fitting Assembly: Do not assemble a Parker Fitting with a Tube that is not specifically listed by Parker for that Fitting, unless authorized in writing by the engineering manager or chief engineer of the appropriate Parker division. The Tube must meet the requirements specified to the Fitting. The Parker published instructions must be followed for assembling the Fittings to a Tube. These instructions

are provided in the Parker Fitting catalog for the specific Parker Fitting being used, or by calling 1-800-CPARKER, or at www.parker.com.

4.3 Related Accessories: Do not preset or flange Parker Fitting components using another manufacturer's equipment or procedures unless authorized in writing by the engineering manager or chief engineer of the appropriate Parker division. Tube, Fitting component and tooling must be check for correct style, size and material. Operation and maintenance of Related Accessories must be in accordance with the operation manual for the designated Accessory.

4.4 Securement: In many applications, it may be necessary to restrain, protect, or guide the Tube to protect it from damage by unnecessary flexing, pressure surges, vibration, and contact with other mechanical components. Care must be taken to insure such restraints do not introduce additional stress or wear points.

4.5 Proper Connection of Ports: Proper physical installation of the Tube Assembly requires a correctly installed port connection insuring that no torque is transferred to the Tube when the Fittings are being tightened or otherwise during use.

4.6 External Damage: Proper installation is not complete without insuring that tensile loads, side loads, flattening, potential abrasion, thread damage or damage to sealing surfaces are corrected or eliminated. See instruction 2.10.

4.7 System Checkout: All air entrapment must be eliminated and the system pressurized to the maximum system pressure (at or below the Tube Assembly maximum working pressure) and checked for proper function and freedom from leaks. Personnel must stay out of potential hazardous areas while testing and using.

Routing: The Tube Assembly should be routed in such a manner so if a failure does occur, the escaping media will not cause personal injury or property damage. In addition, if fluid media comes in contact with hot surfaces, open flame or sparks, a fire or explosion may occur. See section 2.4.

5.0 HOSE AND FITTING MAINTENANCE AND REPLACEMENT INSTRUCTIONS

5.1 Even with proper selection and installation, Hose life may be significantly reduced without a continuing maintenance program. The severity of the application, risk potential from a possible Hose failure, and experience with any Hose failures in the application or in similar applications should determine the frequency of the inspection and the replacement for the Products so that Products are replaced before any failure occurs. Certain products require maintenance and inspection per industry requirements. Failure to adhere to these requirements may lead to premature failure. A maintenance program must be established and followed by the user and, at minimum, must include instructions 5.2 through 5.7

5.2 Visual Inspection Hose/Fitting: Any of the following conditions require immediate shut down and replacement of the Hose Assembly:

- Fitting slippage on Hose;
- Damaged, cracked, cut or abraded cover (any reinforcement exposed);
- Hard, stiff, heat cracked, or charred Hose;
- Cracked, damaged, or badly corroded Fittings;
- Leaks at Fitting or in Hose;
- Kinked, crushed, flattened or twisted Hose; and
- Blistered, soft, degraded, or loose cover.

5.3 Visual Inspection All Other: The following items must be tightened, repaired, corrected or replaced as required:

- Leaking port conditions;
- Excess dirt buildup;
- Worn clamps, guards or shields; and
- System fluid level, fluid type, and any air entrapment.

5.4 Functional Test: Operate the system at maximum operating pressure and check for possible malfunctions and leaks. Personnel must avoid potential hazardous areas while testing and using the system. See section 2.2.

5.5 Replacement Intervals: Hose assemblies and elastomeric seals used on Hose Fittings and adapters will eventually age, harden, wear and deteriorate under thermal cycling and compression set. Hose Assemblies and elastomeric seals should be inspected and replaced at specific replacement intervals, based on previous service life, government or industry recommendations, or when failures could result in unacceptable downtime, damage, or injury risk. See section 1.2. Hose and Fittings may be subjected to internal mechanical and/or chemical wear from the conveying fluid and may fail without warning. The user must determine the product life under such circumstances by testing. Also see section 2.5.

5.6 Hose Inspection and Failure: Hydraulic power is accomplished by utilizing high pressure fluids to transfer energy and do work. Hoses, Fittings and Hose Assemblies all contribute to this by transmitting fluids at high pressures. Fluids under pressure can be dangerous and potentially lethal and, therefore, extreme caution must be exercised when working with fluids under pressure and handling the Hoses transporting the fluids. From time to time, Hose Assemblies will fail if they are not replaced at proper time intervals. Usually these failures are the result of some form of misapplication, abuse, wear or failure to perform proper maintenance. When Hoses fail, generally the high pressure fluids inside escape in a stream which may or may not be visible to the user. Under no circumstances should the user attempt to locate the leak by "feeling" with their hands or any other part of their body. High pressure fluids can and will penetrate the skin and cause severe tissue damage and possibly loss of limb. Even seemingly minor hydraulic fluid injection injuries must be treated immediately by a physician with knowledge of the tissue damaging properties of hydraulic fluid.

If a Hose failure occurs, immediately shut down the equipment and leave the area until pressure has been completely released from the Hose Assembly. Simply shutting down the hydraulic pump may or may not eliminate the pressure in the Hose Assembly. Many times check valves, etc., are employed in a system and can cause pressure to remain in a Hose Assembly even when pumps or equipment are not operating. Tiny holes in the Hose, commonly known as pinholes, can eject small, dangerously powerful but hard to see streams of hydraulic fluid. It may take several minutes or even hours for the pressure to be relieved so that the Hose Assembly may be examined safely. Once the pressure has been reduced to zero, the Hose Assembly may be taken off the equipment and examined. It must always be replaced if a failure has occurred. Never attempt to patch or repair a Hose Assembly that has failed. Consult the nearest Parker distributor or the appropriate Parker division for Hose Assembly replacement information. Never touch or examine a failed Hose Assembly unless it is obvious that the Hose no longer contains fluid under pressure. The high pressure fluid is extremely dangerous and can cause serious and potentially fatal injury.

5.7 Elastomeric seals: Elastomeric seals will eventually age, harden, wear and deteriorate under thermal cycling and compression set. Elastomeric seals should be inspected and replaced.

5.8 Refrigerant gases: Special care should be taken when working with refrigeration systems. Sudden escape of refrigerant gases can cause blindness if the escaping gases contact the eye and can cause freezing or other severe injuries if it contacts any other portion of the body.

5.9 Compressed natural gas (CNG): Parker CNG Hose Assemblies should be tested after installation and before use, and at least on a monthly basis per instructions provided on the Hose Assembly tag. The recommended procedure is to pressurize the Hose and check for leaks and to visually inspect the Hose for damage and to perform an electrical resistance test.

Caution: Matches, candles, open flame or other sources of ignition shall not be used for Hose inspection. Leak check solutions should be rinsed off after use.

6.0 HOSE STORAGE

6.1 Age Control: Hose and Hose Assemblies must be stored in a manner that facilitates age control and first-in and first-out usage based on manufacturing date of the Hose and Hose Assemblies. Unless otherwise specified by the manufacturer or defined by local laws and regulations:

6.1.1 The shelf life of rubber hose in bulk form or hose made from two or more materials is 28 quarters (7 years) from the date of manufacture, with an extension of 12 quarters (3 years), if stored in accordance with ISO 2230;

6.1.2 The shelf life of thermoplastic and polytetrafluoroethylene hose is considered to be unlimited;

6.1.3 Hose assemblies that pass visual inspection and proof test shall not be stored for longer than 2 years.

6.1.4 Storage: Stored Hose and Hose Assemblies must not be subjected to damage that could reduce their expected service life and must be placed in a cool, dark and dry area with the ends capped. Stored Hose and Hose Assemblies must not be exposed to temperature extremes, ozone, oils, corrosive liquids or fumes, solvents, high humidity, rodents, insects, ultraviolet light, electromagnetic fields or radioactive materials.

Technical Data

Technical Data	
Hose Overview	Ab-2 – Ab-4
Hose Fittings Overview	Ab-5 – Ab-8
Hose Fittings Pressure Ratings	Ab-9 – Ab-11
Hose Fittings Nomenclature	Ab-12 – Ab-15
Classification Bodies	Ab-16
Approvals for Parker Hydraulic Hoses	Ab-17 – Ab-19
Conversion Chart	Ab-20
Temperature / Pressure Chart	Ab-21
Flow Capacity Nomogram	Ab-22
The Correct Method to Fit Female Swivel Ends	Ab-23
The Correct Method to Fit ISO 6162-1 and ISO 6162-2 Flanges	Ab-24 – Ab-25
Chemical Resistance Table	Ab-26 – Ab-34

Hose Overview
Low pressure

		Hose	Fitting serie	Working Pressure (MPa) at size / DN																Temp.	Construction	Standard
				-3	-4	-5	-6	-8	-10	-12	-16	-20	-24	-32	-40	-48	-56	-64	-80	-96			
				5	6	8	10	12	16	19	25	31	38	51	63	76	90	100	125	150			
Push-Lok	Multipurpose	801Plus	*82*		2.4		2.4	2.1	2.1	2.1	1.4										-40/+100	1 braid, fibre	
		830M	*82*		1.6		1.6	1.6	1.6	1.6											-40/+80	1 braid, fibre	
		831	*82*		2.4		2.0	2.0	2.0	2.0	1.4										-40/+100	1 braid, fibre	
		837BM	*82*		1.6		1.6	1.6	1.6	1.6	1.6										-40/+100	1 braid, fibre	
		837PU	*82*		1.6		1.6	1.6	1.6	1.6	1.6										-40/+100	1 braid, fibre	
	Phosphate Ester	804	*82*		1.7		1.7	1.7		1.7											-40/+80	1 braid, fibre	
	Fire retardant	821FR	*82*		2.4		2.0	2.0		1.7											-40/+100	1 braid, fibre	
	High temperature	836	*82*		1.7		1.7	1.7	1.7	1.7											-48/+150	1 braid, fibre	
	Non-conductive	838M	*82*		1.6		1.6	1.6	1.6	1.6											-40/+80	1 braid, fibre	
Transport + Hydraulic	Standard	601	*(43, 48)*		8.6		7.8	6.9		5.2	3.9										-40/+125	2 braids, fibre	EN 854-R3 - SAE 100R3
		681	*47*		7.5	6.8	6.3	5.8	5.0	4.5	4.0										-40/+100	1 braid, fibre	EN 854-2TE
	High temperature	611HT	*47*		2.8		2.8	2.8	2.4	2.1											-40/+150	1 braid, fibre	EN 854-R6
	Railway	681DB	*47*		7.5	6.8	6.3	5.8	5.0	4.5	4.0										-40/+100	1 braid, fibre	EN 854-2TE
	Transportation	201	*26*		20.7	20.7	15.5	13.8	12.0	10.3	5.5	4.3	3.5	2.4							-40/+150	1 braid, wire	SAE 100R5 - SAE J1402 AII
		206	*26*		20.7	20.7	15.5	13.8	12.0	10.3	5.5	4.3	3.5	2.4							-48/+150	1 braid, wire	SAE 100R5 - SAE J1402 AII
		213	*26*		13.8	10.3	10.3	8.6	6.9	5.2	2.8	2.1	1.7	1.4							-45/+150	1 braid, wire	SAE J1402 AI
		293	*26*		3.5		3.5	3.5	3.1	3.1	3.1										-50/+150	1 braid, wire	SAE J1402 AI
	Fire retardant	221FR	*26*			3.5	3.5	3.5	3.5	3.5	3.5										-20/+100	1 braid, wire	SAE J1527 R3
	Refrigeration	285	*26*		3.4		3.4	3.4	3.4	3.4											-31/+125	1 braid, wire	SAE J2064 C

in parentheses "( )": The fitting series depends on the hose ID (size). For details, please refer to the respective hose page in this catalogue

Hose Overview
Medium pressure

	Hose	Fitting serie	Working Pressure (MPa) at size / DN																	Temp.	Construction	Standard
			-3	-4	-5	-6	-8	-10	-12	-16	-20	-24	-32	-40	-48	-56	-64	-80	-96			
			5	6	8	10	12	16	19	25	31	38	51	63	76	90	100	125	150			
GlobalCore	387	(43/48, 77)		21.0		21.0	21.0	21.0	21.0	21.0	21.0	21.0	21.0							-40/+100	1/2 braids, wire [1]	Exceeds ISO 18752-AC - ISO 18752-BC [2]
	387TC	(43/48, 77)		21.0		21.0	21.0	21.0	21.0	21.0	21.0	21.0	21.0							-40/+125	1/2 braids, wire [1]	Exceeds ISO 18752-AC - ISO 18752-CC [2]
	387ST	(43/48, 77)		21.0		21.0	21.0	21.0	21.0	21.0	21.0	21.0	21.0							-40/+125	1/2 braids, wire [1]	Exceeds ISO 18752-AC - ISO 18752-CC [2]
	487	(43/48, 77)		28.0		28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0							-40/+100	1/2 braids, wire [1]	Exceeds ISO 18752-AC - ISO 18752-BC [2]
	487TC	(43/48, 77)		28.0		28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0							-40/+125	1/2 braids, wire [1]	Exceeds ISO 18752-AC - ISO 18752-CC [2]
	487ST	(43/48, 77)		28.0		28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0							-40/+125	1/2 braids, wire [1]	Exceeds ISO 18752-AC - ISO 18752-CC [2]
Standard	421SN	48		22.5	21.5	18.0	16.0	13.0	10.5	8.8	6.3	5.0	4.0							-40/+100	1 braid, wire	EN 853-1SN - ISO 1436-1SN/R1AT - SAE 100R1AT
	301SN	48		40.0	35.0	33.0	27.5	25.0	21.5	16.5	12.5	9.0	8.0							-40/+100	2 braids, wire	EN 853-2SN - ISO 1436-2SN/R2AT - SAE 100R2AT
	441	46/48		35.0	29.7	28.0	24.5	19.2	15.7	14.0										-40/+125	1/2 braids, wire [1]	ISO 11237-R16 - SAE 100R16
	492	46		28.0	25.0	22.5	19.0	15.0	15.0	11.0	7.5									-40/+100	1 braid, wire	Exceeds EN 857-1SC - ISO 11237-1SC
	462	(46, 48)		42.5	40.0	35.0	31.0	28.0	28.0	21.0	17.2									-40/+100	2 braids, wire	Exceeds EN 857-2SC - ISO 11237-2SC
Chlorine Free	462CLF	(46, 48)		42.5	40.0	35.0	31.0	28.0	28.0	21.0	17.2									-40/+100	2 braids, wire	Exceeds EN 857-2SC - ISO 11237-2SC
High abrasion resistance MSHA approved	301TC	48		40.0	35.0	33.0	27.5	25.0	21.5	16.5	12.5	9.0	8.0							-40/+100	2 braids, wire	Exceeds EN 853-2SN - ISO 1436-2SN/R2AT
	462TC	(48, 48 2p)		42.5	40.0	35.0	31.0	28.0	28.0	21.0	17.2	14.6	11.2	7.0	7.0					-40/+100	2 braids, wire	Exceeds EN 857-2SC - ISO 11237-2SC
	471TC	48		40.0	36.0	35.0	29.7	25.0	21.5	17.5										-40/+100	2 braids, wire	EN 857-2SC - ISO 11237-2SC
	492TC	46		28.0	25.0	22.5	19.0	15.0	15.0	11.0	7.5									-40/+100	1 braid, wire	EN 857-1SC - ISO 11237-1SC
Extreme abrasion resistance	492ST	46		28.0	25.0	22.5	19.0	15.0	15.0	11.0	7.5									-40/+100	1 braid, wire	EN 857-1SC - ISO 11237-1SC
	462ST	(46, 48)		42.5	40.0	35.0	31.0	28.0	28.0	21.0	17.2									-40/+100	2 braids, wire	EN 857-2SC - ISO 11237-2SC
Low / High temperature	426	(43, 48)		19.2		15.7	14.0	10.5	8.7	7.0	4.3	3.5	2.6							-46/+150	1 braid, wire	SAE 100R1AT
	436	48				27.5	24.0	19.0	15.5	13.8										-48/+150	2 braids, wire	SAE 100R16
	461LT	46/48		42.5	40.0	35.0	31.0	28.0	28.0	21.0										-50/+100	2 braids, wire	Exceeds EN 857-2SC - ISO 11237-2SC
Phosphate Ester	304	(43, 48)		34.5		27.5	24.0		15.5	13.8	11.2	8.6	7.8							-40/+80	2 braids, wire	SAE 100R2AT
Railway	441RH	46/48		35.0	29.7	28.0	24.5	19.2	15.7	14.0										-40/+125	1/2 braids, wire [1]	ISO 11237-R16 - SAE 100R16
	421RH	48									6.3	5.0	4.0							-40/+100	1 braid, wire	EN 853-1SN - ISO 1436-1SN/R1AT - SAE 100R1AT
Water cleaning	493	48		20.0	20.0	20.0	17.5													max. +120	1 braid, wire	
	463	46			40.0	40.0	35.0													max. +120	2 braids, wire	
Pilot	412	47	12.0	12.0	12.0	12.0														-40/+100	1 braid, wire	
	412ST	47	12.0	12.0	12.0	12.0														-40/+100	1 braid, wire	
Wire cover	421WC	43		19.0		15.5	13.8		8.6	6.9										-40/+120	1 braid, wire	ISO S1436-1SN/R1AT - SAE 100R1AT
Powerlift	477	48		45.0	42.5	40.0	38.0	35.0	35.0	25.0										-40/+100	2 braids, wire	
	477TC	48		45.0	42.5	40.0	38.0	35.0	35.0	25.0										-40/+100	2 braids, wire	
	477ST	48		45.0	42.5	40.0	38.0	35.0	35.0	25.0										-40/+100	2 braids, wire	
Extremely flexible	692	46		21.0	21.0	21.0	21.0	21.0												-40/+100	1/2 braids, wire [1]	Exceeds SAE 100R17
	692TWIN	46		21.0	21.0	21.0	21.0	21.0												-40/+100	1/2 braids, wire [1]	Exceeds SAE 100R17
Suction	811	(48, IF, ⊕)							2.1	1.7	1.4	1.0	0.7	0.4	0.4					-40/+100	1 braid, 1 steelspiral	SAE 100R4
	811S	(IF, ⊕)												1.0	1.0	1.0	1.0	1.0	1.0	-40/+100	1 braid, 1 steelspiral	Exceeds SAE 100R4
	881	(43, 48, ⊕)							2.1	1.7	1.4	1.0	0.7	0.4						-40/+121	1 braid, 1 steelspiral	SAE 100R4

⊕: on request; in parentheses "( )": The fitting series depends on the hose ID (size); 2p: two-piece fitting; 1: The hose construction depends on the hose ID (size). 2: The standard depends on the hose ID (size).
For details, please refer to the respective hose page in this catalogue.

Hose Overview
High pressure

		Hose	Fitting serie	Working Pressure (MPa) at size / DN																	Temp.	Construction	Standard
				-3	-4	-5	-6	-8	-10	-12	-16	-20	-24	-32	-40	-48	-56	-64	-80	-96			
				5	6	8	10	12	16	19	25	31	38	51	63	76	90	100	125	150			
Parklock	GlobalCore	722	43				28.0	28.0	28.0	28.0	28.0										-40/+100	4 spiral, wire	Exceeds ISO 18752-BC
		722TC	43				28.0	28.0	28.0	28.0	28.0										-40/+125	4 spiral, wire	Exceeds ISO 18752-CC
		722ST	43				28.0	28.0	28.0	28.0	28.0										-40/+125	4 spiral, wire	Exceeds ISO 18752-CC
	GlobalCore Compact Spiral	787	77					35.0	35.0	35.0	35.0	35.0	35.0	35.0							-40/+100	4/6 spiral, wire [1]	Exceeds ISO 18752-BC
		787TC	77					35.0	35.0	35.0	35.0	35.0	35.0	35.0							-40/+125	4/6 spiral, wire [1]	Exceeds ISO 18752-DC
		797	77					42.0	42.0	42.0	42.0	42.0	42.0	42.0							-40/+100	4/6 spiral, wire [1]	Exceeds ISO 18752-BC
		797TC	77					42.0	42.0	42.0	42.0	42.0	42.0	42.0							-40/+125	4/6 spiral, wire [1]	Exceeds ISO 18752-DC - ISO 18752-CC [2]
3 braids	Standard	372	70				44.5	41.5	35.0	35.0	28.0										-40/+100	3 braids, wire	
	Low temperature	371LT	70				44.5	41.5	35.0	35.0	28.0										-50/+100	3 braids, wire	
	High abr. resist MSHA	372TC	70				44.5	41.5	35.0	35.0	28.0										-40/+100	3 braids, wire	
	Railway	372RH	70				44.5	41.5	35.0	35.0	28.0										-40/+100	3 braids, wire	
Parkrimp No-Skive	Standard	701	70				45.0	41.5	35.0	35.0	28.0										-40/+100	4 spiral, wire	EN 856-4SP - ISO 3862-4SP
		731	73							42.0	38.0	32.0	29.0	25.0							-40/+100	4 spiral, wire	EN 856-4SH - ISO 3862-4SH
	Chlorine Free	722CLF	43				28.0	28.0	28.0	28.0	28.0										-40/+100	4 spiral, wire	EN 856-R12 - ISO 3862-R12 - SAE 100R12
	Phosphate Ester	774	⊕							28.0	28.0	21.0	17.5	17.5							-40/+80	4 spiral, wire	
		F42	(70, ⊕)					42.0		42.0	42.0	42.0									-40/+80	4/6 spiral, wire [1]	ISO 3862-R15 - SAE 100R15
	High abrasion resistance MSHA approved	701TC	70				45.0	41.5	35.0	35.0	28.0										-40/+100	4 spiral, wire	EN 856-4SP - ISO 3862-4SP
		722TC	43									21.0	17.5	17.5							-40/+125	4 spiral, wire	Exceeds ISO 18752-CC
		731TC	73							42.0	38.0	32.0	29.0	25.0							-40/+125	4 spiral, wire	ISO 3862-4SH - EN 856-4SH
	Extreme abr. resist.	722ST	⊕									21.0	17.5	17.5							-40/+125	4 spiral, wire	Exceeds ISO 18752-CC
	Low temperature	722LT	43					28.0	28.0	28.0	28.0	21.0	17.5								-57/+100	4 spiral, wire	SAE 100R12 – ISO 3862-1 Type R12– EN 856 Type R12
	Standard	H31	(VS, V4)		50.0		44.5	41.5	39.0	35.0	31.0										-40/+100	4 spiral, wire	Exceeds EN 856-4SP - ISO 3862-4SP
		H29	V4							43.0	40.0	35.0	31.0	28.0							-40/+100	4 spiral, wire	Exceeds EN 856-4SH - ISO 3862-4SH
		R35	(V4, V6)							35.0	35.0	35.0	35.0	35.0							-40/+125	4/6 spiral, wire [1]	EN 856-R13 - ISO 3862-R13 - SAE 100R13
		R42	(V4, V6)						42.0	42.0	42.0	42.0	42.0	42.0							-40/+125	4/6 spiral, wire [1]	ISO 3862-R15 - SAE 100R15
	High abrasion resistance MSHA approved	H31TC	(VS, V4)		50.0		44.5	41.5	39.0	35.0	31.0										-40/+100	4 spiral, wire	Exceeds EN 856-4SP - ISO 3862-4SP
		H29TC	V4							43.0	40.0	35.0	31.0	28.0							-40/+100	4 spiral, wire	Exceeds EN 856-4SH - ISO 3862-4SH
		R35TC	(V4, V6)							35.0	35.0	35.0	35.0	35.0	35.0						-40/+125	4/6 spiral, wire [1]	EN 856-R13 - ISO 3862-R13 - SAE 100R13
		RS35TC	V6													21.0*						-40/+125	6 spiral, wire	ISO 6907-D
		R42TC	(V4, V6)						42.0	42.0	42.0	42.0	42.0	42.0							-40/+125	4/6 spiral, wire [1]	ISO 3862-R15 - SAE 100R15
		R50TC	(V4, V6)						50.0	50.0	50.0	50.0									-40/+100	4/6 spiral, wire [1]	Exceeds ISO 3862-R15
		R56TC	V5				56.0	56.0													-40/+100	4 spiral, wire	Exceeds ISO 3862-R15
	Extreme abrasion resistance	H31ST	(VS, V4)		50.0		44.5	41.5	39.0	35.0	31.0										-40/+100	4 spiral, wire	Exceeds EN 856-4SP - ISO 3862-4SP
		H29ST	V4							43.0	40.0	35.0	31.0	28.0							-40/+100	4 spiral, wire	Exceeds EN 856-4SH - ISO 3862-4SH
		R42ST	(V4, V6)						42.0	42.0	42.0	42.0	42.0	42.0							-40/+125	4/6 spiral, wire [1]	ISO 3862-R15 - SAE 100R15
	Railway	H29RH	V4								40.0	35.0	31.0								-40/+100	4 spiral, wire	Exceeds EN 856-4SH - ISO 3862-4SH
	Water-Blasting	BPK	WB		110.0		110.0	110.0		110.0	80.0										@	4/6 spiral, wire [1]	DIN EN 1829-2


⊕: on request;
in parentheses "( )": The fitting series depends on the hose ID (size);
1: The hose construction depends on the hose ID (size).
2: The standard depends on the hose ID (size).
For details, please refer to the respective hose page in this catalogue.

* 35 MPa: Static applications according to ISO 6807-D
* 21 MPa: Dynamic hydraulic application design factor > 4:1

@ Continuous Service Temperature Range -10 °C up to +70 °C
Max. Service Temperature Range -40 °C up to +93 °C

Fittings Overview

DIN – Metric


CA

Female Metric 24°
Light Series with O–Ring
Swivel – Straight
ISO 12151-2-SWS-L – DKOL


CE

Female Metric 24°
Light Series with O–Ring
Swivel – 45° Elbow
ISO 12151-2-SWE 45°-L – DKOL 45°

CF

Female Metric 24°
Light Series with O–Ring
Swivel – 90° Elbow
ISO 12151-2-SWE-L – DKOL 90°

D0

Male Metric 24°
Light Series – Rigid
Straight
ISO 12151-2-S-L – CEL


C3

Female Metric
Light Series – Swivel
Straight (Ball Nose for 24° or 60° Cone)
DKL

C4

Female Metric
Light Series – Swivel
45° Elbow (Ball Nose for 24° or 60° Cone)
DKL 45°

C5

Female Metric
Light Series – Swivel
90° Elbow (Ball Nose for 24° or 60° Cone)
DKL 90°


C9

Female Metric 24° – Swivel
Heavy Series with O-Ring
Straight
ISO 12151-2-SWS-S – DKOS


0C


Female Metric 24° – Swivel
Heavy Series with O–Ring
45° Elbow
ISO 12151-2 – SWE 45°-S – DKOS 45°


1C

Female Metric 24° – Swivel
Heavy Series with O–Ring
90° Elbow
ISO 12151-2-SWE-S – DKOS 90°

D2

Male Metric 24° – Rigid
Heavy Series – Straight
ISO 12151-2-S-S – CES

C6

Female Metric – Swivel
Heavy Series – Straight (Ball Nose)
DKS


49

Metric Banjo
Straight
DIN 7642

9B

Female Metric Swivel
Light Series
45° Elbow (Ball Nose for 24° or 60° Cone)

9C

Female Metric Swivel
Light Series
90° Elbow (Ball Nose for 24° or 60° Cone)

BSP


92

Female BSP Parallel Pipe
Swivel – Straight (60° Cone)
BS5200-A – DKR


B1


Female BSP Parallel Pipe
Swivel
45° Elbow (60° Cone)
BS 5200-D – DKR 45°


B2


Female BSP Parallel Pipe
Swivel
90° Elbow (60° Cone)
BS 5200-B – DKR 90°


B4

Female BSP Parallel Pipe
Swivel – 90° Elbow
Block Type (60° Cone)
BS 5200-E – DKR 90°


EA

BSP Swivel Female
with O–Ring (60° Cone)
BS 5200 – ISO 12151-6 – DKOR


EB

BSP Swivel Female
with O–Ring
45° Elbow (60° Cone)
BS 5200 – ISO 12151-6 – DKOR 45°

EC

BSP Swivel Female
with O–Ring
90° Elbow (60° Cone)
BS 5200 – ISO 12151-6 – DKOR 90°


D9

Male BSP Parallel Pipe
Rigid – Straight (60° Cone)
BS5200 – AGR

91

Male BSP Taper Pipe – Rigid
Straight
BS5200 – AGR-K

B5

Female BSP Parallel Pipe
Swivel
Straight (Flat Seat)


34

Inch Standpipe (Brass)


SAE


01

Male NPTF Pipe
Rigid – Straight
SAE J476A / J516 – AGN


02


Female NPTF Pipe – Rigid
Straight
SAE J476A / J516

03

Male JIC 37° – Rigid
Straight
ISO12151-5-S – AGJ

05

Male SAE Straight Thread
with O–Ring – Rigid
Straight
ISO 11926 – SAE J516

06/68

Female – JIC 37°
SAE 45° Dual Flare
Swivel – Straight
ISO12151-5-SWS – DKJ


37/3V

Female JIC 37°
SAE 45° – Dual Flare
Swivel Female 45° Elbow
ISO 12151-5-SWE 45° – DKJ 45°


39/3W

Female JIC 37°
SAE 45° – Dual Flare
Swivel Female 90° Elbow
ISO 12151-5-SWES – DKJ 90°


41/3Y

Female JIC 37° / 45°
Swivel Female 90° Elbow (Long)
ISO 12151-5-SWEL – DKJ 90°L

Flange


15/4A

ISO 6162-1 Flange
Straight
ISO 12151-3-S-L – SFL
(35.0 MPa/ 5000 psi)


16

ISO 6162-1 Flange
22.5° Elbow
ISO 12151-3-E22ML – SFL 22.5°
(21.0 MPa/ 3000 psi)

17/4F

ISO 6162-1 Flange
45° Elbow
ISO 12151-3 – E45S – L – SFL 45°
(35.0 MPa/ 5000 psi)

19/4N


ISO 6162-1 Flange
90° Elbow
ISO 12151-3-E-L – SFL 90°
(35.0 MPa/ 5000 psi)


6A

ISO 6162-2 Flange
Straight
ISO 12151-3-S-S – SFS
(42.0 MPa/ 6000 psi)


6E

ISO 6162-2 Flange
30° Elbow
SFS 30°
(42.0 MPa/ 6000 psi)


6F


ISO 6162-2 Flange
45° Elbow – Heavy Series
ISO 12151-3 – E45-S – SFS 45°
(42.0 MPa/ 6000 psi)


6N

ISO 6162-2 Flange
90° Elbow
ISO 12151-3 – E-S – SFS 90°
(42.0 MPa/ 6000 psi)

8A

Flange – Straight
8000 psi

8F

Flange – 45° Elbow
8000 psi


8N

Flange – 90° Elbow
8000 psi


X5

Flange – Straight
Full flange system for
ISO 6162-1 or ISO 6162-2


X7

Flange – 45° Elbow
Full flange system for
ISO 6162-1 or ISO 6162-2


X9


Flange – 90° Elbow
Full flange system for
ISO 6162-1 or ISO 6162-2


PY

Flange – 24° Male
French Gas
Straight

XA

Caterpillar® Flange
Straight

XF

Caterpillar® Flange
45° Elbow


XG

Caterpillar® Flange
60° Elbow

XN

Caterpillar® Flange
90° Elbow


K5

Komatsu® Flange
Straight


K7


Komatsu® Flange
45° Elbow

K9

Komatsu® Flange
90° Elbow

ORFS

JC

Female ORFS
Swivel – Straight
Short
ISO 12151-1 – SWSA SAE J516 – ORFS

JS

ORFS Swivel Female (Long)
ISO 12151-1-SWSB
SAE J516 – ORFS

J7

Female ORFS – Swivel
45° Elbow
ISO 12151-1 – SWE 45°
SAE J516 – ORFS 45°

J9


Female ORFS – Swivel
90° Elbow – Short Drop
ISO 12151-1 – SWES
SAE J516 – ORFS 90°


J1

Female ORFS – Swivel
90° Elbow – Long Drop
ISO 12151-1 – SWEL
SAE J 516 – ORFS 90° L


J5


Female ORFS – Swivel
90° Elbow – Medium Drop
ISO 12151-1 – SWEM – ORFS 90° M


JM

ORFS Male
ISO 12151-1-S – SAE J516


JD

Male ORFS
Bulkhead with Locknut
Straight (with O–ring)
ISO 12151-1 – SAE J516

JIS


FU

Female BSP Parallel Pipe
Swivel – Straight (30° Flare)
ISO 228-1 – JIS B8363 – GUI

GU

Female BSP Parallel Pipe
Swivel – Straight (60° Cone)
ISO 228-1 – JIS B8363 – GUO

MU

Female Metric – Swivel
Straight (30° Flare)
JIS B8363 – MU


MZ

Female Metric – Swivel
90° Elbow (30° Flare)
JIS B8363


French Standard


FG

Male French Gas Series
Rigid – Straight (24° Cone)


F2

Female French Gas Series
Swivel – 90° Elbow


F4

Female French Gas Series
Swivel – Straight
(Ball Nose)


F6

French Male Metric Series (24° Cone)


F9

French Female Metric Series
Swivel – (Ball Nose)

FA

Metric Male for Agriculture Valves


High Pressure Cleaning


CW

Power Cleaner Connection


NW

Female Kärcher
Metric Cleaning Hose Fitting
Swivel – Straight


PW

Male Kärcher
Metric Cleaning Hose Fitting
Rigid – Straight

Others

XU

Female Metric – Swivel
Straight (30° Flare)
JIS B8363

XY

Female Metric – Swivel
90° Elbow (30° Flare)
JIS B8363

DK

Male Metric L – Rigid
Bulkhead with Locknut
(24° Cone)


DX

Female Metric Swivel
(M27x2) O–Ring
Light Series


FF


Metru–Lok Swivel Female


AF


Male BSP Parallel Pipe
Rigid – Straight
(with O–ring Seal)


82

Push–Lok® Union

5C

60° Cone Swivel Female


6C

60° Cone Swivel Female
45° Elbow


7C

60° Cone Swivel Female
90° Elbow


5S

Female Tube O–ring Swivel
Short Pilot

5T

Female Tube O–Ring Swivel
90° Elbow – Short Pilot

UPTC

EN

UPTC – Male
Straight

EU

UPTC – Male
45° Elbow

ET

UPTC – Male
90° Elbow

Hose Fittings Pressure Ratings

* static working pressure
** dynamic working pressure

Fitting end connection	Description	Inch fittings (size) *Maximum working pressure (MPa) – design factor 4:1*														
		-4	-5	-6	-8	-10	-12	-16	-20	-24	-32	-40	-48	-56	-64	-80
92, B1, B2	BSP swivel female	63.0		55.0	43.0	42.0	42.0	42.0	35.0	30.0	25.0					
B5	BSP swivel female flat seat	63.0		55.0	43.0	37.5	35.0	28.0	25.0	21.0	21.0					
B4	BSP swivel female (compact brazed)	35.0	35.0	35.0	35.0	35.0	35.0	28.0	25.0	21.0	21.0					
EA, EB, EC	BSP swivel female with O-ring	45.0		45.0	42.0	42.0	42.0	42.0	35.0	30.0	25.0					
91, D9	BSP male	63.0		55.0	43.0		35.0	28.0	25.0	21.0	21.0					
01	NPTF male	83.0		69.0	69.0		52.0	45.0	35.0	21.0	17.5	35,0	35,0* 21,0**			
02	NPTF female	48.0		41.0	35.0		28.0	21.0	17.5	14.0	14.0					
03, 33	SAE (JIC) 37° male	41.0	41.0	35.0	35.0	35.0	35.0	28.0	21.0	17.5	17.5					
04	SAE 45° male	41.0	41.0	35.0	35.0	35.0	35.0	28.0	21.0	17.5	17.5					
05	SAE male with O-ring	41.0	41.0	35.0	35.0	35.0	35.0	28.0	21.0	17.5	17.5					
06/68,37/3V, 39/3W, L9, 41/3Y	SAE (JIC) 37° swivel female	41.0	41.0	35.0	35.0	35.0	35.0	28.0	21.0	17.5	17.5					
07	Female NPSM-pipe swivel	48.0		41.0	35.0		28.0	21.0								
08, 77, 79	Female SAE 45° swivel	21.0	21.0	21.0	21.0	19.0	15.5	14.0	11.0	9.0	8.0					
1L	Male NPTF pipe swivel 90° Elbow	21.0	21.0	21.0	21.0	19.0	15.5	14.0	11.0	9.0	8.0					
S2	Female NPTF pipe swivel	21.0	21.0	21.0	21.0	19.0	15.5	14.0	11.0	9.0	8.0					
0G, 0L	Male SAE O-ring	21.0	21.0	21.0	21.0	19.0	15.5	14.0	11.0	9.0	8.0					
28, 67, 69	SAE Male inverted 45° swivel	19.0	17.5	15.5	14.0											
15, 16, 17, 18, 19, 26, 27, 89, X5, X7, X9	ISO 6162-1 Flange (21.0 MPa/ 3000 psi)				35.0	35.0	35.0	35.0	28.0	28.0	21.0	17,5	16,0	3,5	3,5	3,5
4A, 4N, 4F	ISO 6162-1 Flange (35.0 MPa/ 5000 psi)								35.0	35.0	35.0					
6E, 6F, 6G, 6N, XA, XF, XG, XN, X5, X7, X9	ISO 6162-2 Flange (42.0 MPa/ 6000 psi)				42.0		42.0	42.0	42.0	42.0	42.0					
6A	ISO 6162-2 Flange (42.0 MPa/ 6000 psi)				42.0		42.0	42.0	42.0	42.0	42.0	42,0	42,0			
8A, 8F, 8N	SAE Flange 8000 psi						56.0	56.0	56.0							
A0	Male Super SteckO Rigid				51.8		42.0	38.0	35.0	35.0	35.0					
S0	Male SteckO Rigid	45.0		40.0	36.2		28.0	28.0	21.0	21.0	17.0					

Fitting end connection	Description	Inch fittings (size) *Maximum working pressure (MPa) – design factor 4:1*									
		-4	-5	-6	-8	-10	-12	-16	-20	-24	-32
JM, JC, JS, J1, J5, J7, J9, JD	ORFS male / female	63.5		63.5	63.5	41.0	41.0	41.0	28.0	28.0	
GU	JIS / BSP swivel female 60° cone	35.0	35.0	35.0	35.0		28.0	21.0	17.5		
FU	Female JIS / BSP 30° parallel pipe swivel	35.0	35.0	35.0	35.0	28.0	28.0	21.0	17.5		
MU	JIS 30° metric swivel female	35.0	35.0	35.0	35.0	28.0	28.0	21.0	17.5		
MZ	Metric swivel female 90° Elbow	35.0	35.0	35.0	35.0	28.0	28.0	21.0	17.5		
UT	JIS / BSP male 60° cone	35.0		35.0	35.0		28.0	21.0	17.5		
V1	Banjo soft seal with UNF bolt	25.0	25.0		21.5	21.5	20.0				
V3	Banjo soft seal with BSPP bolt	25.0	25.0		21.5	21.5	20.0				
XU, XY	Female Metric swivel 30° Flare	35.0	35.0	35.0	35.0	28.0	28.0	21.0	17.5		

Fitting end connection	Description	Metric tube (mm) • Light series – L *Maximum working pressure (MPa) – design factor 4:1*									
		6	8	10	12	15	18	22	28	35	42
C3, C4, C5	DIN 20078 Form A swivel female	25.0	25.0	25.0	25.0	25.0	16.0	16.0	10.0	10.0	10.0
CA, CE, CF	ISO 12151-2 swivel female with O-ring	31.5	42.5	40.0	35.0	31.5	31.5	28.0	21.0	16.0	16.0
D0, DF, DG, DK	ISO 12151-2 male stud	25.0	42.5	40.0	35.0	31.0	28.0	28.0	21.0	16.0	16.0
DX	Metric swivel female with O-ring	31.5	42.5	40.0	35.0	31.5	31.5	28.0	21.0	16.0	16.0
1D, DD, 5D	Metric standpipe	25.0	25.0	25.0	25.0	25.0	16.0	16.0	10.0	10.0	10.0
CW, NW	High pressure cleaning hose connection					40.0					
PW	High pressure cleaning hose connection			22.5							
EN, ET, EU	Universal push-in connector		40.0	35.0	35.0	29.5	28.0	21.5			

Fitting end connection	Description	Metric tube (mm) • Very light series – LL *Maximum working pressure (MPa) – design factor 4:1*									
		8	10	12	15	18	20	25	32	42	50
C0	DIN 20078 Form C swivel female DKLL						6.3	6.3	6.3	6.3	4.0

Fitting end connection	Description	Metric tube (mm) • Metric *Maximum working pressure (MPa) – design factor 4:1*										
		6	8	10	12	14	16	18	20	22	25	27
49	Metric Banjo - straight (DIN 7642)	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0	
V2	Banjo soft seal with metric bolt				25.0	25.0		21.5		21.5		20.0

Fitting end connection	Description	Metric tube (mm) • Heavy series – S *Maximum working pressure (MPa) – design factor 4:1*									
		6	8	10	12	14	16	20	25	30	38
C6, C7, C8	Swivel female	63.0	63.0	63.0	63.0	63.0	40.0	40.0	40.0	25.0	25.0
C9, 0C, 1C	ISO 12151-2 swivel female with O-ring	63.0	63.0	63.0	63.0	63.0	42.0	42.0	42.0	42.0	42.0
D2	Male stud	63.0	63.0	63.0	63.0	63.0	42.0	42.0	42.0	42.0	42.0
3D	Metric standpipe	63.0	63.0	63.0	63.0	63.0	40.0	40.0	40.0	25.0	25.0

Fitting end connection	Description	Metric tube (mm) • French gas series *Maximum working pressure (MPa) – design factor 4:1*				
		13	17	21	27	33
F2	Swivel female 90° Elbow	36.0	27.0	25.5	20.0	17.0
F4	Swivel female (Ball Nose)	36.0	27.0	25.5	20.0	17.0
FG	Male stud	36.0	27.0	25.5	20.0	17.0

Fitting end connection	Description	Metric tube (mm) • French metric series *Maximum working pressure (MPa) – design factor 4:1*						
		10	12	14	18	20	22	30
F9	Swivel female	20.0		14.0	16.0	14.0	13.0	12.2
F6	Male agricultural valves	20.0		14.0	16.0	14.0	13.0	12.2
FA	Male agricultural valves		25.0					

Hose Fittings Nomenclature

End Configuration	Description	Standards	Common Terms
01	Male NPTF Pipe – Rigid – Straight	SAE J476A / J516	AGN
02	Female NPTF Pipe – Rigid – Straight	SAE J476A / J516	
03	Male JIC 37° – Rigid – Straight	ISO12151-5-S	AGJ
04	Male SAE 45° – Rigid – Straight	SAE J516	
05	Male SAE Straight Thread with O-ring – Rigid – Straight	ISO 11926, SAE J516	
06	Female JIC 37° Swivel – Straight	ISO12151-5-SWS	DKJ
06/68	Female – JIC 37° / SAE 45° Dual Flare – Swivel – Straight	ISO12151-5-SWS	DKJ
07	Female NPSM Pipe Swivel		
08	Female SAE 45° – Swivel – Straight	SAE J516	
0C	Female Metric 24° – Heavy Series with O-ring – Swivel – 45° Elbow	ISO 12151-2 – SWE 45°-S	DKOS 45°
0G	Male O-ring Straight		
0L	Male O-ring 90° Elbow		
11	„Ferrul-Fix“		
12	Female SAE Flareless Swivel – Straight (24° Cone)		
13	Male NPTF Pipe Swivel	SAE J476A / J516	
15	ISO 6162-1 – Flange Head – Straight	ISO 12151-3-S-L	SFL / 3000 psi
15/4A	ISO 6162-1 – Flange Head – Straight / SAE Flange Head (5000 psi)	ISO 12151-3-S-L	SFL
16	ISO 6162-1 – Flange Head – 22.5° Elbow	ISO 12151-3-E22ML	SFL 22.5° / 3000 psi
17	ISO 6162-1 – Flange Head – 45° Elbow	ISO 12151-3 – E45 – L	SFL 45° / 3000 psi
17/4F	ISO 6162-1 – Flange – 45° Elbow – 45° Elbow (5000 psi)	ISO 12151-3 – E45S – L	SFL 45°
18	ISO 6162-1 – Flange – 67.5° Elbow		SFL 67.5°
19	ISO 6162-1 – Flange Head – 90° Elbow	ISO 12151-3 – E– L	SFL 90° / 3000 psi
19/4N	ISO 6162-1 – Flange Head – 90° Elbow (5000 psi)	ISO 12151-3-E-L	SFL 90°
1C	Female Metric 24° – Heavy Series with O-ring – Swivel – 90° Elbow	ISO 12151-2-SWE-S	DKOS 90°
1D	Metric Standpipe – Light Series – Rigid – Straight	ISO 8434-1	BEL
1L	Male NPTF Pipe Swivel – 90° Elbow		
26	ISO 6162-1 Flange – 30° Elbow		SFL 30°
27	ISO 6162-1 Flange – 60° Elbow		SFL 60°
28	SAE Male Inverted 45° Elbow		
33	Male JIC 37° – Rigid – 45° Elbow	ISO 12151-5	AGJ 45°
34	Inch Standpipe (Brass)		
37	Female JIC 37° – Swivel – 45° Elbow	ISO 12151-5-SWE 45°	DKJ 45°
37/3V	Female JIC 37° /SAE 45° – Dual Flare – Swivel Female 45° Elbow	ISO 12151-5-SWE 45°	DKJ 45°
39	Female JIC 37° – Swivel – 90° Elbow	ISO 12151-5-SWES	DKJ 90°
39/3W	Female JIC 37° / SAE 45° – Dual Flare – Swivel Female 90° Elbow	ISO 12151-5-SWES	DKJ 90°
3D	Metric Standpipe – Heavy Series – Rigid – Straight	ISO 8434-1	BES
3V	Female JIC 37°/SAE – 45° Swivel – 45° Elbow		DKJ 45°
3W	Female JIC 37°/SAE – 45° Swivel – 90° Elbow		DKJ 90°
3Y	Female JIC 37°/SAE – 45° Swivel – 90° Elbow (Long)		DKJ 90°
41	Female JIC 37° Swivel – 90° Elbow (Long)		DKJ 90°
41/3Y	Female JIC 37° / 45° Swivel Female 90° Elbow (Long)	ISO 12151-5-SWEL	DKJ 90°L
45	Male Tube O-ring Swivel – Long Pilot		

End Configu-ration	Description	Standards	Common Terms
49	Metric Banjo – Straight	DIN 7642	
4A	ISO 6162-1 – Flange – Straight (5000 psi)		
4F	ISO 6162-1 – Flange – 45° Elbow (5000 psi)		
4N	ISO 6162-1 – Flange – 90° Elbow (5000 psi)		
59	Female Tube O-ring Swivel – Long Pilot		
59PT	Male Tube O-ring Swivel – Long Pilot	With Charge Port at 180° for 134a	
5C	60° Cone Swivel Female		
5D	Metric Standpipe – Light Series – Rigid – 90° Elbow	ISO 8434-1	BEL 90°
5G	Male Tube O-ring Rigid Port (3 step) Straight		
5GPR	Female Tube O-ring Rigid Port (3 step) Straight	With Charge Port for R12	
5H	Female Tube O-ring Swivel – 45° Elbow – Short Pilot		
5K	Male Tube O-ring Swivel – 90° Elbow – Short Pilot		
5LPR	Female Tube O-ring Swivel – 90° Elbow – Long Pilot		
5LPT	Female Tube O-ring Swivel – 90° Elbow – Long Pilot	With Charge Port at 180° for 134a	
5MPR	Male Tube O-ring Swivel – 90° Elbow – Long Pilot	With Charge Port at 180° for R12	
5MPV	Male Tube O-ring Swivel – 90° Elbow – Long Pilot	With Charge Port at 270° for 134a	
5N	Female Tube O-ring Swivel – 45° Elbow – Long Pilot		
5P	Female Tube O-ring Swivel – 45° Elbow – Long Pilot		
5R	Male Tube O-ring Swivel – 45° Elbow – Short Pilot		
5S	Female Tube O-ring Swivel – Short Pilot		
5T	Female Tube O-ring Swivel – 90° Elbow – Short Pilot		
5V	Female Compressor – Swivel 45° Elbow		
5W	Female Compressor – Swivel 90° Elbow		
5Z	Female Compressor – Swivel 90° Elbow – Block Type		
67	SAE Male Inverted Flare Swivel – 45° Elbow		
68	Female JIC 37° / SAE 45° Swivel		DKJ
69	SAE Male Inverted Flare Swivel – 90° Elbow		
6A	ISO 6162-2 – Flange – Straight	ISO 12151-3-S-S	SFS / 6000 psi
6B	ISO 6162-2 – Flange – 22.5° Elbow		SFS 22.5°
6C	60° Cone Swivel Female – 45° Elbow		
6E	ISO 6162-2 – Flange – 30° Elbow		SFS 30°
6F	ISO 6162-2 – Flange –45° Elbow	ISO 12151-3 – E45-S	SFS 45° / 6000 psi
6G	ISO 6162-2 – Flange – 60° Elbow		SFS 60°
6N	ISO 6162-2 – Flange – 90° Elbow	ISO 12151-3 – E-S	SFS 90° / 6000 psi
77	Female SAE 45° Swivel – 45° Elbow		
79	Female SAE 45° Swivel – 90° Elbow		
7C	60° Cone Swivel Female – 90° Elbow		
7D	Male Standpipe Metric S – Rigid – 90° Elbow		BES 90°
82	Push-Lok® Union		
89	ISO 6162-1 – Flange – 90° Elbow (Long) – Standard Series		
8A	Flange – Straight – 8000 psi		
8F	Flange – 45° Elbow – 8000 psi		
8N	Flange – 90° Elbow – 8000 psi		
91	Male BSP Taper Pipe – Rigid – Straight	BS5200	AGR-K

End Configuration	Description	Standards	Common Terms
92	Female BSP Parallel Pipe – Swivel – Straight (60° Cone)	BS5200-A	DKR
93	Female JIC 37° – Swivel – 90° Elbow (Block Type)		
9B	Metric – Swivel Female 45° Elbow – Light Series		
9C	Light Series Metric Swivel Female 90° Elbow		
AF	Male BSP Parallel Pipe – Rigid – Straight (with O-ring Seal)		
B1	Female BSP Parallel Pipe – Swivel – 45° Elbow (60° Cone)	BS 5200-D	DKR 45°
B2	Female BSP Parallel Pipe – Swivel – 90° Elbow (60° Cone)	BS 5200-B	DKR 90°
B4	Female BSP Parallel Pipe – Swivel – 90° Elbow Block Type (60° Cone)	BS 5200-E	DKR 90°
B5	Female BSP Parallel Pipe – Swivel – Straight (Flat Seat)		
C0	Female Metric – Very Light Series LL – Swivel – Straight (Ball Nose)		DKM
C3	Female Metric – Light Series – Swivel – Straight (Ball Nose)		DKL
C4	Female Metric – Light Series – Swivel – 45° Elbow (Ball Nose)		DKL 45°
C5	Female Metric – Light Series – Swivel – 90° Elbow (Ball Nose)		DKL 90°
C6	Female Metric – Heavy Series – Swivel – Straight (Ball Nose)		DKS
C7	Female Metric Swivel – 45° Elbow "Heavy" Series		DKS 45°
C8	Female Metric Swivel – 90° Elbow "Heavy" Series		DKS 90°
C9	Female Metric 24° – Heavy Series with O-ring – Swivel – Straight	ISO 12151-2-SWS-S	DKOS
CA	Female Metric 24° – Light Series with O-ring – Swivel – Straight	ISO 12151-2-SWS-L	DKOL
CE	Female Metric 24° – Light Series with O-ring – Swivel – 45° Elbow	ISO 12151-2-SWE 45°-L	DKOL 45°
CF	Female Metric 24° – Light Series with O-ring – Swivel – 90° Elbow	ISO 12151-2-SWE-L	DKOL 90°
CW	Power Cleaner Connection		
D0	Male Metric 24° – Light Series – Rigid – Straight	ISO 12151-2-S-L	CEL
D2	Male Metric 24° – Heavy Series – Rigid – Straight	ISO 12151-2-S-S	CES
D9	Male BSP Parallel Pipe – Rigid – Straight (60° Cone)	BS5200	AGR
DD	Metric Standpipe – Light Series – Rigid – 45° Elbow		BEL 45°
DE	Double Banjo Union		
DK	Male Metric L – Rigid – Bulkhead with Locknut (24° Cone)		
DP	Metric Swivel Female Tee / Male Stud		
DR	Metric Swivel Female Tee		
DS	Metric Swivel Female Tee / Standpipe		
DW	Female Metric Swivel „Light" Series		TGL
DX	Female Metric Swivel (M27x2) O-ring – Light Series		
EA	BSP Swivel Female with O-ring (60° Cone)	BS 5200, ISO 12151-6	DKOR
EB	BSP Swivel Female with O-ring – 45° Elbow (60° Cone)	BS 5200, ISO 12151-6	DKOR 45°
EC	BSP Swivel Female with O-ring – 90° Elbow (60° Cone)	BS 5200, ISO 12151-6	DKOR 90°
EN	UPTC – Male – Straight		
ET	UPTC – Male – 90° Elbow		
EU	UPTC – Male – 45° Elbow		
F2	Female French Swivel Female – Gas Series 90° Elbow		
F4	Female French Gas Series – Swivel – Straight (Ball Nose)		
F6	French Male Metric Series (24° Cone)		
F9	French Swivel Female Metric Series – (Ball Nose)		
FA	Metric Male For Agriculture Valves		
FB	French Metric		

End Configu-ration	Description	Standards	Common Terms
FF	Metru-Lok Swivel Female		
FG	Male French Gas Series – Rigid – Straight (24° Cone)		
FU	Female BSP Parallel Pipe – Swivel – Straight (30° Flare)	ISO 228-1, JIS B8363	GUI
GE	French Gas Standpipe		
GU	Female BSP Parallel Pipe – Swivel – Straight (60° Cone)	ISO 228-1, JIS B8363	GUO
J1	Female ORFS – Swivel – 90° Elbow – Long Drop	ISO 12151-1 – SWEL, SAE J 516	ORFS 90° L
J5	Female ORFS – Swivel – 90° Elbow – Medium Drop	ISO 12151-1 – SWEM	ORFS 90° M
J7	Female ORFS – Swivel – 45° Elbow	ISO 12151-1 – SWE 45°, SAE J516	ORFS 45°
J9	Female ORFS – Swivel – 90° Elbow – Short Drop	ISO 12151-1 – SWES, SAE J516	ORFS 90°
JC	Female ORFS – Swivel – Straight – Short	ISO 12151-1 – SWSA, SAE J516	ORFS
JD	Male ORFS – Bulkhead with Locknut – Straight (with O-ring)	ISO 12151-1 – SAE J516	
JM	ORFS Male	ISO 12151-1-S, SAE J516	
JS	ORFS Swivel Female (Long)	ISO 12151-1-SWSB, SAE J516	ORFS
L9	Female JIC 37° – Swivel – 90° Elbow – Medium Drop	ISO 12151-5-SWEM	DKJ 90° M
MU	Female Metric – Swivel – Straight (30° Flare)	JIS B8363	MU
MZ	Female Metric – Swivel – 9 0° Elbow (30° Flare)	JIS B8363	
NM	Male BSP Parallel Pipe – L Series – Rigid – Straight – ED-Seal	ISO 1179	
NW	Female Kärcher Metric Cleaning Hose Fitting – Swivel – Straight		
PW	Male Kärcher Metric Cleaning Hose Fitting – Rigid – Straight		
PY	Flange – 24° Male – French Gas – Straight		
S2	Female NPTF Pipe Swivel		
S5	Male Tube O-ring Swivel – Short Pilot		
T1	Male Refrigerant Tube Mender – Straight (with Nut and Ferrule)		
UT	Male BSP Taper Pipe – Rigid – Straight (60° Cone)	JIS B 8363-R	
V1	Ermeto standard Pressure Banjo – Straight (with UNF Bolt and O-ring)		
VW	Push In Connector	(VW-Standard 39-V-16619)	
VW121	BSP Swivel Female	(VW-Norm 39-V-16631)	
VW39D	Push In Connector	(VW-Standard 39D-1401)	
WKS	Rubber hand grip		
X5	Flange – Straight – Full flange system for ISO 6162-1 or ISO 6162-2		
X7	Flange – 45° Elbow – Full flange system for ISO 6162-1 or ISO 6162-2		
X9	Flange – 90° Elbow – Full flange system for ISO 6162-1 or ISO 6162-2		
XA	Caterpillar® Flange Head – Straight		
XF	Caterpillar® Flange Head – 45° Elbow		
XG	Caterpillar® Flange Head – 60° Elbow		
XN	Caterpillar® Flange Head – 90° Elbow		
XU	Female Metric – Swivel – Straight (30° Flare)	JIS B8363	
XY	Female Metric – Swivel – 90° Elbow (30° Flare)	JIS B8363	
YW	Male Standpipe – Rigid – Straight – A-Lok	Metric Size Tube O.D. with Vee Notch	

Classification Bodies

The mission of classification bodies is to contribute to the development and implementation of technical standards for the protection of life, property and the environment.

(1) Det Norske Veritas - Germanischer Lloyd (DNV-GL)
Norwegian service company for managing risk in ship classification, off-shore industry, etc... German independent organisation of technical experts approving products for the German merrcantile marine and the energy sector – GLIS (oil and gas, wind energy, etc...)

(2) RINA (Registro Italiano Navale)
Italian company offering certification, verification, control, assistance in marine, energy & process, transport and industry.

(3) Lloyd's Register (LR)
English independent organisation providing certification around the world. Marine services, Rail services and Energy services are their main activities.

(4) American Bureau of Shipping (ABS)
US company providing rules for safety in the marine environment.

(5) European Rail Standard (EN 45545)
Railway application – Fire protection on railway vehicles. Requirements for fire behavior of materials and components (hose and hose assemblies).

(6) US Department of Transportation (DOT)
US organisation providing certifications to ensure a fast, safe, efficient, accessible and convenient transportation system in this country.

(7) US Coast Guard (USCG)
Provides maritime safety, law enforcement, recreational boating safety, and environmental protection information for merchant mariners. The approved hoses are not accepted for all applications automatically. If the column contains "H", the hose is accepted for hydraulic systems only and not for fuel and lube systems.

(8) Mine Safety and Health Administration (MSHA)
US organisation for safety in the mining industry

(9) MarED
MarED is the Group of Notified Bodies for the Implementation of the Marine Equipment Directive.

(10) Bureau Veritas (BV)
Bureau Veritas is today the most widely recognized certification body in the world, offering solutions in the key strategic fields of operations: Quality, Health & Safety, Environment and Social Responsibility.

(11) Verteidigungs-Gerätenorm (VG)
German Organisation providing approvals for military equipment.

(12) OBAC
The OBAC (Ośrodek Badań Atestacji i Certyfikacji – Institute for Research and Certification Ltd.) is a private certification body authorised to test and certify equipment and components for use in Polish underground mines.

EN European Standard
ISO International Organisation for Standardization
SAE Society of Automotive Engineers (US organisation)

Approvals for Parker Hydraulic Hoses

Low pressure

Description (1)-(12) see Ab-16

			Hose	Construction	Standard	DNV-GL (1)	RINA (2)	LR (3)	ABS (4)	Rail *(EN 45545)* (5)	DOT (6)	USCG (7)	MSHA (8)	MarED (9)	BV (10)	VG (11)	OBAC (12)
Low pressure	Push-Lok	Multipurpose	801Plus	1 braid, fibre													
			830M	1 braid, fibre													
			831	1 braid, fibre													
			837BM	1 braid, fibre													
			837PU	1 braid, fibre													
		Phosphate Ester	804	1 braid, fibre													
		Fire retardant	821FR	1 braid, fibre													
		High temperature	836	1 braid, fibre									X				
		Non-conductive	838M	1 braid, fibre													
	Transport + Hydraulic	Standard	601	2 braids, fibre	EN 854-R3 - SAE 100R3												
			681	1 braid, fibre	EN 854-2TE												
		High temperature	611HT	1 braid, fibre	EN 854-R6								X				
		Railway	681DB	1 braid, fibre	EN 854-2TE					X							
		Transportation	201	1 braid, wire	SAE 100R5 - SAE J1402 AII						X						
			206	1 braid, wire	SAE 100R5 - SAE J1402 AII						X						
			213	1 braid, wire	SAE J1402 AI						X						
			293	1 braid, wire	SAE J1402 AI						X						
		Fire retardant	221FR	1 braid, wire	SAE J1527 R3	X			X			H	X				
		Refrigeration	285	1 braid, wire	SAE J2064 C												

Approvals for Parker Hydraulic Hoses

Medium pressure

Description (1)-(12) see Ab-16

		Hose	Construction	Standard	DNV-GL (1)	RINA (2)	LR (3)	ABS (4)	Rail (EN 45545) (5)	DOT (6)	USCG (7)	MSHA (8)	MarED (9)	BV (10)	VG (11)	OBAC (12)
Medium pressure	GlobalCore	387	1/2 braids, wire [1]	Exceeds ISO 18752-AC - ISO 18752-BC [2]	X			X			X	X				
		387TC	1/2 braids, wire [1]	Exceeds ISO 18752-AC - ISO 18752-CC [2]	X			X			X	X				
		387ST	1/2 braids, wire [1]	Exceeds ISO 18752-AC - ISO 18752-CC [2]	X			X			X	X				
		487	1/2 braids, wire [1]	Exceeds ISO 18752-AC - ISO 18752-BC [2]	X			X			X	X				
		487TC	1/2 braids, wire [1]	Exceeds ISO 18752-AC - ISO 18752-CC [2]	X			X			X	X				
		487ST	1/2 braids, wire [1]	Exceeds ISO 18752-AC - ISO 18752-CC [2]	X			X			X	X				
	Standard	421SN	1 braid, wire	EN 853-1SN - ISO 1436-1SN/R1AT - SAE 100R1AT	X	X	X	X					X	X	X	
		301SN	2 braids, wire	EN 853-2SN - ISO 1436-2SN/R2AT - SAE 100R2AT	X	X	X	X					X	X	X	
		441	1/2 braids, wire [1]	ISO 11237-R16 - SAE 100R16												
		492	1 braid, wire	Exceeds EN 857-1SC - ISO 11237-1SC	X	X	X	X					X		X	
		462	2 braids, wire	Exceeds EN 857-2SC - ISO 11237-2SC	X	X	X	X					X		X	
	Chlorine Free	462CLF	2 braids, wire	Exceeds EN 857-2SC - ISO 11237-2SC												
	High abrasion resistance MSHA approved	301TC	2 braids, wire	Exceeds EN 853-2SN - ISO 1436-2SN/R2AT	X			X				X				X
		462TC	2 braids, wire	Exceeds EN 857-2SC - ISO 11237-2SC	X			X				X				
		471TC	2 braids, wire	EN 857-2SC - ISO 11237-2SC								X				
		492TC	1 braid, wire	EN 857-1SC - ISO 11237-1SC								X				
	Extreme abrasion resistance	492ST	1 braid, wire	EN 857-1SC - ISO 11237-1SC	X			X								
		462ST	2 braids, wire	EN 857-2SC - ISO 11237-2SC	X			X								
	Low / High temperature	426	1 braid, wire	SAE 100R1AT				X			X	X				
		436	2 braids, wire	SAE 100R16				X			X	X				
		461LT	2 braids, wire	Exceeds EN 857-2SC - ISO 11237-2SC												
	Phosphate Ester	304	2 braids, wire	SAE 100R2AT												
	Railway	441RH	1/2 braids, wire [1]	ISO 11237-R16 - SAE 100R16					X							
		421RH	1 braid, wire	EN 853-1SN - ISO 1436-1SN/R1AT - SAE 100R1AT					X							
	Water cleaning	493	1 braid, wire													
		463	2 braids, wire													
	Pilot	412	1 braid, wire													
		412ST	1 braid, wire													
	Wire cover	421WC	1 braid, wire	ISO S1436-1SN/R1AT - SAE 100R1AT												
	Powerlift	477	2 braids, wire													
		477TC	2 braids, wire													
		477ST	2 braids, wire													
	Extremely flexible	692	1/2 braids, wire [1]	Exceeds SAE 100R17												
		692TWIN	1/2 braids, wire [1]	Exceeds SAE 100R17												
	Suction	811	1 braid, 1 steelspiral	SAE 100R4	X			X								
		811S	1 braid, 1 steelspiral	Exceeds SAE 100R4	X			X								
		881	1 braid, 1 steelspiral	SAE 100R4							H	X				

1: The hose construction depends on the hose ID (size). 2: The standard depends on the hose ID (size). For details, please refer to the respective hose page in this catalogue.

Approvals for Parker Hydraulic Hoses

High pressure

Description (1)-(12) see Ab-16

			Hose	Construction	Standard	DNV-GL (1)	RINA (2)	LR (3)	ABS (4)	Rail (EN 45545) (5)	DOT (6)	USCG (7)	MSHA (8)	MarED (9)	BV (10)	VG (11)	OBAC (12)
High pressure	3 braids	GlobalCore	722	4 spiral, wire	Exceeds ISO 18752-BC	X		X	X			X	X				
			722TC	4 spiral, wire	Exceeds ISO 18752-CC	X		X	X			X	X				
			722ST	4 spiral, wire	Exceeds ISO 18752-CC	X		X	X			X	X				
		GlobalCore Compact Spiral	787	4/6 spiral, wire [1]	Exceeds ISO 18752-BC	X		X	X			X	X				
			787TC	4/6 spiral, wire [1]	Exceeds ISO 18752-DC	X		X	X			X	X				
			797	4/6 spiral, wire [1]	Exceeds ISO 18752-BC	X		X	X			X	X				
			797TC	4/6 spiral, wire [1]	Exceeds ISO 18752-DC - ISO 18752-CC [2]	X		X	X			X	X				
		Standard	372	3 braids, wire		X		X	X					X			
		Low temperature	371LT	3 braids, wire													
		High abr. resist. MSHA	372TC	3 braids, wire		X							X				
		Railway	372RH	3 braids, wire													
	Parkrimp No-Skive	Standard	701	4 spiral, wire	EN 856-4SP - ISO 3862-4SP	X	X									X	
			731	4 spiral, wire	EN 856-4SH - ISO 3862-4SH												
		Chlorine Free	722CLF	4 spiral, wire	EN 856-R12 - ISO 3862-R12 - SAE 100R12	X			X								
		Phosphate Ester	774	4 spiral, wire													
			F42	4/6 spiral, wire [1]	ISO 3862-R15 - SAE 100R15												
		High abrasion resistance MSHA approved	701TC	4 spiral, wire	EN 856-4SP - ISO 3862-4SP								X				
			722TC	4 spiral, wire	Exceeds ISO 18752-CC	X		X	X			X	X				
			731TC	4 spiral, wire	ISO 3862-4SH - EN 856-4SH								X				
		Extreme abr. resist.	722ST	4 spiral, wire	Exceeds ISO 18752-CC	X		X	X			X	X				
		Low temperature	722LT	4 spiral, wire	SAE 100R12 – ISO 3862-1 Type R12– EN 856 Type R12												
		Standard	H31	4 spiral, wire	Exceeds EN 856-4SP - ISO 3862-4SP	X	X	X	X					X	X		
			H29	4 spiral, wire	Exceeds EN 856-4SH - ISO 3862-4SH	X		X	X					X	X		
			R35	4/6 spiral, wire [1]	EN 856-R13 - ISO 3862-R13 - SAE 100R13	X		X	X								
			R42	4/6 spiral, wire [1]	ISO 3862-R15 - SAE 100R15	X		X	X					X			
		High abrasion resistance MSHA approved	H31TC	4 spiral, wire	Exceeds EN 856-4SP - ISO 3862-4SP	X			X				X				X
			H29TC	4 spiral, wire	Exceeds EN 856-4SH - ISO 3862-4SH	X			X				X				X
			R35TC	4/6 spiral, wire [1]	EN 856-R13 - ISO 3862-R13 - SAE 100R13	X			X				X				X
			RS35TC	6 spiral, wire	ISO 6907-D	X			X				X				
			R42TC	4/6 spiral, wire [1]	ISO 3862-R15 - SAE 100R15	X							X				X
			R50TC	4/6 spiral, wire [1]	Exceeds ISO 3862-R15								X				
			R56TC	4 spiral, wire	Exceeds ISO 3862-R15								X				
		Extreme abrasion resistance	H31ST	4 spiral, wire	Exceeds EN 856-4SP - ISO 3862-4SP	X			X								
			H29ST	4 spiral, wire	Exceeds EN 856-4SH - ISO 3862-4SH	X			X								
			R42ST	4/6 spiral, wire [1]	ISO 3862-R15 - SAE 100R15	X											
		Railway	H29RH	4 spiral, wire	Exceeds EN 856-4SH - ISO 3862-4SH												
		Water-Blasting	BPK	4/6 spiral, wire [1]	DIN EN 1829-2												

1: The hose construction depends on the hose ID (size). 2: The standard depends on the hose ID (size). For details, please refer to the respective hose page in this catalogue.


Conversion Chart

	Unit	Base Unit	Conversion Unit	Factor
Length	1 inch	in	mm	25.4
	1 milllimetre	mm	in	0.03934
	1 foot	ft	m	0.3048
	1 metre	m	ft	3.28084
Area	1 square inch	sq in	cm^2	6.4516
	1 square centimetre	cm^2	sq in	0.1550
Volume	1 gallon (UK)	gal	l	4.54596
	1 litre	l	gal (UK)	0.219976
	1 gallon (US)	gal	l	3.78533
	1 litre	l	gal (US)	0.264177
Weight	1 pound	lb	kg	0.453592
	1 kilogramme	kg	lb	2.204622
Torque	1 pound foot	lb • ft	N • m	1.488164
	1 Newton metre	N • m	lb • ft	0.671969
Pressure	1 pound per square inch	psi	bar	0.06895
	1 bar	bar	psi	14.5035
	1 pound per square inch	psi	MPa	0.006895
	1 mega pascal	MPa	psi	145.035
	1 kilo pascal	kPa	bar	0.01
	1 bar	bar	kPa	100
	1 mega pascal	MPa	bar	10
	1 bar	bar	MPa	0.1
Velocity	1 foot per second	ft / s	m / s	0.3048
	1 metre per second	m / s	ft / s	3.28084
Flow rate	1 gallon per minute (UK)	gal / min.	l / min.	4.54596
	1 litre per minute	l / min.	gal / min. (UK)	0.219976
	1 gallon per minute (US)	gal / min.	l / min.	3.78533
	1 litre per minute	l / min.	gal / min. (US)	0.264178
Temperature	Fahrenheit degree	°F	°C	5/9 • (°F-32)
	Celsius degree	°C	°F	°C • (9/5) +32

(UK) Unit of United Kingdom
(US) Unit of USA

Temperature / Pressure Chart

Reference 201, 206, 213 and 293 hose.



EXAMPLE: 201-8 hose to be used at 121 °C

Maximum Working Pressure up to 100 °C		Multiplication Factor from Chart		Maximum Working Pressure at 121 °C
13.8 MPa (2000 psi)	x	85%	=	11.7 MPa (1700 psi)


Flow Capacity Nomogram

The chart below is provided as an aid in the determination of the correct hose size.
Example: at 10 gallons per minute (gal/min), what is the proper hose size within the recommended velocity range for pressure lines?
Locate 10 gallons per minute in the left-hand column and 20 feet per second in the right-hand column (the maximum recommended velocity range for pressure lines). Lay a straight line across these two points.
The inside diameter shown in the centre column is above -6 so we have to use -8 (1/2"). For suction hose, follow the same procedure except use recommended velocity range for intake lines in the right-hand column.

where: Q = flow in gallons per minute (gal/min & l/min)
V = velocity in feet per second (f/s & m/s)
d = hose inside diameter (mm & dash size)

Example
Flow Q = 45 l/m
Velocity V = 6,1 m/s
Konstant K = 21,2025

$$D = \sqrt{\frac{Q * K}{V}} = \sqrt{\frac{45\,\frac{l}{m} * 21{,}2025}{6{,}1\,\frac{m}{s}}} = 12{,}5\ mm$$



* Recommended velocities are according to hydraulic fluids of maximum viscosity 315 S.S.U. at 38°C working at roomtemperature within 18° and 68°C.

The Correct Method to Fit Female Swivel Ends

To ensure a leakproof seal between swivel female hose ends shown in this catalogue and the appropriate adaptors it is necessary to follow the procedure below which is different from hydraulic tube assembly.

Flats From Wrench Resistance (FFWR)

Parker's recommended assembly method for JIC 37° flare, SAE 45° flare and ORFS swivel female is Flats From Wrench Resistance (FFWR). The torque values assigned by size are for reference only, and are only applicable to Parker system components using the FFWR method with trivalent chromate passivation on zinc plating of carbon steel components without lubrication.

Metal-to-metal seal

Screw the nut up hand tight and then tighten further with a spanner according to the values mentioned in the table below. Ensure that in all cases the hose is correctly aligned before tightening the nut onto the corresponding adaptor.

Spanner torque values

Metric swivel female

Thread metric	Tube O.D.	Nm nominal	Nm min. - max.
M 12x1.5	06L	16	15 - 17
M 14x1.5	08L	16	15 - 17
M 16x1.5	10L	26	25 - 28
M 18x1.5	12L	37	35 - 39
M 22x1.5	15L	47	45 - 50
M 26x1.5	18L	89	85 - 94
M 30x2	22L	116	110 - 121
M 36x2	28L	137	130 - 143
M 45x2	35L	226	215 - 237
M 52x2	42L	347	330 - 363
M 14x1.5	06S	26	25 - 28
M 16x1.5	08S	42	40 - 44
M 18x1.5	10S	53	50 - 55
M 20x1.5	12S	63	60 - 66
M 22x1.5	14S	79	75 - 83
M 24x1.5	16S	84	80 - 88
M 30x2	20S	126	120 - 132
M 36x2	25S	179	170 - 187
M 42x2	30S	263	250 - 275
M 52x2	38S	368	350 - 385

BSP swivel female

Thread BSPP	size	Nm nominal	Nm min. - max.
G1/4	-4	20	15 - 25
G3/8	-6	34	27 - 41
G1/2	-8	60	42 - 76
G5/8	-10	69	44 - 94
G3/4	-12	115	95 - 135
G1	-16	140	115 - 165
G1-1/4	-20	210	140 - 280
G1-1/2	-24	290	215 - 365
G2	-32	400	300 - 500

JIC 37° swivel female

Thread UNF	size	Flats From Wrench Resistance (FFWR)	Swivel Nut Torque Nm (Ref)
7/16-20	-4	2	18
1/2-20	-5	2	20
9/16-18	-6	1-1/2	30
3/4-16	-8	1-1/2	57
7/8-14	-10	1-1/2	81
1.1/16-12	-12	1-1/4	114
1.5/16-12	-16	1	160
1.5/8-12	-20	1	228
1.7/8-12	-24	1	265
2.1/2-12	-32	1	360

ORFS swivel female

Thread UNF	size	Flats From Wrench Resistance (FFWR)	Swivel Nut Torque Nm (Ref)
9/16-18	-4	1/2 to 3/4	25
11/16-16	-6	1/2 to 3/4	40
13/16-16	-8	1/2 to 3/4	55
1-14	-10	1/2 to 3/4	80
1.3/16-12	-12	1/3 to 1/2	115
1.7/16-12	-16	1/3 to 1/2	150
1.11/16-12	-20	1/3 to 1/2	205
2-12	-24	1/3 to 1/2	315
2-1/2x12	-32	–	–

Note: The assembly torques listed are higher than the test torques published in SAE J1453.





The torque values for other materials are as follows:

- Brass fittings and adapters
  - 65 % of the torque value for steel.
- Stainless steel and Monel
  - Use 5% higher than listed for steel. Threads to be lubricated for these materials.
- Dissimilar metals
  - Use torque value designated for the lower of the two metals.
- All fittings are dry except as noted above.

Note

Values given in tables are typical to achieve the recommended assembly methods when fitting material is steel zinc plated. For other materials different values will be applicable (see our recommendations for other materials on this page).

The Correct Method to Fit ISO 6162-1 Flange

			
• Make sure sealing surfaces are free of burrs, nicks, scratches or any contamination • Lubricate the O-ring with system fluid or compatible lubricant	• Position flange and clamp halves • Place lock washers on bolts and bolt through clamp halves	• Hand tighten bolts • Torque bolts in diagonal sequence in small increments to the appropriate torque level listed in chart	• Tighten bolts according to chart

Spanner torque values





ISO 6162-1 Flange

DN	Inch	Size	G Thread metric	Assembly torque Tolerances: max. 10%; min. 0% Nm	G Thread UNC (Inch)	Assembly torque Tolerances: max. 10%; min. 0% Nm
13	1/2	-8	M8x1.25	24	5/16-18	24
19	3/4	-12	M10x1.5	50	3/8-16	43
25	1	-16	M10x1.5	50	3/8-16	43
32	1-1/4	-20	M10x1.5	50	7/16-14	70
38	1-1/2	-24	M12x1.75	92	1/2-13	105
51	2	-32	M12x1.75	92	1/2-13	105
64	2-1/2	-40	M12x1.75	92	1/2-13	105
76	3	-48	M16x2	210	5/8-11	210
89	3-1/2	-56	M16x2	210	5/8-11	210
102	4	-64	M16x2	210	5/8-11	210
127	5	-80	M16x2	210	5/8-11	210

ISO 6162-1 Flange 5000 psi

DN	Inch	Size	G Thread metric	Assembly torque Tolerances: max. 10%; min. 0% Nm	G Thread UNC (Inch)	Assembly torque Tolerances: max. 10%; min. 0% Nm
32	1-1/4	-20	-	-	7/16-14	70
38	1-1/2	-24	-	-	1/2-13	105
51	2	-32	-	-	1/2-13	105

The Correct Method to Fit ISO 6162-2 Flange

			
• Make sure sealing surfaces are free of burrs, nicks, scratches or any contamination • Lubricate the O-ring with system fluid or compatible lubricant	• Position flange and clamp halves • Place lock washers on bolts and bolt through clamp halves	• Hand tighten bolts • Torque bolts in diagonal sequence in small increments to the appropriate torque level listed in chart	• Tighten bolts according to chart

Spanner torque values

ISO 6162-2 Flange

DN	Inch	Size	G Thread	Assembly torque Tolerances: max. 10%; min. 0%	G Thread	Assembly torque Tolerances: max. 10%; min. 0%
			metric	Nm	UNC (Inch)	Nm
13	1/2	-8	M8x1.25	24	5/16-18	24
19	3/4	-12	M10x1.5	50	3/8-16	43
25	1	-16	M12x1.75	92	7/16-14	70
32	1-1/4	-20	M12x1.75	130	1/2-13	105
32	1-1/4	-20	M14x2	150	-	-
38	1-1/2	-24	M16x2	210.0	5/8-11	210
51	2	-32	M20x2.5	400.0	3/4-10	360
64	2-1/2	-40	M24x3	600.0	-	-
76	3	-48	M30x3.5	650.0	-	-

ISO 6162-2 Flange 8000 psi

DN	Inch	Size	G Thread	Assembly torque Tolerances: max. 10%; min. 0%	G Thread	Assembly torque Tolerances: max. 10%; min. 0%
			metric	Nm	UNC (Inch)	Nm
19	3/4	-12	M10x1.5	60	3/8-16	-
25	1	-16	M12x1.75	92	7/16-14	-
32	1-1/4	-20	M12x1.75	130	1/2-13	-
32	1-1/4	-20	M14x2	150	-	-

Chemical Resistance Table

Warning ! **This chemical compatibility guide must not be used in conjunction with any other compatibility guides from previous or future catalogue editions, bulletins or publications. Incorrect use of these charts could result in death, personal injury or property damage.**

Hose Selection by Medium and Hose Type

This hose compatibility chart is a ready reference of Parker hose compatibility with various fluid media. It is intended as a guide to chemical compatibility with inner tube materials and assembly lubricants applied internally.

The outer cover of the hose is intended to protect the reinforcement layer(s) from mechanical influences (abrasion, weathering etc), as such the cover compounds are not designed to exhibit the same chemical resistance as the tube compounds. The Hose Division Technical Department should be consulted about the compatibility of the cover should the application involve the extended exposure or immersion in a liquid.

The specific recommendations are based upon field experience, the advice of various polymer or fluid suppliers, and specific laboratory experiments. It must be stressed, however, that this information is offered only as a guide. Final hose selection depends also upon pressure, fluid temperature, ambient temperature, and special requirements or variations, which may not be known by Parker. Legal and other regulations must be followed with particular care.
Where an external compatibility problem may occur, or for fluids not listed, we encourage you to first contact the fluid manufacturer for a recommendation prior to contacting your Parker Field Representative or the Technical Department, Hose Products Division Europe (**HPDE_Helpdesk@parker.com**)

Use the Chart as Follows:

1. Locate medium to be carried using the Chemical Resistance Table on the following pages.
2. Select suitability of hose and fitting material from the table based on the letter rating in the table. See resistance rating key below for explanation of compatibility ratings. See list of numerals below for an explanation when a numeral, or a numeral and a letter rating are present in the table.
3. The Column headings on the Chemical Resistance Table, I, II, III, IV, V refer to specific groups of hoses.
4. Locate hose part number under Column I, II, III, IV, V. VI from the list below.
5. For fitting material availability refer to appropriate fitting section of catalogue.
6. Check hose specifications in this catalogue. Contact Hose Products Division Europe Technical Department on any items not catalogued.

Resistance Rating Key

A = Preferred, good to excellent with little or no change in physical properties.
F = Fair, marginal or conditional with noticeable effects on physical properties.
X = Unsuitable, severe effects on physical properties.
~ = No rating, insufficient information.

Numerals

1. For air or gaseous applications above 250 psi (1.7 MPa), the cover should be pin pricked.
2. Legal and insurance regulations must be considered. Contact HPDE Technical Department for more information.
3. Push-Lok hoses (801, 804, 821FR, 831, 836, 837BM, 837PU, 830M, 838M) are not recommended for any type of fuel.
4. Use 285 hose. The compatibility of the system's refrigeration oil with these hoses needs to be evaluated on a case by case basis. Contact HPDE Technical Department for more information. Chemical compatibility does not imply low permeation.
5. 65 °C (150 °F) maximum.
6. Satisfactory at some concentrations and temperatures, unsatisfactory at others.
7. For phosphate ester fluids use 304, 774, 804 or F42 hoses.
8. Acceptable for flushing hose assemblies.
9. 221FR hose recommended.
10. For dry air applications, hoses with inner tubes from columns IV and V are preferred. See hose specifications for maximum recommended temperatures with air.
11. 100 °C (212 °F) maximum.
12. 121 °C (250 °F) maximum.
13. Hoses for gas application are available from Parker.
    Please contact the Technical Department for more information about the products as well as the legal application requirements.
14. 70 °C maximum for hoses 801, 837BM, 837PU
15. No rating / insufficient information about chemical compatibility for hoses 801, 837BM, 837PU.

Hose Types

Column I:	201, 601, 701, 701TC , 731, 731TC, 77C, 881, H31, H29, R35, RS35TC, R42, H31TC, H29TC, R35TC, R42TC, H31ST, H29ST, R42ST, H29RH, R50TC, R56TC, BPK
Column II:	371LT, 421TC, 421WC, 441, 441RH, 461LT, 471TC, 493, 681, 681DB, 811, 811S
Column III:	221FR, 301SN, 301TC, 372, 372RH, 372TC, 387, 387ST, 387TC, 412, 412ST, 421RH, 421SN, 462, 462CLF, 462ST, 462TC, 477, 477ST, 477TC, 487, 487TC, 487ST, 492, 492ST, 492TC, 692, 692Twin, 722, 722ST, 722TC, 722 CLF, 787, 787TC, 797, 797TC, 831
Column IV:	206, 213, 293, 426, 436, 611HT, 821FR, 836, 801*, 837BM*, 837PU*
Column V:	304, 774, 804, F42 - Special EPDM hose for Phosphoric Ester
Column VI:	830M, 838M

Note: * See Numeral 15

Caution: The fluid manufacturer's recommended maximum operating temperature for any specific name-brand fluid should be closely observed by the user. Specific name brand fluids can vary greatly between manufacturers even though they are considered to be from the same family of fluids. Using fluids above the manufacturer's maximum recommended temperature can cause the fluid to break down, creating by-products that can be harmful to elastomers or other materials used in the system. When selecting a hose type, both the fluid manufacturer and hose manufacturer's maximum temperature limit must be taken into consideration, with the lower of the two taking precedence.

Medium	I	II	III	IV	V	VI	STEEL	BRASS	SS
3M FC-75	A	A	A	A 15	A	A	A	A	A
A									
Acetic Acid	X	X	X	A 15	6	X	X	X	A
Acetone	X	X	X	A 15	A	X	A	A	A
Acetylene	X	X	X	X	X	-	-	-	-
AEROSHELL Turbine Oil 500 (See MIL-L-23699)	X	X	F	X	X	-	A	A	A
Agip Arnica 46	A	A	A	A	X	A			
Agip synth 2000	A	A	A	A	X	A			
Air	A, 1, 10	A, 1, 10	A, 1, 10	A 1, 10	A, 1, 10	A	A	A	A
Air (dry)	X	F, 1, 10	F, 1, 10	A 1, 10	A, 1, 10	A	A	A	A
AEROSHELL Fluid 41	-	F	A	-	-	-			
Alusol M	-	A	A	-	-	-			
Alcohol (Methanol-Ethanol)	F	F	F	A 15	F	-	F	A	A
Ammonia (Anhydrous)	X	X	X	X	X	-	X	X	X
Ammonium Chloride	A	A	A	A 15	A	A	X	X	X
Ammonium Hydroxide	F	F	F	A 15	A	X	F	X	A
Ammonium Nitrate	A	A	A	A 15	A	-	F	X	A
Ammonium Phosphate	A	A	A	A 15	A	-	X	X	F
Ammonium Sulfate	A	A	A	A 15	A	-	F	X	F
Ambra Multi G (NH 410 B)	-	A	A	-	-	-			
Amoco 32 Rykon	X	A	A	F 14	X	A	A	A	A
Ampol PE 46	X	X	X	X	A, 7	F	A	A	A
AMSOIL Synthetic ATF	F	A	A	A 15	X	F	A	A	A
Amyl Alcohol	X	X	X	A 15	F	-	X	A	A
Anderol 495,497,500,750	X	X	F	A 15	X	X	A	A	A
Aniline	X	X	X	A 15	A	X	A	X	A
Animal Fats	X	F	F	A 15	F	-	6	6	A
Aquacent Light, Heavy	X	A	A	X	X	A	A	A	A
Aral Vitam HF46	A	A	A	X	X	F			
Argon	A	A	A	A	A	A	A	A	A
Aromatic 100,150	X	F	F	-	X	F	A	A	A
Arrow 602P	A	A	A	A 14	X	A	A	A	A
Asphalt	X	F	F	F 14	X	A	F	F	A
ASTM #3 Oil	F	F	F	A 15	X	-	A	A	A
ATF-M	F	A	A	A 14	X	A	A	A	A
Avantin 361	-	A	A	-	-	-			
Avia Syntofluid PE B50	A	A	A	-	-	-			
Avialith 2 WC	-	A	A	-	-	-			
Automotive Brake Fluid	X	X	X	X	-	X	X	X	X
AW 32,46,68	F	A	A	A 14	X	A	A	A	A
B									
BCF	F	F	F	F 15	-	-	A	A	A
Benz Petraulic 32,46,68,100,150,220,320,460	F	A	A	A 14	X	A	A	A	A
Benzene, Benzol	X	X	X	A 15	X	F	A	A	A
Benzgrind HP 15	-	A	A	A 15	X	-	A	A	A
Benzine	X	X	X	F 15	X	-	A	A	A
Biodegradable Hydraulic Fluid 112B	X	A	A	X	-	-	A	A	A
Biodiesel E20	X	F	X	X	X	X	-	-	-
Biodiesel E100	X	F	X	X	X	X	-	-	-
Biodiesel E60	X	F	X	X	X	X	-	-	-
Biodiesel E80	X	F	X	X	X	X	-	-	-
Borax	F	F	F	A 15	A	-	F	A	A
Boric Acid	A	A	A	X	A	X	X	6	A
Brayco 882	X	A	A	A 15	X	-	A	A	A
Brayco Micronic 745	X	X	A	F 14	X	A	A	A	A
Brayco Micronic 776RP	F	A	A	F 14	X	A	A	A	A
Brayco Micronic 889	X	F	F	-	X	-	A	A	A
Brine	F	F	F	A 15	A	-	X	F	F

Medium	I	II	III	IV	V	VI	STEEL	BRASS	SS
Butane		See 2 & 13				F	A	A	A
Butyl Alcohol, Butanol	F	F	F	A 15	F	-	F	F	A
C									
Calcium Chloride	A	A	A	A 15	A	-	F	F	X
Calcium Hydroxide	A	A	A	A 15	A	-	A	A	A
Calcium Hypochlorite	X	X	X	A 15	A	-	X	F	X
Calibrating Fluid	A	A	A	A 14	X	A	A	A	A
Carbon Dioxide, gas	F	F	F	F 15	6	-	A	A	A
Carbon Disulfide	X	X	X	A 15	X	-	A	F	A
Carbon Monoxide (hot)	F	F	F	A 15	6	-	F	6	A
Carbon Tetrachloride	X	X	X	A 15	X	-	6	6	6
Carbonic Acid	F	F	F	X	F	X	X	X	F
Castor Oil	A	A	A	A 15	A	-	A	A	A
Castrol 5000	X	F	F	A 15	X	X	A	A	A
Castrol Wendax	-	A	A	-	-	-			
Cellosolve Acetate	X	X	X	X	A	-	X	X	A
Celluguard	A	A	A	-	A	-	A	A	A
Cellulube 90, 150, 220 300, 550, 1000	X	X	X	-	A	-	A	A	A
Chevron Clarity AW 32, 46, 68	A	A	A	A 14	X	A	A	A	A
Chevron FLO-COOL 180	F	F	F	-	X	-	A	A	A
Chevron FR-8, 10, 13, 20	X	X	X	X	A, 7	F	A	A	A
Chevron Hydraulic Oils AW MV 15, 32, 46, 68, 100	A	A	A	A 14	X	A	A	A	A
Chevron HyJet IV (9)	X	X	X	X	A, 7	F	A	A	A
Citric Acid	F	A	A	X	A	X	X	X	6
Commonwealth EDM 242, 244	A	A	A	-	X	A	A	A	A
CompAir CN300	X	X	X	A 15	X	X	A	A	A
CompAir CS100, 200, 300, 400	X	X	X	A 15	X	X	A	A	A
Condat D46 - D68	F	A	A	-	-	-			
Coolanol 15, 20, 25, 35, 45	A	A	A	A 15	A	X	A	A	A
Copper Chloride	F	A	A	X	A	-	X	X	X
Copper Sulfate	A	A	A	X	A	-	X	X	F
Cosmolubric HF-122, HF-130, HF-144	X	F	A	X	X	-	A	A	A
Cosmolubric HF-1530	X	F	A	X	X	-	A	A	A
Cottonseed Oil	F	A	A	F 15	X	-	A	A	A
CPI CP-4000	X	X	X	A 15	X	-	A	A	A
Crude Petroleum Oil	F	A	A	A 14	X	A	F	F	A
CSS 1001Dairy Hydraulic Fluid	F	A	A	A 15	X	-	A	A	A
D									
Daphne AW32	A	A	A	A 14	X	A	A	A	A
Dasco FR 201-A	A	A	A	-	X	-	A	A	A
Dasco FR150, 200, 310	F	A	A	-	A	-	A	A	A
Dasco FR300, FR2550	X	X	X	-	X	F	A	A	A
Dasco FR355-3	X	F	A	X	X	X	A	A	A
Deicer Fluid 419R	A	A	A	-	-	A	A	A	A
Deionized Water	A	A	A	A 15	A	-	F	F	A
Dexron II ATF	F	A	A	A 14	X	A	A	A	A
Dexron III ATF	X	F, 11	F, 11	A 15, 12	X	-	A	A	A
Diesel Fuel	F, 3	A, 3	A, 3	A 15, 3	X	A(2)	A	A	A
Diester Fluids	X	X	X	X	X	X	A	A	A
Divinol HLP 46	-	A	A	-	-	-			
DOT III-IV	X	X	X	X	F	-			
Dow Corning 2-1802 Sullair (24KT)	-	-	-	F 15	-	-	A	A	A
Dow Corning DC 200, 510, 550, 560, FC126	A	A	A	A 15	-	-	A	A	A
Dow HD50-4	F	F	F	-	-	-	-	-	A
Dow Sullube 32	-	-	-	F 15	-	-	A	A	A
Dowtherm A,E	X	X	X	A 15	X	-	A	A	A
Dowtherm G	X	X	X	X	X	-	A	A	A
Duro AW-16, 31	A	A	A	-	X	-	A	A	A

Medium	I	II	III	IV	V	VI	STEEL	BRASS	SS
Duro FR-HD	A	A	A	-	X	-	A	A	A
E									
EcoSafe FR-68	A	A	A	-	X	X	A	A	A
Ethanol	F	F	F	A 15	F	-	F	A	A
Ethers	X	X	X	A 15	X	-	A	A	A
Ethyl Acetate	X	X	X	A 15	F	-	F	A	A
Ethyl Alcohol	F	F	F	A 15	F	-	F	A	A
Ethyl Cellulose	F	F	F	A 15	F	-	X	F	F
Ethyl Chloride	X	X	X	X	A	-	F	F	F
Ethylene Dichloride	X	X	X	A 15	X	-	X	A	X
Ethylene Glycol	F	A	A	A	A	A	A	F	A
Exxon 3110 FR	A	A	A	A 15	X	A	A	A	A
Exxon Esstic	A	A	A	A 14	A	A	A	A	A
Exxon Nuto H 46, 68	A	A	A	A 14	X	A	A	A	A
Exxon Tellura Indusrial Process Oils	A	A	A	A 14	X	A	A	A	A
Exxon Terresstic, EP	A	A	A	A 14	A	A	A	A	A
Exxon Turbo Oil 2380	X	F	F	A 15	X	X	A	A	A
Exxon Univolt 60, N61	F	A	A	A 14	X	A	A	A	A
F									
FE 232 (Halon)	X	X	X	X	F	-	A	A	A
Fenso 150	-	A	A	-	X	A	A	A	A
Formaldehyde	X	X	X	A 15	A	-	X	F	A
Formic Acid	X	X	X	X	A	X	X	6	X
Freons see refrigerants	-	-	-	-	-	-	-	-	-
Fuel Oil	F, 3	A, 3	A, 3	A 15, 3	X	A(2)	A	A	A
Fyre-Safe 120C,126,155,1090E,1150,1220,1300E	X	X	X	X	A, 7	F	A	A	A
Fyre-Safe 200C, 225, 211	F	A	A	A	A	F	A	A	A
Fyre-Safe W/O	A	A	A	A 15	X	A	A	A	A
Fyrguard 150, 150-M, 200	A	A	A	A	A	F	A	A	A
Fyrquel 60, 90, 150, 220, 300, 550, 1000	X	X	X	X	A, 7	F	A	A	A
Fyrquel EHC, GT, LT, VPF	X	X	X	X	A, 7	F	A	A	A
Fyrtek MF, 215, 290, 295	X	X	X	X	X	F	A	A	A
G									
Gardner-Denver GD5000, GD8000	X	X	X	A 15	X	X	A	A	A
Gasoline		See 9				-	A	A	A
Glue	F	F	F	-	X	-	A	F	A
Glycerine, Glycerol	A	A	A	A 15	A	-	A	F	A
Grease	A	A	A	A 14	X	A	A	A	A
Gulf-FR Fluid P37, P40, P43, P45, P47	X	X	X	A 15	A	-	A	A	A
H									
H-515 (NATO)	A	A	A	-	X	-	A	A	A
Halon 1211, 1301	F	F	F	F 15	-	-	A	A	A
Helium Gas	X	X	X	X	X	-	A	A	A
Heptane	X	F	F	A 15	X	-	A	A	A
Hexane	X	F	F	A 15	X	-	A	A	A
HF-20, HF-28		A	A	A	A	F	A	A	A
Houghto-Safe 1055, 1110, 1115, 1120, 1130 (9)	X	X	X	X	A, 7	F	A	A	A
Houghto-Safe 271 to 640	F	A	A	A	A	F	A	A	A
Houghto-Safe 419 Hydraulic Fluid	A	A	A	-	X	-	A	A	A
Houghto-Safe 419R Deicer Fluid	A	A	A	-	-	A	A	A	A
Houghto-Safe 5046, 5046W, 5047-F	A	A	A	A 15	X	-	A	A	A
HP 100C (Jack hammer oil)	F	A	A	A 14	X	A	A	A	A
HPWG 46B	F	A	A	A	-	F	A	A	A
Hul-E-Mul	A	A	A	-	X	-	A	A	A
Hychem C, EP1000, RDF	A	A	A	A 15	A	-	A	A	A
Hycut SE 12	F	A	A	-	-	-			
Hycut SE 46	F	A	A	-	-	-			
Hydra Safe E-190	A	A	A	A 15	X	-	A	A	A

Medium	I	II	III	IV	V	VI	STEEL	BRASS	SS
Hydra-Cut 481, 496	A	A	A	-	X	-	A	A	A
Hydrafluid 760	A	A	A	-	X	-	A	A	A
Hydrochloric Acid	X	X	X	X	X	X	X	X	X
Hydrofluoric Acid	X	X	X	X	X	X	X	6	X
Hydrogen Gas	X	X	X	X	X	-	A	A	A
Hydrogen Peroxide	X	X	X	A 15	X	-	X	X	6
Hydrogen Sulfide	X	X	X	X	A	-	X	X	6
Hydrolube	A	A	A	A 15	A	-	A	A	A
Hydrolubric 120-B, 141, 595	F	A	A	A 15	A	-	A	A	A
Hydrosafe Glycol 200	A	A	A	A	A	F	A	F	A
Hydrovane Fluid Force 2000	-	A	A	-	-	-			
HyJet IV	X	X	X	X	A, 7	-	A	A	A
HT BRADOL (Virto)	-	A	A	-	-	-			
I									
Ideal Yellow 77	A	A	A	A 15	X	-	A	A	A
Imol S150 to S550	X	X	X	-	-	-	A	A	A
Ingersoll Rand SSR Coolant	X	X	X	A 15	X	X	A	A	A
Isocyanates	X	X	X	A 15	X	-	A	-	A
Isooctane	X	F	F	A 15	X	-	A	A	A
Isopar H	X	X	X	X	X	-	A	A	A
Isopropyl Alcohol	F	F	F	A 15	F	-	F	A	A
J									
Jayflex DIDP	X	X	X	X	A	-	A	A	A
JP3 and JP4	X	A,3	A,3	-	X	A(2)	A	A	A
JP5	X	A,3	A,3	F 15,3	X	A(2)	A	A	A
JP9	X	X	X	X	X	-	A	-	A
K									
Kaeser 150P, 175P, 325R, 687R	X	X	X	A 15	X	-	A	A	A
Kerosene	X	A	A	F 14	X	A	A	A	A
KSL-214, 219, 220, 222	X	X	X	A 15	X	-	A	A	A
L									
Lacquer	X	X	X	A 15	X	-	X	A	A
Lacquer Solvents	X	X	X	A 15	X	-	X	A	A
Lactic Acids	X	X	X	X	X	X	X	X	A
Lindol HF	X	X	X	A 15	A	-	A	A	A
Linseed Oil	F	A	A	A 15	A	-	A	A	A
LP-Gas		See 13				-	A	A	A
M									
Magnesium Chloride	A	A	A	A 15	A	-	X	X	X
Magnesium Hydroxide	F	F	F	A 15	A	-	F	F	F
Magnesium Sulfate	A	A	A	A 15	A	-	A	F	A
Mercaptans	X	X	X	X	X	-	-	-	-
Methane		See 13				-	A	A	A
Methanol	A	F	A	A 15	F	-	F	A	A
Methyl Alcohol	A	F	A	A 15	F	-	F	A	A
Methyl Chloride	X	X	X	A 15	X	-	A	A	A
Methyl Ethyl Ketone (MEK)	X	X	X	A 15	X	-	F	A	A
Methyl Isopropyl-Ketone	X	X	X	X	X	-	F	A	A
Metsafe FR303, FR310, FR315, FR330, FR350	X	X	X	X	X	F	A	A	A
Microzol-T46	X	A	A	-	X	-	A	A	A
MIL-H-544	-	A	A	-	-	-			
MIL-B-46176A	X	X	X	X	X	-	X	X	X
MIL-H-46170	X	F	F	A 15	X	-	A	A	A
MIL-H-5606	F	A	A	A 14	X	A	A	A	A
MIL-H-6083	F	A	A	A 15	X	-	A	A	A
MIL-H-7083	F	A	A	A 15	X	-	A	A	A
MIL-H-83282	F	A	A	A 15	X	-	A	A	A
MIL-L-2104, 2104B	F	A	A	A 14	X	A	A	A	A

Medium	I	II	III	IV	V	VI	STEEL	BRASS	SS
MIL-L-23699	X	X	X	X	X	X	A	A	A
MIL-L-7808	F	A	A	-	X	-	A	A	A
Mine Guard FR	A	A	A	-	A	-	A	A	A
Mineral Oil	A	A	A	F 14	X	A	A	A	A
Mineral Spirits	8	8	8	8	X	-	A	A	A
Mobil Aero HF	-	A	A	-	-	-			
Mobil Aero HFE	F	A	A	F 14	X	A	A	A	A
Mobil ATF 220	-	A	A	-	-	-			
Mobil DTE 11M, 13M, 15M, 16M, 18M, 19M	F	A	A	A 14	X	A	A	A	A
Mobil DTE 22, 24, 25, 26	F	A	A	A 14	X	A	A	A	A
Mobil EAL 224H	X	A	A	X	-	-	A	A	A
Mobil EAL Artic 10, 15, 22,32, 46, 68, 100	X	X	X	X	X	X	A	A	A
Mobil Glygoyle 11, 22, 30, 80	X	F	F	-	X	-	A	A	A
Mobil HFA	F	A	A	A 15	X	-	A	A	A
Mobil Jet 2	X	F	F	A 15	X	-	A	A	A
Mobil Nyvac 20, 30, 200, FR	F	A	A	A	A	F	A	A	A
Mobil Rarus 824, 826, 827	X	X	X	A 15	X	X	A	A	A
Mobil SHC 524	-	A	A	-	-	-			
Mobil SHC 600 Series	F	A	A	A 15	X	-	A	A	A
Mobil SHC 800 Series	F	A	A	A 15	X	-	A	A	A
Mobil Vactra Oil	A	A	A	F 14	X	A	A	A	A
Mobil XRL 1618B	X	X	X	X	A, 7	F	A	A	A
Mobilfluid 423	F	A	A	A 14	X	A	A	A	A
Mobilgear SHC 150, 220, 320, 460, 680	F	F	F	A 15	X	-	A	A	A
Mobilarma 525	A	A	A	F 14	X	A	A	A	A
Molub-Alloy 890	X	X	X	A 15	X	-	A	A	A
Moly Lube "HF" 902	F	F	F	F 14	X	A	A	A	A
Monolec 6120 Hydraulic Oil	A	A	A	A 14	X	A	A	A	A
Morpholine (pure additive)	X	X	X	X	X	-	X	X	A
Motorex Corex HLP 46	A	A	A	-	-	-			
N									
Naptha	F	F	A	A 15	X	-	A	A	A
Napthalene	X	X	X	A 15	X	-	A	A	A
Natural Gas		See 13				-	A	A	A
Nitric Acid	X	X	X	X	X	X	X	X	F
Nitrobenzene	X	X	X	A 15	X	-	X	X	A
Neste SE 46	F	A	A	-	-	-			
Neste 46 32	A	A	A	-	-	-			
Nitrogen, gas	F, 1	F, 1	F, 1	F 15, 1	F, 1	-	A	A	A
NORPAR 12, 13, 15	8	8	8	8	X	-	A	A	A
Nuto H 46, 68	A	A	A	A 14	X	A	A	A	A
Nyvac 20, 30, 200, FR	F	A	A	A	A	F	A	A	A
Nyvac Light	X	X	X	-	A	-	A	A	A
O									
Oceanic HW	F	A	A	A	X	F	A	A	A
Oxygen, gas	A	X	X	X	X	-	X	A	A
Ozone	F	X	F	F	A	A	A	A	A
P									
Pacer SLC 150, 300, 500, 700	X	X	X	A 15	X	-	A	A	A
Panolin HLP 46	F	A	A	-	-	-			
Panolin TURWANDA SYNTH 46	F	A	A	-	-	-			
Pennzbell AWX	F	A	A	F 14	X	A	A	A	A
PENTOSIN CHF 11S	F	A	A	F	A	X	A	A	A
Perchloroethylene	X	X	X	X	X	-	F	X	A
Petroleum Ether	X	F	F	F 14	X	A	A	A	A
Petroleum Oils	A	A	A	A 14	X	A	A	A	A
Phenol (Carbolic Acid)	X	X	X	A 15	X	X	X	F	A
Phosphate Ester Blends	X	X	X	X	X	F	A	A	A

Medium	I	II	III	IV	V	VI	STEEL	BRASS	SS
Phosphate Esters	X	X	X	X	A, 7	-	A	A	A
Phosphoric Acid 10 %	F	X	X	X	A	X	X	X	F
Plantosin HVI 46	-	A	A	-	-	-			
Plexus 46	F	A	A	-	-	-			
Polyalkylene Glycol	A	F	F	-	X	-	A	A	A
Polyol Ester	X	F	A	X	X	-	A	A	A
Potassium Chloride	A	A	A	A 15	A	-	X	F	F
Potassium Hydroxide	X	X	X	A 15	A	-	6	X	A
Potassium Sulfate	A	A	A	A 15	A	-	A	A	A
Propane		See 13				-	A	A	A
Propylene Glycol	A	A	A	A 15	A	-	F	F	F
Pydraul 10-E, 29-E, 50-E, 65-E, 90-E, 115-E	X	X	X	X	A, 7	F	A	A	A
Pydraul 230-C, 312-C, 68-S	X	X	X	X	A, 7	F	A	A	A
Pydraul 60, 150, 625, F9	X	X	X	X	A, 7	-	A	A	A
Pydraul 90, 135, 230, 312, 540, MC	X	X	X	X	X	-	A	A	A
Pydraul A-200	X	X	X	A 15	X	-	A	A	A
Pyro Gard 43, 230, 630	X	X	X	X	X	-	A	A	A
Pyro Gard C, D, R, 40S, 40W	F	A	A	F 15	X	A	A	A	A
Pyro Guard 53, 55, 51, 42	X	X	X	X	A, 7	-	A	A	A
Q									
Q8 Holbein Bio Plus	F	A	A	-	-	-			
Quintolubric 700	A	A	A	A 15	A	-	A	F	A
Quintolubric 807-SN	F	A	A	-	X	-	A	A	A
Quintolubric 822, 855	X	F, 5	A, 5	X	X	X	A	A	A
Quintolubric 888	F	A, 5	A, 5	X	X	-	A	A	A
R									
Rando	A	A	A	A 14	X	A	A	A	A
Rando HD 46	-	A	A	-	-	-			
Rayco 782	X	F	A	X	X	-	X	X	X
Renault ST 46M	A	A	A	-	-	-			
Renolin Lift	-	A	A	-	-	-			
Renolin HVI 46	-	A	A	-	-	-			
Refrigerant 124		See 4				X	A	A	A
Refrigerant Freon 113, 114	X	X	X	X	X	X	A	A	A
Refrigerant Freon 12		See 4				X	A	A	A
Refrigerant Freon 22		See 4				X	A	A	A
Refrigerant Freon 502		See 4				X	A	A	A
Refrigerant HFC134A		See 4				X	A	A	A
Reolube Turbofluid 46	X	X	X	X	A, 7	-	A	A	A
Rivolta B.H.23	F	A	A	-	-	-			
Rotella	A	A	A	A 14	X	A	A	A	A
Royal Bio Guard 3032, 3046, 3068, 3100	X	~	A	X	X	X	A	A	A
Royco 2200, 2210, 2222, 2232, 2246, 2268	X	X	X	X	X	X	A	A	A
Royco 4032, 4068, 4100, 4150	X	X	X	A 15	X	X	A	A	A
Royco 756, 783	A	A	A	A 14	X	A	A	A	A
Royco 770	X	F	F	F 15	X	-	A	A	A
RTV Silicone Adhesive Sealants	X	X	X	X	X	-	A	A	A
S									
Safco-Safe T10, T20	-	-	-	-	A	-	F	F	A
Safety-Kleen ISO 32, 46, 68 hydraulic oil	F	A	A	-	X	A	A	A	A
Safety-Kleen Solvent	8	8	8		X	8	A	A	A
Santoflex 13	F	F	F	-	F	-	A	A	A
Santosafe 300	X	X	X	-	X	-	A	A	A
Santosafe W/G 15 to 30	-	-	-	A 15	A	-	A	A	A
Sea Water	A	F	F	A 15	A	A	X	F	A
Sewage	F	F	F	A 15	F	-	X	F	A
Shell 140 Solvent	8	8	8	8	X	-	A	A	A
Shell Clavus HFC 68	X	X	X	X	X	X	A	A	A

Medium	I	II	III	IV	V	VI	STEEL	BRASS	SS
Shell Comptella Oil	F	F	F	A 14	X	A	A	A	A
Shell Comptella Oil S 46, 68	F	F	F	A 14	X	A	A	A	A
Shell Comptella Oil SM	F	F	F	A 14	X	A	A	A	A
Shell Diala A, (R) Oil AX	F	A	A	F 14	X	A	A	A	A
Shell FRM	-	-	-	-	X	-	A	A	A
Shell IRUS 902, 905	A	A	A	-	A	-	A	A	A
Shell IRUS Fluid DU 46	F	A	A	-	-	-			
Shell Naturelle HF-E	F	A	A	F	X	F14	A	A	A
Shell Pella-A	A	A	A	A 15	X	-	A	A	A
Shell Tellus	F	A	A	A 14	X	A	A	A	A
Shell Tellus TD 46	A	A	A	A	A	X	A	A	A
Shell Thermia Oil C	A	A	A	A 14	X	A	A	A	A
Shell Turbo R	X	F	F	A 15	X	X	A	A	A
SHF 220, 300, 450	X	X	A	X	X	X	A	A	A
Silicate Esters	A	F	F	A 15	X	-	A	A	A
Silicone Oils	A	A	A	-	-	-	A	A	A
Silicone Sealants	X	X	X	X	X	-	A	A	A
Skydrol 500B-4, LD-4	X	X	X	X	A, 7	F	A	A	A
Soap Solutions	E	F	F	F 15	A	A	A	A	A
Soda Ash, Sodium Carbonate	A	A	A	A 15	A	-	A	F	A
Sodium Bisulfate	F	X	X	A 15	A	-	F	A	F
Sodium Chloride	A	F	F	A 15	A	-	X	F	A
Sodium Hydroxide	A	X	X	A 15	A	-	A	X	A
Sodium Hypochlorite	A	X	X	X	A	X	X	X	X
Sodium Nitrate	A	F	F	A 15	A	A	A	F	A
Sodium Peroxide	F	X	X	X	A	X	X	X	A
Sodium Silicate	A	A	A	A 15	A	-	A	A	A
Sodium Sulfate	A	A	A	A 15	A	-	A	A	A
Soybean Oil	F	A	A	A 15	X	-	A	A	A
SSR Coolant	X	X	X	A 15	X	X	A	A	A
Steam	X	X	X	X	X	-	F	A	A
Stoddard Solvent	8	8	8	8	X	8	A	A	A
Sulfur Chloride	X	X	X	F	X	-	X	X	X
Sulfur Dioxide	X	X	X	X	F	-	X	F	F
Sulfur Trioxide	X	X	X	F	F	-	X	X	X
Sulfuric Acid (0% to 30% room temperture)	F, 6	F, 6	F, 6	X	F, 6	-	6	X	6
Summa-20, Rotor, Recip	X	X	X	F	X	-	A	A	A
Summit DSL-32,68,100,125	X	X	X	F	X	-	A	A	A
Sun Minesafe, Sun Safe	X	F	F	F	X	-	A	A	A
Sundex 8125	X	F	F	-	X	-	A	A	A
Suniso 3GS	A	A	A	A 14	X	A	A	A	A
Sun-Vis 722	X	F	F	-	X	-	A	A	A
Super Hydraulic Oil 100, 150, 220	A	A	A	A 14	X	A	A	A	A
SUVA MP 39, 52, 66	X	X	X	X	X	X	A	A	A
SYNCON Oil	X	X	X	X	X	-	A	A	A
Syndale 2820	X	F	F	-	-	-	A	A	A
Synesstic 32,68,100	X	X	X	X	X	X	A	A	A
Syn-Flo 70,90	X	X	X	X	X	-	A	A	A
SYN-O-AD 8478	X	X	X	X	A, 7	F	A	A	A
T									
Tannic Acid	F	A	A	F	A	X	X	F	X
Tar	F	F	F	F	X	-	X	F	A
Tellus (Shell)	F	A	A	A 14	X	F	A	A	A
Texaco 760 Hydrafluid	-	-	-	-	X	-	A	A	A
Texaco 766, 763 (200 - 300)	-	-	-	-	A	-	F	F	A
Texaco A-Z Oil	A	A	A	F 14	X	A	A	A	A
Texaco Spindura Oil 22	F	F	F	F 14	X	A	A	A	A
Texaco Way Lubricant 68	A	A	A	A 14	X	A	A	A	A

Medium	I	II	III	IV	V	VI	STEEL	BRASS	SS
Thanol-R-650-X	X	F	F	-	X	-	A	A	A
Thermanol 60	X	X	X	X	X	-	A	A	A
Toluene, Toluol	X	X	X	X	X	-	A	A	A
Transmission Oil	A	A	A	A 14	X	A	A	A	A
Tribol 1440	X	X	X	X	A	F	A	A	A
Trichloroethylene	X	X	X	F	X	-	X	A	A
Trim-Sol	F	A	A	F	X	-	A	A	A
Turbinol 50, 1122, 1223	X	X	X	X	A, 7	-	A	A	A
Turpentine	X	X	X	F	X	-	A	A	A
U									
Ucon Hydrolubes	F	A	A	A	A	F	A	A	A
UltraChem 215,230,501,751	X	X	X	A 15	X	-	A	A	A
Univis J26	A	A	A	A 14	X	A	A	A	A
Unleaded Gasoline		See 9				-	A	A	A
Unocal 66/3 Mineral Spirits	8	8	8	8	X	-	A	A	A
Urea	F	F	F	A 15	F	-	F	-	F
Urethane Formulations	A	A	A	A 15	-	-	A	A	A
V									
Van Straaten 902	A	A	A	A 15	X	-	A	A	A
Varnish	X	X	X	F	X	-	F	F	A
Varsol	8	F	F	8	X	-	A	A	A
Versilube F44, F55	-	A	A	A 15	-	-	A	A	A
Vinegar	X	X	X	A 15	A	-	F	X	A
Vital 29, 4300, 5230, 5310	X	X	X	X	X	-	A	A	A
Volt Esso 35	A	A	A	A 15	X	-	A	A	A
W									
Water	A	A	A	A	A	A	F	A	A
Water / Glycols	A	A	A	A	A	F	A	F	A
X									
Xylene, Xylol	X	X	X	X	X	-	A	A	A
Z									
Zerol 150	A	A	A	A 14	X	A	A	A	A
Zinc Chloride	A	A	A	X	A	-	X	X	F
Zinc Sulfate	A	A	A	X	A	-	X	A	A





aerospace
climate control
electromechanical
filtration
fluid & gas handling
hydraulics
pneumatics
process control
sealing & shielding





Hydraulic Hoses, Fittings and Equipment

Low Pressure




Parker

ENGINEERING YOUR SUCCESS.

Low Pressure Push-Lok®

The self-grip hose system for low-pressure applications



One fitting series for all hose types

with DIN, BSP, SAE, JIC and ORFS connections in brass, steel and stainless steel



Wide variety of hose types

6 rubber hose types

801Plus for a variety of applications
804 for high-temperature water/phosphate ester fluids
821FR with fire-retardant hose cover
831 ideal for petroleum-based fluids
836 for high oil temperatures
837BM for a variety of applications including automotive

2 thermoplastic hose types

830M for a variety of applications including automotive
838M for non-conductive applications

1 hybrid hose type

837PU-Plus for a variety of applications including automotive


Applications

Push-Lok® hoses offer variety, excellent performance and durability for the following applications



6 different colours

- easy identification
- simple production processes
  – one colour for one particular medium
- easy control of maintenance intervals
- simple stock planning in different departments



Easy assembly – no tools or clamps required

Push-Lok® assembly (1a, b)

- Cut the hose with a sharp knife
- Push the nipple into the hose – that's all!


Push-Lok® disassembly (2a, b)

- Cut lengthwise along a line at approximately a 20° angle from the centre line of the hose. The cut should be approximately 2 cm long. Be careful not to nick barbs when cutting the hose.
- Grip hose and give a sharp downward tug to disengage from fitting.
- Before re-using the nipple, please check it for any damage.









Low Pressure Push-Lok

Hoses			Page
	801Plus	Multipurpose	B1a-1
	804	Phosphate Ester	B1a-2
	821FR	Fire retardant	B1a-3
	830M	Multipurpose	B1a-4
	831	Multipurpose	B1a-5
	836	High temperature	B1a-6
	837BM	Multipurpose	B1a-7
	837PU	Multipurpose	B1a-8
	838M	Non-conductive	B1a-9

Fittings Series	82
Chapter	B1b
DIN – Metric	1 – 7
BSP	8 – 10
SAE	11 – 14
ORFS	15
Others	16 – 18
Assembly Instructions / Tools	19

Parker Hannifin assumes no liability for typographical errors or other errors

Multipurpose

801Plus
B1a-1

Push-Lok Plus
For a variety of applications

830M
B1a-4

Push-Lok
For a variety of applications
including automotive

831
B1a-5

Push-Lok
Ideal for petroleum based fluids

837BM
B1a-7

Push-Lok
For a variety of applications
including automotive

837PU-*Plus*
B1a-8

Hybrid Push-Lok
For a variety of applications
including automotive

Phosphate Ester

804
B1a-2


Push-Lok
For high temperature
water and phosphate ester fluid

High temperature

836
B1a-6

Push-Lok
For high oil temperatures

Fire retardant

821FR
B1a-3

Push-Lok
With fire retardant hose cover

Non-conductive

838M
B1a-9

Push-Lok
For non-conductive applications

801Plus

Push-Lok Plus

For a variety of applications



- Very flexible
- Wide range of colours
- Available up to size -16

Primary Applications

All Markets: For low pressure applications
Paper and Pulp: For water / air applications

Restrictions

Not permitted for use in air brake systems.
Not suitable for high dynamic pulsation systems.
Not recommended for fuels (petrol, diesel etc.).
Not recommended for mineral based hydraulic and lubricating oils.

Construction

Tube: Synthetic rubber
Reinforcement: High-tensile fibre braid
Cover: High performance synthetic rubber in different colours

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Air, water, water-oil-emulsions and water-glycol-emulsions.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series




Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		Vaccum*	min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	kPa	mm	kg
801-4-XXX-RL	6	1/4	-4	6.4	12.7	2.4	350	9.7	1400	95	65	0.13
801-6-XXX-RL	10	3/8	-6	9.5	15.9	2.4	350	9.7	1400	95	75	0.16
801-8-XXX-RL	12	1/2	-8	12.7	19.8	2.1	300	8.4	1200	95	125	0.27
801-10-XXX-RL	16	5/8	-10	15.9	23.0	2.1	300	8.4	1200	51	150	0.28
801-12-XXX-RL	19	3/4	-12	19.1	26.2	2.1	300	8.4	1200	51	180	0.36
801-16-XXX-RL	25	1	-16	25.4	32.5	1.4	200	5.6	800	51	250	0.55

* the vacuum values listed in the table are vacuum pressure values in kPa. For an absolute value subtract the table value from 101 kPa
Note: when ordering, specify Push-Lok hose part number, followed by size, followed by colour. Example: 801-4-XXX-RL

XXX = BLK = black
BLU = blue
RED = red
GRN = green
GRA = grey
YEL = yellow

Example: 801-4-GRN-RL (green)



Hose layline example



804

Push-Lok

For high temperature
water and phosphate ester fluid



- For hot water up to +93 °C
- For phosphate ester fluids

Primary Applications

Injection Moulding: For special tempering circuits.

Restrictions

Not permitted for use in air brake systems.
Not suitable for high dynamic pulsation systems.
Do not allow tube to contact any petroleum based fluids.

Construction

Tube:	EPDM material
Reinforcement:	High-tensile fibre braid
Cover:	Black EPDM material

Temperature Range ..... -40 °C up to +80 °C

Exception:	Air	..... max. +70 °C
	Water	..... max. +93 °C

Recommended Fluids

Phosphate ester based hydraulic fluids, water, water glycol emulsions, air. Use liquid soap as lubricant. Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

82

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		Vaccum*	min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	kPa	mm	kg
804-4-RL	6	1/4	-4	6.4	12.7	1.7	250	6.8	1000	51	65	0.13
804-6-RL	10	3/8	-6	9.5	15.9	1.7	250	6.8	1000	51	75	0.16
804-8-RL	12	1/2	-8	12.7	19.8	1.7	250	6.8	1000	51	130	0.27
804-12-RL	19	3/4	-12	19.1	26.2	1.7	250	6.8	1000	51	180	0.28

RL = only available on reels

Hose layline example

Parker PUSH-LOK 804-8 WP 1,0 MPA (150 PSI) 12,5 mm (1/2) 1Q95

821FR

Push-Lok

With fire retardant hose cover



- Fire retardant hose cover
- Very flexible
- For high level air temperatures

Primary Applications

All Markets: For a variety of applications

Restrictions

Not permitted for use in air brake systems.
Not suitable for high dynamic pulsation systems.
Not recommended for fuels (petrol, diesel etc.)

Construction

Tube: Synthetic PKR-rubber
Reinforcement: High-tensile fibre braid
Cover: A fire retardant special fiber outer cover

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +100 °C
Water ..... max. +85 °C

Recommended Fluids

Mineral based hydraulic and lubricating oils, coolant, antifreeze, air, water and water-oil emulsions.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

82

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		Vaccum*	min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	kPa	mm	kg
821FR-4-XXX-RL	6	1/4	-4	6.4	12.7	2.4	350	9.7	1400	95	65	0.12
821FR-6-XXX-RL	10	3/8	-6	9.5	15.9	2.0	300	8.3	1200	95	75	0.16
821FR-8-XXX-RL	12	1/2	-8	12.7	19.8	2.0	300	8.3	1200	95	130	0.18
821FR-12-XXX-RL	19	3/4	-12	19.1	26.2	1.7	250	6.8	1000	95	180	0.33

* the vacuum values listed in the table are vacuum pressure values in kPa. For an absolute value subtract the table value from 101 kPa
Note: when ordering, specify Push-Lok hose part number, followed by size, followed by colour. Example: 821FR-4-XXX-RL
XXX = BLK = black
BLU = blue
GRN = green



Example: 821FR-4-GRN-RL (green)
RL = only available on reels

Hose layline example

PARKER PUSH-LOK 821FR-8 WP 2,0 MPa (300 PSI) 12,5 mm (1/2) 11-4Q85

830M

Push-Lok

For a variety of applications
including automotive



- Chemical resistant for a wide range of fluids
- High abrasion resistance
- Free of wetting disturbing substances (LABS free)
- Small OD and bend radii
- Excellent UV and ozone resistance

Primary Applications

All Markets: For a variety of applications
Robot and Automotive market:
For hose bundle systems

Restrictions

Not permitted for use in air brake systems.
Not suitable for high dynamic pulsation systems.
Not recommended for fuels (petrol, diesel etc.)

Construction

Tube: Polyurethane material
Reinforcement: High-tensile fibre braid
Cover: High performance polyurethane material in different colours

Recommended Fluids

Mineral based hydraulic and lubricating oils, coolant, antifreeze, air, water and water-oil emulsions.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.


Temperature Range ..... -40 °C up to +80 °C

Fitting Series



Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		Vaccum*	min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	kPa	mm	kg
830M-4-XXX-RL	6	1/4	-4	6.4	10.7	1.6	232	6.4	928	10	30	0.08
830M-6-XXX-RL	10	3/8	-6	9.5	14.9	1.6	232	6.4	928	10	50	0.13
830M-8-XXX-RL	12	1/2	-8	12.7	19.1	1.6	232	6.4	928	10	70	0.20
830M-10-XXX-RL	16	5/8	-10	15.9	23.0	1.6	232	6.4	928	10	90	0.26
830M-12-XXX-RL	19	3/4	-12	19.1	26.0	1.6	232	6.4	928	10	110	0.31

* the vacuum values listed in the table are vacuum pressure values in kPa. For an absolute value subtract the table value from 101 kPa
Note: when ordering, specify Push-Lok hose part number, followed by size, followed by colour. Example: 830M-4-XXX-RL
XXX = BLK = black
BLU = blue
RED = red
GRN = green
Example: 830M-4-GRN-RL (green)
RL = only available on reels



831

Push-Lok

Ideal for petroleum based fluids



- Max. working pressure up to 2.4 MPa
- High temperature level for petroleum based fluids
- Nitrile (NBR) inner tube – extended fluid compatibility

Primary Applications

All Markets: For a wide range of fluids

Restrictions

Not permitted for use in air brake systems.
Not suitable for high dynamic pulsation systems.
Not recommended for fuels (petrol, diesel etc.)

Construction

Tube: Nitrile (NBR)
Reinforcement: High-tensile fibre braid
Cover: High performance synthetic rubber in different colours

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Mineral based hydraulic and lubricating oils, coolant, antifreeze, air, water and water-oil emulsions.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series



Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		Vaccum*	min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	kPa	mm	kg
831-4-XXX-RL	6	1/4	-4	6.4	12.7	2.4	350	9.7	1400	95	65	0.13
831-6-XXX-RL	10	3/8	-6	9.5	15.9	2.0	300	8.3	1200	95	75	0.16
831-8-XXX-RL	12	1/2	-8	12.7	19.8	2.0	300	8.3	1200	95	130	0.27
831-10-XXX-RL	16	5/8	-10	15.9	23.0	2.0	300	8.3	1200	51	150	0.28
831-12-XXX-RL	19	3/4	-12	19.1	26.2	2.0	300	8.3	1200	51	180	0.36
831-16-XXX-RL	25	1	-16	25.4	32.5	1.4	200	5.5	800	51	250	0.37

* the vacuum values listed in the table are vacuum pressure values in kPa. For an absolute value subtract the table value from 101 kPa
Note: when ordering, specify Push-Lok hose part number, followed by size, followed by colour. Example: 831-4-XXX-RL
XXX = BLK = black
BLU = blue
RED = red
GRN = green



Example: 831-4-GRN-RL (green)
RL = only available on reels

Hose layline example

PARKER PUSH-LOK 831-8 WP 2,1 MPa (300 PSI) I • • 12,5 mm (1/2)

836

Push-Lok

For high oil temperatures



- Max. oil temperature up to +150 °C
- Blue hose cover
- MSHA approved

Primary Applications

All Markets: Special high temperature applications

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Restrictions

Not permitted for use in air brake systems.
Not suitable for high dynamic pulsation systems.
Not recommended for fuels (petrol, diesel etc.)

Construction

Tube: Synthetic PKR rubber
Reinforcement: High-tensile fibre braid
Cover: MSHA approved
blue synthetic PKR rubber

Temperature Range ..... -48 °C up to +150 °C

Exception: Air ..... max. +100 °C
Water ..... max. +85 °C

Recommended Fluids

Mineral based hydraulic and lubricating oils, coolant, antifreeze, air, water and water-oil emulsions.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series



Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		Vaccum*	min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	kPa	mm	kg
836-4-RL	6	1/4	-4	6.4	12.7	1.7	250	6.8	1000	95	65	0.13
836-6-RL	10	3/8	-6	9.5	15.7	1.7	250	6.8	1000	95	75	0.16
836-8-RL	12	1/2	-8	12.7	19.8	1.7	250	6.8	1000	95	130	0.27
836-10-RL	16	5/8	-10	15.9	23.1	1.7	250	6.8	1000	51	150	0.28
836-12-RL	19	3/4	-12	19.1	26.2	1.7	250	6.8	1000	51	180	0.36

* the vacuum values listed in the table are vacuum pressure values in kPa. For an absolute value subtract the table value from 101 kPa
RL = only available on reels

Hose layline example

PARKER HI-TEMP PUSH-LOK 836-8 WP 1,7 MPa (250 PSI) MSHA IC-40/22 I • • 12,5 mm (1/2)

837BM

Push-Lok

For a variety of applications including automotive



- High level of hose flexibility
- High abrasion resistance
- Free from wetting disturbing substances
- Low push-in forces

Primary Applications

All Markets: For a variety of applications
Automotive: For water / air applications

Restrictions

Not permitted for use in air brake systems
Not suitable for high dynamic pulsation systems
Not recommended for fuels (petrol, diesel etc.)
Not recommended for mineral based hydraulic and lubricating oils

Construction

Tube: Synthetic rubber
Reinforcement: High-tensile fibre braid
Cover: High performance synthetic rubber in different colours

Recommended Fluids

Air, dry air, water, water-oil-emulsions and water-glycol-emulsions.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Fitting Series



Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		Vaccum*	min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	kPa	mm	kg
837BM-4-XXX-RL	6	1/4	-4	6.4	12.7	1.6	235	6.4	940	95	65	0.13
837BM-6-XXX-RL	10	3/8	-6	9.5	15.9	1.6	235	6.4	940	95	75	0.16
837BM-8-XXX-RL	12	1/2	-8	12.7	19.8	1.6	235	6.4	940	95	130	0.27
837BM-10-XXX-RL	16	5/8	-10	15.9	23.0	1.6	235	6.4	940	51	150	0.28
837BM-12-XXX-RL	19	3/4	-12	19.1	26.2	1.6	235	6.4	940	51	180	0.36
837BM-16-XXX-RL	25	1	-16	25.4	32.5	1.6	235	6.4	940	51	250	0.55

* the vacuum values listed in the table are vacuum pressure values in kPa. For an absolute value subtract the table value from 101 kPa
Note: when ordering, specify Push-Lok hose part number, followed by size, followed by colour. Example: 837BM-4-XXX-RL
XXX = BLK = black
BLU = blue
RED = red
GRN = green
GRA = grey
Example: 837BM-4-GRN-RL (green)
RL = only available on reels



Hose layline example

PARKER PUSH-LOK 837BM-10 WP 1,6 MPa (235 PSI) I • • 16 mm (5/8)

837PU-*Plus*

Hybrid Push-Lok

For a variety of applications
including automotive



- High level of hose flexibility
- High abrasion resistance
- High torsion resistance
- Free from wetting disturbing substances
- Low push-in forces

Primary Applications

All Markets: For high demand applications
For energy chain systems
Robot and Automotive market:
For hose bundle systems

Restrictions

Not permitted for use in air brake systems
Not suitable for high dynamic pulsation systems
Not recommended for fuels (petrol, diesel etc.)
Not recommended for mineral based hydraulic and lubricating oils

Construction

Tube: Synthetic rubber
Reinforcement: High-tensile fibre braid
Cover: High performance polyurethane material in different colours

Recommended Fluids

Air, dry air, water, water-oil-emulsions and water-glycol-emulsions.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Fitting Series

82

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		Vaccum*	min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	kPa	mm	kg
837PU-4-xxx-RL	6	1/4	-4	6.4	12.7	1.6	235	6.4	940	95	30	0.11
837PU-6-xxx-RL	10	3/8	-6	9.5	15.9	1.6	235	6.4	940	95	50	0.15
837PU-8-xxx-RL	12	1/2	-8	12.7	19.8	1.6	235	6.4	940	95	70	0.26
837PU-10-xxx-RL	16	5/8	-10	15.9	23.0	1.6	235	6.4	940	51	90	0.27
837PU-12-xxx-RL	19	3/4	-12	19.1	26.2	1.6	235	6.4	940	51	110	0.33
837PU-16-xxx-RL	25	1	-16	25.4	32.5	1.6	235	6.4	940	51	180	0.52

* the vacuum values listed in the table are vacuum pressure values in kPa. For an absolute value subtract the table value from 101 kPa
Note: when ordering, specify Push-Lok hose part number, followed by size, followed by colour. Example: 837PU-4-XXX-RL
XXX = BLK = black
BLU = blue
RED = red
GRN = green
GRA = grey
Example: 837PU-4-GRN-RL (green)
RL = only available on reels



Hose layline example

PARKER PUSH-LOK 837PU-*Plus*-8 WP 1,6 MPa (235 PSI) I ° ° 12,5 mm (1/2)

838M

Push-Lok

For non-conductive applications



- Non conductive hose
- High level of hose flexibility

Primary Applications

Special Market: For special electrical requirements, e.g. cooling lines with de-ionized water

Restrictions

Not permitted for use in air brake systems.
Not suitable for high dynamic pulsation systems.
Not recommended for fuels (petrol, diesel etc.)

Construction

Tube: Polyurethane material
Reinforcement: High-tensile fibre braid
Cover: Orange coloured polyurethane material

Temperature Range ..... -40 °C up to +80 °C

Recommended Fluids

Mineral based hydraulic and lubricating oils, coolant, antifreeze, water, water-oil emulsions.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

82


Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		Vaccum*	min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	kPa	mm	kg
838M-4-RL	6	1/4	-4	6.4	11.2	1.6	232	6.4	928	10	30	0.08
838M-6-RL	10	3/8	-6	9.5	15.0	1.6	232	6.4	928	10	50	0.13
838M-8-RL	12	1/2	-8	12.7	19.1	1.6	232	6.4	928	10	70	0.20
838M-10-RL	16	5/8	-10	15.9	23.0	1.6	232	6.4	928	10	90	0.26
838M-12-RL	19	3/4	-12	19.1	26.0	1.6	232	6.4	928	10	110	0.31

* the vacuum values listed in the table are vacuum pressure values in kPa. For an absolute value subtract the table value from 101 kPa
RL = only available on reels

DIN – Metric

Page B1b-1– B1b-7

CA B1b-1



Female Metric 24° Light Series with O–Ring Swivel – Straight
ISO 12151-2-SWS-L – DKOL

CE B1b-1




Female Metric 24° Light Series with O–Ring Swivel – 45° Elbow
ISO 12151-2-SWE 45°-L – DKOL 45°

CF B1b-2




Female Metric 24° Light Series with O–Ring Swivel – 90° Elbow
ISO 12151-2-SWE-L – DKOL 90°

D0 B1b-2



Male Metric 24° Light Series – Rigid Straight
ISO 12151-2-S-L – CEL

C3 B1b-3



Female Metric Light Series – Swivel Straight (Ball Nose for 24° or 60° Cone) DKL

C4 B1b-4




Female Metric Light Series – Swivel 45° Elbow (Ball Nose for 24° or 60° Cone) DKL 45°

C5 B1b-5




Female Metric Light Series – Swivel 90° Elbow (Ball Nose for 24° or 60° Cone) DKL 90°

49 B1b-6



Metric Banjo Straight
DIN 7642

9B B1b-6



Female Metric Swivel Light Series 45° Elbow (Ball Nose for 24° or 60° Cone)

9C B1b-7




Female Metric Swivel Light Series 90° Elbow (Ball Nose for 24° or 60° Cone)

BSP

Page B1b-8 – B1b-10

92 B1b-8




Female BSP Parallel Pipe Swivel – Straight (60° Cone)
BS5200-A – DKR

B1 B1b-8



Female BSP Parallel Pipe Swivel 45° Elbow (60° Cone)
BS 5200-D – DKR 45°

B2 B1b-9



Female BSP Parallel Pipe Swivel 90° Elbow (60° Cone)
BS 5200-B – DKR 90°

D9 B1b-9




Male BSP Parallel Pipe Rigid – Straight (60° Cone)
BS5200 – AGR

91 B1b-10



Male BSP Taper Pipe – Rigid Straight
BS5200 – AGR-K

34 B1b-10




Inch Standpipe (Brass)

SAE

Page B1b-11 – B1b-14

01 B1b-11



Male NPTF Pipe Rigid – Straight
SAE J476A / J516 – AGN

02 B1b-11




Female NPTF Pipe – Rigid Straight
SAE J476A / J516

03 B1b-12



Male JIC 37° – Rigid Straight
ISO12151-5-S – AGJ

06/68 B1b-12



Female – JIC 37° SAE 45° Dual Flare Swivel – Straight
ISO12151-5-SWS – DKJ

08 B1b-13




Female SAE 45° – Swivel Straight
SAE J516

37/3V B1b-13



Female JIC 37° SAE 45° – Dual Flare Swivel Female 45° Elbow
ISO 12151-5-SWE 45° – DKJ 45°

39/3W B1b-14



Female JIC 37° SAE 45° – Dual Flare Swivel Female 90° Elbow
ISO 12151-5-SWES – DKJ 90°

ORFS

Page B1b-15

JC
B1b-15

Female ORFS
Swivel – Straight
Short
ISO 12151-1 – SWSA SAE J516 – ORFS

Others


Page B1b-16 – B1b-18


FF
B1b-16


Metru–Lok Swivel Female

AF
B1b-16

Male BSP Parallel Pipe
Rigid – Straight
(with O–ring Seal)

82
B1b-17

Push–Lok® Union

5C
B1b-17

60° Cone Swivel Female

6C
B1b-18

60° Cone Swivel Female
45° Elbow

7C
B1b-18

60° Cone Swivel Female
90° Elbow


Assembly Instructions / Tools


Page B1b-19

CA

Female Metric 24° Light Series with O-Ring Swivel – Straight

ISO 12151-2-SWS-L – DKOL






Part Number	Hose I.D.				Thread	Tube O.D.	A	B	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
3CA82-6-4B	6	1/4	-4	6.4	M12x1.5	6	40	21	14
3CA82-6-4	6	1/4	-4	6.4	M12x1.5	6	40	21	14
3CA82-8-4	6	1/4	-4	6.4	M14x1.5	8	36	17	17
3CA82-8-4B	6	1/4	-4	6.4	M14x1.5	8	36	17	17
3CA82-10-4	6	1/4	-4	6.4	M16x1.5	10	36	17	19
3CA82-10-6	10	3/8	-6	9.5	M16x1.5	10	40	17	19
3CA82-10-6B	10	3/8	-6	9.5	M16x1.5	10	39	17	19
3CA82-12-6	10	3/8	-6	9.5	M18x1.5	12	40	17	22
3CA82-12-6B	10	3/8	-6	9.5	M18x1.5	12	39	17	22
3CA82-15-8	12	1/2	-8	12.7	M22x1.5	15	44	18	27
3CA82-15-8B	12	1/2	-8	12.7	M22x1.5	15	44	17	27
3CA82-15-10B	16	5/8	-10	15.9	M22x1.5	15	60	23	27
3CA82-18-10	16	5/8	-10	15.9	M26x1.5	18	56	19	32
3CA82-22-12B	19	3/4	-12	19.1	M30x2	22	58	21	36
3CA82-22-12	19	3/4	-12	19.1	M30x2	22	58	21	36


Hose fittings are delivered with ozone resistant Nitrile (NBR) O-ring as a standard version. Working temperature from -40 °C up to +105 °C.
Hose fittings with special O-rings (Viton or EPDM) available on request. O-ring dimensions and part-numbers see in section Eb.

CE

Female Metric 24° Light Series with O-Ring Swivel – 45° Elbow

ISO 12151-2-SWE 45°-L – DKOL 45°





Part Number	Hose I.D.				Thread	Tube O.D.	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
3CE82-6-4	6	1/4	-4	6.4	M12x1.5	6	56	37	21	14
3CE82-8-4	6	1/4	-4	6.4	M14x1.5	8	51	31	16	17
3CE82-10-6	10	3/8	-6	9.5	M16x1.5	10	59	37	19	19
3CE82-12-6	10	3/8	-6	9.5	M18x1.5	12	60	37	19	22
3CE82-15-8	12	1/2	-8	12.7	M22x1.5	15	69	43	21	27
3CE82-18-10	16	5/8	-10	15.9	M26x1.5	18	83	46	23	32
3CE82-22-12	19	3/4	-12	19.1	M30x2	22	97	60	26	36

Hose fittings are delivered with ozone resistant Nitrile (NBR) O-ring as a standard version. Working temperature from -40 °C up to +105 °C.
Hose fittings with special O-rings (Viton or EPDM) available on request. O-ring dimensions and part-numbers see in section Eb.

Also available in stainless steel. Details can be found in CAT 4400.1/UK

K: without plastic ring; **B**: Brass; **SM**: Metric Hexagon


Approved **fitting series** for **hose types**:


82 | 801 | 804 | 821FR | 830M | 831 | 836 | 837BM | 837PU | 838M

CF

Female Metric 24° Light Series with O-Ring Swivel – 90° Elbow

ISO 12151-2-SWE-L – DKOL 90°






Part Number	Hose I.D.				Thread	Tube O.D.	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
3CF82-6-4	6	1/4	-4	6.4	M12x1.5	6	42	23	36	14
3CF82-8-4	6	1/4	-4	6.4	M14x1.5	8	41	23	29	17
3CF82-10-4	6	1/4	-4	6.4	M16x1.5	10	42	23	31	19
3CF82-10-6	10	3/8	-6	9.5	M16x1.5	10	49	27	35	19
3CF82-10-6B	10	3/8	-6	9.5	M16x1.5	10	49	27	35	19
3CF82-12-6B	10	3/8	-6	9.5	M18x1.5	12	49	27	35	22
3CF82-12-6	10	3/8	-6	9.5	M18x1.5	12	49	27	35	22
3CF82-15-8B	12	1/2	-8	12.7	M22x1.5	15	60	34	41	27
3CF82-15-8	12	1/2	-8	12.7	M22x1.5	15	60	34	41	27
3CF82-18-10	16	5/8	-10	15.9	M26x1.5	18	74	37	45	32
3CF82-22-12	19	3/4	-12	19.1	M30x2	22	88	52	55	36


Hose fittings are delivered with ozone resistant Nitrile (NBR) O-ring as a standard version. Working temperature from -40 °C up to +105 °C.
Hose fittings with special O-rings (Viton or EPDM) available on request. O-ring dimensions and part-numbers see in section Eb.

D0

Male Metric 24° Light Series – Rigid Straight

ISO 12151-2-S-L – CEL





Part Number	Hose I.D.				Thread	Tube O.D.	A	B	H
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
3D082-6-4	6	1/4	-4	6.4	M12x1.5	6	35	16	12
3D082-8-4	6	1/4	-4	6.4	M14x1.5	8	36	17	14
3D082-10-6B	10	3/8	-6	9.5	M16x1.5	10	41	18	17
3D082-10-6	10	3/8	-6	9.5	M16x1.5	10	41	18	17
3D082-12-6B	10	3/8	-6	9.5	M18x1.5	12	41	18	19
3D082-12-6	10	3/8	-6	9.5	M18x1.5	12	41	18	19
3D082-15-8BK	12	1/2	-8	12.7	M22x1.5	15	49	22	22
3D082-15-8B	12	1/2	-8	12.7	M22x1.5	15	49	22	22
3D082-15-8	12	1/2	-8	12.7	M22x1.5	15	49	23	22
3D082-18-8	12	1/2	-8	12.7	M26x1.5	18	48	21	27
3D082-18-10	16	5/8	-10	15.9	M26x1.5	18	58	21	27
3D082-22-12B	19	3/4	-12	19.1	M30x2	22	63	27	30
3D082-22-12	19	3/4	-12	19.1	M30x2	22	63	27	30
3D082-22-12BK	19	3/4	-12	19.1	M30x2	22	63	27	30

Also available in stainless steel. Details can be found in CAT 4400.1/UK

Approved **fitting series** for **hose types**:


K: without plastic ring; **B:** Brass; **SM:** Metric Hexagon


82 | 801 | 804 | 821FR | 830M | 831 | 836 | 837BM | 837PU | 838M

C3

Female Metric Light Series – Swivel Straight (Ball Nose for 24° or 60° Cone)

DKL





Part Number	Hose I.D.				Thread	Tube O.D.	A	B	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
3C382-6-4	6	1/4	-4	6.4	M12x1.5	6	33	14	14
3C382-6-4BK	6	1/4	-4	6.4	M12x1.5	6	33	14	14
3C382-6-4B	6	1/4	-4	6.4	M12x1.5	6	33	14	14
3C382-8-4	6	1/4	-4	6.4	M14x1.5	8	33	14	17
3C382-8-4BK	6	1/4	-4	6.4	M14x1.5	8	36	17	19
3C382-8-4B	6	1/4	-4	6.4	M14x1.5	8	36	17	19
3C382-10-4	6	1/4	-4	6.4	M16x1.5	10	34	15	19
3C382-10-4BK	6	1/4	-4	6.4	M16x1.5	10	34	15	19
3C382-10-6	10	3/8	-6	9.5	M16x1.5	10	37	15	19
3C382-10-6BK	10	3/8	-6	9.5	M16x1.5	10	40	17	19
3C382-10-6B	10	3/8	-6	9.5	M16x1.5	10	40	17	19
3C382-12-6BK	10	3/8	-6	9.5	M18x1.5	12	40	17	22
3C382-12-6	10	3/8	-6	9.5	M18x1.5	12	38	16	22
3C382-15-8	12	1/2	-8	12.7	M22x1.5	15	42	15	27
3C382-15-8B	12	1/2	-8	12.7	M22x1.5	15	46	19	27
3C382-15-8BK	12	1/2	-8	12.7	M22x1.5	15	46	19	27
3C382-15-10	16	5/8	-10	15.9	M22x1.5	15	56	19	27
3C382-18-10B	16	5/8	-10	15.9	M26x1.5	18	58	22	32
3C382-18-10	16	5/8	-10	15.9	M26x1.5	18	53	17	32
3C382-18-10BK	16	5/8	-10	15.9	M26x1.5	18	58	22	32
3C382-22-12B	19	3/4	-12	19.1	M30x2	22	58	22	36
3C382-22-12	19	3/4	-12	19.1	M30x2	22	53	17	36
3C382-22-12BK	19	3/4	-12	19.1	M30x2	22	58	22	36
3C382-28-16	25	1	-16	25.4	M36x2	28	58	22	41
3C382-28-16-K	25	1	-16	25.4	M36x2	28	58	22	41
3C382-28-16BK	25	1	-16	25.4	M36x2	28	58	22	41

Also available in stainless steel. Details can be found in CAT 4400.1/UK


K: without plastic ring; **B**: Brass; **SM**: Metric Hexagon


Approved **fitting series** for **hose types**:

82 | 801 | 804 | 821FR | 830M | 831 | 836 | 837BM | 837PU | 838M

C4 Female Metric Light Series – Swivel 45° Elbow (Ball Nose for 24° or 60° Cone)

DKL 45°





Part Number	Hose I.D.				Thread	Tube O.D.	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
3C482-6-4	6	1/4	-4	6.4	M12x1.5	6	51	32	16	14
3C482-6-4B	6	1/4	-4	6.4	M12x1.5	6	51	32	16	14
3C482-8-4	6	1/4	-4	6.4	M14x1.5	8	51	32	16	17
3C482-8-4B	6	1/4	-4	6.4	M14x1.5	8	51	32	16	17
3C482-10-6	10	3/8	-6	9.5	M16x1.5	10	58	35	18	19
3C482-10-6B	10	3/8	-6	9.5	M16x1.5	10	58	35	17	19
3C482-12-6	10	3/8	-6	9.5	M18x1.5	12	59	36	18	22
3C482-12-6B	10	3/8	-6	9.5	M18x1.5	12	58	36	18	22
3C482-15-8B	12	1/2	-8	12.7	M22x1.5	15	67	41	19	27
3C482-15-8	12	1/2	-8	12.7	M22x1.5	15	68	41	19	27
3C482-15-10	16	5/8	-10	15.9	M22x1.5	15	82	45	21	27
3C482-15-10B	16	5/8	-10	15.9	M22x1.5	15	82	45	21	27
3C482-18-10	16	5/8	-10	15.9	M26x1.5	18	81	45	21	32
3C482-18-10B	16	5/8	-10	15.9	M26x1.5	18	81	45	21	32
3C482-18-12	19	3/4	-12	19.1	M26x1.5	18	96	60	26	32
3C482-22-12	19	3/4	-12	19.1	M30x2	22	88	52	23	36
3C482-22-12B	19	3/4	-12	19.1	M30x2	22	88	52	23	36
3C482-28-16-K	25	1	-16	25.4	M36x2	28	110	73	31	41

Also available in stainless steel. Details can be found in CAT 4400.1/UK

K: without plastic ring; **B**: Brass; **SM**: Metric Hexagon


Approved **fitting series** for **hose types**:


82 | 801 | 804 | 821FR | 830M | 831 | 836 | 837BM | 837PU | 838M

C5

Female Metric Light Series – Swivel 90° Elbow (Ball Nose for 24° or 60° Cone)

DKL 90°





Part Number	Hose I.D.				Thread	Tube O.D.	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
3C582-6-4	6	1/4	-4	6.4	M12x1.5	6	42	23	29	14
3C582-8-4	6	1/4	-4	6.4	M14x1.5	8	42	23	29	17
3C582-8-4B	6	1/4	-4	6.4	M14x1.5	8	41	23	29	17
3C582-10-4	6	1/4	-4	6.4	M16x1.5	10	42	23	29	19
3C582-10-6	10	3/8	-6	9.5	M16x1.5	10	49	27	33	19
3C582-12-6B	10	3/8	-6	9.5	M18x1.5	12	49	27	34	22
3C582-12-6	10	3/8	-6	9.5	M18x1.5	12	49	27	34	22
3C582-15-8	12	1/2	-8	12.7	M22x1.5	15	65	38	39	27
3C582-15-8B	12	1/2	-8	12.7	M22x1.5	15	65	38	39	27
3C582-18-10B	16	5/8	-10	15.9	M26x1.5	18	74	37	43	32
3C582-18-10	16	5/8	-10	15.9	M26x1.5	18	74	37	43	32
3C582-22-12B	19	3/4	-12	19.1	M30x2	22	88	52	50	36
3C582-22-12	19	3/4	-12	19.1	M30x2	22	88	51	50	36
3C582-28-16B	25	1	-16	25.4	M36x2	28	101	64	66	41
3C582-28-16-K	25	1	-16	25.4	M36x2	28	99	61	70	41

Also available in stainless steel. Details can be found in CAT 4400.1/UK


K: without plastic ring; **B**: Brass; **SM**: Metric Hexagon


Approved **fitting series** for **hose types**:

82 | 801 | 804 | 821FR | 830M | 831 | 836 | 837BM | 837PU | 838M

49 Metric Banjo Straight


DIN 7642






Part Number	Hose I.D.				A	B	D
	DN	Inch	Size	mm	mm	mm	mm
34982-8-4	6	1/4	-4	6.4	36	17	8
34982-10-4	6	1/4	-4	6.4	38	19	10
34982-12-4	6	1/4	-4	6.4	40	21	12
34982-14-4	6	1/4	-4	6.4	42	23	14
34982-10-6	10	3/8	-6	9.5	42	19	10
34982-12-6	10	3/8	-6	9.5	44	21	12
34982-14-6	10	3/8	-6	9.5	47	24	14
34982-16-6	10	3/8	-6	9.5	49	26	16
34982-17-6	10	3/8	-6	9.5	49	26	17
34982-14-8	12	1/2	-8	12.7	51	25	14
34982-18-8	12	1/2	-8	12.7	55	28	18
34982-22-8	12	1/2	-8	12.7	57	31	22
34982-22-10	16	5/8	-10	15.9	68	32	22
34982-26-12	19	3/4	-12	19.1	74	38	26

9B Female Metric Swivel Light Series 45° Elbow (Ball Nose for 24° or 60° Cone)





Part Number	Hose I.D.				Thread	Tube O.D.	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
39B82-6-4BK	6	1/4	-4	6.4	M12x1.5	6	44	25	16	14
39B82-8-4BK	6	1/4	-4	6.4	M14x1.5	8	43	24	15	19
39B82-10-6BK	10	3/8	-6	9.5	M16x1.5	10	48	25	16	19
39B82-12-6BK	10	3/8	-6	9.5	M18x1.5	12	50	27	17	22
39B82-15-8BK	12	1/2	-8	12.7	M22x1.5	15	54	28	18	27


Also available in stainless steel. Details can be found in CAT 4400.1/UK


K: without plastic ring; **B**: Brass; **SM**: Metric Hexagon

Approved **fitting series** for **hose types**:

82 | 801 | 804 | 821FR | 830M | 831 | 836 | 837BM | 837PU | 838M

9C Female Metric Swivel Light Series 90° Elbow (Ball Nose for 24° or 60° Cone)





Part Number	Hose I.D.				Thread	Tube O.D.	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
39C82-6-4BK	6	1/4	-4	6.4	M12x1.5	6	30	11	22	14
39C82-8-4BK	6	1/4	-4	6.4	M14x1.5	8	30	11	22	19
39C82-10-6BK	10	3/8	-6	9.5	M16x1.5	10	34	12	25	19
39C82-12-6BK	10	3/8	-6	9.5	M18x1.5	12	34	11	25	22
39C82-15-8BK	12	1/2	-8	12.7	M22x1.5	15	42	16	32	27

Also available in stainless steel. Details can be found in CAT 4400.1/UK


K: without plastic ring; **B**: Brass; **SM**: Metric Hexagon


Approved **fitting series** for **hose types**:

82 | 801 | 804 | 821FR | 830M | 831 | 836 | 837BM | 837PU | 838M

92 Female BSP Parallel Pipe Swivel – Straight (60° Cone)

BS5200-A – DKR







Part Number	Hose I.D.				Thread	A	B	W
	DN	Inch	Size	mm	BSP	mm	mm	mm
39282-4-4	6	1/4	-4	6.4	1/4x19	33	14	17
39282-4-4B	6	1/4	-4	6.4	1/4x19	36	16	17
39282-6-4B	6	1/4	-4	6.4	3/8x19	37	18	22
39282-6-6	10	3/8	-6	9.5	3/8x19	37	14	19
39282-8-8B	12	1/2	-8	12.7	1/2x14	46	19	27
39282-8-8	12	1/2	-8	12.7	1/2x14	42	15	27
39282-10-10	16	5/8	-10	15.9	5/8x14	53	16	30
39282-10-10B	16	5/8	-10	15.9	5/8x14	55	18	30
39282-12-12	19	3/4	-12	19.1	3/4x14	58	21	32
39282-16-16B	25	1	-16	25.4	1x11	57	21	41

B1 Female BSP Parallel Pipe Swivel 45° Elbow (60° Cone)

BS 5200-D – DKR 45°





Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	BSP	mm	mm	mm	mm
3B182-4-4	6	1/4	-4	6.4	1/4x19	51	32	16	17
3B182-6-6	10	3/8	-6	9.5	3/8x19	58	35	17	19
3B182-6-6B	10	3/8	-6	9.5	3/8x19	58	35	17	19
3B182-8-8B	12	1/2	-8	12.7	1/2x14	67	41	19	27
3B182-8-8	12	1/2	-8	12.7	1/2x14	68	41	19	27
3B182-10-10	16	5/8	-10	15.9	5/8x14	81	45	21	30
3B182-12-12	19	3/4	-12	19.1	3/4x14	92	55	27	32
3B182-16-16-K	25	1	-16	25.4	1x11	107	70	33	41

Also available in stainless steel. Details can be found in CAT 4400.1/UK


K: without plastic ring; **B**: Brass; **SM**: Metric Hexagon


Approved **fitting series** for **hose types**:

82 | 801 | 804 | 821FR | 830M | 831 | 836 | 837BM | 837PU | 838M

B2 Female BSP Parallel Pipe Swivel 90° Elbow (60° Cone)

BS 5200-B – DKR 90°







Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	BSP	mm	mm	mm	mm
3B282-4-4	6	1/4	-4	6.4	1/4x19	42	23	29	17
3B282-6-6	10	3/8	-6	9.5	3/8x19	49	26	33	19
3B282-8-8B	12	1/2	-8	12.7	1/2x14	60	34	39	27
3B282-8-8	12	1/2	-8	12.7	1/2x14	60	34	39	27
3B282-10-8	12	1/2	-8	12.7	5/8x14	58	32	40	30
3B282-10-10	16	5/8	-10	15.9	5/8x14	74	37	43	30
3B282-10-10B	16	5/8	-10	15.9	5/8x14	74	37	44	30
3B282-12-12	19	3/4	-12	19.1	3/4x14	83	46	53	32
3B282-12-12B	19	3/4	-12	19.1	3/4x14	83	46	53	32
3B282-16-16-K	25	1	-16	25.4	1x11	99	61	68	41

D9 Male BSP Parallel Pipe Rigid – Straight (60° Cone)

BS5200 – AGR





Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	BSP	mm	mm	mm
3D982-2-4	6	1/4	-4	6.4	1/8x28	36	17	14
3D982-4-4B	6	1/4	-4	6.4	1/4x19	41	23	19
3D982-4-4	6	1/4	-4	6.4	1/4x19	41	23	19
3D982-4-6B	10	3/8	-6	9.5	1/4x19	44	21	19
3D982-4-6	10	3/8	-6	9.5	1/4x19	44	21	19
3D982-6-6	10	3/8	-6	9.5	3/8x19	45	23	22
3D982-8-8B	12	1/2	-8	12.7	1/2x14	53	27	27
3D982-8-8	12	1/2	-8	12.7	1/2x14	53	27	27
3D982-8-10	16	5/8	-10	15.9	1/2x14	62	25	27
3D982-12-12	19	3/4	-12	19.1	3/4x14	65	28	32

Also available in stainless steel. Details can be found in CAT 4400.1/UK


K: without plastic ring; **B**: Brass; **SM**: Metric Hexagon


Approved **fitting series** for **hose types**:

82 | 801 | 804 | 821FR | 830M | 831 | 836 | 837BM | 837PU | 838M

91 Male BSP Taper Pipe – Rigid Straight


BS5200 – AGR-K






Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	BSP	mm	mm	mm
39182-2-4B	6	1/4	-4	6.4	1/8x28	37	18	12
39182-4-4B	6	1/4	-4	6.4	1/4x19	40	21	14
39182-4-6B	10	3/8	-6	9.5	1/4x19	44	21	14
39182-6-6B	10	3/8	-6	9.5	3/8x19	45	22	19
39182-6-8B	12	1/2	-8	12.7	3/8x19	49	22	19
39182-8-8B	12	1/2	-8	12.7	1/2x14	55	29	22
39182-8-10B	16	5/8	-10	15.9	1/2x14	65	28	22
39182-12-10B	16	5/8	-10	15.9	3/4x14	69	32	30
39182-12-12B	19	3/4	-12	19.1	3/4x14	69	32	30

34 Inch Standpipe (Brass)





Part Number	Hose I.D.				A	B	D
	DN	Inch	Size	mm	mm	mm	mm
33482-4-4B	6	1/4	-4	6.4	48	29	26
33482-6-6B	10	3/8	-6	9.5	57	34	31
33482-8-8B	12	1/2	-8	12.7	55	28	25
33482-10-10B	16	5/8	-10	15.9	67	30	25
33482-12-12B	19	3/4	-12	19.1	67	30	25

Also available in stainless steel. Details can be found in CAT 4400.1/UK


K: without plastic ring; **B**: Brass; **SM**: Metric Hexagon


Approved **fitting series** for **hose types**:

82 | 801 | 804 | 821FR | 830M | 831 | 836 | 837BM | 837PU | 838M

01 Male NPTF Pipe Rigid – Straight

SAE J476A / J516 – AGN







Part Number	Hose I.D.				Thread	A	B	H	
	DN	Inch	Size	mm	NPTF	mm	mm	mm	*Inch*
30182-2-4B	6	1/4	-4	6.4	1/8x27	35	16	*7/16*	
30182-2-4-SM	6	1/4	-4	6.4	1/8x27	35	16	12	
30182-4-4-SM	6	1/4	-4	6.4	1/4x18	40	21	14	
30182-4-4B	6	1/4	-4	6.4	1/4x18	40	21	*9/16*	
30182-6-4	6	1/4	-4	6.4	3/8x18	42	22	*11/16*	
30182-6-4B	6	1/4	-4	6.4	3/8x18	42	22	*11/16*	
30182-4-6-SM	10	3/8	-6	9.5	1/4x18	45	23	14	
30182-4-6B	10	3/8	-6	9.5	1/4x18	45	22	*9/16*	
30182-6-6-SM	10	3/8	-6	9.5	3/8x18	45	23	19	
30182-8-6-SM	10	3/8	-6	9.5	1/2x14	52	29	22	
30182-8-6B-SM	10	3/8	-6	9.5	1/2x14	52	29	22	
30182-6-8B	12	1/2	-8	12.7	3/8x18	49	22	*11/16*	
30182-8-8B-SM	12	1/2	-8	12.7	1/2x14	55	29	22	
30182-8-8-SM	12	1/2	-8	12.7	1/2x14	55	29	22	
30182-8-10B	16	5/8	-10	15.9	1/2x14	66	29	*7/8*	
30182-8-10-SM	16	5/8	-10	15.9	1/2x14	66	29	22	
30182-12-10	16	5/8	-10	15.9	3/4x14	66	29	*1 1/16*	
30182-8-12-SM	19	3/4	-12	19.1	1/2x14	66	29	22	
30182-8-12B	19	3/4	-12	19.1	1/2x14	66	29	*7/8*	
30182-12-12-SM	19	3/4	-12	19.1	3/4x14	66	30	27	
30182-12-12	19	3/4	-12	19.1	3/4x14	66	29	*1 1/16*	
30182-12-12B	19	3/4	-12	19.1	3/4x14	66	29	*1 1/16*	

02 Female NPTF Pipe – Rigid Straight

SAE J476A / J516





Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	NPTF	mm	mm	*Inch*
30282-4-4B	6	1/4	-4	6.4	1/4x18	40	21	*3/4*
30282-6-6B	10	3/8	-6	9.5	3/8x18	46	23	*7/8*
30282-8-8B	12	1/2	-8	12.7	1/2x14	55	28	*1 1/16*

Also available in stainless steel. Details can be found in CAT 4400.1/UK


K: without plastic ring; **B**: Brass; **SM**: Metric Hexagon


Approved **fitting series** for **hose types**:

82 | 801 | 804 | 821FR | 830M | 831 | 836 | 837BM | 837PU | 838M

03 Male JIC 37° – Rigid Straight

ISO12151-5-S – AGJ






Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	NPTF	mm	mm	*Inch*
30382-4-4	6	1/4	-4	6.4	7/16x20	40	21	*1/2*
30382-6-6	10	3/8	-6	9.5	9/16x18	45	22	*5/8*
30382-6-6B	10	3/8	-6	9.5	9/16x18	45	22	*5/8*
30382-8-8B	12	1/2	-8	12.7	3/4x16	52	26	*3/4*
30382-8-8	12	1/2	-8	12.7	3/4x16	52	26	*3/4*
30382-12-12B	19	3/4	-12	19.1	1 1/16x12	69	32	*1 1/8*
30382-12-12	19	3/4	-12	19.1	1 1/16x12	69	32	*1 1/8*

06/68 Female – JIC 37° SAE 45° Dual Flare Swivel – Straight

ISO12151-5-SWS – DKJ





Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	NPTF	mm	mm	mm *Inch*
30682-4-4-SM	6	1/4	-4	6.4	7/16x20	40	21	14
30682-4-4B	6	1/4	-4	6.4	7/16x20	39	19	*9/16*
30682-5-4B	6	1/4	-4	6.4	1/2x20	40	21	*5/8*
30682-6-4B	6	1/4	-4	6.4	9/16x18	42	22	*11/16*
30682-5-6B	10	3/8	-6	9.5	1/2x20	44	21	*5/8*
30682-6-6-SM	10	3/8	-6	9.5	9/16x18	45	22	19
30682-6-6	10	3/8	-6	9.5	9/16x18	46	22	*11/16*
30682-6-6B-SM	10	3/8	-6	9.5	9/16x18	45	22	19
36882-8-6-SM	10	3/8	-6	9.5	3/4x16	48	25	22
30682-8-6B	10	3/8	-6	9.5	3/4x16	47	24	*7/8*
36882-8-8B-SM	12	1/2	-8	12.7	3/4x16	51	25	22
36882-8-8-SM	12	1/2	-8	12.7	3/4x16	51	25	22
30682-10-8B	12	1/2	-8	12.7	7/8x14	52	25	*1*
30682-10-10-SM	16	5/8	-10	15.9	7/8x14	65	28	27
30682-10-10B	16	5/8	-10	15.9	7/8x14	62	25	*1*
30682-12-12-SM	19	3/4	-12	19.1	1 1/16x12	67	30	32
30682-12-12B-SM	19	3/4	-12	19.1	1 1/16x12	67	31	32

Also available in stainless steel. Details can be found in CAT 4400.1/UK


K: without plastic ring; **B**: Brass; **SM**: Metric Hexagon


Approved **fitting series** for **hose types**:

82 | 801 | 804 | 821FR | 830M | 831 | 836 | 837BM | 837PU | 838M

08 Female SAE 45° – Swivel Straight

SAE J516







Part Number	Hose I.D.				Thread	A	B	W
	DN	Inch	Size	mm	UNF	mm	mm	*inch*
30882-4-4	6	1/4	-4	6.4	7/16x20	39	19	*9/16*
30882-4-4B	6	1/4	-4	6.4	7/16x20	39	19	*9/16*
30882-5-4B	6	1/4	-4	6.4	1/2x20	40	21	*5/8*
30882-6-6-SM	10	3/8	-6	9.5	5/8x18	46	22	19
30882-6-6B	10	3/8	-6	9.5	5/8x18	46	23	*3/4*
30882-8-8B	12	1/2	-8	12.7	3/4x16	51	25	*7/8*
30882-8-8	12	1/2	-8	12.7	3/4x16	51	25	*7/8*
30882-10-10B	16	5/8	-10	15.9	7/8x14	65	28	*1*
30882-10-10	16	5/8	-10	15.9	7/8x14	65	28	*1*
30882-12-12	19	3/4	-12	19.1	1 1/16x14	67	30	*1 1/4*
30882-12-12B	19	3/4	-12	19.1	1 1/16x14	67	30	*1 1/4*

37/3V Female JIC 37° SAE 45° – Dual Flare Swivel Female 45° Elbow

ISO 12151-5-SWE 45° – DKJ 45°





Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm *Inch*
33V82-4-4B-SM	6	1/4	-4	6.4	7/16x20	44	25	10	17
33782-4-4	6	1/4	-4	6.4	7/16x20	39	20	8	*9/16*
33782-6-6-SM	10	3/8	-6	9.5	9/16x18	51	28	11	19
33782-8-8	12	1/2	-8	12.7	3/4x16	54	35	14	*7/8*

Also available in stainless steel. Details can be found in CAT 4400.1/UK


K: without plastic ring; **B**: Brass; **SM**: Metric Hexagon


Approved **fitting series** for **hose types**:

82 | 801 | 804 | 821FR | 830M | 831 | 836 | 837BM | 837PU | 838M

39/3W Female JIC 37° SAE 45° – Dual Flare Swivel Female 90° Elbow

ISO 12151-5-SWES – DKJ 90°





Part Number	Hose I.D.				Thread	A	B	E	W	
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm	*Inch*
33W82-4-4-SM	6	1/4	-4	6.4	7/16x20	39	20	21	17	
33982-4-4	6	1/4	-4	6.4	7/16x20	39	20	17		*5/8*
33982-6-6	10	3/8	-6	9.5	9/16x18	50	28	22		*11/16*
33982-6-6-SM	10	3/8	-6	9.5	9/16x18	47	25	23	19	
33982-8-8	12	1/2	-8	12.7	3/4x16	59	33	28		*7/8*
33W82-8-8-SM	12	1/2	-8	12.7	3/4x16	55	29	28	22	
33982-10-10	16	5/8	-10	15.9	7/8x14	74	37	31		*1*
33982-12-12	19	3/4	-12	19.1	1 1/16x12	84	46	46		*1 1/4*
33982-12-12-SM	19	3/4	-12	19.1	1 1/16x12	88	52	48	32	

Also available in stainless steel. Details can be found in CAT 4400.1/UK

K: without plastic ring; **B**: Brass; **SM**: Metric Hexagon


Approved **fitting series** for **hose types**:


82 | 801 | 804 | 821FR | 830M | 831 | 836 | 837BM | 837PU | 838M

JC

Female ORFS Swivel – Straight Short

ISO 12151-1 – SWSA
SAE J516 – ORFS





Part Number	Hose I.D.				Thread	A	B	H	W
	DN	Inch	Size	mm	UNF	mm	mm	mm *Inch*	mm *Inch*
3JC82-4-4	6	1/4	-4	6.4	9/16x18	36	17	*9/16*	*11/16*
3JC82-6-6	10	3/8	-6	9.5	11/16x16	40	18	*11/16*	*13/16*
3JC82-6-6-SM	10	3/8	-6	9.5	11/16x16	40	18	19	22
3JC82-8-6-SM	10	3/8	-6	9.5	13/16x16	43	21	22	24
3JC82-8-8-SM	12	1/2	-8	12.7	13/16x16	47	21	22	24
3JC82-8-10	16	5/8	-10	15.9	13/16x16	57	21	*3/4*	*15/16*
3JC82-10-10	16	5/8	-10	15.9	1x14	61	24	*15/16*	*1 1/8*
3JC82-10-12	19	3/4	-12	19.1	1x14	61	24	*1*	*1 1/8*
3JC82-12-12	19	3/4	-12	19.1	1 3/16x12	67	30	*1 1/8*	*1 3/8*


Also available in stainless steel. Details can be found in CAT 4400.1/UK


K: without plastic ring; **B**: Brass; **SM**: Metric Hexagon

Approved **fitting series** for **hose types**:

82 | 801 | 804 | 821FR | 830M | 831 | 836 | 837BM | 837PU | 838M


FF Metru-Lok Swivel Female





Part Number	Hose I.D.				Thread	Tube O.D.	A	B	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
3FF82-6-4B	6	1/4	-4	6.4	M10x1	6	36	16	14
3FF82-8-4B	6	1/4	-4	6.4	M12x1	8	31	12	14
3FF82-10-6B	10	3/8	-6	9.5	M14x1	10	35	12	17
3FF82-12-6B	10	3/8	-6	9.5	M16x1	12	35	12	19
3FF82-14-8B	12	1/2	-8	12.7	M18x1	14	38	12	22
3FF82-16-8B	12	1/2	-8	12.7	M22x1.5	16	38	12	27
3FF82-18-10B	16	5/8	-10	15.9	M24x1.5	18	51	15	27
3FF82-22-12B	19	3/4	-12	19.1	M28x1.5	22	51	15	32

AF Male BSP Parallel Pipe Rigid – Straight (with O-ring Seal)





Part Number	Hose I.D.				Thread	A	B	W
	DN	Inch	Size	mm	BSP	mm	mm	mm
3AF82-2-4B	6	1/4	-4	6.4	1/8x28	34	15	17
3AF82-4-4B	6	1/4	-4	6.4	1/4x19	39	20	19
3AF82-4-6B	10	3/8	-6	9.5	1/4x19	43	20	19
3AF82-6-6B	10	3/8	-6	9.5	3/8x19	46	23	22
3AF82-6-8B	12	1/2	-8	12.7	3/8x19	49	22	22
3AF82-8-8B	12	1/2	-8	12.7	1/2x14	53	26	27
3AF82-8-10B	16	5/8	-10	15.9	1/2x14	63	27	27


Also available in stainless steel. Details can be found in CAT 4400.1/UK


K: without plastic ring; **B:** Brass; **SM:** Metric Hexagon

Approved **fitting series** for **hose types**:

82 | 801 | 804 | 821FR | 830M | 831 | 836 | 837BM | 837PU | 838M


82 Push-Lok® Union






Part Number	Hose I.D.				A
	DN	Inch	Size	mm	mm
38282-4-4	6	1/4	-4	6.4	45
38282-4-4B	6	1/4	-4	6.4	46
38282-6-6B	10	3/8	-6	9.5	54
38282-8-8B	12	1/2	-8	12.7	64
38282-8-8	12	1/2	-8	12.7	64
38282-10-10	16	5/8	-10	15.9	84
38282-10-10B	16	5/8	-10	15.9	84
38282-12-12	19	3/4	-12	19.1	84
38282-12-12B	19	3/4	-12	19.1	84

5C 60° Cone Swivel Female





Part Number	Hose I.D.				Thread	A	B	W
	DN	Inch	Size	mm	metric	mm	mm	mm
35C82-6-4BK	6	1/4	-4	6.4	M12x1.5	33	14	14
35C82-10-6BK	10	3/8	-6	9.5	M16x1.5	38	15	19
35C82-10-6B	10	3/8	-6	9.5	M16x1.5	38	15	19
35C82-15-8BK	12	1/2	-8	12.7	M22x1.5	44	18	27
35C82-18-10BK	16	5/8	-10	15.9	M26x1.5	57	21	32


Also available in stainless steel. Details can be found in CAT 4400.1/UK


K: without plastic ring; **B**: Brass; **SM**: Metric Hexagon

Approved **fitting series** for **hose types**:

82 | 801 | 804 | 821FR | 830M | 831 | 836 | 837BM | 837PU | 838M


6C 60° Cone Swivel Female 45° Elbow






Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
36C82-6-4BK	6	1/4	-4	6.4	M12x1.5	44	25	16	14
36C82-10-6BK	10	3/8	-6	9.5	M16x1.5	48	26	16	19
36C82-15-8BK	12	1/2	-8	12.7	M22x1.5	54	28	18	27

7C 60° Cone Swivel Female 90° Elbow





Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
37C82-6-4BK	6	1/4	-4	6.4	M12x1.5	30	11	22	14
37C82-10-6BK	10	3/8	-6	9.5	M16x1.5	34	11	25	19
37C82-15-8BK	12	1/2	-8	12.7	M22x1.5	43	16	32	27

Also available in stainless steel. Details can be found in CAT 4400.1/UK

K: without plastic ring; **B**: Brass; **SM**: Metric Hexagon

Approved **fitting series** for **hose types**:

82 | 801 | 804 | 821FR | 830M | 831 | 836 | 837BM | 837PU | 838M





Assembly Instructions

1. Cut the hose right angled with a sharp knife. If necessary it is possible to use a lubricant (water/soap solution with 5 % soap fluid and 95 % water) for easy assembly.

2. Insert fitting into hose until first barb is in hose. Place end of fitting against a flat object (bench, door, wall) and grip hose approximately 1“ from end and push with a steady force until end of hose is covered by yellow plastic collar. Alternatively please use the Parker Assembly Tool No. 611050G or 611050HV.

Attention!
During assembly, please keep in mind that Push-Lok fittings will provide an effective grip only when the Push-Lok hose is pushed fully on the insert, where the cropped end of the hose should be fully concealed by the plastic collar. **For easy assembly of hose 830M, 837BM and 837PU please use only Push-Lok Assembly Oil No. H896137.** Push-Lok Assembly Oil is free from wetting disturbing substances.
Don’t use oil, lubricant or soap fluids for this hose!





Disassembly Instructions

1. Cut lengthwise along a line at approximately a 20 angle from centre line of hose. The cut should be approximately 1” long.
   Be careful not to nick barbs when cutting the hose.


2. Grip hose and give a sharp down-ward tug to disengage from fitting.

Attention!
Before re-use of the nipple please check nipple for damage. Damaged nipples can cause leakage.


Assembly Tool

Tool designed for assembly of Push-Lok fittings and hose in all sizes. Toggle actions greatly reduce effort necessary to hold hose and press in fitting. Only a few pounds of force is needed on either handle to quickly assemble any size.

Light version
Part Number: 611050G



Heavy version
Part Number: 611050HV




Push-Lok Assembly Oil
1-litre bottle
Part Number: H896137



Low Pressure Transportation and Hydraulic Hose and Fittings

– the right solution for special applications and requirements





- A wide range of different hose types in rubber is available, with textile-braided or fire-retardant covers
- Proven, safe and easy self-assembly system
- Large bore sizes available
- High working temperatures
- One fitting series for all SAE 100 R5 and similar hoses

Applications

The definitive hose range for all special applications and requirements














Parkrimp® *No-Skive*

The system for fast and leak-free assemblies

The perfect match



The complete system from one source. No-Skive hose, No-Skive fitting and crimping machine with world-wide guarantee and availability.


Parker's colour-coded die sets



No loose parts to mismatch or misplace – die set segments linked together.

Die sets provide 360° evenly applied crimping forces for an ideal crimp result.

Parkalign®



Parker's exclusive Parkalign® positions the fitting in the dies perfectly every time.



KarryKrimp® 1

KarryKrimp® 2

Parkrimp®

KarryKrimp® 2 Bench Mount



Parkrimp® *No-Skive*

- No skiving tool needed
- No need to remove the cover
- Crimps one-piece fittings
- Parkalign positions the fittings in the dies perfectly every time
- Quick and easy: no gauges to set on the machine
- Portable machines for field repair
- Meets EN safety regulations

Low Pressure Transportation and Hydraulic

Hoses			Page
	201	Transportation	B2a-1
	206	Transportation	B2a-2
	213	Transportation	B2a-3
	221FR	Fire retardant	B2a-4
	285	Refrigeration	B2a-5
	293	Transportation	B2a-6
	601	Standard	B2a-7
	611HT	High temperature	B2a-8
	681	Standard	B2a-9
	681DB	Railway	B2a-10

Index

Fittings Series	26
Chapter	B2b
DIN – Metric	1 – 2
BSP	3 – 4
SAE	5 – 7
ORFS	8
Others	9

Parker Hannifin assumes no liability for typographical errors or other errors

Standard

601
B2a-7

No-Skive
SAE 100R3

681
B2a-9

No-Skive **2TE**
EN 854-2TE

High temperature

611HT
B2a-8

No-Skive
High-temperature textile hose

Railway

681DB
B2a-10

No-Skive **2TE**
EN 854-2TE
(with approvals for rail transportation)

Transportation

201
B2a-1

No-Skive **Airbrake**
SAE 100R5 – SAE J1402All

206
B2a-2

No-Skive **Airbrake**
SAE 100R5 – SAE J1402All

213
B2a-3

No-Skive **High Temperature**
For engines and compressed air systems

293
B2a-6

No-Skive **High Temperature**
Engine and air brake/truck hose

Fire retardant

221FR
B2a-4

No-Skive **Fire Retardant**
Marine fuel and engine hose

Refrigeration

285
B2a-5

Air Conditioning and Refrigeration
SAE J2064 Type C, Class 1

201

No-Skive Airbrake

SAE 100R5 – SAE J1402AII



- Textile braided cover
- *No-Skive* hose construction
- 150 °C working temperature

Primary Applications

Transportation: Air brake hose
General: Low pressure applications

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

SAE 100R5, SAE J1402AII, D. O. T. FMVSS 106-AII

Construction

Tube: Synthetic rubber
Reinforcement: One fibre inner braid,
one high-tensile steel wire braid
Cover: Rubber layer and textile braided cover

Temperature Range ..... -40 °C up to +150 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum based hydraulic fluids, water-glycol and water-oil emulsion hydraulic fluids, grease, lubricants, crude and fuel oils, air and water.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

26

Part Number	Hose I.D.			Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		Vaccum*	min. bend radius	weight
	Inch	Size	mm	mm	MPa	psi	MPa	psi	kPa	mm	kg
201-4	3/16	-4	5.0	12.2	20.7	3000	83.0	12000	95	75	0.22
201-5	1/4	-5	6.3	14.8	20.7	3000	83.0	12000	95	85	0.27
201-6	5/16	-6	8.0	17.2	15.5	2250	62.0	9000	95	100	0.34
201-8	13/32	-8	10.0	19.5	13.8	2000	55.0	8000	95	120	0.40
201-10	1/2	-10	12.5	23.4	12.0	1750	48.0	7000	95	140	0.55
201-12	5/8	-12	16.0	27.4	10.3	1500	41.0	6000	95	165	0.68
201-16	7/8	-16	22.0	31.4	5.5	800	22.0	3200	67	185	0.68
201-20	1 1/8	-20	29.0	38.1	4.3	625	17.0	2500	67	230	0.76
201-24	1 3/8	-24	35.0	44.5	3.5	500	14.0	2000	51	265	1.01
201-32	1 13/16	-32	46.0	56.4	2.4	350	10.0	1400	37	335	1.32

* the vacuum values listed in the table are vacuum pressure values in kPa. For an absolute value subtract the table value from 101kPa.
The combination of high temperature and high pressure could reduce the hose life.
The maximum working pressures shown in the table are for service up to a maximum temperature of 100 °C.
For use at higher temperatures, consult the pressure/temperature curve in section A for the reduced maximum working pressure.

Hose layline example

Parker 201-6 AIR BRAKE DOT XXXXX AII 8 mm (5/16) SAE J1402 DOT XXXXX AII WP 15,7 MPa (2250 PSI) DOT XXXXX AII SA

206

No-Skive Airbrake

SAE 100R5 – SAE J1402AII



- Blue textile braided cover
- *No-Skive* hose construction
- For very low (-48 °C) working temperature

Primary Applications

Transportation: Air brake hose
General: Low pressure applications

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

SAE 100R5, SAE J1402AII, D. O. T. FMVSS 106-AII

Construction

Tube: Parker PKR-elastomer tube
Reinforcement: One fibre inner braid, one high-tensile steel wire braid
Cover: Rubber layer and blue textile braided cover

Temperature Range ..... -48 °C up to +150 °C

Exception: Air ..... max. +100 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum based hydraulic fluids, water-glycol and water-oil emulsion hydraulic fluids, grease, lubricants, crude and fuel oils, air and water.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.


Fitting Series



Part Number	Hose I.D.			Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		Vaccum*	min. bend radius	weight
	Inch	Size	mm	mm	MPa	psi	MPa	psi	kPa	mm	kg
206-4	3/16	-4	5.0	13.2	20.7	3000	83.0	12000	95	75	0.22
206-5	1/4	-5	6.3	14.8	20.7	3000	83.0	12000	95	85	0.27
206-6	5/16	-6	8.0	17.1	15.5	2250	62.0	9000	95	90	0.34
206-8	13/32	-8	10.0	19.5	13.8	2000	55.0	8000	95	90	0.40
206-10	1/2	-10	12.5	23.4	12.0	1750	48.0	7000	95	100	0.55
206-12	5/8	-12	16.0	27.4	10.3	1500	41.0	6000	95	100	0.68
206-16	7/8	-16	22.0	31.4	5.5	800	22.0	3200	67	100	0.68
206-20	1 1/8	-20	29.0	38.1	4.3	625	17.0	2500	67	140	0.76
206-24	1 3/8	-24	35.0	44.5	3.5	500	14.0	2000	51	190	1.01
206-32	1 13/16	-32	46.0	56.4	2.4	350	10.0	1400	37	335	1.32

* the vacuum values listed in the table are vacuum pressure values in kPa. For an absolute value subtract the table value from 101kPa.
The combination of high temperature and high pressure could reduce the hose life.
The maximum working pressures shown in the table are for service up to a maximum temperature of 100 °C.
For use at higher temperatures, consult the pressure/temperature curve in section A for the reduced maximum working pressure.

Hose layline example



213

No-Skive High Temperature

For engines and compressed air systems



- *No-Skive* hose construction
- Ideal for high-temperature and small bend radii applications
- Compatible with a large range of fluids

Primary Applications

Transportation: Air brake hose
Compressors: Compressed air hose

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

SAE J1402AI, D.O.T. FMVSS 106-AI

Construction

Tube: Parker PKR-elastomer tube
Reinforcement: One fibre inner braid, one high-tensile steel wire braid
Cover: Rubber layer and black textile braided cover include 2 green strips

Recommended Fluids

Petroleum based hydraulic fluids, water-glycol and water-oil emulsion hydraulic fluids, grease, lubricants, crude and fuel oils, air and water.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Temperature Range ..... -45 °C up to +150 °C

Exception: Air ..... max. +100 °C
Water ..... max. +85 °C

Fitting Series



Part Number	Hose I.D.			Hose O.D.	Pressure Rating				min. bend radius	weight
					max. working pressure		min. burst pressure			
	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
213-4	3/16	-4	5.0	12.5	13.8	2000	55.0	8000	20	0.18
213-5	1/4	-5	6.3	14.1	10.3	1500	41.0	6000	25	0.21
213-6	5/16	-6	8.0	15.7	10.3	1500	41.0	6000	30	0.25
213-8	13/32	-8	10.0	18.7	8.6	1250	34.0	5000	45	0.30
213-10	1/2	-10	12.5	21.1	6.9	1000	28.0	4000	55	0.33
213-12	5/8	-12	16.0	24.3	5.2	750	21.0	3000	70	0.36
213-16	7/8	-16	22.0	30.6	2.8	400	11.0	1600	90	0.45
213-20	1 1/8	-20	29.0	37.8	2.1	300	8.0	1200	115	0.65
213-24	1 3/8	-24	35.0	44.0	1.7	300	8.0	1200	190	0.73
213-32	1 13/16	-32	46.0	54.5	1.4	200	5.5	800	355	1.00

The combination of high temperature and high pressure could reduce the hose life.
The maximum working pressures shown in the table are for service up to a maximum temperature of 100 °C.
For use at higher temperatures, consult the pressure/temperature curve in section A for the reduced maximum working pressure.

Hose layline example

PARKER 213-16 WP 2,8 MPa (400 PSI) 22 mm (7/8) 3Q88 PARKER 213-16 WP 2,8

221FR

No-Skive Fire Retardant

Marine fuel and engine hose



- Fire retardant hose cover
- *No-Skive* hose construction
- Marine approvals

Primary Applications

Marine: Marine fuel hose
General: Where fire retardance is an issue

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

SAE J1527 R3, USCG Type AI, SAE J1942, ISO 7840

Construction

Tube: Fuel and oil-resistant rubber
Reinforcement: One high-tensile steel wire braid
Cover: Flame retardant special fibre outer cover

Temperature Range ..... -20 °C up to +100 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum based hydraulic fluids, water-glycol and water-oil emulsion hydraulic fluids, grease, lubricants, crude, fuel oils and water.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

26

Part Number	Hose I.D.			Hose O.D.	Pressure Rating				Vaccum*	min. bend radius	weight
					max. working pressure		min. burst pressure				
	Inch	Size	mm	mm	MPa	psi	MPa	psi	kPa	mm	kg
221FR-5	1/4	-5	6.3	15	3.5	500	14.0	2000	81	25	0.28
221FR-6	5/16	-6	8.0	17	3.5	500	14.0	2000	81	30	0.34
221FR-8	13/32	-8	10.0	20	3.5	500	14.0	2000	81	45	0.42
221FR-10	1/2	-10	12.5	23	3.5	500	14.0	2000	68	55	0.58
221FR-12	5/8	-12	16.0	27	3.5	500	14.0	2000	68	70	0.61
221FR-16	7/8	-16	22.0	31	3.5	500	14.0	2000	68	90	0.70

* the vacuum values listed in the table are vacuum pressure values in kPa. For an absolute value subtract the table value from 101kPa.
The combination of high temperature and high pressure could reduce the hose life.

Hose layline example

PARKER 221FR-10 SAE J1527 USCG TYPE A1 CE 1085 ISO 7840-A1 WITH 26 SERIES CRIMP FITTINGS ONLY

285

Air Conditioning and Refrigeration

SAE J2064 Type C, Class 1



- *No-Skive* hose construction
- Usable for main refrigerant fluids
- Compatible with modern refrigerants

Primary Applications

Air Conditioning: For industrial and mobile applications

Applicable Specifications

SAE J2064 Type C, Class 1

Construction

Tube:	Nylon barrier between two elastomeric layers
Reinforcement:	One textile braid
Cover:	Heat, moisture and ozone resistant rubber

Temperature Range ..... -30 °C up to +125 °C

Recommended Fluids

For use with Freon refrigerants 12, 134a and 22. Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series



Part Number	Hose I.D.			Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		Vaccum*	min. bend radius	weight
	Inch	Size	mm	mm	MPa	psi	MPa	psi	kPa	mm	kg
285-4-RL	3/16	-4	5.0	12.4	3.4	500	17.2	2500	95	25	0.14
285-6-RL	5/16	-6	8.0	15.7	3.4	500	17.2	2500	95	38	0.19
285-8-RL	13/32	-8	10.0	18.8	3.4	500	17.2	2500	95	51	0.25
285-10-RL	1/2	-10	12.5	21.1	3.4	500	17.2	2500	95	64	0.27
285-12-RL	5/8	-12	16.0	24.4	3.4	500	17.2	2500	95	76	0.34

* the vacuum values listed in the table are vacuum pressure values in kPa. For an absolute value subtract the table value from 101kPa.
For size -16 a hose 285-16 is available on request.
RL = only available on reels.

Hose layline example

PARKER 285-10 WP 3,4 MPa (500 PSI) SAE J2064 TYPE C CLASS I 12,5 mm (1/2) 10-4Q09

293

No-Skive High Temperature

Engine and air brake/truck hose



- High temperature – high flex hose performance
- *No-Skive* hose construction
- Wide temperature range

Primary Applications

Truck Market: Air brake hose
Engine cooling circuit

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

SAE J1402AI, D.O.T. FMVSS 106

Construction

Tube: Synthetic PKR rubber
Reinforcement: One fibre braid
Cover: Black nylon braid

Temperature Range ..... -50 °C up to +150 °C

Exception: Air ..... max. +100 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum-based hydraulic fluids and lubrication oils, diesel fuels and antifreeze solutions; water-, water-oil- and water-glycol emulsion hydraulic fluids.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series



Part Number	Hose I.D.			Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
293-4-RL	3/16	-4	5.0	12.5	3.5	500	13.8	2000	15	0.15
293-6-RL	5/16	-6	8.0	15.7	3.5	500	13.8	2000	25	0.22
293-8-RL	13/32	-8	10.0	18.7	3.5	500	13.8	2000	40	0.27
293-10-RL	1/2	-10	12.5	21.1	3.1	450	12.4	1800	50	0.30
293-12-RL	5/8	-12	16.0	24.3	3.1	450	12.4	1800	65	0.33
293-16-RL	7/8	-16	22.0	30.6	3.1	450	12.4	1800	80	0.37

The combination of high temperature and high pressure could reduce the hose life.
RL = only available on reels.

Hose layline example

PARKER 293-6 AIR BRAKE 8 mm (5/16) SAE J1402 W.P. 3,5 MPa (500 PSI) ——— PARKER 293-6

601

No-Skive

SAE 100R3



- Textile braided reinforcement
- *No-Skive* hose construction
- Small bend radii
- Up to +125 °C working temperature

Primary Applications

General Market: Low pressure hydraulic applications

Applicable Specifications

SAE 100R3, EN 854-R3

Construction

Tube: Synthetic rubber
Reinforcement: Two fibre braids
Cover: MSHA accepted synthetic rubber

Temperature Range ..... -40 °C up to +125 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum based hydraulic fluids, water-glycol and water-oil emulsion hydraulic fluids, grease, lubricants, crude and fuel oils, air and water.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

43

Part Number	Hose I.D.				Hose O.D.	Pressure Rating				min. bend radius	weight
						max. working pressure		min. burst pressure			
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
601-4	6	1/4	-4	6.4	14.0	8.6	1250	35.0	5000	75	0.19
601-6	10	3/8	-6	9.5	19.0	7.8	1125	31.0	4500	100	0.33
601-8	12	1/2	-8	12.7	23.0	6.9	1000	28.0	4000	130	0.42
601-12	19	3/4	-12	19.1	32.0	5.2	750	21.0	3000	150	0.64
601-16	25	1	-16	25.4	38.0	3.9	565	16.0	2250	200	0.91

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example

PARKER 601-8 WP 6,9 MPa (1000 PSI) MSHA XXXX SAE100R3-8 12,5 mm (1/2) X 2F 7-3Q83

611HT

No-Skive

High-temperature textile hose



- For high demand applications, such as diesel fuel lines, water cooling or high-temp lines up to +150 °C
- MSHA approved
- According to EN 854-R6
- *No-Skive* hose construction for 2-piece fittings

Primary Applications

General Market: Low pressure hydraulic applications/ high temperature applications

Engine Applications: Diesel fuel lines, engine cooling circuits

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

EN 854-R6

Construction

Tube: Synthetic PKR rubber

Reinforcement: One fibre braid

Cover: MSHA accepted synthetic rubber

Temperature Range ..... -40 °C up to +150 °C

Exception: Air ..... max. +100 °C

Water ..... max. +85 °C

Recommended Fluids

Petroleum-based hydraulic fluids and lubrication oils, diesel fuels and antifreeze solutions; water-glycol and water-oil emulsion, air and water.

Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

- Compatible with 2-piece fittings for use with adjustable crimpers only (47 series nipple and 10064 series shell)

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
611HT-4	6	1/4	-4	6.4	12.8	2.8	400	11.2	1600	65	0.13
611HT-6	10	3/8	-6	9.5	16.0	2.8	400	11.2	1600	75	0.16
611HT-8	12	1/2	-8	12.7	20.0	2.8	400	11.2	1600	100	0.27
611HT-10	16	5/8	-10	15.9	23.2	2.4	350	9.6	1400	125	0.28
611HT-12	19	3/4	-12	19.1	26.2	2.1	300	8.4	1200	150	0.36

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example

PARKER 611HT-4 HI-TEMP WP 2,8 MPa (400 PSI) MSHA IC-40/10 I • • SAE 100R6-4 6,3 mm (1/4) X 1F EN854/R6/

681

No-Skive 2TE

EN 854-2TE



- One layer of fabric braid
- *No-Skive* hose construction
- Small bend radii

Primary Applications

General Market: Low pressure hydraulic application

Applicable Specifications

EN 854-2TE

Construction

Tube: Synthetic rubber
Reinforcement: One fibre braid
Cover: Synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum based hydraulic fluids, water-glycol and water-oil emulsion hydraulic fluids, grease, lubricants, crude and fuel oils, air and water.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

- Compatible with 2-piece fittings for use with adjustable crimpers only (47 series nipple and 10064 series shell)

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
681-4	6	1/4	-4	6.4	13.1	7.5	1090	30.0	4360	40	0.15
681-5	8	5/16	-5	7.9	14.6	6.8	980	27.0	3920	50	0.16
681-6	10	3/8	-6	9.5	16.2	6.3	910	25.0	3640	60	0.19
681-8	12	1/2	-8	12.7	19.9	5.8	840	23.0	3360	70	0.24
681-10	16	5/8	-10	15.9	23.4	5.0	725	20.0	2900	90	0.35
681-12	19	3/4	-12	19.1	26.5	4.5	650	18.0	2600	110	0.39
681-16	25	1	-16	25.4	33.4	4.0	580	16.0	2320	150	0.59

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example

PARKER 681-4 WP 7,5 MPa (1090 PSI) I • • 6,3 mm (1/4) EN854/2TE/6/DIN made in Italy

681DB

No-Skive 2TE

EN 854-2TE
(with approvals for rail transportation)



- One layer of fabric braid
- *No-Skive* hose construction
- Small bend radii
- Flame retardant rubber cover
- Railway approved as follows:
  European Standard EN45545 +
  ISO15540: HL2
  (hose need FS-F-Fire Sleeve)
  FS-F on page Eb-14

Primary Applications

General Market: Low pressure hydraulic application
Rail Transportation Market:
Hydraulic applications around train vehicles

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

EN 854-2TE

Construction

Tube: Synthetic rubber
Reinforcement: One fibre braid
Cover: Flame retardant synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum based hydraulic fluids, water-glycol and water-oil emulsion hydraulic fluids, grease, lubricants, crude and fuel oils, air and water.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

- Compatible with 2-piece fittings for use with adjustable crimpers only (47 series nipple and 10064 series shell)

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
681DB-4	6	1/4	-4	6.4	13.1	7.5	1090	30.0	4360	40	0.15
681DB-5	8	5/16	-5	7.9	14.6	6.8	980	27.0	3920	50	0.16
681DB-6	10	3/8	-6	9.5	16.2	6.3	910	25.0	3640	60	0.19
681DB-8	12	1/2	-8	12.7	19.9	5.8	840	23.0	3360	70	0.24
681DB-10	16	5/8	-10	15.9	23.4	5.0	725	20.0	2900	90	0.35
681DB-12	19	3/4	-12	19.1	26.5	4.5	650	18.0	2600	110	0.39
681DB-16	25	1	-16	25.4	33.4	4.0	580	16.0	2320	150	0.59


The combination of high temperature and high pressure could reduce the hose life.


Hose layline example

PARKER 681DB-6 WP 6,3 MPa (910 PSI) – – – • • 10 MM (3/8) EN854/2TE/10/DIN M/D/Y

DIN – Metric


Page B2b-1 – B2b-2

CA
B2b-1

Female Metric 24°
Light Series with O–Ring
Swivel – Straight
ISO 12151-2-SWS-L – DKOL

CE
B2b-1

Female Metric 24°
Light Series with O–Ring
Swivel – 45° Elbow
ISO 12151-2-SWE 45°-L – DKOL 45°


CF
B2b-2

Female Metric 24°
Light Series with O–Ring
Swivel – 90° Elbow
ISO 12151-2-SWE-L – DKOL 90°

49
B2b-2

Metric Banjo
Straight
DIN 7642


BSP


Page B2b-3 – B2b-4

92
B2b-3

Female BSP Parallel Pipe
Swivel – Straight (60° Cone)
BS5200-A – DKR

B1
B2b-3


Female BSP Parallel Pipe
Swivel
45° Elbow (60° Cone)
BS 5200-D – DKR 45°


B2
B2b-4

Female BSP Parallel Pipe
Swivel
90° Elbow (60° Cone)
BS 5200-B – DKR 90°


91
B2b-4

Male BSP Taper Pipe – Rigid
Straight
BS5200 – AGR-K


SAE

Page B2b-5 – B2b-7

01
B2b-5

Male NPTF Pipe
Rigid – Straight
SAE J476A / J516 – AGN

06/68
B2b-5

Female – JIC 37°
SAE 45° Dual Flare
Swivel – Straight
ISO12151-5-SWS – DKJ

08
B2b-6

Female SAE 45° – Swivel
Straight
SAE J516

37/3V
B2b-6

Female JIC 37°
SAE 45° – Dual Flare
Swivel Female 45° Elbow
ISO 12151-5-SWE 45° – DKJ 45°

39/3W
B2b-7


Female JIC 37°
SAE 45° – Dual Flare
Swivel Female 90° Elbow
ISO 12151-5-SWES – DKJ 90°

ORFS

Page B2b-8

JC

B2b-8




Female ORFS
Swivel – Straight
Short
ISO 12151-1 – SWSA SAE J516 – ORFS

Others

Page B2b-9

5S

B2b-9



Female Tube O–ring Swivel
Short Pilot

5T

B2b-9





Female Tube O–Ring Swivel
90° Elbow – Short Pilot

CA

Female Metric 24° Light Series with O-Ring Swivel – Straight

ISO 12151-2-SWS-L – DKOL






Part Number	Hose I.D.			Thread	Tube O.D.	A	B	W
	Inch	Size	mm	metric	mm	mm	mm	mm
1CA26-6-4	3/16	-4	5.0	M12x1.5	6	40	20	14
1CA26-8-4	3/16	-4	5.0	M14x1.5	8	41	21	17
1CA26-10-5	1/4	-5	6.3	M16x1.5	10	41	20	19
1CA26-10-6	5/16	-6	8.0	M16x1.5	10	41	20	19
1CA26-12-6	5/16	-6	8.0	M18x1.5	12	41	21	22
1CA26-12-8	13/32	-8	10.0	M18x1.5	12	41	21	22
1CA26-15-8	13/32	-8	10.0	M22x1.5	15	42	21	27
1CA26-18-10	1/2	-10	12.5	M26x1.5	18	46	23	32
1CA26-18-12	5/8	-12	16.0	M26x1.5	18	46	23	32
1CA26-22-12	5/8	-12	16.0	M30x2	22	48	25	36
1CA26-28-16	7/8	-16	22.0	M36x2	28	54	28	41
1CA26-28-20	1 1/8	-20	29.0	M36x2	28	60	33	41
1CA26-35-20	1 1/8	-20	29.0	M45x2	35	56	29	50
1CA26-35-24	1 3/8	-24	35.0	M45x2	35	62	34	50
1CA26-42-24	1 3/8	-24	35.0	M52x2	42	59	31	60


Hose fittings are delivered with ozone resistant Nitrile (NBR) O-ring as a standard version. Working temperature from -40 °C up to +105 °C.
Hose fittings with special O-rings (Viton or EPDM) available on request. O-ring dimensions and part-numbers see in section Eb.

CE

Female Metric 24° Light Series with O-Ring Swivel – 45° Elbow

ISO 12151-2-SWE 45°-L – DKOL 45°





Part Number	Hose I.D.			Thread	Tube O.D.	A	B	E	W
	Inch	Size	mm	metric	mm	mm	mm	mm	mm
1CE26-10-6	5/16	-6	8.0	M16x1.5	10	66	45	17	19
1CE26-12-6	5/16	-6	8.0	M18x1.5	12	66	45	17	22
1CE26-12-8	13/32	-8	10.0	M18x1.5	12	60	39	17	22
1CE26-15-8	13/32	-8	10.0	M22x1.5	15	60	39	17	27
1CE26-18-10	1/2	-10	12.5	M26x1.5	18	68	46	20	32
1CE26-18-12	5/8	-12	16.0	M26x1.5	18	73	50	22	32
1CE26-22-12	5/8	-12	16.0	M30x2	22	77	55	26	36
1CE26-28-16	7/8	-16	22.0	M36x2	28	105	78	33	41

Hose fittings are delivered with ozone resistant Nitrile (NBR) O-ring as a standard version. Working temperature from -40 °C up to +105 °C.
Hose fittings with special O-rings (Viton or EPDM) available on request. O-ring dimensions and part-numbers see in section Eb.


Approved **fitting series** for **hose types**:


26 | 201 | 206 | 213 | 221FR | 285 | 293

CF

Female Metric 24° Light Series with O-Ring Swivel – 90° Elbow

ISO 12151-2-SWE-L – DKOL 90°






Part Number	Hose I.D.			Thread	Tube O.D.	A	B	E	W
	Inch	Size	mm	metric	mm	mm	mm	mm	mm
1CF26-8-4	3/16	-4	5.0	M14x1.5	8	48	28	29	17
1CF26-10-5	1/4	-5	6.3	M16x1.5	10	55	36	29	19
1CF26-10-6	5/16	-6	8.0	M16x1.5	10	55	34	31	19
1CF26-12-6	5/16	-6	8.0	M18x1.5	12	56	35	35	22
1CF26-12-8	13/32	-8	10.0	M18x1.5	12	50	30	31	22
1CF26-15-8	13/32	-8	10.0	M22x1.5	15	58	38	41	27
1CF26-18-10	1/2	-10	12.5	M26x1.5	18	57	34	38	32
1CF26-18-12	5/8	-12	16.0	M26x1.5	18	69	46	45	32
1CF26-22-12	5/8	-12	16.0	M30x2	22	78	55	47	36
1CF26-18-16	7/8	-16	22.0	M26x1.5	18	92	65	70	32
1CF26-28-16	7/8	-16	22.0	M36x2	28	96	70	71	41
1CF26-28-20	1 1/8	-20	29.0	M36x2	28	117	90	81	41
1CF26-35-20	1 1/8	-20	29.0	M45x2	35	117	90	77	50
1CF26-35-24	1 3/8	-24	35.0	M45x2	35	117	89	79	50


Hose fittings are delivered with ozone resistant Nitrile (NBR) O-ring as a standard version. Working temperature from -40 °C up to +105 °C.
Hose fittings with special O-rings (Viton or EPDM) available on request. O-ring dimensions and part-numbers see in section Eb.

49

Metric Banjo Straight

DIN 7642






Part Number	Hose I.D.			A	B	D
	Inch	Size	mm	mm	mm	mm
14926-12-6	5/16	-6	8.0	47	26	12
14926-14-6	5/16	-6	8.0	49	28	14
14926-14-8	13/32	-8	10.0	48	28	14
14926-16-8	13/32	-8	10.0	50	30	16


Approved **fitting series** for **hose types**:

26 | 201 | 206 | 213 | 221FR | 285 | 293

92 Female BSP Parallel Pipe Swivel – Straight (60° Cone)

BS5200-A – DKR







Part Number	Hose I.D.			Thread	A	B	W
	Inch	Size	mm	BSP	mm	mm	mm
19226-4-4	3/16	-4	5.0	1/4x19	41	20	19
19226-6-6	5/16	-6	8.0	3/8x19	42	21	22
19226-6-8	13/32	-8	10.0	3/8x19	41	21	22
19226-8-8	13/32	-8	10.0	1/2x14	44	23	27
19226-8-10	1/2	-10	12.5	1/2x14	45	22	27
19226-12-12	5/8	-12	16.0	3/4x14	45	24	32
19226-16-16	7/8	-16	22.0	1x11	52	25	41
19226-20-20	1 1/8	-20	29.0	1 1/4x11	58	31	50

B1 Female BSP Parallel Pipe Swivel 45° Elbow (60° Cone)

BS 5200-D – DKR 45°






Part Number	Hose I.D.			Thread	A	B	E	W
	Inch	Size	mm	BSP	mm	mm	mm	mm
1B126-4-4	3/16	-4	5.0	1/4x19	53	33	15	19
1B126-6-6	5/16	-6	8.0	3/8x19	56	36	16	22
1B126-8-8	13/32	-8	10.0	1/2x14	62	42	16	27
1B126-10-10	1/2	-10	12.5	5/8x14	67	44	20	30
1B126-12-12	5/8	-12	16.0	3/4x14	70	47	18	32


Approved **fitting series** for **hose types**:

26	201 | 206 | 213 | 221FR | 285 | 293

B2 Female BSP Parallel Pipe Swivel 90° Elbow (60° Cone)

BS 5200-B – DKR 90°







Part Number	Hose I.D.			Thread	A	B	E	W
	Inch	Size	mm	BSP	mm	mm	mm	mm
1B226-4-4	3/16	-4	5.0	1/4x19	44	24	26	19
1B226-6-6	5/16	-6	8.0	3/8x19	47	26	29	22
1B226-8-8	13/32	-8	10.0	1/2x14	54	34	31	27
1B226-10-10	1/2	-10	12.5	5/8x14	57	34	36	30
1B226-12-12	5/8	-12	16.0	3/4x14	62	40	37	32
1B226-16-16	7/8	-16	22.0	1x11	96	69	69	41
1B226-20-20	1 1/8	-20	29.0	1 1/4x11	117	90	76	50

91 Male BSP Taper Pipe – Rigid Straight

BS5200 – AGR-K






Part Number	Hose I.D.			Thread	A	B	H
	Inch	Size	mm	BSP	mm	mm	mm
19126-6-6	5/16	-6	8.0	3/8x19	47	26	19
19126-8-8	13/32	-8	10.0	1/2x14	53	32	22
19126-12-12	5/8	-12	16.0	3/4x14	58	36	30
19126-16-16	7/8	-16	22.0	1x11	69	43	36

Approved **fitting series** for **hose types**:

26 201 | 206 | 213 | 221FR | 285 | 293

01 Male NPTF Pipe Rigid – Straight

SAE J476A / J516 – AGN







Part Number	Hose I.D.			Thread	A	B	H
	Inch	Size	mm	NPTF	mm	mm	*Inch*
10126-4-5	1/4	-5	6.3	1/4x18	48	26	*9/16*
10126-4-6	5/16	-6	8.0	1/4x18	48	26	*3/4*
10126-6-6	5/16	-6	8.0	3/8x18	48	26	*11/16*
10126-6-8	13/32	-8	10.0	3/8x18	48	26	*11/16*
10126-8-8	13/32	-8	10.0	1/2x14	54	33	*7/8*
10126-8-10	1/2	-10	12.5	1/2x14	57	33	*7/8*
10126-12-12	5/8	-12	16.0	3/4x14	59	35	*1 1/16*

06/68 Female – JIC 37° SAE 45° Dual Flare Swivel – Straight

ISO12151-5-SWS – DKJ






Part Number	Hose I.D.			Thread	Tube	A	B	W
	Inch	Size	mm	UNF	mm	mm	mm	mm *Inch*
16826-4-4-SM	3/16	-4	5.0	7/16x20	1/4	43	24	14
16826-5-5-SM	1/4	-5	6.3	1/2x20	5/16	44	23	17
16826-5-5BA	1/4	-5	6.3	1/2x20	5/16	45	23	*5/8*
10626-6-6-SM	5/16	-6	8.0	9/16x18	3/8	45	25	19
10626-6-6BS	5/16	-6	8.0	9/16x18	3/8	45	23	*11/16*
10626-6-6	5/16	-6	8.0	9/16x18	3/8	45	23	*11/16*
16826-8-8-SM	13/32	-8	10.0	3/4x16	1/2	48	27	22
16826-8-10	1/2	-10	12.5	3/4x16	1/2	60	36	*7/8*
16826-10-10BA	1/2	-10	12.5	7/8x14	5/8	55	31	*1*
16826-10-10-SM	1/2	-10	12.5	7/8x14	5/8	54	32	27
16826-10-12-SM	5/8	-12	16.0	7/8x14	5/8	61	33	27
16826-10-12	5/8	-12	16.0	7/8x14	5/8	61	37	*1*
10626-12-12-SM	5/8	-12	16.0	1 1/16x12	3/4	56	34	32
10626-16-16-SM	7/8	-16	22.0	1 5/16x12	1	62	35	41
10626-20-20-SM	1 1/8	-20	29.0	1 5/8x12	1 1/4	66	39	50
10626-24-24-SM	1 3/8	-24	35.0	1 7/8x12	1 1/2	71	44	60
10626-32-32	1 13/16	-32	46.0	2 1/2x12	2	84	52	*2 7/8*


Approved **fitting series** for **hose types**: **BA**: Nipple: Brass, Nut and Shell: Steel; **BS**: Nipple and Nut: Brass, Shell: Steel; **SM**: Metric Hexagon

26 201 | 206 | 213 | 221FR | 285 | 293

08 Female SAE 45° – Swivel Straight

SAE J516







Part Number	Hose I.D.			Thread	Tube	A	B	W
	Inch	Size	mm	UNF	mm	mm	mm	*Inch*
10826-6-6BA	5/16	-6	8.0	5/8x18	3/8	47	25	*3/4*
10826-6-6	5/16	-6	8.0	5/8x18	3/8	47	25	*3/4*
10826-12-12	5/8	-12	16.0	1 1/16x14	3/4	56	32	*1 1/4*

37/3V Female JIC 37° SAE 45° – Dual Flare Swivel Female 45° Elbow

ISO 12151-5-SWE 45° – DKJ 45°





Part Number	Hose I.D.			Thread	Tube	A	B	E	W	
	Inch	Size	mm	UNF	mm	mm	mm	mm	mm	*Inch*
13V26-4-4-SM	3/16	-4	5.0	7/16x20	1/4	50	24	10	14	
13726-6-6-SM	5/16	-6	8.0	9/16x18	3/8	54	33	11	19	
13V26-8-8-SM	13/32	-8	10.0	3/4x16	1/2	59	38	15	22	
13V26-10-10	1/2	-10	12.5	7/8x14	5/8	69	44	17	*1*	
13726-12-12-SM	5/8	-12	16.0	1 1/16x12	3/4	75	53	20	32	
13726-16-16-SM	7/8	-16	22.0	1 5/16x12	1	102	76	24	41	


Approved **fitting series** for **hose types**:


BA: Nipple: Brass, Nut and Shell: Steel; **SM**: Metric Hexagon

26 | 201 | 206 | 213 | 221FR | 285 | 293

39/3W Female JIC 37° SAE 45° – Dual Flare Swivel Female 90° Elbow

ISO 12151-5-SWES – DKJ 90°





Part Number	Hose I.D.			Thread	Tube	A	B	E	W
	Inch	Size	mm	UNF	mm	mm	mm	mm	mm
13W26-4-4-SM	3/16	-4	5.0	7/16x20	1/4	45	20	21	14
13W26-5-5-SM	1/4	-5	6.3	1/2x20	5/16	50	30	20	17
13926-6-6-SM	5/16	-6	8.0	9/16x18	3/8	49	29	22	19
13W26-8-6-SM	5/16	-6	8.0	3/4x16	3/8	53	32	29	22
13W26-8-8-SM	13/32	-8	10.0	3/4x16	1/2	53	32	29	22
13W26-8-10-SM	1/2	-10	12.5	3/4x16	5/8	56	34	29	22
13W26-10-10-SM	1/2	-10	12.5	7/8x14	5/8	62	39	33	27
13W26-10-12-SM	5/8	-12	16.0	7/8x14	5/8	63	41	33	27
13926-12-12-SM	5/8	-12	16.0	1 1/16x12	3/4	73	51	46	32
13926-16-16-SM	7/8	-16	22.0	1 5/16x12	1	102	75	59	41
13926-20-20-SM	1 1/8	-20	29.0	1 5/8x12	1 1/4	109	81	70	50

Approved **fitting series** for **hose types**:


SM: Metric Hexagon


26 | 201 | 206 | 213 | 221FR | 285 | 293

JC

Female ORFS Swivel – Straight Short

ISO 12151-1 – SWSA
SAE J516 – ORFS






Part Number	Hose I.D.			Thread	A	B	C	H	W
	Inch	Size	mm	UNF	mm	mm	mm	mm	mm
1JC26-4-4-SM	3/16	-4	5.0	9/16x18	35	14	8	–	17
1JC26-6-6-SM	5/16	-6	8.0	11/16x16	36	15	9	–	22
1JC26-8-6-SM	5/16	-6	8.0	13/16x16	44	23	11	19	24
1JC26-8-8-SM	13/32	-8	10.0	13/16x16	37	17	11	–	24
1JC26-10-10-SM	1/2	-10	12.5	1x14	49	27	12	24	30
1JC26-12-12-SM	5/8	-12	16.0	1 3/16x12	43	21	14	–	36
1JC26-16-16-SM	7/8	-16	22.0	1 7/16x12	61	34	14	36	41
1JC26-20-20-SM	1 1/8	-20	29.0	1 11/16x12	62	35	15	50	50


Approved **fitting series** for **hose types**:

SM: Metric Hexagon

26 201 | 206 | 213 | 221FR | 285 | 293


5S Female Tube O-ring Swivel Short Pilot






Part Number	Hose I.D.			Thread	A	B	D	W
	Inch	Size	mm	UNF	mm	mm	mm	*Inch*
15S26-6-6	5/16	-6	8.0	5/8x18	66	44	4.7	*3/4*
15S26-8-8	13/32	-8	10.0	3/4x16	67	45	4.7	*7/8*
15S26-10-10	1/2	-10	12.5	7/8x14	71	47	4.7	*1 1/16*
15S26-10-12	5/8	-12	16.0	7/8x14	71	47	4.7	*1 1/16*

5T Female Tube O-Ring Swivel 90° Elbow – Short Pilot





Part Number	Hose I.D.			Thread	A	B	D	E	W
	Inch	Size	mm	UNF	mm	mm	mm	mm	*Inch*
15T26-6-6	5/16	-6	8.0	5/8x18	56	34	4.7	36	*3/4*
15T26-8-8	13/32	-8	10.0	3/4x16	63	41	4.7	37	*7/8*
15T26-10-10	1/2	-10	12.5	7/8x14	73	49	4.7	44	*1 1/16*

Approved **fitting series** for **hose types**:

26 | 201 | 206 | 213 | 221FR | 285 | 293





aerospace
climate control
electromechanical
filtration
fluid & gas handling
hydraulics
pneumatics
process control
sealing & shielding





Hydraulic Hoses, Fittings and Equipment

Medium Pressure



Parker

ENGINEERING YOUR SUCCESS.

Medium Pressure Hoses and Fittings

The perfect range for the more demanding market requirements



This medium pressure hose range contains the Elite No-Skive compact hydraulic hoses exceeding ISO and EN specifications and the classic No-Skive hydraulic hoses according to ISO, EN and SAE specifications. This hose range is complemented by a full selection of compatible No-Skive fittings in steel and stainless steel.

- *Extended range* of working temperatures: -50 °C up to +150 °C
- Selected hoses feature *nitrile inner tubes* suitable for mineral and bio-degradable oils
- Full range of *fluid compatibility*; oil, water, phosphate ester etc.



- Using *high quality compounds* allows thin covers – less weight – long service life still assured
- *High flexibility* for easier installation and increased service life
- *Small bend radii* and *light weight* for applications where space and weight are determining factors
- High *abrasion resistance* hose covers superior to ISO 6945 requirements, extending service life
- High *ozone-resistant* cover compounds extending weathering and ageing resistance
- *Parkrimp* machines, portable or bench mount for easy assembly operation – hose assemblies meet CE directives
- Complete *No-Skive fitting technology* across the full range of medium pressure hoses providing simpler, quicker and safer hose assembly

Applications


The definitve hose range for all medium-pressure applications



Parkrimp® *No-Skive*

The system for fast and leak-free assemblies

The perfect match



The complete system from one source. No-Skive hose, No-Skive fitting and crimping machine with world-wide guarantee and availability.


Parker's colour-coded die sets



No loose parts to mismatch or misplace – die set segments linked together.

Die sets provide 360° evenly applied crimping forces for an ideal crimp result.

Parkalign®



Parker's exclusive Parkalign® positions the fitting in the dies perfectly every time.



KarryKrimp® 1

KarryKrimp® 2

Parkrimp®

KarryKrimp® 2 Bench Mount



Parkrimp® *No-Skive*

- No skiving tool needed
- No need to remove the cover
- Crimps one-piece fittings
- Parkalign positions the fittings in the dies perfectly every time
- Quick and easy: no gauges to set on the machine
- Portable machines for field repair
- Meets EN safety regulations

Elite No-Skive Hoses

for reliability, performance, sustainability and prevention

Designers of hydraulic machinery are increasingly defining new products that require hydraulic circuits with tighter curves, higher pressures and less space in which to route flexible connections and achieve a solution.
The option to use flexible connections that are tested over and above the generally accepted norms and specifications and, that offer reliability and performance to the highest market standards, give peace of mind and the possibility to enhance the reputation and dependability of products developed by engineering and design departments. To meet hydraulic application demands for reliability and performance, engineers typically look at medium pressure braided hose ranges with a compact design and no-skive fittings. They often tend towards well known and established names on the market, where real-world long life and dependability have been proven.

Reliability

One of the most important factors engineers look for is reliability. In the case of a hydraulic hose line that primarily means the integrity of its connection. Hoses that use the Parker®
No-Skive technology, such as the Elite range from Parker, are the preferred choice for all medium pressure mobile and industrial applications.



Leakfree No-Skive hose assembly

Performance

Particularly challenging are applications in earth-moving and construction machinery that require higher performance from the hoses they use in terms of flexibility, a tight bending radius and resistance to very low temperatures. The Elite low temperature hose 461LT can be used in applications with an ambient temperature of down to -50 °C.



Low temperature hose 461LT



Sustainability

Sustainability is a strategy that underlines many initiatives, integrating life cycles assessment into the product development process for leading, responsible manufacturers. Transparency in the use of chemicals, processes and materials and utilising technical know-how and engineering skills are key to meet this increasingly important and globally relevant requirements. Therefore the development of the new 462CLF with pure chlorine-free tube and cover compound is our contribution for ensuring the sustainability of our planet.
This hose type is environmental friendly from production to disposal.



Chlorine-free hose 462CℓF

Elite No-Skive Hoses

with outstanding technical properties



Chrome6-free fittings

The wire braided Elite No-Skive hose range with outstanding technical properties such as superior flexibility, tighter bend radii and tough or super tough hose cover exceeds the EN specifications and meets the OEM and MRO requirements of today and tomorrow!
The range also includes a new chlorine-free hose type with a smooth pure nitrile inner tube – a hose which is environmentally friendly from production to disposal and that with an excellent chemical resistance.


Prevention

High performance most often goes hand-in-hand with long life and reliability which translates into reduced machine downtime caused by hose assembly failure. However, through a preventive maintenance program, unexpected, unscheduled and costly downtime can be largely avoided. A Preventive Maintenance Program may comprise regular checks of the hydraulic circuit and of all the flexible parts that compose it.
Identification systems such as the Parker Tracking System (PTS) are designed to help customers reduce vehicle or asset downtime through increases in speed, timing and accuracy of necessary repairs.



Exceeds European specifications

– higher abrasion resistance
– higher pressure ratings




long service life achieved through implementing

– nitrile inner tubes for better fluid compatibility
– tested and approved hose and fitting combinations




innovative product line with excellent technical characteristics

– high flexibility
– tight bending radii
– compact thin cover hoses
– No-Skive technology



temperature range

– up to +125 °C
– down to -50 °C for low temperature (LT) hoses



extreme abrasion resistance

> 1 Mio cycles with ST cover according to ISO 6945 (which represents 450 times the standard cover)


GLOBALCORE™

The world's first high-performance, cohesive hose and fitting system

387 / 387TC / 387ST *No-Skive* GlobalCore

Delivering value and performance for high-pressure systems

Primary Applications




Parker's GlobalCore 387 hose provides 21 MPa (3,000 psi) constant working pressure in all sizes. Available in a variety of cover options so you can match the right cover to your application, 387 hose offers you the choice of Standard, ToughCover and SuperTough. Designed, built and tested to the ISO 18752 performance specification, Parker's 387 hose is unmatched in today's marketplace.

487 / 487TC / 487ST *No-Skive* GlobalCore

Highly flexible across all sizes

Primary Applications



Parker's GlobalCore 487 hose provides 28 MPa (4,000 psi) constant working pressure in all sizes. Designed for high performance, 487 is available in a variety of cover options, including Standard, ToughCover and SuperTough. Its synthetic rubber inner tube provides a wider range of fluid compatibility. Rated to the ISO 18752 performance specification, 487 will excel in multiple applications around the world.

www.parker.com/globalcore

GlobalCore significantly reduces system complexity



- ½ ISO 18752 minimum bend radius
- Low force to flex for ease of installation
- 21 MPa (3,000 psi) constant working pressure in all sizes
- Exceeds ISO 18752 performance specification (AC, BC and CC)
- Synthetic rubber inner tube provides a wider range of fluid compatibility
- TC cover provides 80 times the abrasion resistance compared to Standard rubber cover hose
- ST cover provides 450 times the abrasion resistance compared to Standard rubber cover hose






- ½ ISO 18752 minimum bend radius
- Low force to flex for ease of installation
- 28 MPa (4,000 psi) constant working pressure in all sizes
- Exceeds ISO 18752 performance specification (AC, BC & CC)
- TC cover provides 80 times the abrasion resistance compared to Standard rubber cover hose
- ST cover provides 450 times the abrasion resistance compared to Standard rubber cover hose



Universal Push-to-Connect (UPTC)

The unique push-in system for tubes and hoses





As a standard solution it's a stroke of genius

Parker's UPTC is the standardised push-in system for Parker 24° DIN fitting bodies.


In use with tube and hose
Because of its flexibility, UPTC is a unique push-in system for tube and hose terminations.







Assembly
- Simply introduce the hose or tube into the works-assembled fitting and push in.




Assembled connector

Simple
- Visual assembly inspection
- Marker inside the nut = unambiguous assembly results

Safe
- Security ring locks in place
- Termination is held in the connector


Leak-proof
- Elastomeric seal
- 100 % leak-proof





Disassembly
- Removable and fit for reassembly just like conventional screw fittings – possible even in very dirty conditions

- Repair-friendly
- No special tools required

Examples







For more information about UPTC please refer to pages *Cc-49* and *Cc-50*

Medium Pressure GLOBALCORE™

Hoses		Page
387	GlobalCore	Caa-1
387TC	GlobalCore	Caa-2
387ST	GlobalCore	Caa-3
487	GlobalCore	Caa-4
487TC	GlobalCore	Caa-5
487ST	GlobalCore	Caa-6

Fittings Series	43	46/48
Chapter	Cb	Cc
DIN – Metric	1 – 4	1 – 11
BSP	5 – 8	12 – 20
SAE	9 – 11	21 – 28
Flange	12 – 14	29 – 33
ORFS	15 – 17	34 – 39
JIS		40 – 41
French Standard		42 – 44
Others		47 – 48
UPTC		49 – 50

Parker Hannifin assumes no liability for typographical errors or other errors

GlobalCore

387

Caa-1



No-Skive **GlobalCore**
Sizes -4 to -16 exceed ISO 18752-AC
Sizes -20 and -32 exceed ISO 18752-BC

387TC

Caa-2



No-Skive **GlobalCore Tough Cover**
Sizes -4 to -16 exceed ISO 18752-AC
Sizes -20 and -32 exceed ISO 18752-CC

387ST

Caa-3



No-Skive **GlobalCore Super Tough**
Sizes -4 to -16 exceed ISO 18752-AC
Sizes -20 and -32 exceed ISO 18752-CC

487

Caa-4



No-Skive **GlobalCore**
Sizes -4 to -12 exceed ISO 18752-AC
Sizes -16 and -32 exceed ISO 18752-BC

487TC

Caa-5



No-Skive **GlobalCore Tough Cover**
Sizes -4 to -12 exceed ISO 18752-AC
Sizes -16 and -32 exceed ISO 18752-CC

487ST

Caa-6



No-Skive **GlobalCore Super Tough**
Sizes -4 to -12 exceed ISO 18752-AC
Sizes -16 and -32 exceed ISO 18752-CC

387

No-Skive GlobalCore

Sizes -4 to -16 exceed ISO 18752-AC
Sizes -20 and -32 exceed ISO 18752-BC



- GlobalCore - *No-Skive*
- ½ ISO 18752 minimum bend radius
- Low force to flex for ease of installation
- 21 MPa constant working pressure

Primary Applications

General medium pressure hydraulic applications

Applicable Specifications

Exceed ISO 18752-AC and ISO 18752-BC

Construction

Tube: Synthetic rubber
Reinforcement: One- or two-braid steel wire (four-spiral for sizes -20 up to -32)
Cover: Synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

Series 43/48 for sizes -4 to -20
Series 77 for sizes -24 to -32



Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
387-4	6	1/4	-4	6.4	13.4	21.0	3000	84.0	12000	50	0.24
387-6	10	3/8	-6	9.5	17.4	21.0	3000	84.0	12000	65	0.34
387-8	12	1/2	-8	12.7	20.7	21.0	3000	84.0	12000	90	0.43
387-10	16	5/8	-10	15.9	23.9	21.0	3000	84.0	12000	100	0.49
387-12	19	3/4	-12	19.1	27.8	21.0	3000	84.0	12000	120	0.86
387-16	25	1	-16	25.4	35.4	21.0	3000	84.0	12000	150	1.17
387-20	31	1 1/4	-20	31.8	46.3	21.0	3000	84.0	12000	210	2.59
387-24	38	1 1/2	-24	38.1	52.8	21.0	3000	84.0	12000	250	2.99
387-32	51	2	-32	50.8	66.2	21.0	3000	84.0	12000	320	4.09

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



387TC

No-Skive GlobalCore Tough Cover

Sizes -4 to -16 exceed ISO 18752-AC
Sizes -20 and -32 exceed ISO 18752-CC



- GlobalCore - *No-Skive*
- ½ ISO 18752 minimum bend radius
- Low force to flex for ease of installation
- 21 MPa constant working pressure
- Highly abrasion resistant TOUGH COVER
- MSHA approved
- Hose is suitable for temporary immersion in mineral oil up to 70 °C with frequent inspections

Primary Applications

General medium pressure hydraulic applications

Applicable Specifications

Exceed ISO 18752-AC and ISO 18752-CC

Construction

Tube:	Synthetic rubber
Reinforcement:	One- or two-braid steel wire (four-spiral for sizes -20 up to -32)
Cover:	High abrasion resistance MSHA approved synthetic rubber

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Temperature Range ..... -40 °C up to +125 °C

Exception:	Air	..... max. +70 °C
	Water	..... max. +85 °C

Fitting Series

Series 43/48 for sizes -4 to -20
Series 77 for sizes -24 to -32



Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
387TC-4	6	1/4	-4	6.4	13.4	21.0	3000	84.0	12000	50	0.24
387TC-6	10	3/8	-6	9.5	17.4	21.0	3000	84.0	12000	65	0.34
387TC-8	12	1/2	-8	12.7	20.7	21.0	3000	84.0	12000	90	0.43
387TC-10	16	5/8	-10	15.9	23.9	21.0	3000	84.0	12000	100	0.49
387TC-12	19	3/4	-12	19.1	27.8	21.0	3000	84.0	12000	120	0.86
387TC-16	25	1	-16	25.4	35.4	21.0	3000	84.0	12000	150	1.17
387TC-20	31	1 1/4	-20	31.8	46.3	21.0	3000	84.0	12000	210	2.59
387TC-24	38	1 1/2	-24	38.1	52.8	21.0	3000	84.0	12000	250	2.99
387TC-32	51	2	-32	50.8	66.2	21.0	3000	84.0	12000	320	4.09

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



387ST

No-Skive GlobalCore Super Tough

Sizes -4 to -16 exceed ISO 18752-AC
Sizes -20 and -32 exceed ISO 18752-CC



- GlobalCore - *No-Skive*
- ½ ISO 18752 minimum bend radius
- Low force to flex for ease of installation
- 21 MPa constant working pressure
- Extreme abrasion resistant SUPER TOUGH cover

Primary Applications

Medium pressure hydraulic applications with extremely high abrasion risks

Applicable Specifications

Exceed ISO 18752-AC and ISO 18752-CC

Construction

Tube: Synthetic rubber
Reinforcement: One- or two-braid steel wire (four-spiral for sizes -20 up to -32)
Cover: Synthetic rubber with a special polyethylene coating

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Temperature Range ..... -40 °C up to +125 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Fitting Series

Series 43/48 for sizes -4 to -20
Series 77 for sizes -24 to -32



Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
387ST-4	6	1/4	-4	6.4	13.4	21.0	3000	84.0	12000	50	0.24
387ST-6	10	3/8	-6	9.5	17.4	21.0	3000	84.0	12000	65	0.34
387ST-8	12	1/2	-8	12.7	20.7	21.0	3000	84.0	12000	90	0.43
387ST-10	16	5/8	-10	15.9	23.9	21.0	3000	84.0	12000	100	0.49
387ST-12	19	3/4	-12	19.1	27.8	21.0	3000	84.0	12000	120	0.86
387ST-16	25	1	-16	25.4	35.4	21.0	3000	84.0	12000	150	1.17
387ST-20	31	1 1/4	-20	31.8	46.3	21.0	3000	84.0	12000	210	2.59
387ST-24	38	1 1/2	-24	38.1	52.8	21.0	3000	84.0	12000	250	2.99
387ST-32	51	2	-32	50.8	66.2	21.0	3000	84.0	12000	320	4.09

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



487

No-Skive GlobalCore

Sizes -4 to -12 exceed ISO 18752-AC
Sizes -16 and -32 exceed ISO 18752-BC



- GlobalCore - *No-Skive*
- ½ ISO 18752 minimum bend radius
- Low force to flex for ease of installation
- 28 MPa constant working pressure

Primary Applications

General medium pressure hydraulic applications

Applicable Specifications

Exceed ISO 18752-AC and ISO 18752-BC

Construction

Tube:	Synthetic rubber
Reinforcement:	One- or two-braid steel wire for sizes -4 up to -12 (four spiral for sizes -16 up to -32)
Cover:	Synthetic rubber

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Temperature Range ..... -40 °C up to +100 °C

Exception:	Air	max. +70 °C
	Water	max. +85 °C

Fitting Series


Series 43/48 for sizes -4 to -12
Series 43 for size -16
Series 77 for sizes -20 to -32



Part Number	Hose I.D. DN	Hose I.D. Inch	Hose I.D. Size	Hose I.D. mm	Hose O.D. mm	Pressure Rating max. working pressure MPa	Pressure Rating max. working pressure psi	Pressure Rating min. burst pressure MPa	Pressure Rating min. burst pressure psi	min. bend radius mm	weight kg
487-4	6	1/4	-4	6.4	13.1	28.0	4000	112.0	16000	50	0.30
487-6	10	3/8	-6	9.5	17.2	28.0	4000	112.0	16000	65	0.42
487-8	12	1/2	-8	12.7	20.4	28.0	4000	112.0	16000	90	0.52
487-10	16	5/8	-10	15.9	23.9	28.0	4000	112.0	16000	100	0.66
487-12	19	3/4	-12	19.1	27.8	28.0	4000	112.0	16000	120	0.86
487-16*	25	1	-16	25.4	37.8	28.0	4000	112.0	16000	150	1.99
487-20	31	1 1/4	-20	31.8	46.3	28.0	4000	112.0	16000	210	2.59
487-24	38	1 1/2	-24	38.1	52.8	28.0	4000	112.0	16000	250	3.08
487-32	51	2	-32	50.8	64.8	28.0	4000	112.0	16000	320	4.09

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



487TC

No-Skive GlobalCore Tough Cover

Sizes -4 to -12 exceed ISO 18752-AC
Sizes -16 and -32 exceed ISO 18752-CC



- GlobalCore - *No-Skive*
- ½ ISO 18752 minimum bend radius
- Low force to flex for ease of installation
- 28 MPa constant working pressure
- Highly abrasion resistant **TOUGH** COVER
- MSHA approved
- Hose is suitable for temporary immersion in mineral oil up to 70 °C with frequent inspections

Primary Applications

General medium pressure hydraulic applications

Applicable Specifications

Exceed ISO 18752-AC and ISO 18752-BC

Construction

Tube: Synthetic rubber
Reinforcement: One- or two-braid steel wire
for sizes -4 up to -12
(four spiral for sizes -16 up to -32)
Cover: High abrasion resistance
MSHA approved synthetic rubber

Temperature Range ..... -40 °C up to +125 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series


Series 43/48 for sizes -4 to -12
Series 43 for size -16
Series 77 for sizes -20 to -32



Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
487TC-4	6	1/4	-4	6.4	13.1	28.0	4000	112.0	16000	50	0.30
487TC-6	10	3/8	-6	9.5	17.2	28.0	4000	112.0	16000	65	0.42
487TC-8	12	1/2	-8	12.7	20.4	28.0	4000	112.0	16000	90	0.52
487TC-10	16	5/8	-10	15.9	23.9	28.0	4000	112.0	16000	100	0.66
487TC-12	19	3/4	-12	19.1	27.8	28.0	4000	112.0	16000	120	0.86
487TC-16*	25	1	-16	25.4	37.8	28.0	4000	112.0	16000	150	1.99
487TC-20	31	1 1/4	-20	31.8	46.3	28.0	4000	112.0	16000	210	2.59
487TC-24	38	1 1/2	-24	38.1	52.8	28.0	4000	112.0	16000	250	3.08
487TC-32	51	2	-32	50.8	64.8	28.0	4000	112.0	16000	320	4.09

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



487ST

No-Skive GlobalCore Super Tough

Sizes -4 to -12 exceed ISO 18752-AC
Sizes -16 and -32 exceed ISO 18752-CC



- GlobalCore - *No-Skive*
- ½ ISO 18752 minimum bend radius
- Low force to flex for ease of installation
- 28 MPa constant working pressure
- Extreme abrasion resistant SUPER TOUGH cover

Primary Applications

Medium pressure hydraulic applications with extremely high abrasion risks

Applicable Specifications

Exceed ISO 18752-AC and ISO 18752-BC

Construction

Tube:	Synthetic rubber
Reinforcement:	One- or two-braid steel wire for sizes -4 up to -12 (four spiral for sizes -16 up to -32)
Cover:	Synthetic rubber with a special polyethylene

Temperature Range ..... -40 °C up to +125 °C

Exception:	Air	max. +70 °C
	Water	max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series


Series 43/48 for sizes -4 to -12
Series 43 for size -16
Series 77 for sizes -20 to -32



Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
487ST-4	6	1/4	-4	6.4	13.1	28.0	4000	112.0	16000	50	0.30
487ST-6	10	3/8	-6	9.5	17.2	28.0	4000	112.0	16000	65	0.42
487ST-8	12	1/2	-8	12.7	20.4	28.0	4000	112.0	16000	90	0.52
487ST-10	16	5/8	-10	15.9	23.9	28.0	4000	112.0	16000	100	0.66
487ST-12	19	3/4	-12	19.1	27.8	28.0	4000	112.0	16000	120	0.86
487ST-16	25	1	-16	25.4	37.8	28.0	4000	112.0	16000	150	1.99
487ST-20	31	1 1/4	-20	31.8	46.3	28.0	4000	112.0	16000	210	2.59
487ST-24	38	1 1/2	-24	38.1	52.8	28.0	4000	112.0	16000	250	3.08
487ST-32	51	2	-32	50.8	64.8	28.0	4000	112.0	16000	320	4.09

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



Medium Pressure

Hoses		Page
301SN No-Skive	Standard	Cab-1
301TC No-Skive	High abrasion resistance	Cab-2
304 No-Skive	Phosphate Ester	Cab-3
412 Elite No-Skive	Pilot	Cab-4
412ST Elite No-Skive	Pilot	Cab-5
421RH No-Skive	Railway	Cab-6
421SN No-Skive	Standard	Cab-7
421WC No-Skive	Wire cover	Cab-8
426 No-Skive	Low / High temperature	Cab-9
436 No-Skive	Low / High temperature	Cab-10
441 Elite No-Skive	Standard	Cab-11
441RH No-Skive	Railway	Cab-12
461LT Elite No-Skive	Low / High temperature	Cab-13
462 Elite No-Skive	Standard	Cab-14
462ClF Elite No-Skive	Chlorine Free	Cab-15
462TC Elite No-Skive	High abrasion resistance	Cab-16
462ST Elite No-Skive	Extreme abrasion resistance	Cab-17
463 No-Skive	Water cleaning	Cab-18
471TC	High abrasion resistance	Cab-19
477 Elite No-Skive	Powerlift	Cab-20
477TC Elite No-Skive	Powerlift	Cab-21
477ST Elite No-Skive	Powerlift	Cab-22
492 Elite No-Skive	Standard	Cab-23
492TC Elite No-Skive	High abrasion resistance	Cab-24
492ST Elite No-Skive	Extreme abrasion resistance	Cab-25
493 No-Skive	Water cleaning	Cab-26
692 No-Skive	Extremely flexible	Cab-27
692Twin No-Skive	Extremely flexible	Cab-28
811 No-Skive	Suction	Cab-29
811S No-Skive	Suction	Cab-30
881 No-Skive	Suction	Cab-31

Fittings Series	43	46/48	2piece 48	2piece IF
Chapter	Cb	Cc	Cd	Ce
DIN – Metric	1 – 4	1 – 11		
BSP	5 – 8	12 – 20		
SAE	9 – 11	21 – 28	1	
Flange	12 – 14	29 – 33	2	1 – 3
ORFS	15 – 17	34 – 39		
JIS		40 – 41		
French Standard		42 – 44		
High Pressure Cleaning		45 – 46		
Others		47 – 48		
UPTC		49 – 50		

Parker Hannifin assumes no liability for typographical errors or other errors

Standard

301SN
Cab-1

No-Skive
EN 853 2SN – ISO 1436 Type 2

421SN
Cab-7

No-Skive
EN 853 1SN – ISO 1436 Type 1

441
Cab-11

Elite No-Skive
ISO 11237 Type R16 – SAE 100R16

462
Cab-14

Elite No-Skive **Compact**
Exceeds EN 857-2SC – ISO 11237 Type 2SC

492
Cab-23

Elite No-Skive **Compact**
EN 857 1SC – ISO 11237 Type 1SC

Chlorine Free

462ClF
Cab-15

Elite No-Skive **Chlorine Free**
Exceeds EN 857-2SC – ISO 11237 Type 2SC

High abrasion resistance

301TC
Cab-2

No-Skive **Tough Cover**
EN 853 2SN – ISO 1436 Type 2

462TC
Cab-16

Elite No-Skive **Compact Tough Cover**
Exceeds EN 857-2SC – ISO 11237 Type 2SC

471TC / 472TC
Cab-19

No-Skive
EN 857 2SC – ISO 11237 Type 2SC

492TC
Cab-24

Elite No-Skive **Compact Tough Cover**
EN 857 1SC – ISO 11237 Type 1SC

Extreme abrasion resistance

462ST
Cab-17



Elite No-Skive **Super Tough Compact**
EN 857 2SC – ISO 11237 Type 2SC

492ST
Cab-25



Elite No-Skive **Super Tough Compact**
EN 857 1SC – ISO 11237 Type 1SC

Low / High temperature

426
Cab-9



No-Skive
SAE 100R1AT high temperature

436
Cab-10



No-Skive **Compact**
SAE 100R16 high temperature

461LT
Cab-19



Elite No-Skive **Compact**
EN 857 2SC low temperature

Phosphate Ester

304
Cab-3



No-Skive
Phosphate ester resistant hose

Railway

421RH
Cab-6



No-Skive
Fire-retardant cover

441RH
Cab-12



No-Skive **Compact**
Fire-retardant cover

Water cleaning

463
Cab-18



No-Skive **Compact**
High pressure water cleaning applications

493
Cab-26



No-Skive **Compact**
High pressure water cleaning applications

Pilot

412
Cab-4



Elite No-Skive **RemoFlex**
1 wire braided hose for pilot lines


412ST
Cab-5



Elite No-Skive **RemoFlex**
1 wire braided hose for pilot lines

Wire cover

421WC
Cab-8



No-Skive
Galvanised steel wire cover

Powerlift

477
Cab-20



Elite No-Skive **PowerLift**
2 wire braided

477TC
Cab-21



Elite No-Skive **PowerLift**
Tough Cover
2 wire braided

477ST
Cab-22



Elite No-Skive **PowerLift**
2 wire braided

Extremely flexible

692
Cab-27



No-Skive **Compact**
Constant pressure, tight bend radius

692Twin
Cab-28



No-Skive **Compact**
Twin constant pressure, tight bend radius

Suction

811
Cab-29



No-Skive **Suction and Return Line**
SAE 100R4

811S
Cab-30



No-Skive **Suction and Return Line**
Exceeds SAE 100R4

881
Cab-31



No-Skive **Suction and Return Line**
SAE 100R4

301SN

No-Skive

EN 853 2SN – ISO 1436 Type 2



- *No-Skive* thin cover hose construction
- Nitrile (NBR) inner tube
  – extended fluid compatibility

Primary Applications

General medium pressure hydraulic applications

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

EN 853 2SN – ISO 1436 Type 2 – SAE 100R2AT

Construction

Tube: Nitrile (NBR)
Reinforcement: Two high-tensile steel wire braids
Cover: Synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

48

Part Number	Hose I.D.				Hose O.D.	Pressure Rating				min. bend radius	weight
						max. working pressure		min. burst pressure			
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
301SN-4	6	1/4	-4	6.4	15.0	40.0	5800	160.0	23200	100	0.39
301SN-5	8	5/16	-5	7.9	16.6	35.0	5075	140.0	20300	115	0.42
301SN-6	10	3/8	-6	9.5	19.0	33.0	4775	132.0	19100	130	0.55
301SN-8	12	1/2	-8	12.7	22.2	27.5	4000	110.0	16000	180	0.67
301SN-10	16	5/8	-10	15.9	25.4	25.0	3600	100.0	14500	200	0.77
301SN-12	19	3/4	-12	19.1	29.3	21.5	3100	86.0	12400	240	1.00
301SN-16	25	1	-16	25.4	38.1	16.5	2400	66.0	9600	300	1.49
301SN-20	31	1 1/4	-20	31.8	47.5	12.5	1800	50.0	7200	420	1.73
301SN-24	38	1 1/2	-24	38.1	55.0	9.0	1300	36.0	5200	500	2.14
301SN-32	51	2	-32	50.8	67.0	8.0	1150	32.0	4600	630	2.96

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example

PARKER NO-SKIVE 301SN-4 WP 40,0 MPa (400 BAR) I · · SAE100R2AT-4 6,3MM (1/4") X 2W EN853/2SN/6/DIN

301TC

No-Skive Tough Cover

EN 853 2SN – ISO 1436 Type 2



- *No-Skive* thin cover hose construction
- Nitrile (NBR) inner tube – extended fluid compatibility
- Highly abrasion resistant TOUGH COVER
- MSHA approved
- Hose is suitable for temporary immersion in mineral oil up to 70 °C with frequent inspections

Primary Applications

General medium pressure hydraulic applications where high abrasion is required

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

EN 853 2SN – ISO 1436 Type 2 – SAE 100R2AT

Construction

Tube:	Nitrile (NBR)
Reinforcement:	Two high-tensile steel wire braids
Cover:	MSHA approved synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception:	Air	max. +70 °C
	Water	max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series



Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
301TC-4	6	1/4	-4	6.4	15.0	40.0	5800	160.0	23200	100	0.39
301TC-5	8	5/16	-5	7.9	16.6	35.0	5075	140.0	20300	115	0.42
301TC-6	10	3/8	-6	9.5	19.0	33.0	4775	132.0	19100	130	0.55
301TC-8	12	1/2	-8	12.7	22.2	27.5	4000	110.0	16000	180	0.67
301TC-10	16	5/8	-10	15.9	25.4	25.0	3600	100.0	14500	200	0.77
301TC-12	19	3/4	-12	19.1	29.3	21.5	3100	86.0	12400	240	1.00
301TC-16	25	1	-16	25.4	38.1	16.5	2400	66.0	9600	300	1.49
301TC-20	31	1 1/4	-20	31.8	47.5	12.5	1800	50.0	7200	420	1.73
301TC-24	38	1 1/2	-24	38.1	55.0	9.0	1300	36.0	5200	500	2.14
301TC-32	51	2	-32	50.8	67.0	8.0	1150	32.0	4600	630	2.96

Replace the hose when any deformation or damage on the hose cover are visible.
The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



304

No-Skive

Phosphate ester resistant hose



- *No-Skive* thin cover hose construction
- Phosphate ester and weather resistant, green, EPDM synthetic rubber cover
- SAE 100R2 pressure rating

Primary Applications

Aerospace, foundries, steel mills:
Medium pressure hydraulic applications with phosphate ester fluids

Applicable Specifications

Parker specification

Restrictions

Do not allow tube to contact any petroleum base fluids.
Use liquid soap as hose lubricant.

Construction

Tube:	EPDM synthetic rubber
Reinforcement:	Two high-tensile steel wire braids
Cover:	Phosphate ester and weather resistant, green, EPDM synthetic rubber cover

Temperature Range ..... -40 °C up to +80 °C

Exception:	Air ..... max. +70 °C
	Water, water glycol fluids .. max. +85 °C

Recommended Fluids

Phosphate ester based hydraulic fluids, water-glycol based fluids, air and water.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series



Series 43 for sizes -4 to -32
Series 48 for sizes -20 to -32

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
304-4	6	1/4	-4	6.4	15.0	34.5	5000	138.0	20000	100	0.39
304-6	10	3/8	-6	9.5	19.0	27.5	4000	110.0	16000	130	0.55
304-8	12	1/2	-8	12.7	22.0	24.0	3500	96.0	14000	180	0.67
304-12	19	3/4	-12	19.1	30.0	15.5	2250	62.0	9000	240	1.00
304-16	25	1	-16	25.4	38.0	13.8	2000	55.0	8000	300	1.49
304-20	31	1 1/4	-20	31.8	48.0	11.2	1625	45.0	6500	420	1.73
304-24	38	1 1/2	-24	38.1	55.0	8.6	1250	35.0	5075	500	2.14
304-32	51	2	-32	50.8	68.0	7.8	1125	31.0	4500	630	2.96

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example

Parker NO-SKIVE 304-8 WP 24,0 MPa (3500 PSI) 12,5 mm (1/2) X 2W 3Q78

412

Elite No-Skive RemoFlex

1 wire braided hose for pilot lines



- *No-Skive* hose construction
- 12.0 MPa rubber pilot line hose (20 % higher working pressure than 402 hose)
- Very tight bending radii – allowing compact machine design

Primary Applications

Mobile hydraulic equipment: Pilot lines

Construction

Tube:	Nitrile (NBR)
Reinforcement:	One high-tensile steel wire braid
Cover:	Synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception:	Air	..... max. +70 °C
	Water	..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

- Available as complete hose assembly
- Compatible with 2-piece fittings for use with adjustable crimpers only (47 series nipple and 10049 series shell)

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
412-3	5	3/16	-3	4.8	9.1	12.0	1700	48.0	6800	20	0.08
412-4	6	1/4	-4	6.4	11.0	12.0	1700	48.0	6800	25	0.14
412-5	8	5/16	-5	7.9	13.0	12.0	1700	48.0	6800	30	0.18
412-6	10	3/8	-6	9.5	14.0	12.0	1700	48.0	6800	40	0.23

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



412ST

Elite No-Skive RemoFlex

1 wire braided hose for pilot lines



- *No-Skive* hose construction
- 12.0 MPa rubber pilot line hose
- Very tight bending radii – allowing compact machine design
- Extreme abrasion resistant SUPER TOUGH cover

Primary Applications

Mobile hydraulic equipment: Pilot lines

Construction

Tube: Nitrile (NBR)
Reinforcement: One high-tensile steel wire braid
Cover: Synthetic rubber with a special polyethylene coating

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

- Available as complete hose assembly
- Compatible with 2-piece fittings for use with adjustable crimpers only (47 series nipple and 10049 series shell)

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
412ST-3	5	3/16	-3	4.8	9.6	12.0	1700	48.0	6800	20	0.08
412ST-4	6	1/4	-4	6.4	11.6	12.0	1700	48.0	6800	25	0.14
412ST-5	8	5/16	-5	7.9	13.0	12.0	1700	48.0	6800	30	0.18
412ST-6	10	3/8	-6	9.5	14.0	12.0	1700	48.0	6800	40	0.23

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example

Parker Elite 1 SUPER TOUGH 412ST-6 RemoFlex WP 12,0 MPa (1700 PSI) | • • 9,5 mm (3/8") Made in Italy

421RH

No-Skive

Fire-retardant cover



- *No-Skive* thin cover hose construction
- Nitrile (NBR) inner tube – extended fluid compatibility
- Suitable with 48 series fittings
- Fire-retardant cover
- Railway approved as follow: European Standard EN45545 + ISO15540: HL2 (without the need of FS-F-Fire Sleeve)

Primary Applications

General medium-pressure hydraulic and pneumatic systems as well as water and oil cooling circuits

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

EN 853 1SN – ISO 1436 Typ 1 – SAE 100R1AT

Construction

Tube:	Nitrile (NBR)
Reinforcement:	One high-tensile steel wire braid
Cover:	Fire retardant synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception:	Air	max. +70 °C
	Water	max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air and gas above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series



Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
421RH-20	31	1 1/4	-20	31.8	44.8	6.3	900	25.0	3600	420	1.19
421RH-24	38	1 1/2	-24	38.1	51.1	5.0	725	20.0	2900	500	1.49
421RH-32	51	2	-32	50.8	64.7	4.0	575	16.0	2300	630	2.23

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



421SN

No-Skive

EN 853 1SN – ISO 1436 Type 1



- *No-Skive* thin cover hose construction
- Nitrile (NBR) inner tube
  – extended fluid compatibility

Primary Applications

General medium pressure hydraulic applications

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

EN 853 1SN – ISO 1436 Type 1 – SAE 100R1AT

Construction

Tube: Nitrile (NBR)
Reinforcement: One high-tensile steel wire braid
Cover: Synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

48

Part Number	Hose I.D.				Hose O.D.	Pressure Rating				min. bend radius	weight
						max. working pressure		min. burst pressure			
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
421SN-4	6	1/4	-4	6.4	13.4	22.5	3250	90.0	13000	100	0.24
421SN-5	8	5/16	-5	7.9	15.0	21.5	3125	86.0	12500	115	0.27
421SN-6	10	3/8	-6	9.5	17.4	18.0	2600	72.0	10400	130	0.34
421SN-8	12	1/2	-8	12.7	20.7	16.0	2325	64.0	9300	180	0.43
421SN-10	16	5/8	-10	15.9	23.9	13.0	1875	52.0	7500	200	0.49
421SN-12	19	3/4	-12	19.1	27.8	10.5	1525	42.0	6100	240	0.63
421SN-16	25	1	-16	25.4	35.8	8.8	1275	35.0	5075	300	0.94
421SN-20	31	1 1/4	-20	31.8	44.8	6.3	900	25.2	3600	420	1.19
421SN-24	38	1 1/2	-24	38.1	51.1	5.0	725	20.0	2900	500	1.49
421SN-32	51	2	-32	50.8	64.7	4.0	575	16.0	2300	630	2.23

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example

PARKER NO-SKIVE 421SN-8 WP 16,0 MPa (160 BAR) I * * SAE 100R1AT-8 12,5 MM (1/2) X1W EN 853/1SN/12/DIN

421WC

No-Skive

Galvanised steel wire cover



- *No-Skive* thin cover hose construction
- Metal and glass hot-spot resistance

Primary Applications

Machine tool and glass industry

Applicable Specifications

SAE 100 R1AT

Construction

Tube: Synthetic rubber
Reinforcement: One high-tensile steel wire braid
Cover: Galvanized steel wire

Temperature Range ..... -40 °C up to +125 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series



Part Number	Hose I.D.				Hose O.D.	Pressure Rating				min. bend radius	weight
						max. working pressure		min. burst pressure			
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
421WC-4	6	1/4	-4	6.4	15.0	19.0	2750	76.0	11000	100	0.38
421WC-6	10	3/8	-6	9.5	19.0	15.5	2250	62.0	9000	130	0.54
421WC-8	12	1/2	-8	12.7	22.0	13.8	2000	55.0	8000	180	0.67
421WC-12	19	3/4	-12	19.1	29.0	8.6	1250	35.0	5075	240	0.95
421WC-16	25	1	-16	25.4	37.0	6.9	1000	28.0	4000	300	1.31

The combination of high temperature and high pressure could reduce the hose life.

426

No-Skive

SAE 100R1AT high temperature



- *No-Skive* thin cover hose construction
- SAE 100R1 pressure rating
- Ideal for high temperature applications

Primary Applications

Medium pressure hydraulic applications at high temperature

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

SAE 100 R1AT

Construction

Tube: PKR synthetic rubber
Reinforcement: One high-tensile steel wire braid
Cover: Blue synthetic rubber

Temperature Range ..... -46 °C up to +150 °C

Exception: Air ..... max. +70 °C
Water, water glycol fluids .. max. +85 °C

Recommended Fluids

Petroleum hydraulic fluids, lubricating oils, water-glycol based fluids, air and water.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series



Series 43 for sizes -4 to -6
Series 48 for sizes -8 to -32

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
426-4-RL	6	1/4	-4	6.4	13.4	19.2	2750	77.0	11000	100	0.24
426-6-RL	10	3/8	-6	9.5	17.4	15.7	2250	63.0	9000	125	0.34
426-8-RL	12	1/2	-8	12.7	20.7	14.0	2000	56.0	8000	180	0.43
426-10-RL	16	5/8	-10	15.9	23.9	10.5	1500	42.0	6000	200	0.49
426-12-RL	19	3/4	-12	19.1	27.8	8.7	1250	35.0	5075	240	0.65
426-16-RL	25	1	-16	25.4	35.8	7.0	1000	28.0	4000	300	0.98
426-20	31	1 1/4	-20	31.8	45.0	4.3	625	17.2	2500	420	1.40
426-24	38	1 1/2	-24	38.1	51.0	3.5	500	14.0	2000	500	1.46
426-32	51	2	-32	50.8	64.0	2.6	375	10.4	1500	630	2.18

The combination of high temperature and high pressure could reduce the hose life.
RL = only available on reels.

Hose layline example

Parker NO-SKIVE 426-8 WP 14,0 MPa (2000 PSI) MSHA XXXX SAE 100R1AT-8 HI-TEMP 12,5 mm (1/2) 1Q03

436

No-Skive Compact

SAE 100R16 high temperature



- *No-Skive* thin cover hose construction
- Compact hose construction with tight bend radius
- MSHA approved
- Ideal for high temperature applications

Primary Applications

Medium pressure hydraulic applications at high temperature

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

SAE 100R16

Construction

Tube:	PKR synthetic rubber
Reinforcement:	Two high-tensile steel wire braids
Cover:	MSHA approved blue synthetic rubber

Temperature Range ..... -48 °C up to +150 °C

Exception:	Air ..... max. +70 °C
	Water, water glycol fluids .. max. +85 °C

Recommended Fluids

Petroleum hydraulic fluids, lubricating oils, water-glycol based fluids, air and water.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series



Part Number	Hose I.D.				Hose O.D.	Pressure Rating				min. bend radius	weight
						max. working pressure		min. burst pressure			
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
436-6-BLU-RL	10	3/8	-6	9.5	17.0	27.5	4000	110.0	16000	65	0.42
436-8-BLU-RL	12	1/2	-8	12.7	20.0	24.0	3500	96.0	14000	90	0.51
436-10-BLU-RL	16	5/8	-10	15.9	24.0	19.0	2750	76.0	11000	100	0.66
436-12-BLU-RL	19	3/4	-12	19.1	28.0	15.5	2250	62.0	9000	120	0.80
436-16-BLU-RL	25	1	-16	25.4	36.0	13.8	2000	55.0	8000	150	1.22

The combination of high temperature and high pressure could reduce the hose life.
RL = only available on reels.

Hose layline example

Parker NO-SKIVE 436-8 WP 24,5 MPa (3500 PSI) MSHA XXXX 12,5 mm (1/2) X 2W 2Q88

441

Elite No-Skive

ISO 11237 Type R16 – SAE 100R16



- *No-Skive* hose construction
- One wire braid construction – two wire braid performance
- +125 °C working temperature

Primary Applications

Many industrial and mobile applications, with typical usage seen on agricultural machines or in power steering circuits

Applicable Specifications

ISO 11237 Type R16 – SAE 100R16

Construction

Tube: Synthetic rubber
Reinforcement: One high-tensile steel wire braid
Cover: Synthetic rubber

Temperature Range ..... -40 °C up to +125 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series





Part Number	Hose I.D.				Hose O.D.	Pressure Rating				min. bend radius	weight
						max. working pressure		min. burst pressure			
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
441-4	6	1/4	-4	6.4	13.4	35.0	5000	140.0	20000	50	0.27
441-5	8	5/16	-5	7.9	15.0	29.7	4250	118.8	17000	55	0.32
441-6	10	3/8	-6	9.5	17.4	28.0	4000	112.0	16000	65	0.42
441-8	12	1/2	-8	12.7	20.7	24.5	3500	98.0	14000	90	0.50
441-10	16	5/8	-10	15.9	23.8	19.2	2750	76.8	11000	100	0.65
441-12	19	3/4	-12	19.1	27.8	15.7	2250	62.8	9000	120	0.80
441-16	25	1	-16	25.4	35.8	14.0	2000	56.0	8000	150	1.22

The combination of high temperature and high pressure could reduce the hose life.
Also available on reels up to size -12 under part number 441-xx-RL

Hose layline example



441RH

No-Skive Compact

Fire-retardant cover



- *No-Skive* hose construction
- One wire braid construction – two wire braid performance
- +125 °C working temperature
- Fire-retardant cover
- Railway approved as follow: European Standard EN45545 + ISO15540: HL2 (without the need of FS-F-Fire Sleeve)

Primary Applications

General medium-pressure hydraulic and pneumatic systems as well as water and oil cooling circuits

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

Parker specification; Working pressure to SAE 100R2; Bend radius to SAE 100R16

Construction

Tube:	Synthetic rubber
Reinforcement:	One high-tensile steel wire braid
Cover:	Fire retardant synthetic rubber

Temperature Range ..... -40 °C up to +125 °C

Exception:	Air ..... max. +70 °C
	Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air and gas above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series





Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
441RH-4	6	1/4	-4	6.4	13.4	35.0	5000	140.0	20000	50	0.27
441RH-5	8	5/16	-5	7.9	15.0	29.7	4250	118.8	17000	55	0.32
441RH-6	10	3/8	-6	9.5	17.4	28.0	4000	112.0	16000	65	0.42
441RH-8	12	1/2	-8	12.7	20.7	24.5	3500	98.0	14000	90	0.50
441RH-10	16	5/8	-10	15.9	23.8	19.2	2750	76.8	11000	100	0.65
441RH-12	19	3/4	-12	19.1	27.8	15.7	2250	62.8	9000	120	0.80
441RH-16	25	1	-16	25.4	35.8	14.0	2000	56.0	8000	150	1.22

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



461LT

Elite No-Skive Compact

EN 857 2SC low temperature



- *No-Skive* thin cover hose construction
- Excellent ozone resistance
- Ideal for low temperature working conditions (-50 °C)

Primary Applications

Mobile applications in low temperature environments:
Forestry machines, refrigerated warehouses

Applicable Specifications

EN 857 2SC

Construction

Tube: Synthetic rubber
Reinforcement: Two high-tensile steel wire braids
Cover: Synthetic rubber

Temperature Range ..... -50 °C up to +100 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series



Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
461LT-4	6	1/4	-4	6.4	13	42.5	6160	170.0	24640	75	0.30
461LT-5	8	5/16	-5	7.9	15	40.0	5800	160.0	23200	85	0.35
461LT-6	10	3/8	-6	9.5	17	35.0	5075	140.0	20300	90	0.42
461LT-8	12	1/2	-8	12.7	21	31.0	4495	124.0	17980	130	0.52
461LT-10	16	5/8	-10	15.9	24	28.0	4060	112.0	16240	160	0.66
461LT-12	19	3/4	-12	19.1	28	28.0	4060	112.0	16240	195	0.86
461LT-16	25	1	-16	25.4	35	21.0	3045	84.0	12180	250	1.17

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



462

Elite No-Skive Compact

Exceeds EN 857-2SC – ISO 11237 Type 2SC



- *No-Skive* hose construction – Compact design
- Nitrile (NBR) inner tube – extended fluid compatibility
- Exceeding EN/ISO specifications for pressure, bend radius and abrasion resistance

Primary Applications

Demanding medium pressure hydraulic applications in all markets

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

Exceeds EN 857-2SC – ISO 11237 Type 2SC

Construction

Tube: Nitrile (NBR)
Reinforcement: Two high-tensile steel wire braids
Cover: Synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

Size -4 up to -16



Size -20



Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
462-4	6	1/4	-4	6.4	13.4	42.5	6160	170.0	24640	75	0.30
462-5	8	5/16	-5	7.9	15.0	40.0	5800	160.0	23200	85	0.35
462-6	10	3/8	-6	9.5	17.2	35.0	5075	140.0	20300	90	0.42
462-8	12	1/2	-8	12.7	20.4	31.0	4495	124.0	17980	130	0.52
462-10	16	5/8	-10	15.9	23.9	28.0	4060	112.0	16240	160	0.66
462-12	19	3/4	-12	19.1	27.7	28.0	4060	112.0	16240	195	0.86
462-16	25	1	-16	25.4	35.4	21.0	3045	84.0	12180	250	1.17
462-20	31	1 1/4	-20	31.8	45.1	17.2	2495	68.8	9980	335	1.80

The combination of high temperature and high pressure could reduce the hose life.
From size -4 to -16, smooth cover, 462-20 wrapped cover
Also available in reels up to size -12 under part number 462-xx-RL

Hose layline example



462ClF

Elite No-Skive Chlorine Free

Exceeds EN 857-2SC – ISO 11237 Type 2SC



- *No-Skive* hose construction – Compact design
- Exceeding EN/ISO specifications for pressure, bend radius and abrasion resistance
- Chlorine free compounds

Primary Applications

Demanding medium pressure hydraulic applications in all markets

Applicable Specifications

Exceeds EN 857-2SC – ISO 11237 Type 2SC

Construction

Tube: Chlorine free synthetic rubber
Reinforcement: Two high-tensile steel wire braids
Cover: Chlorine free synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C


Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

Size -4 up to -16

Size -20



Part Number	Hose I.D.				Hose O.D.	Pressure Rating				min. bend radius	weight
						max. working pressure		min. burst pressure			
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
462CLF-4	6	1/4	-4	6.4	13.4	42.5	6160	170.0	24640	75	0.30
462CLF-5	8	5/16	-5	7.9	15.0	40.0	5800	160.0	23200	85	0.35
462CLF-6	10	3/8	-6	9.5	17.2	35.0	5075	140.0	20300	90	0.42
462CLF-8	12	1/2	-8	12.7	20.4	31.0	4495	124.0	17980	130	0.52
462CLF-10	16	5/8	-10	15.9	23.9	28.0	4060	112.0	16240	160	0.66
462CLF-12	19	3/4	-12	19.1	27.7	28.0	4060	112.0	16240	195	0.86
462CLF-16	25	1	-16	25.4	35.4	21.0	3045	84.0	12180	250	1.17
462CLF-20 *	31	1 1/4	-20	31.8	45.1	17.2	2495	68.8	9980	335	1.80

The combination of high temperature and high pressure could reduce the hose life.
From size -4 to -16, smooth. For size -20, wrapped.
* 462CLF-20 only with 48 series

Hose layline example



462TC

Elite No-Skive Compact Tough Cover

Exceeds EN 857-2SC – ISO 11237 Type 2SC



- *No-Skive* hose construction – Compact design
- Nitrile (NBR) inner tube – extended fluid compatibility
- Exceeding EN/ISO specifications for pressure, bend radius and abrasion resistance
- Highly abrasion resistant TOUGH COVER
- MSHA approved

Primary Applications

Demanding medium pressure hydraulic applications in all markets

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

Exceeds EN 857-2SC – ISO 11237 Type 2SC

Construction

Tube:	Nitrile (NBR)
Reinforcement:	Two high-tensile steel wire braids
Cover:	MSHA approved synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception:	Air	..... max. +70 °C
	Water	..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

Size -4 up to -16

Size -20 up to -32

Size -40 up to -48



2piece 48

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
462TC-4	6	1/4	-4	6.4	13.4	42.5	6160	170.0	24640	75	0.30
462TC-5	8	5/16	-5	7.9	15.0	40.0	5800	160.0	23200	85	0.35
462TC-6	10	3/8	-6	9.5	17.2	35.0	5075	140.0	20300	90	0.42
462TC-8	12	1/2	-8	12.7	20.4	31.0	4495	124.0	17980	130	0.52
462TC-10	16	5/8	-10	15.9	23.9	28.0	4060	112.0	16240	160	0.66
462TC-12	19	3/4	-12	19.1	27.7	28.0	4060	112.0	16240	195	0.86
462TC-16	25	1	-16	25.4	35.4	21.0	3045	84.0	12180	250	1.17
462TC-20 *	31	1 1/4	-20	31.8	45.1	17.2	2495	68.8	9980	335	1.80
462TC-24 *	38	1 1/2	-24	38.1	52.0	14.6	2118	58.4	8472	400	2.20
462TC-32 *	51	2	-32	50.8	64.0	11.2	1624	44.8	6496	500	2.90
462TC-40 **	63	2 1/2	-40	63.5	76.0	7.0	1015	28.0	4060	760	3.00
462TC-48 **	76	3	-48	76.2	87.5	7.0	1015	28.0	4060	760	3.30

The combination of high temperature and high pressure could reduce the hose life.

* Size -20 up to -32 only with fitting series 48
** Size -40 up to -48 only with 2piece fitting series 48

Hose layline example

Parker Elite TOUGH COVER 462TC-40 WP 7,0 MPa (1015 PSI) MSHA IC 40/26 | • • 63,5 mm (2 1/2) Made in Italy

462ST

Elite No-Skive Super Tough Compact

EN 857 2SC – ISO 11237 Type 2SC



- *No-Skive* hose construction – Compact design
- Nitrile (NBR) inner tube – extended fluid compatibility
- Extreme abrasion resistant SUPER TOUGH cover
- Exceeding EN/ISO specifications for pressure, bend radius and abrasion resistance

Primary Applications

Mobile market: Medium pressure hydraulic applications with extremely high abrasion risks

Applicable Specifications

EN 857 2SC – ISO 11237 Type 2SC

Construction

Tube: Nitrile (NBR)
Reinforcement: Two high-tensile steel wire braids
Cover: Synthetic rubber with a special polyethylene coating

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C


Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

Size -4 up to -16

Size -20



Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
462ST-4	6	1/4	-4	6.4	13.4	42.5	6160	170.0	24640	75	0.30
462ST-5	8	5/16	-5	7.9	15.0	40.0	5800	160.0	23200	85	0.35
462ST-6	10	3/8	-6	9.5	17.2	35.0	5075	140.0	20300	90	0.42
462ST-8	12	1/2	-8	12.7	20.4	31.0	4495	124.0	17980	125	0.52
462ST-10	16	5/8	-10	15.9	23.9	28.0	4060	112.0	16240	160	0.66
462ST-12	19	3/4	-12	19.1	27.7	28.0	4060	112.0	16240	195	0.86
462ST-16	25	1	-16	25.4	35.4	21.0	3045	84.0	12180	250	1.17
462ST-20 *	31	1 1/4	-20	31.8	45.1	17.2	2495	68.8	9980	335	1.80

The combination of high temperature and high pressure could reduce the hose life.
* 462ST-20 only with fitting series 48

Hose layline example



463

No-Skive Compact

High pressure water cleaning applications



- 2 wire *No-Skive* Compact design
- For water up to +120 °C constant temperature

Primary Applications

High pressure water cleaners

Construction

Tube: Synthetic rubber
Reinforcement: Two high-tensile steel wire braids
Cover: Synthetic rubber in black or blue colour

Temperature Range ..... water max. +120 °C

Fitting Series



Part Number	Hose I.D.				Hose O.D.	Pressure Rating				min. bend radius	weight
						max. working pressure		min. burst pressure			
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
463-5	8	5/16	-5	7.9	15.0	40.0	5800	120.0	17400	75	0.31
463-5-BLU	8	5/16	-5	7.9	15.0	40.0	5800	120.0	17400	75	0.31
463-6	10	3/8	-6	9.5	17.4	40.0	5800	120.0	17400	90	0.38
463-6-BLU	10	3/8	-6	9.5	17.4	40.0	5800	120.0	17400	90	0.38
463-8	12	1/2	-8	12.7	20.6	35.0	5075	105.0	15225	110	0.48
463-8-BLU	12	1/2	-8	12.7	20.6	35.0	5075	105.0	15225	110	0.48

WKS rubber hand grip for No-Skive high pressure water cleaning hoses can be found on page Eb-17.
The combination of high temperature and high pressure could reduce the hose life.
Also available on reels under part number 463-xx-RL

Hose layline example

PARKER NO-SKIVE 463-5 WP 40,0 MPa (5800 PSI) 1 ° ° 8 mm (5/16) max. 120°C WATER

471TC

No-Skive

EN 857 2SC – ISO 11237 Type 2SC



- *No-Skive* hose construction – Compact design
- Reduced bend radii
- Highly abrasion resistant TOUGH COVER
- MSHA approved
- Hose is suitable for temporary immersion in mineral oil up to 70 °C with frequent inspections

Primary Applications

Small bending radii demanding medium pressure hydraulic applications

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

EN 857 2SC – ISO 11237 Type 2SC

Construction

Tube: Synthetic rubber
Reinforcement: Two high-tensile steel wire braids
Cover: MSHA approved synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

48

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
471TC-4	6	1/4	-4	6.4	13	40.0	5800	160.0	23200	50	0.30
471TC-5	8	5/16	-5	7.9	15	36.0	5250	144.0	21000	55	0.35
471TC-6	10	3/8	-6	9.5	17	35.0	5075	140.0	20000	65	0.42
471TC-8	12	1/2	-8	12.7	20	29.7	4250	119.0	17000	90	0.52
471TC-10	16	5/8	-10	15.9	24	25.0	3625	100.0	14500	100	0.66
471TC-12	19	3/4	-12	19.1	28	21.5	3125	86.0	12500	120	0.86
471TC-16	25	1	-16	25.4	35	17.5	2500	70.0	10000	150	1.17

Replace the hose when any deformation or damages on the hose cover are visible.
The combination of high temperature and high pressure could reduce the hose life.


Hose layline example



477

Elite No-Skive PowerLift

2 wire braided



- *No-Skive* hose construction – Compact design
- Tested at 120 % of the maximum working pressure at 400,000 impulses
- Smaller bend radius and reduced outside diameter bringing a significant advantage in terms of space and weight on compact equipment

Primary Applications

For truck cranes and lifting equipment such as fork lift trucks, aerial lifts, cranes, telehandlers, lifting platforms.

Restrictions

Should not be used for high impulse hydraulic applications to replace spiral construction hoses.

Construction

Tube: Nitrile (NBR)
Reinforcement: Two high-tensile steel wire braids
Cover: Synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series



Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
477-4	6	1/4	-4	6.4	13.1	45.0	6500	180.0	26000	65	0.32
477-5	8	5/16	-5	7.9	14.9	42.5	6100	170.0	24400	70	0.35
477-6	10	3/8	-6	9.5	17.2	40.0	5800	160.0	23200	75	0.42
477-8	12	1/2	-8	12.7	20.4	38.0	5500	152.0	22000	105	0.55
477-10	16	5/8	-10	15.9	23.4	35.0	5000	140.0	20000	160	0.65
477-12	19	3/4	-12	19.1	27.2	35.0	5000	140.0	20000	200	1.10
477-16	25	1	-16	25.4	34.8	25.0	3600	100.0	14400	250	1.30

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



477TC

Elite No-Skive PowerLift Tough Cover

2 wire braided



- *No-Skive* hose construction – Compact design
- Tested at 120 % of the maximum working pressure at 400,000 impulses
- Smaller bend radius and reduced outside diameter bringing a significant advantage in terms of space and weight on compact equipment
- Highly abrasion resistant TOUGH COVER
- MSHA approved

Primary Applications

For truck cranes and lifting equipment such as fork lift trucks, aerial lifts, cranes, telehandlers, lifting platforms.

Restrictions

Should not be used for high impulse hydraulic applications to replace spiral construction hoses.

Construction

Tube: Nitrile (NBR)
Reinforcement: Two high-tensile steel wire braids
Cover: MSHA approved synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series



Part Number	Hose I.D.				Hose O.D.	Pressure Rating				min. bend radius	weight
						max. working pressure		min. burst pressure			
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
477TC-4	6	1/4	-4	6,4	13,1	45,0	6500	180,0	26000	65	0,32
477TC-5	8	5/16	-5	7,9	14,9	42,5	6100	170,0	24400	70	0,35
477TC-6	10	3/8	-6	9,5	17,2	40,0	5800	160,0	23200	75	0,42
477TC-8	12	1/2	-8	12,7	20,4	38,0	5500	152,0	22000	105	0,55
477TC-10	16	5/8	-10	15,9	23,4	35,0	5000	140,0	20000	160	0,65
477TC-12	19	3/4	-12	19,1	27,2	35,0	5000	140,0	20000	200	1,10
477TC-16	25	1	-16	25,4	34,8	25,0	3600	100,0	14400	250	1,30

The combination of high temperature and high pressure could reduce the hose life.


Hose layline example



477ST

Elite No-Skive PowerLift

2 wire braided



- *No-Skive* hose construction – Compact design
- Extreme abrasion resistant SUPER TOUGH cover
- Tested at 120 % of the maximum working pressure at 400,000 impulses
- Smaller bend radius and reduced outside diameter

Primary Applications

For truck cranes and lifting equipment such as fork lift trucks, aerial lifts, cranes, telehandlers, lifting platforms.

Restrictions

Should not be used for high impulse hydraulic applications to replace spiral construction hoses.

Construction

Tube: Nitrile (NBR)
Reinforcement: Two high-tensile steel wire braids
Cover: Synthetic rubber with a special polyethylene coating

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

48

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
477ST-4	6	1/4	-4	6.4	13.1	45.0	6500	180.0	26000	65	0.30
477ST-5	8	5/16	-5	7.9	14.9	42.5	6100	170.0	24400	70	0.35
477ST-6	10	3/8	-6	9.5	17.2	40.0	5800	160.0	23200	75	0.42
477ST-8	12	1/2	-8	12.7	20.4	38.0	5500	152.0	22000	105	0.55
477ST-10	16	5/8	-10	15.9	23.4	35.0	5000	140.0	20000	160	0.65
477ST-12	19	3/4	-12	19.1	27.2	35.0	5000	140.0	20000	200	1.20
477ST-16	25	1	-16	25.4	34.8	25.0	3600	100.0	14400	250	1.30

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



492

Elite No-Skive Compact

EN 857 1SC – ISO 11237 Type 1SC



- *No-Skive* hose construction – Compact design
- Nitrile (NBR) inner tube – extended fluid compatibility
- Exceeding EN/ISO specifications for pressure, bend radius and abrasion resistance

Primary Applications

Demanding medium pressure hydraulic applications

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

EN 857 1SC – ISO 11237 Type 1SC

Construction

Tube: Nitrile (NBR)
Reinforcement: One high-tensile steel wire braid
Cover: Synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series



Part Number	Hose I.D.				Hose O.D.	Pressure Rating				min. bend radius	weight
						max. working pressure		min. burst pressure			
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
492-4	6	1/4	-4	6.4	11.5	28.0	4060	112.0	16240	75	0.18
492-5	8	5/16	-5	7.9	13.6	25.0	3625	100.0	14500	85	0.21
492-6	10	3/8	-6	9.5	15.5	22.5	3260	90.0	13050	90	0.25
492-8	12	1/2	-8	12.7	18.9	19.0	2755	76.0	11020	130	0.33
492-10	16	5/8	-10	15.9	22.2	15.0	2175	60.0	8700	150	0.41
492-12	19	3/4	-12	19.1	26.0	15.0	2175	60.0	8700	180	0.56
492-16	25	1	-16	25.4	33.3	11.0	1595	44.0	6380	230	0.75
492-20-WR	31	1 1/4	-20	31.8	40.0	7.5	1085	30.0	4350	335	0.93

Part Number without a suffix: the hose cover has a smooth appearance. Part Number with a suffix (WR): the hose cover has a wrapped appearance.
The combination of high temperature and high pressure could reduce the hose life.
Also available in reels up to size -16 under part number 492-xx-RL

Hose layline example

Parker Elite 492-6 WP 22,5 MPa (3260 PSI) | • • 10 mm (3/8) ISO11237/EN857 1SC 10 Made in Italy

492TC

Elite No-Skive Compact Tough Cover

EN 857 1SC – ISO 11237 Type 1SC



- *No-Skive* hose construction – Compact design
- Nitrile (NBR) inner tube – extended fluid compatibility
- Exceeding EN/ISO specifications for pressure, bend radius and abrasion resistance
- Highly abrasion resistant TOUGH COVER
- MSHA approved

Primary Applications

Demanding medium pressure hydraulic applications

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

EN 857 1SC – ISO 11237 Type 1SC

Construction

Tube:	Nitrile (NBR)
Reinforcement:	One high-tensile steel wire braid
Cover:	MSHA approved synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception:	Air	max. +70 °C
	Water	max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series



Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
492TC-4	6	1/4	-4	6.4	11.5	28.0	4060	112.0	16240	75	0.18
492TC-5	8	5/16	-5	7.9	13.6	25.0	3625	100.0	14500	85	0.21
492TC-6	10	3/8	-6	9.5	15.5	22.5	3260	90.0	13050	90	0.25
492TC-8	12	1/2	-8	12.7	18.9	19.0	2755	76.0	11020	130	0.33
492TC-10	16	5/8	-10	15.9	22.2	15.0	2175	60.0	8700	150	0.41
492TC-12	19	3/4	-12	19.1	26.0	15.0	2175	60.0	8700	180	0.56
492TC-16	25	1	-16	25.4	33.3	11.0	1595	44.0	6380	230	0.75

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example

PARKER NO-SKIVE Tough Cover 492TC-8 WP 19,0 MPa (2755 PSI) MSHA | • • 12,7 mm (1/2) Made in Italy

492ST

Elite No-Skive Super Tough Compact

EN 857 1SC – ISO 11237 Type 1SC



- *No-Skive* hose construction – Compact design
- Nitrile (NBR) inner tube – extended fluid compatibility
- Extreme abrasion resistant SUPER TOUGH cover
- Exceeding EN/ISO specifications for pressure, bend radius and abrasion resistance

Primary Applications

Mobile market: Medium pressure hydraulic applications with extremely high abrasion risks

Applicable Specifications

EN 857 1SC – ISO 11237 Type 1SC

Construction

Tube: Nitrile (NBR)
Reinforcement: One high-tensile steel wire braid
Cover: Synthetic rubber with a special polyethylene coating

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series



Part Number	Hose I.D.				Hose O.D.	Pressure Rating				min. bend radius	weight
						max. working pressure		min. burst pressure			
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
492ST-4	6	1/4	-4	6.4	12.0	28.0	4000	112.0	16240	75	0.18
492ST-5	8	5/16	-5	7.9	13.6	25.0	3625	100.0	14500	85	0.21
492ST-6	10	3/8	-6	9.5	15.5	22.5	3260	90.0	13050	90	0.25
492ST-8	12	1/2	-8	12.7	18.9	19.0	2755	76.0	11020	130	0.33
492ST-10	16	5/8	-10	15.9	22.3	15.0	2175	60.0	8700	150	0.41
492ST-12	19	3/4	-12	19.1	26.0	15.0	2175	60.0	8700	180	0.56
492ST-16	25	1	-16	25.4	33.6	11.0	1595	44.0	6380	230	0.75
492ST-20	31	1 1/4	-20	31.8	40.0	7.5	1085	30.0	4350	335	0.93

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



493

No-Skive Compact

High pressure water cleaning applications



- One wire *No-Skive* construction
- For water up to +120 °C constant temperature

Primary Applications

High pressure water cleaners

Construction

Tube: Synthetic rubber
Reinforcement: One high-tensile steel wire braid
Cover: Synthetic rubber in black or blue colour

Temperature Range ..... water max. +120 °C

Fitting Series

48

Part Number	Hose I.D.				Hose O.D.	Pressure Rating				min. bend radius	weight
						max. working pressure		min. burst pressure			
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
493-4	6	1/4	-4	6.4	13.4	20.0	2898	60.0	8695	60	0.18
493-4-BLU	6	1/4	-4	6.4	13.4	20.0	2898	60.0	8695	60	0.18
493-5	8	5/16	-5	7.9	15.0	20.0	2898	60.0	8695	75	0.21
493-5-BLU	8	5/16	-5	7.9	15.0	20.0	2898	60.0	8695	75	0.21
493-6	10	3/8	-6	9.5	17.4	20.0	2898	60.0	8695	90	0.25
493-6-BLU	10	3/8	-6	9.5	17.4	20.0	2898	60.0	8695	90	0.25
493-8	12	1/2	-8	12.7	20.6	17.5	2536	52.5	7608	110	0.33
493-8-BLU	12	1/2	-8	12.7	20.6	17.5	2536	52.5	7608	110	0.33

WKS rubber hand grip for No-Skive high pressure water cleaning hoses can be found on page Eb-17.
The combination of high temperature and high pressure could reduce the hose life.
Also available on reels under part number 493-xx-RL

Hose layline example

PARKER NO-SKIVE 493-5 WP 20,0 MPa (2898 PSI) 1 ° ° 8 mm (5/16) max. 120°C WATER

692

No-Skive Compact

Constant pressure, tight bend radius



- *No-Skive* hose construction – Compact design
- Nitrile (NBR) inner tube – extended fluid compatibility
- Constant working pressure of 21.0 MPa

Primary Applications

Material handling:
General small bending radii hydraulic applications, ideal for over the sheave or reel applications.

Applicable Specifications

Parker specification

Construction

Tube: Nitrile (NBR)
Reinforcement: One or two high-tensile steel wire braids
Cover: Synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series



Part Number	Hose I.D.				Hose O.D.	Pressure Rating				min. bend radius	weight
						max. working pressure		min. burst pressure			
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
692-4	6	1/4	-4	6.4	11.5	21.0	3045	84.0	12180	40	0.18
692-5	8	5/16	-5	7.9	13.6	21.0	3045	84.0	12180	40	0.21
692-6	10	3/8	-6	9.5	15.5	21.0	3045	84.0	12180	40	0.25
692-8	12	1/2	-8	12.7	20.4	21.0	3045	84.0	12180	50	0.52
692-10	16	5/8	-10	15.9	23.9	21.0	3045	84.0	12180	60	0.66

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example

Parker 692-10 WP 21,0 MPa (3000 PSI) I • • 16 mm (5/8)

692Twin

No-Skive Compact

Twin constant pressure, tight bend radius



- *No-Skive* hose construction – Compact design
- Nitrile (NBR) inner tube – extended fluid compatibility
- Constant working pressure of 21.0 MPa

Primary Applications

Lifting and material handling equipment:
General small bending radii hydraulic applications, ideal over the sheave or reel applications

Applicable Specifications

Parker specification

Construction

Tube:	Nitrile (NBR)
Reinforcement:	One or two high-tensile steel wire braids
Cover:	Synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series



Part Number	Hose I.D.				Hose O.D.	Pressure Rating				min. bend radius	weight
						max. working pressure		min. burst pressure			
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
692-4-4	6	1/4	-4	6.4	25.8	21.0	3045	84.0	12180	40	0.34
692-5-5	8	5/16	-5	7.9	27.4	21.0	3045	84.0	12180	40	0.40
692-6-6	10	3/8	-6	9.5	31.2	21.0	3045	84.0	12180	40	0.48
692-8-8	12	1/2	-8	12.7	41.5	21.0	3045	84.0	12180	50	1.02
692-10-10	16	5/8	-10	15.9	48.7	21.0	3045	84.0	12180	60	1.30

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example

Parker 692-8-8 WP 21,0 MPa (3000 PSI) I ° ° 12,5 mm (1/2)

811

No-Skive Suction and Return Line

SAE 100R4



- *No-Skive* hose construction
- Helical wire to prevent collapse under vacuum
- Small bend radii

Primary Applications

All Markets: General applications

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Construction

Tube: Synthetic rubber
Reinforcement: Two fibre spiral, one helical wire
Cover: Oil and weather resistant synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

Up to size - 32

For size -40 and -48



Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		Vaccum*	min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	kPa	mm	kg
811-12	19	3/4	-12	19.1	30.0	2.1	300	8.3	1200	85	65	0.63
811-16	25	1	-16	25.4	38.0	1.7	250	6.9	1000	85	75	0.96
811-20	31	1 1/4	-20	31.8	45.0	1.4	200	5.5	800	85	100	1.22
811-24	38	1 1/2	-24	38.1	52.0	1.0	150	4.1	600	85	130	1.55
811-32	51	2	-32	50.8	64.0	0.7	100	2.8	400	85	150	1.87
811-40	63	2 1/2	-40	63.5	75.0	0.4	62	1.6	248	85	180	2.45
811-48	76	3	-48	76.2	90.0	0.4	62	1.6	248	85	230	3.20

* The vacuum values listed in the table are vacuum pressure values in kPa. For an absolute value subtract the table value from 101 kPa.
** size -12 and size -16 = on Parkrimp 2 crimping press or adjustable crimpers only.
The combination of high temperature and high pressure could reduce the hose life.

Hose layline example

PARKER 811-12 SUCTION HOSE SAE 100R4-12 19 mm (3/4) 3Q81 PARKER 811-12 SUC

811S

No-Skive Suction and Return Line

Exceeds SAE 100R4



- *No-Skive* hose construction
- Helical wire to prevent collapse under vacuum
- Small bend radii
- Isobaric 1.0 MPa for all sizes

Primary Applications

All Markets: General applications

Type Approvals

For size -64 and -80, details please find on pages ***Ab-16*** to ***Ab-19***

Construction

Tube: Synthetic rubber
Reinforcement: Two fibre spiral, one helical wire
Cover: Oil and weather resistant synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

IF

Part Number	Hose I.D.		Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius
	Size	mm	mm ± 1.6	MPa	psi	MPa	psi	mm
811S-40	-40	63.5	75.0	1.0	145	4.0	580	240
811S-48	-48	76.2	90.0	1.0	145	4.0	580	300
811S-56	-56	88.9	106.0	1.0	145	4.0	580	360
811S-64	-64	101.6	116.0	1.0	145	4.0	580	400
811S-80	-80	127.0	142.0	1.0	145	4.0	580	500
811S-96	-96	152.4	172.0	1.0	145	4.0	580	600

Hose layline example

Parker 811S-40 SUCTION AND RETURN LINE HOSE - (MC25) - Exceed SAE 100R4 – 63.5 mm (2"1/2) Q/Y

881

No-Skive Suction and Return Line

SAE 100R4



- *No-Skive* hose construction
- Helical wire to prevent collapse under vacuum
- Up to +121 °C working temperature
- MSHA approved

Primary Applications

All Markets: For high temperature applications
For general applications

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Construction

Tube: Synthetic rubber
Reinforcement: Two fibre braid, one helical wire
Cover: Synthetic rubber MSHA approved

Temperature Range ..... -40 °C up to +121 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series



Series 43 for sizes -12, -16
Series 48 for sizes -20 up to -32
For size -40 fittings series on request

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		Vaccum*	min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	kPa	mm	kg
881-12	19	3/4	-12	19.1	30.0	2.1	300	8.3	1200	95	130	0.74
881-16	25	1	-16	25.4	38.0	1.7	250	6.9	1000	95	150	0.89
881-20	31	1 1/4	-20	31.8	45.0	1.4	200	5.5	800	95	200	1.32
881-24	38	1 1/2	-24	38.1	52.0	1.0	150	4.1	600	95	250	1.65
881-32	51	2	-32	50.8	63.0	0.7	100	2.8	400	95	300	1.89
881-40	63	2 1/2	-40	63.5	75.0	0.4	62	1.6	248	95	355	2.71


* The vacuum values listed in the table are vacuum pressure values in kPa. For an absolute value subtract the table value from 101kPa.
The combination of high temperature and high pressure could reduce the hose life.

Hose layline example

PARKER 881-12 SUCTION HOSE MSHA XXXX SAE 100R4-12 19 mm (3/4) 3Q78 PARKER

DIN – Metric

Page Cb-1 – Cb-4


CA Cb-1

Female Metric 24° Light Series with O–Ring Swivel – Straight
ISO 12151-2-SWS-L – DKOL


CE Cb-1

Female Metric 24° Light Series with O–Ring Swivel – 45° Elbow
ISO 12151-2-SWE 45°-L – DKOL 45°

CF Cb-2

Female Metric 24° Light Series with O–Ring Swivel – 90° Elbow
ISO 12151-2-SWE-L – DKOL 90°

D0 Cb-2

Male Metric 24° Light Series – Rigid Straight
ISO 12151-2-S-L – CEL


C9 Cb-3

Female Metric 24° – Swivel Heavy Series with O-Ring Straight
ISO 12151-2-SWS-S – DKOS

0C Cb-3

Female Metric 24° – Swivel Heavy Series with O–Ring 45° Elbow
ISO 12151-2 – SWE 45°-S – DKOS 45°


1C Cb-4


Female Metric 24° – Swivel Heavy Series with O–Ring 90° Elbow
ISO 12151-2-SWE-S – DKOS 90°


D2 Cb-4

Male Metric 24° – Rigid Heavy Series – Straight
ISO 12151-2-S-S – CES


BSP


Page Cb-5 – Cb-8


92 Cb-5

Female BSP Parallel Pipe Swivel – Straight (60° Cone)
BS5200-A – DKR


B1 Cb-5

Female BSP Parallel Pipe Swivel 45° Elbow (60° Cone)
BS 5200-D – DKR 45°

B2 Cb-6

Female BSP Parallel Pipe Swivel 90° Elbow (60° Cone)
BS 5200-B – DKR 90°

EA Cb-6

BSP Swivel Female with O–Ring (60° Cone)
BS 5200 – ISO 12151-6 – DKOR


EB Cb-7

BSP Swivel Female with O–Ring 45° Elbow (60° Cone)
BS 5200 – ISO 12151-6 – DKOR 45°


EC Cb-7

BSP Swivel Female with O–Ring 90° Elbow (60° Cone)
BS 5200 – ISO 12151-6 – DKOR 90°


D9 Cb-8

Male BSP Parallel Pipe Rigid – Straight (60° Cone)
BS5200 – AGR


SAE

Page Cb-9 – Cb-11

01 Cb-9

Male NPTF Pipe Rigid – Straight
SAE J476A / J516 – AGN

03 Cb-9

Male JIC 37° – Rigid Straight
ISO12151-5-S – AGJ

06 Cb-10

Female JIC 37° – Swivel Straight
ISO12151-5-SWS – DKJ


37 Cb-10

Female JIC 37° – Swivel 45° Elbow
ISO 12151-5-SWE 45° – DKJ 45°


39/3W Cb-11

Female JIC 37° SAE 45° – Dual Flare Swivel Female 90° Elbow
ISO 12151-5-SWES – DKJ 90°

Flange


Page Cb-12 – Cb-14


15
Cb-12

ISO 6162-1 Flange
Straight
ISO 12151-3-S-L – SFL
(21.0 MPa/ 3000 psi)

17
Cb-12

ISO 6162-1 Flange
45° Elbow
ISO 12151-3 – E45 – L – SFL 45°
(21.0 MPa/ 3000 psi)

19
Cb-13


ISO 6162-1 Flange
90° Elbow
ISO 12151-3 – E– L – SFL 90°
(21.0 MPa/ 3000 psi)


6A
Cb-13

ISO 6162-2 Flange
Straight
ISO 12151-3-S-S – SFS
(42.0 MPa/ 6000 psi)

6N
Cb-14

ISO 6162-2 Flange
90° Elbow
ISO 12151-3 – E-S – SFS 90°
(42.0 MPa/ 6000 psi)

ORFS


Page Cb-15 – Cb-17


JC
Cb-15

Female ORFS
Swivel – Straight
Short
ISO 12151-1 – SWSA SAE J516 – ORFS

JS
Cb-15

ORFS Swivel Female (Long)
ISO 12151-1-SWSB
SAE J516 – ORFS

J7
Cb-16

Female ORFS – Swivel
45° Elbow
ISO 12151-1 – SWE 45°
SAE J516 – ORFS 45°


J9
Cb-16

Female ORFS – Swivel
90° Elbow – Short Drop
ISO 12151-1 – SWES
SAE J516 – ORFS 90°


JM
Cb-17

ORFS Male
ISO 12151-1-S – SAE J516

CA

Female Metric 24° Light Series with O-Ring Swivel – Straight

ISO 12151-2-SWS-L – DKOL






Part Number	Hose I.D.				Thread	Tube O.D.	A	B	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
1CA43-10-6	10	3/8	-6	9.5	M16x1.5	10	53	24	19
1CA43-12-6	10	3/8	-6	9.5	M18x1.5	12	49	19	22
1CA43-15-8	12	1/2	-8	12.7	M22x1.5	15	56	21	27
1CA43-18-10	16	5/8	-10	15.9	M26x1.5	18	61	22	32
1CA43-22-10	16	5/8	-10	15.9	M30x2	22	64	24	36
1CA43-18-12	19	3/4	-12	19.1	M26x1.5	18	65	26	32
1CA43-22-12	19	3/4	-12	19.1	M30x2	22	63	24	36
1CA43-28-16	25	1	-16	25.4	M36x2	28	78	33	41
1CA43-35-16	25	1	-16	25.4	M45x2	35	76	31	50


Hose fittings are delivered with ozone resistant Nitrile (NBR) O-ring as a standard version. Working temperature from -40 °C up to +105 °C.
Hose fittings with special O-rings (Viton or EPDM) available on request. O-ring dimensions and part-numbers see in section Eb.

CE

Female Metric 24° Light Series with O-Ring Swivel – 45° Elbow

ISO 12151-2-SWE 45°-L – DKOL 45°





Part Number	Hose I.D.				Thread	Tube O.D.	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
1CE43-12-6	10	3/8	-6	9.5	M18x1.5	12	69	39	19	22
1CE43-15-8	12	1/2	-8	12.7	M22x1.5	15	81	46	22	27
1CE43-18-10	16	5/8	-10	15.9	M26x1.5	18	89	49	23	32
1CE43-22-12	19	3/4	-12	19.1	M30x2	22	98	58	26	36
1CE43-28-16	25	1	-16	25.4	M36x2	28	127	80	34	41

Hose fittings are delivered with ozone resistant Nitrile (NBR) O-ring as a standard version. Working temperature from -40 °C up to +105 °C.
Hose fittings with special O-rings (Viton or EPDM) available on request. O-ring dimensions and part-numbers see in section Eb.

Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK


43 | 304 | 387 | 387ST | 387TC | 421WC | 426 | 487 | 487ST | 487TC | 722 | 722CLF | 722TC | 722ST | 881

CF

Female Metric 24° Light Series with O-Ring Swivel – 90° Elbow

ISO 12151-2-SWE-L – DKOL 90°






Part Number	Hose I.D.				Thread	Tube O.D.	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
1CF43-12-6	10	3/8	-6	9.5	M18x1.5	12	64	35	36	22
1CF43-15-8	12	1/2	-8	12.7	M22x1.5	15	71	37	43	27
1CF43-18-10	16	5/8	-10	15.9	M26x1.5	18	81	41	45	32
1CF43-22-12	19	3/4	-12	19.1	M30x2	22	89	49	55	36
1CF43-28-16	25	1	-16	25.4	M36x2	28	114	68	78	41


Hose fittings are delivered with ozone resistant Nitrile (NBR) O-ring as a standard version. Working temperature from -40 °C up to +105 °C.
Hose fittings with special O-rings (Viton or EPDM) available on request. O-ring dimensions and part-numbers see in section Eb.

D0

Male Metric 24° Light Series – Rigid Straight

ISO 12151-2-S-L – CEL





Part Number	Hose I.D.				Thread	Tube O.D.	A	B	H
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
1D043-15-8	12	1/2	-8	12.7	M22x1.5	15	60	26	22
1D043-28-16	25	1	-16	25.4	M36x2	28	79	32	36


Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK

43 | 304 | 387 | 387ST | 387TC | 421WC | 426 | 487 | 487ST | 487TC | 722 | 722CLF | 722TC | 722ST | 881

C9 Female Metric 24° – Swivel Heavy Series with O-Ring Straight

ISO 12151-2-SWS-S – DKOS







Part Number	Hose I.D.				Thread	Tube O.D.	A	B	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
1C943-10-6	10	3/8	-6	9.5	M18x1.5	10	50	21	22
1C943-12-6	10	3/8	-6	9.5	M20x1.5	12	52	22	24
1C943-14-6	10	3/8	-6	9.5	M22x1.5	14	50	21	27
1C943-12-8	12	1/2	-8	12.7	M20x1.5	12	60	25	24
1C943-16-8	12	1/2	-8	12.7	M24x1.5	16	59	24	30
1C943-16-10	16	5/8	-10	15.9	M24x1.5	16	66	27	30
1C943-20-10	16	5/8	-10	15.9	M30x2	20	66	27	36
1C943-20-12	19	3/4	-12	19.1	M30x2	20	66	27	36
1C943-25-12	19	3/4	-12	19.1	M36x2	25	68	28	46
1C943-25-16	25	1	-16	25.4	M36x2	25	78	33	46
1C943-30-16	25	1	-16	25.4	M42x2	30	80	33	50

Hose fittings are delivered with ozone resistant Nitrile (NBR) O-ring as a standard version. Working temperature from -40 °C up to +105 °C.
Hose fittings with special O-rings (Viton or EPDM) available on request. O-ring dimensions and part-numbers see in section Eb.

0C Female Metric 24° – Swivel Heavy Series with O–Ring 45° Elbow

ISO 12151-2 – SWE 45°-S – DKOS 45°





Part Number	Hose I.D.				Thread	Tube O.D.	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
10C43-12-6	10	3/8	-6	9.5	M20x1.5	12	69	40	20	24
10C43-14-6	10	3/8	-6	9.5	M22x1.5	14	76	46	20	27
10C43-16-8	12	1/2	-8	12.7	M24x1.5	16	82	48	24	30
10C43-20-10	16	5/8	-10	15.9	M30x2	20	91	52	25	36
10C43-20-12	19	3/4	-12	19.1	M30x2	20	99	60	28	36
10C43-25-12	19	3/4	-12	19.1	M36x2	25	100	61	29	46
10C43-25-16	25	1	-16	25.4	M36x2	30	123	76	33	46
10C43-30-16	25	1	-16	25.4	M42x2	30	126	79	36	50

Hose fittings are delivered with ozone resistant Nitrile (NBR) O-ring as a standard version. Working temperature from -40 °C up to +105 °C.
Hose fittings with special O-rings (Viton or EPDM) available on request. O-ring dimensions and part-numbers see in section Eb.


Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK

43 | 304 | 387 | 387ST | 387TC | 421WC | 426 | 487 | 487ST | 487TC | 722 | 722CLF | 722TC | 722ST | 881

1C Female Metric 24° – Swivel Heavy Series with O–Ring 90° Elbow

ISO 12151-2-SWE-S – DKOS 90°







Part Number	Hose I.D.				Thread	Tube O.D.	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
11C43-8-6	10	3/8	-6	9.5	M16x1.5	8	67	38	37	19
11C43-12-6	10	3/8	-6	9.5	M20x1.5	12	65	35	37	24
11C43-14-6	10	3/8	-6	9.5	M22x1.5	14	64	35	37	27
11C43-16-8	12	1/2	-8	12.7	M24x1.5	16	72	37	45	30
11C43-20-10	16	5/8	-10	15.9	M30x2	20	79	40	48	36
11C43-25-10	16	5/8	-10	15.9	M36x2	25	85	46	52	46
11C43-20-12	19	3/4	-12	19.1	M30x2	20	89	50	58	36
11C43-25-12	19	3/4	-12	19.1	M36x2	25	89	49	59	46
11C43-25-16	25	1	-16	25.4	M36x2	25	109	64	69	46
11C43-30-16	25	1	-16	25.4	M42x2	30	115	68	76	50

Hose fittings are delivered with ozone resistant Nitrile (NBR) O-ring as a standard version. Working temperature from -40 °C up to +105 °C.
Hose fittings with special O-rings (Viton or EPDM) available on request. O-ring dimensions and part-numbers see in section Eb.

D2 Male Metric 24° – Rigid Heavy Series – Straight

ISO 12151-2-S-S – CES





Part Number	Hose I.D.				Thread	Tube O.D.	A	B	H
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
1D243-12-6	10	3/8	-6	9.5	M20x1.5	12	55	26	22
1D243-14-6	10	3/8	-6	9.5	M22x1.5	14	55	25	22
1D243-16-8	12	1/2	-8	12.7	M24x1.5	16	62	28	24
1D243-20-10	16	5/8	-10	15.9	M30x2	20	72	33	30
1D243-20-12	19	3/4	-12	19.1	M30x2	20	72	33	30
1D243-25-12	19	3/4	-12	19.1	M36x2	25	74	35	36
1D243-30-16	25	1	-16	25.4	M42x2	30	85	40	46


Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK

43 | 304 | 387 | 387ST | 387TC | 421WC | 426 | 487 | 487ST | 487TC | 722 | 722CLF | 722TC | 722ST | 881

92 Female BSP Parallel Pipe Swivel – Straight (60° Cone)

BS5200-A – DKR







Part Number	Hose I.D.				Thread	A	B	W
	DN	Inch	Size	mm	BSP	mm	mm	mm
19243-6-6	10	3/8	-6	9.5	3/8x19	49	20	22
19243-8-6	10	3/8	-6	9.5	1/2x14	51	22	27
19243-8-8	12	1/2	-8	12.7	1/2x14	57	22	27
19243-10-8	12	1/2	-8	12.7	5/8x14	55	20	30
19243-10-10	16	5/8	-10	15.9	5/8x14	57	21	30
19243-12-10	16	5/8	-10	15.9	3/4x14	61	22	32
19243-12-12	19	3/4	-12	19.1	3/4x14	61	22	32
19243-16-16	25	1	-16	25.4	1x11	72	25	41

B1 Female BSP Parallel Pipe Swivel 45° Elbow (60° Cone)

BS 5200-D – DKR 45°





Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	BSP	mm	mm	mm	mm
1B143-6-6	10	3/8	-6	9.5	3/8x19	67	37	17	22
1B143-8-8	12	1/2	-8	12.7	1/2x14	79	45	20	27
1B143-10-10	16	5/8	-10	15.9	5/8x14	89	50	23	30
1B143-12-12	19	3/4	-12	19.1	3/4x14	96	57	25	32
1B143-16-16	25	1	-16	25.4	1x11	121	77	33	41


Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK

43 | 304 | 387 | 387ST | 387TC | 421WC | 426 | 487 | 487ST | 487TC | 722 | 722CLF | 722TC | 722ST | 881

B2 Female BSP Parallel Pipe Swivel 90° Elbow (60° Cone)

BS 5200-B – DKR 90°







Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	BSP	mm	mm	mm	mm
1B243-6-6	10	3/8	-6	9.5	3/8x19	66	37	33	22
1B243-8-6	10	3/8	-6	9.5	1/2x14	66	37	35	27
1B243-8-8	12	1/2	-8	12.7	1/2x14	74	39	40	27
1B243-10-10	16	5/8	-10	15.9	5/8x14	81	41	46	30
1B243-12-10	16	5/8	-10	15.9	3/4x14	82	43	45	32
1B243-12-12	19	3/4	-12	19.1	3/4x14	89	50	53	32
1B243-16-16	25	1	-16	25.4	1x11	116	69	69	41

EA BSP Swivel Female with O–Ring (60° Cone)

BS 5200 – ISO 12151-6 – DKOR





Part Number	Hose I.D.				Thread	A	B	W
	DN	Inch	Size	mm	BSP	mm	mm	mm
1EA43-8-8	12	1/2	-8	12.7	1/2x14	56	21	27
1EA43-10-10	16	5/8	-10	15.9	5/8x14	61	21.5	30
1EA43-12-12	19	3/4	-12	19.1	3/4x14	63	23	32
1EA43-16-16	25	1	-16	25.4	1x11	77	31	41

Hose fittings are delivered with ozone resistant Nitrile (NBR) O-ring as a standard version. Working temperature from -40 °C up to +105 °C.
Hose fittings with special O-rings (Viton or EPDM) available on request. O-ring dimensions and part-numbers see in section Eb.

Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK


43 | 304 | 387 | 387ST | 387TC | 421WC | 426 | 487 | 487ST | 487TC | 722 | 722CLF | 722TC | 722ST | 881

EB

BSP Swivel Female with O–Ring 45° Elbow (60° Cone)

BS 5200 – ISO 12151-6 – DKOR 45°






Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	BSP	mm	mm	mm	mm
1EB43-4-4	6	1/4	-4	6.4	1/4x19	57	34	14	19
1EB43-6-6	10	3/8	-6	9.5	3/8x19	73	44	18	22
1EB43-8-8	12	1/2	-8	12.7	1/2x14	79	44	20	27
1EB43-10-10	16	5/8	-10	15.9	5/8	85	49	22	30


Hose fittings are delivered with ozone resistant Nitrile (NBR) O-ring as a standard version. Working temperature from -40 °C up to +105 °C.
Hose fittings with special O-rings (Viton or EPDM) available on request. O-ring dimensions and part-numbers see in section Eb.

EC

BSP Swivel Female with O–Ring 90° Elbow (60° Cone)

BS 5200 – ISO 12151-6 – DKOR 90°





Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	BSP	mm	mm	mm	mm
1EC43-4-4	6	1/4	-4	6.4	1/4x19	50	27	24	19
1EC43-6-4	6	1/4	-4	6.4	3/8x19	51	28	27	22
1EC43-6-6	10	3/8	-6	9.5	3/8x19	64	35	34	22
1EC43-8-8	12	1/2	-8	12.7	1/2x14	71	36	40	27
1EC43-10-10	16	5/8	-10	15.9	5/8	80	43	44	30
1EC43-12-12	19	3/4	-12	19.1	3/4x14	89	49	55	32
1EC43-16-16	25	1	-16	25.4	1x11	115	68	71	41

Hose fittings are delivered with ozone resistant Nitrile (NBR) O-ring as a standard version. Working temperature from -40 °C up to +105 °C.
Hose fittings with special O-rings (Viton or EPDM) available on request. O-ring dimensions and part-numbers see in section Eb.


Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK

43 | 304 | 387 | 387ST | 387TC | 421WC | 426 | 487 | 487ST | 487TC | 722 | 722CLF | 722TC | 722ST | 881

D9 Male BSP Parallel Pipe Rigid – Straight (60° Cone)

BS5200 – AGR





Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	BSP	mm	mm	mm
1D943-2-4	6	1/4	-4	6.4	1/8x28	46	22	14
1D943-4-4	6	1/4	-4	6.4	1/4x19	49	27	19
1D943-6-6	10	3/8	-6	9.5	3/8x19	57	28	22
1D943-8-6	10	3/8	-6	9.5	1/2x14	60	31	27
1D943-8-8	12	1/2	-8	12.7	1/2x14	64	30	27
1D943-10-10	16	5/8	-10	15.9	5/8x14	75	36	30
1D943-12-10	16	5/8	-10	15.9	3/4x14	72	35	32
1D943-12-12	19	3/4	-12	19.1	3/4x14	72	33	32
1D943-16-12	19	3/4	-12	19.1	1x11	77	38	41
1D943-16-16	25	1	-16	25.4	1x11	85	40	41


Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK

43 | 304 | 387 | 387ST | 387TC | 421WC | 426 | 487 | 487ST | 487TC | 722 | 722CLF | 722TC | 722ST | 881

01 Male NPTF Pipe Rigid – Straight

SAE J476A / J516 – AGN







Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	NPTF	mm	mm	mm
10143-6-6-SM	10	3/8	-6	9.5	3/8x18	60	31	19
10143-8-6-SM	10	3/8	-6	9.5	1/2x14	61	32	22
10143-12-12-SM	19	3/4	-12	19.1	3/4x14	79	39	27

03 Male JIC 37° – Rigid Straight

ISO12151-5-S – AGJ





Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	UNF	mm	mm	mm
10343-6-6-SM	10	3/8	-6	9.5	9/16x18	60	31	19
10343-8-6-SM	10	3/8	-6	9.5	3/4x16	59	29	19
10343-10-8-SM	12	1/2	-8	12.7	7/8x14	67	32	24
10343-12-8-SM	12	1/2	-8	12.7	1 1/16x12	71	36	27
10343-12-10-SM	16	5/8	-10	15.9	1 1/16x12	75	36	27
10343-16-16-SM	25	1	-16	25.4	1 5/16x12	94	47	36


Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK

43 | 304 | 387 | 387ST | 387TC | 421WC | 426 | 487 | 487ST | 487TC | 722 | 722CLF | 722TC | 722ST | 881

06 Female JIC 37° – Swivel Straight

ISO12151-5-SWS – DKJ







Part Number	Hose I.D.				Thread	A	B	H	W
	DN	Inch	Size	mm	UNF	mm	mm	mm *Inch*	mm *Inch*
10643-6-6-SM	10	3/8	-6	9.5	9/16x18	58	29	17	19
10643-8-6-SM	10	3/8	-6	9.5	3/4x16	61	32	19	22
10643-8-8*	12	1/2	-8	12.7	3/4x16	66	34	*13/16*	*7/8*
10643-10-8-SM	12	1/2	-8	12.7	7/8x14	72	38	22	27
10643-10-10*	16	5/8	-10	15.9	7/8x14	73	38	*15/16*	*1*
10643-12-10-SM	16	5/8	-10	15.9	1 1/16x12	78	41	27	32
10643-12-12-SM	19	3/4	-12	19.1	1 1/16x12	80	41	27	32
10643-14-12-SM	19	3/4	-12	19.1	1 3/16x12	81	42	32	36
10643-16-12-SM	19	3/4	-12	19.1	1 5/16x12	84	45	32	41
10643-12-16-SM	25	1	-16	25.4	1 1/16x12	89	44	36	32
10643-16-16-SM	25	1	-16	25.4	1 5/16x12	94	47	36	41

* These fittings contain a dual seat that accepts both JIC (37°) and SAE (45°) male configurations.

37 Female JIC 37° – Swivel 45° Elbow

ISO 12151-5-SWE 45° – DKJ 45°





Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
13743-6-6-SM	10	3/8	-6	9.5	9/16x18	60	31	10	19
13743-8-8-SM*	12	1/2	-8	12.7	3/4x16	73	38	14	22
13743-10-10-SM*	16	5/8	-10	15.9	7/8x14	83	44	17	27
13743-12-10-SM	16	5/8	-10	15.9	1 1/16x12	88	48	21	32
13743-12-12-SM	19	3/4	-12	19.1	1 1/16x12	93	54	22	32
13743-16-12-SM	19	3/4	-12	19.1	1 5/16x12	95	56	24	41
13743-16-16-SM	25	1	-16	25.4	1 5/16x12	111	66	24	41

* These fittings contain a dual seat that accepts both JIC (37°) and SAE (45°) male configurations.


Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK

43 | 304 | 387 | 387ST | 387TC | 421WC | 426 | 487 | 487ST | 487TC | 722 | 722CLF | 722TC | 722ST | 881

39/3W Female JIC 37° SAE 45° – Dual Flare Swivel Female 90° Elbow

ISO 12151-5-SWES – DKJ 90°





Part Number	Hose I.D.				Thread	A	B	E	W	
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm	*Inch*
13943-6-6-SM	10	3/8	-6	9.5	9/16x18	57	28	23	19	
13W43-8-6-SM	10	3/8	-6	9.5	3/4x16	64	35	29	22	
13943-10-8-SM*	12	1/2	-8	12.7	7/8x14	74	39	32	27	
13943-10-10*	16	5/8	-10	15.9	7/8x14	80	40	37	*1*	
13W43-10-10-SM*	16	5/8	-10	15.9	7/8x14	80	40	33	27	
13943-12-12-SM	19	3/4	-12	19.1	1 1/16x12	89	50	48	32	
13943-16-12-SM	19	3/4	-12	19.1	1 5/16x12	89	50	51	41	
13943-16-16-SM	25	1	-16	25.4	1 5/16x12	109	64	55	41	

* These fittings contain a dual seat that accepts both JIC (37°) and SAE (45°) male configurations.


Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK

43 | 304 | 387 | 387ST | 387TC | 421WC | 426 | 487 | 487ST | 487TC | 722 | 722CLF | 722TC | 722ST | 881

15 ISO 6162-1 Flange Straight

ISO 12151-3-S-L – SFL
(21.0 MPa/ 3000 psi)







Part Number	Hose I.D.				Flange	A	B	F
	DN	Inch	Size	mm	Inch	mm	mm	mm
11543-8-8	12	1/2	-8	12.7	1/2	89	54	30
11543-12-10	16	5/8	-10	15.9	3/4	69	30	38
11543-12-12	19	3/4	-12	19.1	3/4	98	59	38
11543-16-12	19	3/4	-12	19.1	1	70	31	45
11543-16-16	25	1	-16	25.4	1	108	63	45
11543-20-16	25	1	-16	25.4	1 1/4	82	36	51

To select corresponding half-flange and O-ring see section Eb.

17 ISO 6162-1 Flange 45° Elbow

ISO 12151-3 – E45 – L – SFL 45°
(21.0 MPa/ 3000 psi)





Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
11743-8-8	12	1/2	-8	12.7	1/2	79	44	20	30
11743-12-10	16	5/8	-10	15.9	3/4	96	57	26	38
11743-12-12	19	3/4	-12	19.1	3/4	98	58	26	38
11743-16-16	25	1	-16	25.4	1	119	73	27	45
11743-20-16	25	1	-16	25.4	1 1/4	121	76	32	51

To select corresponding half-flange and O-ring see section Eb.


Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK

43 | 304 | 387 | 387ST | 387TC | 421WC | 426 | 487 | 487ST | 487TC | 722 | 722CLF | 722TC | 722ST | 881

19 ISO 6162-1 Flange 90° Elbow

ISO 12151-3 – E– L – SFL 90°
(21.0 MPa/ 3000 psi)







Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
11943-8-8	12	1/2	-8	12.7	1/2	75	40	41	30
11943-12-12	19	3/4	-12	19.1	3/4	89	50	58	38
11943-16-12	19	3/4	-12	19.1	1	90	50	58	45

To select corresponding half-flange and O-ring see section Eb.

6A ISO 6162-2 Flange Straight

ISO 12151-3-S-S – SFS
(42.0 MPa/ 6000 psi)





Part Number	Hose I.D.				Flange	A	B	F
	DN	Inch	Size	mm	Inch	mm	mm	mm
16A43-12-12	19	3/4	-12	19.1	3/4	105	66	41
16A43-16-16	25	1	-16	25.4	1	127	82	48

To select corresponding half-flange and O-ring see section Eb.


Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK

43 | 304 | 387 | 387ST | 387TC | 421WC | 426 | 487 | 487ST | 487TC | 722 | 722CLF | 722TC | 722ST | 881

6N ISO 6162-2 Flange 90° Elbow

ISO 12151-3 – E-S – SFS 90°
(42.0 MPa/ 6000 psi)





Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
16N43-12-12	19	3/4	-12	19.1	3/4	98	58	54	41
16N43-16-16	25	1	-16	25.4	1	111	64	70	48

To select corresponding half-flange and O-ring see section Eb.

Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK


43 | 304 | 387 | 387ST | 387TC | 421WC | 426 | 487 | 487ST | 487TC | 722 | 722CLF | 722TC | 722ST | 881

JC

Female ORFS Swivel – Straight Short

ISO 12151-1 – SWSA
SAE J516 – ORFS







Part Number	Hose I.D.				Thread	A	B	H	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
1JC43-6-6-SM	10	3/8	-6	9.5	11/16x16	49	20	19	22
1JC43-8-8-SM	12	1/2	-8	12.7	13/16x16	56	22	22	24
1JC43-10-8-SM	12	1/2	-8	12.7	1x14	58	24	24	30
1JC43-10-10-SM	16	5/8	-10	15.9	1x14	64	24	24	30
1JC43-12-12-SM	19	3/4	-12	19.1	1 3/16x12	68	29	32	36
1JC43-16-12-SM	19	3/4	-12	19.1	1 7/16x12	72	33	36	41
1JC43-16-16-SM	25	1	-16	25.4	1 7/16x12	80	35	36	41

JS

ORFS Swivel Female (Long)

ISO 12151-1-SWSB
SAE J516 – ORFS





Part Number	Hose I.D.				Thread	A	B	H	W
	DN	Inch	Size	mm	UNF	mm	mm	mm *Inch*	mm *Inch*
1JS43-10-10-SM	16	5/8	-10	15.9	1x14	79	39	24	*15/16*


Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK

43 | 304 | 387 | 387ST | 387TC | 421WC | 426 | 487 | 487ST | 487TC | 722 | 722CLF | 722TC | 722ST | 881

J7 Female ORFS – Swivel 45° Elbow

ISO 12151-1 – SWE 45°
SAE J516 – ORFS 45°







Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
1J743-8-6-SM	10	3/8	-6	9.5	13/16x16	64	35	15	24
1J743-8-8-SM	12	1/2	-8	12.7	13/16x16	72	37	15	24
1J743-10-10-SM	16	5/8	-10	15.9	1x14	83	44	16	30
1J743-12-12-SM	19	3/4	-12	19.1	1 3/16x12	92	53	21	36
1J743-16-16-SM	25	1	-16	25.4	1 7/16x12	113	66	24	41

J9 Female ORFS – Swivel 90° Elbow – Short Drop

ISO 12151-1 – SWES
SAE J516 – ORFS 90°





Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
1J943-6-6-SM	10	3/8	-6	9.5	11/16x16	58	29	23	22
1J943-8-6-SM	10	3/8	-6	9.5	13/16x16	58	29	29	24
1J943-8-8-SM	12	1/2	-8	12.7	13/16x16	70	35	29	24
1J943-10-8-SM	12	1/2	-8	12.7	1x14	73	38	32	30
1J943-10-10-SM	16	5/8	-10	15.9	1x14	78	39	33	30
1J943-12-10-SM	16	5/8	-10	15.9	1 3/16x12	86	50	48	36
1J943-12-12-SM	19	3/4	-12	19.1	1 3/16x12	89	49	48	36
1J943-16-16-SM	25	1	-16	25.4	1 7/16x12	111	64	56	41


Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK

43 | 304 | 387 | 387ST | 387TC | 421WC | 426 | 487 | 487ST | 487TC | 722 | 722CLF | 722TC | 722ST | 881

JM ORFS Male

ISO 12151-1-S – SAE J516





Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	UNF	mm	mm	mm
1JM43-8-6-SM	10	3/8	-6	9.5	13/16x16	56	27	22
1JM43-8-8-SM	12	1/2	-8	12.7	13/16x16	62	27	22
1JM43-10-8-SM	12	1/2	-8	12.7	1x14	67	32	27
1JM43-10-10-SM	16	5/8	-10	15.9	1x14	71	32	27
1JM43-16-16-SM	25	1	-16	25.4	1 7/16x12	84	39	41

To select corresponding O-ring see section Eb.


Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

43 | 304 | 387 | 387ST | 387TC | 421WC | 426 | 487 | 487ST | 487TC | 722 | 722CLF | 722TC | 722ST | 881

DIN – Metric

Page Cc-1 – Cc-11


CA
Cc-1

Female Metric 24°
Light Series with O–Ring
Swivel – Straight
ISO 12151-2-SWS-L – DKOL


CE
Cc-2

Female Metric 24°
Light Series with O–Ring
Swivel – 45° Elbow
ISO 12151-2-SWE 45°-L – DKOL 45°

CF
Cc-3

Female Metric 24°
Light Series with O–Ring
Swivel – 90° Elbow
ISO 12151-2-SWE-L – DKOL 90°

D0
Cc-4

Male Metric 24°
Light Series – Rigid
Straight
ISO 12151-2-S-L – CEL


C3
Cc-5

Female Metric
Light Series – Swivel
Straight (Ball Nose for 24° or 60° Cone)
DKL

C4
Cc-5

Female Metric
Light Series – Swivel
45° Elbow (Ball Nose for 24° or 60° Cone)
DKL 45°

C5
Cc-6

Female Metric
Light Series – Swivel
90° Elbow (Ball Nose for 24° or 60° Cone)
DKL 90°


C9
Cc-7

Female Metric 24° – Swivel
Heavy Series with O-Ring
Straight
ISO 12151-2-SWS-S – DKOS


0C
Cc-8


Female Metric 24° – Swivel
Heavy Series with O–Ring
45° Elbow
ISO 12151-2 – SWE 45°-S – DKOS 45°

1C
Cc-9

Female Metric 24° – Swivel
Heavy Series with O–Ring
90° Elbow
ISO 12151-2-SWE-S – DKOS 90°


D2
Cc-10

Male Metric 24° – Rigid
Heavy Series – Straight
ISO 12151-2-S-S – CES


C6
Cc-11

Female Metric – Swivel
Heavy Series – Straight (Ball Nose)
DKS


49
Cc-11

Metric Banjo
Straight
DIN 7642


BSP


Page Cc-12 – Cc-20


92
Cc-12

Female BSP Parallel Pipe
Swivel – Straight (60° Cone)
BS5200-A – DKR


B1
Cc-13

Female BSP Parallel Pipe
Swivel
45° Elbow (60° Cone)
BS 5200-D – DKR 45°


B2
Cc-14

Female BSP Parallel Pipe
Swivel
90° Elbow (60° Cone)
BS 5200-B – DKR 90°


B4
Cc-15

Female BSP Parallel Pipe
Swivel – 90° Elbow
Block Type (60° Cone)
BS 5200-E – DKR 90°


EA
Cc-16

BSP Swivel Female
with O–Ring (60° Cone)
BS 5200 – ISO 12151-6 – DKOR

EB
Cc-17

BSP Swivel Female
with O–Ring
45° Elbow (60° Cone)
BS 5200 – ISO 12151-6 – DKOR 45°

EC
Cc-18

BSP Swivel Female
with O–Ring
90° Elbow (60° Cone)
BS 5200 – ISO 12151-6 – DKOR 90°


D9
Cc-19

Male BSP Parallel Pipe
Rigid – Straight (60° Cone)
BS5200 – AGR


91
Cc-20

Male BSP Taper Pipe – Rigid
Straight
BS5200 – AGR-K


B5
Cc-20

Female BSP Parallel Pipe
Swivel
Straight (Flat Seat)


SAE


Page Cc-21 – Cc-28


01 Cc-21

Male NPTF Pipe
Rigid – Straight
SAE J476A / J516 – AGN

03 Cc-22

Male JIC 37° – Rigid
Straight
ISO12151-5-S – AGJ

05 Cc-23

Male SAE Straight Thread
with O–Ring – Rigid
Straight
ISO 11926 – SAE J516

06/68 Cc-24

Female – JIC 37°
SAE 45° Dual Flare
Swivel – Straight
ISO12151-5-SWS – DKJ

08 Cc-25

Female SAE 45° – Swivel
Straight
SAE J516

37/3V Cc-26

Female JIC 37°
SAE 45° – Dual Flare
Swivel Female 45° Elbow
ISO 12151-5-SWE 45° – DKJ 45°

39/3W Cc-27


Female JIC 37°
SAE 45° – Dual Flare
Swivel Female 90° Elbow
ISO 12151-5-SWES – DKJ 90°


41/3Y Cc-28


Female JIC 37° / 45°
Swivel Female 90° Elbow (Long)
ISO 12151-5-SWEL – DKJ 90°L


Flange

Page Cc-29 – Cc-33

15 Cc-29

ISO 6162-1 Flange
Straight
ISO 12151-3-S-L – SFL
(21.0 MPa/ 3000 psi)


17 Cc-30

ISO 6162-1 Flange
45° Elbow
ISO 12151-3 – E45 – L – SFL 45°
(21.0 MPa/ 3000 psi)

19 Cc-31

ISO 6162-1 Flange
90° Elbow
ISO 12151-3 – E– L – SFL 90°
(21.0 MPa/ 3000 psi)

6A Cc-32

ISO 6162-2 Flange
Straight
ISO 12151-3-S-S – SFS
(42.0 MPa/ 6000 psi)


6F Cc-32


ISO 6162-2 Flange
45° Elbow – Heavy Series
ISO 12151-3 – E45-S – SFS 45°
(42.0 MPa/ 6000 psi)

6N Cc-33

ISO 6162-2 Flange
90° Elbow
ISO 12151-3 – E-S – SFS 90°
(42.0 MPa/ 6000 psi)

ORFS

Page Cc-34 – Cc-39

JC Cc-34

Female ORFS
Swivel – Straight
Short
ISO 12151-1 – SWSA SAE J516 – ORFS

JS Cc-35

ORFS Swivel Female (Long)
ISO 12151-1-SWSB
SAE J516 – ORFS

J7 Cc-36

Female ORFS – Swivel
45° Elbow
ISO 12151-1 – SWE 45°
SAE J516 – ORFS 45°

J9 Cc-37


Female ORFS – Swivel
90° Elbow – Short Drop
ISO 12151-1 – SWES
SAE J516 – ORFS 90°

J1 Cc-38

Female ORFS – Swivel
90° Elbow – Long Drop
ISO 12151-1 – SWEL
SAE J 516 – ORFS 90° L

J5 Cc-38

Female ORFS – Swivel
90° Elbow – Medium Drop
ISO 12151-1 – SWEM – ORFS 90° M


JM Cc-39

ORFS Male
ISO 12151-1-S – SAE J516


JD Cc-39


Male ORFS
Bulkhead with Locknut
Straight (with O–ring)
ISO 12151-1 – SAE J516


JIS

Page Cc-40 – Cc-41

FU
Cc-40

Female BSP Parallel Pipe Swivel – Straight (30° Flare)
ISO 228-1 – JIS B8363 – GUI


GU
Cc-40

Female BSP Parallel Pipe Swivel – Straight (60° Cone)
ISO 228-1 – JIS B8363 – GUO

MU
Cc-41

Female Metric – Swivel Straight (30° Flare)
JIS B8363 – MU

MZ
Cc-41

Female Metric – Swivel 90° Elbow (30° Flare)
JIS B8363


French Standard


Page Cc-42 – Cc-44


FG
Cc-42

Male French Gas Series Rigid – Straight (24° Cone)


F2
Cc-42

Female French Gas Series Swivel – 90° Elbow

F4
Cc-43

Female French Gas Series Swivel – Straight (Ball Nose)


F6
Cc-43

French Male Metric Series (24° Cone)


F9
Cc-44

French Female Metric Series Swivel – (Ball Nose)


FA
Cc-44

Metric Male for Agriculture Valves

High Pressure Cleaning

Page Cc-45 – Cc-46


CW
Cc-45

Power Cleaner Connection


NW
Cc-45

Female Kärcher Metric Cleaning Hose Fitting Swivel – Straight


PW
Cc-46

Male Kärcher Metric Cleaning Hose Fitting Rigid – Straight

Others

Page Cc-47 – Cc-48


XU
Cc-47

Female Metric – Swivel Straight (30° Flare)
JIS B8363


DK
Cc-47

Male Metric L – Rigid Bulkhead with Locknut (24° Cone)


DX
Cc-48

Female Metric Swivel (M27x2) O–Ring Light Series

UPTC (Universal push-to-connect)

Page Cc-49 – Cc-50

EN
Cc-49

UPTC – Male Straight


EU
Cc-49

UPTC – Male 45° Elbow


ET
Cc-50

UPTC – Male 90° Elbow

CA

Female Metric 24° Light Series with O-Ring Swivel – Straight

ISO 12151-2-SWS-L – DKOL





Part Number		Hose I.D.				Thread	Tube O.D.	A	B	W
46 series	48 series	DN	Inch	Size	mm	metric	mm	mm	mm	mm
1CA46-6-4	1CA48-6-4	6	1/4	-4	6.4	M12x1.5	6	46	22	14
1CA46-8-4	1CA48-8-4	6	1/4	-4	6.4	M14x1.5	8	46	22	17
1CA46-10-4	1CA48-10-4	6	1/4	-4	6.4	M16x1.5	10	46	22	19
1CA46-12-4	1CA48-12-4	6	1/4	-4	6.4	M18x1.5	12	46	22	22
1CA46-8-5	1CA48-8-5	8	5/16	-5	7.9	M14x1.5	8	50	26	17
1CA46-10-5	1CA48-10-5	8	5/16	-5	7.9	M16x1.5	10	46	22	19
1CA46-12-5	1CA48-12-5	8	5/16	-5	7.9	M18x1.5	12	46	22	22
1CA46-8-6	1CA48-8-6	10	3/8	-6	9.5	M14x1.5	8	49	26	17
1CA46-10-6	1CA48-10-6	10	3/8	-6	9.5	M16x1.5	10	46	23	19
1CA46-12-6	1CA48-12-6	10	3/8	-6	9.5	M18x1.5	12	46	23	22
1CA46-15-6	1CA48-15-6	10	3/8	-6	9.5	M22x1.5	15	47	24	27
1CA46-18-6	1CA48-18-6	10	3/8	-6	9.5	M26x1.5	18	50	28	32
1CA46-12-8	1CA48-12-8	12	1/2	-8	12.7	M18x1.5	12	50	26	22
1CA46-15-8	1CA48-15-8	12	1/2	-8	12.7	M22x1.5	15	50	26	27
1CA46-18-8	1CA48-18-8	12	1/2	-8	12.7	M26x1.5	18	49	25	32
1CA46-15-10	1CA48-15-10	16	5/8	-10	15.9	M22x1.5	15	54	29	27
1CA46-18-10	1CA48-18-10	16	5/8	-10	15.9	M26x1.5	18	50	25	32
1CA46-22-10	1CA48-22-10	16	5/8	-10	15.9	M30x2	22	58	33	36
1CA46-18-12	1CA48-18-12	19	3/4	-12	19.1	M26x1.5	18	51	25	32
1CA46-22-12	1CA48-22-12	19	3/4	-12	19.1	M30x2	22	56	30	36
1CA46-28-12	1CA48-28-12	19	3/4	-12	19.1	M36x2	28	61	35	41
1CA46-22-16	1CA48-22-16	25	1	-16	25.4	M30x2	22	60	30	36
1CA46-28-16	1CA48-28-16	25	1	-16	25.4	M36x2	28	63	33	41
1CA46-35-16	1CA48-35-16	25	1	-16	25.4	M45x2	35	63	33	50
	1CA48-28-20	31	1 1/4	-20	31.8	M36x2	28	81	34	41
	1CA48-35-20	31	1 1/4	-20	31.8	M45x2	35	82	35	50
1CA46-35-20		31	1 1/4	-20	31.8	M45x2	35	69	31	50
	1CA48-42-20	31	1 1/4	-20	31.8	M52x2	42	82	35	60
	1CA48-35-24	38	1 1/2	-24	38.1	M45x2	35	75	37	50
	1CA48-42-24	38	1 1/2	-24	38.1	M52x2	42	77	39	60

Hose fittings are delivered with ozone resistant Nitrile (NBR) O-ring as a standard version. Working temperature from -40 °C up to +105 °C.
Hose fittings with special O-rings (Viton or EPDM) available on request. O-ring dimensions and part-numbers see in section Eb.

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or 48 — 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC

46 — 463 | 492 | 492ST | 492TC | 692 | 692TWIN


48 — 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...


471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

CE

Female Metric 24° Light Series with O-Ring Swivel – 45° Elbow

ISO 12151-2-SWE 45°-L – DKOL 45°





Part Number		Hose I.D.				Thread	Tube O.D.	A	B	E	W
46 series	48 series	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
1CE46-6-4	1CE48-6-4	6	1/4	-4	6.4	M12x1.5	6	70	45	19	14
1CE46-8-4	1CE48-8-4	6	1/4	-4	6.4	M14x1.5	8	59	35	16	17
1CE46-10-4	1CE48-10-4	6	1/4	-4	6.4	M16x1.5	10	59	35	16	19
1CE46-12-4	1CE48-12-4	6	1/4	-4	6.4	M18x1.5	12	59	36	16	22
1CE46-8-5	1CE48-8-5	8	5/16	-5	7.9	M14x1.5	8	64	40	19	17
1CE46-10-5	1CE48-10-5	8	5/16	-5	7.9	M16x1.5	10	67	43	15	19
1CE46-12-5	1CE48-12-5	8	5/16	-5	7.9	M18x1.5	12	61	37	16	22
1CE46-10-6	1CE48-10-6	10	3/8	-6	9.5	M16x1.5	10	68	45	20	19
1CE46-12-6	1CE48-12-6	10	3/8	-6	9.5	M18x1.5	12	68	45	19	22
1CE46-15-6	1CE48-15-6	10	3/8	-6	9.5	M22x1.5	15	68	45	19	27
1CE46-12-8	1CE48-12-8	12	1/2	-8	12.7	M18x1.5	12	74	51	23	22
1CE46-15-8	1CE48-15-8	12	1/2	-8	12.7	M22x1.5	15	71	47	22	27
1CE46-18-8	1CE48-18-8	12	1/2	-8	12.7	M26x1.5	18	71	47	22	32
1CE46-15-10	1CE48-15-10	16	5/8	-10	15.9	M22x1.5	15	79	54	26	27
1CE46-18-10	1CE48-18-10	16	5/8	-10	15.9	M26x1.5	18	75	50	23	32
1CE46-18-12	1CE48-18-12	19	3/4	-12	19.1	M26x1.5	18	90	64	27	32
1CE46-22-12	1CE48-22-12	19	3/4	-12	19.1	M30x2	22	88	62	26	36
1CE46-28-12	1CE48-28-12	19	3/4	-12	19.1	M36x2	28	90	64	28	41
1CE46-22-16	1CE48-22-16	25	1	-16	25.4	M30x2	22	112	82	35	36
1CE46-28-16		25	1	-16	25.4	M36x 2	28	113	83	33	41
	1CE48-28-16	25	1	-16	25.4	M36x2	28	113	83	33	41
	1CE48-28-20	31	1 1/4	-20	31.8	M36x2	28	142	95	40	41
	1CE48-35-20	31	1 1/4	-20	31.8	M45x2	35	141	94	37	50
1CE46-35-20		31	1 1/4	-20	31.8	M45x2	35	130	92	32	50
	1CE48-42-24	38	1 1/2	-24	38.1	M52x2	42	155	117	49	60

Hose fittings are delivered with ozone resistant Nitrile (NBR) O-ring as a standard version. Working temperature from -40 °C up to +105 °C.
Hose fittings with special O-rings (Viton or EPDM) available on request. O-ring dimensions and part-numbers see in section Eb.

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or 48 | 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC

46 | 463 | 492 | 492ST | 492TC | 692 | 692TWIN


48 | 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...


471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

CF

Female Metric 24° Light Series with O-Ring Swivel – 90° Elbow

ISO 12151-2-SWE-L – DKOL 90°





Part Number		Hose I.D.				Thread	Tube O.D.	A	B	E	W
46 series	48 series	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
1CF46-6-4	1CF48-6-4	6	1/4	-4	6.4	M12x1.5	6	57	33	33	14
1CF46-8-4	1CF48-8-4	6	1/4	-4	6.4	M14x1.5	8	51	28	29	17
1CF46-10-4	1CF48-10-4	6	1/4	-4	6.4	M16x1.5	10	52	28	29	19
1CF46-12-4	1CF48-12-4	6	1/4	-4	6.4	M18x1.5	12	53	26	29	22
1CF46-8-5	1CF48-8-5	8	5/16	-5	7.9	M14x1.5	8	62	38	34	17
1CF46-10-5	1CF48-10-5	8	5/16	-5	7.9	M16x1.5	10	61	37	29	19
1CF46-12-5	1CF48-12-5	8	5/16	-5	7.9	M18x1.5	12	61	37	30	22
1CF46-10-6	1CF48-10-6	10	3/8	-6	9.5	M16x1.5	10	60	37	37	19
1CF46-12-6	1CF48-12-6	10	3/8	-6	9.5	M18x1.5	12	58	35	36	22
1CF46-15-6	1CF48-15-6	10	3/8	-6	9.5	M22x1.5	15	58	35	36	27
1CF46-12-8	1CF48-12-8	12	1/2	-8	12.7	M18x1.5	12	63	39	45	22
1CF46-15-8	1CF48-15-8	12	1/2	-8	12.7	M22x1.5	15	61	37	43	27
1CF46-18-8	1CF48-18-8	12	1/2	-8	12.7	M26x1.5	18	65	41	43	32
1CF46-15-10	1CF48-15-10	16	5/8	-10	15.9	M22x1.5	15	67	42	50	27
1CF46-18-10	1CF48-18-10	16	5/8	-10	15.9	M26x1.5	18	66	41	45	32
1CF46-22-10	1CF48-22-10	16	5/8	-10	15.9	M30x2	22	71	46	47	36
1CF46-18-12	1CF48-18-12	19	3/4	-12	19.1	M26x1.5	18	80	54	56	32
1CF46-22-12	1CF48-22-12	19	3/4	-12	19.1	M30x2	22	80	54	55	36
1CF46-28-12	1CF48-28-12	19	3/4	-12	19.1	M36x2	28	80	54	57	41
1CF46-22-16	1CF48-22-16	25	1	-16	25.4	M30x2	22	102	72	74	36
1CF46-28-16	1CF48-28-16	25	1	-16	25.4	M36x2	28	101	72	71	41
	1CF48-22-20	31	1 1/4	-20	31.8	M30x2	22	130	83	81	36
	1CF48-28-20	31	1 1/4	-20	31.8	M36x2	28	129	82	81	41
1CF46-28-20		31	1 1/4	-20	31.8	M36x2	28	124	86	81	41
	1CF48-35-20	31	1 1/4	-20	31.8	M45x2	35	130	83	79	50
1CF46-35-20		31	1 1/4	-20	31.8	M45x2	35	124	86	79	50
	1CF48-35-24	38	1 1/2	-24	38.1	M45x2	35	139	101	99	50
	1CF48-42-24	38	1 1/2	-24	38.1	M52x2	42	139	101	101	60

Hose fittings are delivered with ozone resistant Nitrile (NBR) O-ring as a standard version. Working temperature from -40 °C up to +105 °C.
Hose fittings with special O-rings (Viton or EPDM) available on request. O-ring dimensions and part-numbers see in section Eb.


Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or 48	441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC
46	463 | 492 | 492ST | 492TC | 692 | 692TWIN
48	301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...
	471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

D0 Male Metric 24° Light Series – Rigid Straight

ISO 12151-2-S-L – CEL





Part Number		Hose I.D.				Thread	Tube O.D.	A	B	H
46 series	48 series	DN	Inch	Size	mm	metric	mm	mm	mm	mm
1D046-6-4	1D048-6-4	6	1/4	-4	6.4	M12x1.5	6	44	20	12
1D046-8-4	1D048-8-4	6	1/4	-4	6.4	M14x1.5	8	46	22	14
1D046-10-4	1D048-10-4	6	1/4	-4	6.4	M16x1.5	10	48	24	17
1D046-12-4	1D048-12-4	6	1/4	-4	6.4	M18x1.5	12	48	24	19
1D046-8-5	1D048-8-5	8	5/16	-5	7.9	M14x1.5	8	44	20	14
	1D048-10-5	8	5/16	-5	7.9	M16x1.5	10	48	24	17
1D046-10-5		8	5/16	-5	7.9	M16x1.5	10	47	24	17
1D046-12-5	1D048-12-5	8	5/16	-5	7.9	M18x1.5	12	48	24	19
1D046-10-6	1D048-10-6	10	3/8	-6	9.5	M16x1.5	10	47	24	17
1D046-12-6	1D048-12-6	10	3/8	-6	9.5	M18x1.5	12	47	24	19
1D046-15-6	1D048-15-6	10	3/8	-6	9.5	M22x1.5	15	49	26	22
1D046-12-8		12	1/2	-8	12.7	M18x1.5	12	47	23	19
1D046-15-8	1D048-15-8	12	1/2	-8	12.7	M22x1.5	15	50	26	22
1D046-18-8	1D048-18-8	12	1/2	-8	12.7	M26x1.5	18	53	29	27
1D046-15-10	1D048-15-10	16	5/8	-10	15.9	M22x1.5	15	57	29	27
1D046-18-10	1D048-18-10	16	5/8	-10	15.9	M26x1.5	18	54	29	27
1D046-18-12	1D048-18-12	19	3/4	-12	19.1	M26x1.5	18	55	29	27
1D046-22-12	1D048-22-12	19	3/4	-12	19.1	M30x2	22	59	33	30
1D046-28-12	1D048-28-12	19	3/4	-12	19.1	M36x2	28	60	34	36
1D046-28-16	1D048-28-16	25	1	-16	25.4	M36x2	28	65	35	36
1D046-35-20		31	1 1/4	-20	31.8	M45x2	35	78	40	46
	1D048-35-20	31	1 1/4	-20	31.8	M45x2	35	85	38	46
	1D048-42-24	38	1 1/2	-24	38.1	M52x2	42	77	39	55

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or **48** 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC


46 463 | 492 | 492ST | 492TC | 692 | 692TWIN


48 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...

471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

C3 Female Metric Light Series – Swivel Straight (Ball Nose for 24° or 60° Cone)

DKL







Part Number		Hose I.D.				Thread	Tube O.D.	A	B	W
46 series	48 series	DN	Inch	Size	mm	metric	mm	mm	mm	mm
	1C348-6-4	6	1/4	-4	6.4	M12x1.5	6	46	22	14
	1C348-8-4	6	1/4	-4	6.4	M14x1.5	8	45	21	17
	1C348-10-4	6	1/4	-4	6.4	M16x1.5	10	46	22	19
	1C348-10-5	8	5/16	-5	7.9	M16x1.5	10	46	22	19
	1C348-12-5	8	5/16	-5	7.9	M18x1.5	12	46	22	22
	1C348-10-6	10	3/8	-6	9.5	M16x1.5	10	46	24	19
	1C348-12-6	10	3/8	-6	9.5	M18x1.5	12	45	22	22
	1C348-15-8	12	1/2	-8	12.7	M22x1.5	15	48	24	27
	1C348-18-10	16	5/8	-10	15.9	M26x1.5	18	51	26	32
	1C348-22-12	19	3/4	-12	19.1	M30x2	22	56	30	36
	1C348-28-16	25	1	-16	25.4	M36x2	28	62	33	41

C4 Female Metric Light Series – Swivel 45° Elbow (Ball Nose for 24° or 60° Cone)

DKL 45°





Part Number		Hose I.D.				Thread	Tube O.D.	A	B	E	W
46 series	48 series	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
	1C448-8-4	6	1/4	-4	6.4	M14x1.5	8	56	33	14	17
	1C448-10-5	8	5/16	-5	7.9	M16x1.5	10	58	34	15	19
	1C448-12-6	10	3/8	-6	9.5	M18x1.5	12	67	44	18	22
	1C448-15-8	12	1/2	-8	12.7	M22x1.5	15	68	45	19	27

Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK


46 or 48	441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC
46	463 | 492 | 492ST | 492TC | 692 | 692TWIN
48	301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...
	471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

C5

Female Metric Light Series – Swivel 90° Elbow (Ball Nose for 24° or 60° Cone)

DKL 90°





Part Number		Hose I.D.				Thread	Tube O.D.	A	B	E	W
46 series	48 series	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
	1C548-6-4	6	1/4	-4	6.4	M12x1.5	6	49	26	29	14
	1C548-8-4	6	1/4	-4	6.4	M14x1.5	8	48	25	26	17
	1C548-10-5	8	5/16	-5	7.9	M16x1.5	10	61	37	33	19
	1C548-10-6	10	3/8	-6	9.5	M16x1.5	10	58	35	35	19
	1C548-12-6	10	3/8	-6	9.5	M18x1.5	12	58	35	34	22
	1C548-15-8	12	1/2	-8	12.7	M22x1.5	15	64	41	39	27
	1C548-18-10	16	5/8	-10	15.9	M26x1.5	18	66	41	43	32
	1C548-22-12	19	3/4	-12	19.1	M30x2	22	80	54	50	36

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or **48** 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC


46 463 | 492 | 492ST | 492TC | 692 | 692TWIN


48 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...

471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

C9 Female Metric 24° – Swivel Heavy Series with O-Ring Straight

ISO 12151-2-SWS-S – DKOS





Part Number		Hose I.D.				Thread	Tube O.D.	A	B	W
46 series	48 series	DN	Inch	Size	mm	metric	mm	mm	mm	mm
	1C948-6-4	6	1/4	-4	6.4	M14x1.5	6	49	26	17
1C946-6-4		6	1/4	-4	6.4	M14x1.5	6	48	26	17
1C946-8-4	1C948-8-4	6	1/4	-4	6.4	M16x1.5	8	47	23	19
1C946-10-4	1C948-10-4	6	1/4	-4	6.4	M18x1.5	10	46	22	22
1C946-12-4	1C948-12-4	6	1/4	-4	6.4	M20x1.5	12	47	24	24
1C946-14-4	1C948-14-4	6	1/4	-4	6.4	M22x1.5	14	48	24	27
1C946-8-5	1C948-8-5	8	5/16	-5	7.9	M16x1.5	8	46	23	19
1C946-10-5	1C948-10-5	8	5/16	-5	7.9	M18x1.5	10	46	22	22
1C946-12-5	1C948-12-5	8	5/16	-5	7.9	M20x1.5	12	48	24	24
1C946-14-5	1C948-14-5	8	5/16	-5	7.9	M22x1.5	14	48	24	27
1C946-16-5	1C948-16-5	8	5/16	-5	7.9	M24x1.5	16	52	28	30
1C946-8-6	1C948-8-6	10	3/8	-6	9.5	M16x1.5	8	49	26	19
1C946-10-6	1C948-10-6	10	3/8	-6	9.5	M18x1.5	10	45	22	22
1C946-12-6	1C948-12-6	10	3/8	-6	9.5	M20x1.5	12	47	24	24
1C946-14-6	1C948-14-6	10	3/8	-6	9.5	M22x1.5	14	47	24	27
1C946-16-6	1C948-16-6	10	3/8	-6	9.5	M24x1.5	16	50	28	30
1C946-12-8	1C948-12-8	12	1/2	-8	12.7	M20x1.5	12	51	28	24
1C946-14-8	1C948-14-8	12	1/2	-8	12.7	M22x1.5	14	48	24	27
1C946-16-8	1C948-16-8	12	1/2	-8	12.7	M24x1.5	16	51	28	30
1C946-20-8	1C948-20-8	12	1/2	-8	12.7	M30x2	20	53	29	36
1C946-16-10	1C948-16-10	16	5/8	-10	15.9	M24x1.5	16	53	28	30
1C946-20-10	1C948-20-10	16	5/8	-10	15.9	M30x2	20	53	28	36
	1C948-12-12	19	3/4	-12	19.1	M20x1.5	12	53	28	24
	1C948-16-12	19	3/4	-12	19.1	M24x1.5	16	55	29	30
1C946-20-12	1C948-20-12	19	3/4	-12	19.1	M30x2	20	56	30	36
1C946-25-12	1C948-25-12	19	3/4	-12	19.1	M36x2	25	61	35	46
1C946-25-16	1C948-25-16	25	1	-16	25.4	M36x2	25	63	33	46
1C946-30-16	1C948-30-16	25	1	-16	25.4	M42x2	30	67	38	50
	1C948-25-20	31	1 1/4	-20	31.8	M36x2	25	81	34	46
	1C948-38-20	31	1 1/4	-20	31.8	M52x2	38	80	33	60
1C946-38-20		31	1 1/4	-20	31.8	M52x2	38	74	36	60

Hose fittings are delivered with ozone resistant Nitrile (NBR) O-ring as a standard version. Working temperature from -40 °C up to +105 °C.
Hose fittings with special O-rings (Viton or EPDM) available on request. O-ring dimensions and part-numbers see in section Eb.


Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or 48	441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC
46	463 | 492 | 492ST | 492TC | 692 | 692TWIN
48	301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...
	471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

0C Female Metric 24° – Swivel Heavy Series with O-Ring 45° Elbow

ISO 12151-2 – SWE 45°-S – DKOS 45°





Part Number		Hose I.D.				Thread	Tube O.D.	A	B	E	W
46 series	48 series	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
10C46-6-4	10C48-6-4	6	1/4	-4	6.4	M14x1.5	6	61	38	16	17
10C46-8-4	10C48-8-4	6	1/4	-4	6.4	M16x1.5	8	59	35	16	19
10C46-10-4	10C48-10-4	6	1/4	-4	6.4	M18x1.5	10	59	36	16	22
10C46-12-4	10C48-12-4	6	1/4	-4	6.4	M20x1.5	12	71	48	17	24
10C46-10-5	10C48-10-5	8	5/16	-5	7.9	M18x1.5	10	62	38	17	22
10C46-12-5	10C48-12-5	8	5/16	-5	7.9	M20x1.5	12	70	47	17	24
10C46-10-6	10C48-10-6	10	3/8	-6	9.5	M18x1.5	10	70	47	19	22
10C46-12-6	10C48-12-6	10	3/8	-6	9.5	M20x1.5	12	69	46	20	24
10C46-14-6	10C48-14-6	10	3/8	-6	9.5	M22x1.5	14	69	46	20	27
10C46-14-8	10C48-14-8	12	1/2	-8	12.7	M22x1.5	14	70	46	22	27
10C46-16-8	10C48-16-8	12	1/2	-8	12.7	M24x1.5	16	72	49	23	30
10C46-16-10	10C48-16-10	16	5/8	-10	15.9	M24x1.5	16	77	52	24	30
10C46-20-10	10C48-20-10	16	5/8	-10	15.9	M30x2	20	76	51	25	36
10C46-20-12	10C48-20-12	19	3/4	-12	19.1	M30x2	20	90	64	28	36
10C46-25-12	10C48-25-12	19	3/4	-12	19.1	M36x2	25	91	65	29	46
	10C48-30-12	19	3/4	-12	19.1	M42x2	30	93	67	31	50
	10C48-25-16	25	1	-16	25.4	M36x2	30	109	81	33	46
10C46-25-16		25	1	-16	25.4	M36x2	25	109	80	33	46
10C46-30-16	10C48-30-16	25	1	-16	25.4	M42x2	30	115	86	36	50
10C46-38-20		31	1 1/4	-20	31.8	M52x2	38	136	98	38	60
	10C48-38-20	31	1 1/4	-20	31.8	M52x2	38	140	93	37	60
	10C48-38-24	38	1 1/2	-24	38.1	M52x2	38	155	117	49	60

Hose fittings are delivered with ozone resistant Nitrile (NBR) O-ring as a standard version. Working temperature from -40 °C up to +105 °C.
Hose fittings with special O-rings (Viton or EPDM) available on request. O-ring dimensions and part-numbers see in section Eb.

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or **48** 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC


46 463 | 492 | 492ST | 492TC | 692 | 692TWIN


48 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...

471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

1C Female Metric 24° – Swivel Heavy Series with O-Ring 90° Elbow

ISO 12151-2-SWE-S – DKOS 90°





Part Number		Hose I.D.				Thread	Tube O.D.	A	B	E	W
46 series	48 series	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
11C46-6-4	11C48-6-4	6	1/4	-4	6.4	M14x1.5	6	62	39	32	17
11C46-8-4	11C48-8-4	6	1/4	-4	6.4	M16x1.5	8	50	26	29	19
11C46-10-4	11C48-10-4	6	1/4	-4	6.4	M18x1.5	10	50	26	29	22
11C46-12-4	11C48-12-4	6	1/4	-4	6.4	M20x1.5	12	60	38	30	24
11C46-10-5	11C48-10-5	8	5/16	-5	7.9	M18x1.5	10	60	36	31	22
11C46-12-5	11C48-12-5	8	5/16	-5	7.9	M20x1.5	12	60	36	32	24
11C46-10-6	11C48-10-6	10	3/8	-6	9.5	M18x1.5	10	59	37	36	22
11C46-12-6	11C48-12-6	10	3/8	-6	9.5	M20x1.5	12	58	35	37	24
11C46-14-6	11C48-14-6	10	3/8	-6	9.5	M22x1.5	14	58	35	37	27
	11C48-16-6	10	3/8	-6	9.5	M24x1.5	16	63	38	40	30
	11C48-12-8	12	1/2	-8	12.7	M20x1.5	12	63	39	44	24
11C46-14-8	11C48-14-8	12	1/2	-8	12.7	M22x1.5	14	62	38	42	27
11C46-16-8	11C48-16-8	12	1/2	-8	12.7	M24x1.5	16	61	37	45	30
11C46-20-8	11C48-20-8	12	1/2	-8	12.7	M30x2	20	61	37	46	36
11C46-16-10	11C48-16-10	16	5/8	-10	15.9	M24x1.5	16	66	41	48	30
11C46-20-10	11C48-20-10	16	5/8	-10	15.9	M30x2	20	65	40	48	36
11C46-25-10	11C48-25-10	16	5/8	-10	15.9	M36x2	25	76	51	52	46
11C46-20-12	11C48-20-12	19	3/4	-12	19.1	M30x2	20	79	54	58	36
11C46-25-12	11C48-25-12	19	3/4	-12	19.1	M36x2	25	80	54	59	46
	11C48-30-12	19	3/4	-12	19.1	M42x2	30	80	54	61	50
11C46-25-16	11C48-25-16	25	1	-16	25.4	M36x2	25	102	72	71	46
11C46-30-16	11C48-30-16	25	1	-16	25.4	M42x2	30	104	75	75	50
	11C48-38-16	25	1	-16	25.4	M52x2	38	105	75	75	60
11C46-38-16		25	1	-16	25.4	M52x2	38	105	75	75	60
	11C48-30-20	31	1 1/4	-20	31.8	M42x2	30	130	83	86	50
	11C48-38-20	31	1 1/4	-20	31.8	M52x2	38	130	83	78	60
11C46-38-20		31	1 1/4	-20	31.8	M52x2	38	124	86	80	60
	11C48-38-24	38	1 1/2	-24	38.1	M52x2	38	139	101	101	60

Hose fittings are delivered with ozone resistant Nitrile (NBR) O-ring as a standard version. Working temperature from -40 °C up to +105 °C.
Hose fittings with special O-rings (Viton or EPDM) available on request. O-ring dimensions and part-numbers see in section Eb.


Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or 48	441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC
46	463 | 492 | 492ST | 492TC | 692 | 692TWIN
48	301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...
	471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

D2 Male Metric 24° – Rigid Heavy Series – Straight

ISO 12151-2-S-S – CES





Part Number		Hose I.D.				Thread	Tube O.D.	A	B	H
46 series	48 series	DN	Inch	Size	mm	metric	mm	mm	mm	mm
1D246-6-4	1D248-6-4	6	1/4	-4	6.4	M14x1.5	6	48	24	14
1D246-8-4	1D248-8-4	6	1/4	-4	6.4	M16x1.5	8	48	24	17
1D246-10-4	1D248-10-4	6	1/4	-4	6.4	M18x1.5	10	50	26	19
1D246-12-4	1D248-12-4	6	1/4	-4	6.4	M20x1.5	12	48	26	22
1D246-8-5	1D248-8-5	8	5/16	-5	7.9	M16x1.5	8	48	24	17
1D246-10-5	1D248-10-5	8	5/16	-5	7.9	M18x1.5	10	50	26	19
1D246-12-5	1D248-12-5	8	5/16	-5	7.9	M20x1.5	12	50	26	22
1D246-14-5	1D248-14-5	8	5/16	-5	7.9	M22x1.5	14	51	28	22
	1D248-16-5	8	5/16	-5	7.9	M24x1.5	16	53	29	24
1D246-10-6	1D248-10-6	10	3/8	-6	9.5	M18x1.5	10	50	27	19
1D246-12-6	1D248-12-6	10	3/8	-6	9.5	M20x1.5	12	49	26	22
1D246-14-6	1D248-14-6	10	3/8	-6	9.5	M22x1.5	14	51	28	22
1D246-12-8	1D248-12-8	12	1/2	-8	12.7	M20x1.5	12	49	26	22
	1D248-14-8	12	1/2	-8	12.7	M22x1.5	14	52	28	22
1D246-16-8	1D248-16-8	12	1/2	-8	12.7	M24x1.5	16	52	29	24
	1D248-20-8	12	1/2	-8	12.7	M30x2	20	58	35	30
1D246-16-10	1D248-16-10	16	5/8	-10	15.9	M24x1.5	16	58	30	24
1D246-20-10	1D248-20-10	16	5/8	-10	15.9	M30x2	20	58	32	30
	1D248-16-12	19	3/4	-12	19.1	M24x1.5	16	56	31	27
1D246-20-12	1D248-20-12	19	3/4	-12	19.1	M30x2	20	61	35	30
1D246-25-12	1D248-25-12	19	3/4	-12	19.1	M36x2	25	64	38	36
1D246-25-16	1D248-25-16	25	1	-16	25.4	M36x2	25	68	39	36
1D246-30-16	1D248-30-16	25	1	-16	25.4	M42x2	30	71	42	46
1D246-38-20		31	1 1/4	-20	31.8	M52x2	38	84	46	55
	1D248-38-20	31	1 1/4	-20	31.8	M52x2	38	91	44	55
	1D248-38-24	38	1 1/2	-24	38.1	M52x2	38	84	46	55

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or **48** 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC


46 463 | 492 | 492ST | 492TC | 692 | 692TWIN


48 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...

471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

C6 Female Metric – Swivel Heavy Series – Straight (Ball Nose)

DKS







Part Number		Hose I.D.				Thread	Tube O.D.	A	B	H
46 series	48 series	DN	Inch	Size	mm	metric	mm	mm	mm	mm
	1C648-8-4	6	1/4	-4	6.4	M16x1.5	8	46	23	19
	1C648-12-6	10	3/8	-6	9.5	M20x1.5	12	47	25	24
	1C648-14-6	10	3/8	-6	9.5	M22x1.5	14	47	24	27
	1C648-16-8	12	1/2	-8	12.7	M24x1.5	16	51	28	30

49 Metric Banjo Straight

DIN 7642





Part Number		Hose I.D.				A	B	D
46 series	48 series	DN	Inch	Size	mm	mm	mm	mm
14946-10-4	14948-10-4	6	1/4	-4	6.4	47	24	10
14946-12-4	14948-12-4	6	1/4	-4	6.4	50	26	12
14946-14-4	14948-14-4	6	1/4	-4	6.4	51	28	14
	14948-16-4	6	1/4	-4	6.4	55.6	29	16.1
14946-14-5	14948-14-5	8	5/16	-5	7.9	51	28	14
14946-16-5	14948-16-5	8	5/16	-5	7.9	53	30	16
14946-16-6	14948-16-6	10	3/8	-6	9.5	53	30	16
14946-17-6	14948-17-6	10	3/8	-6	9.5	53	30	17
14946-18-6	14948-18-6	10	3/8	-6	9.5	55	32	18
14946-22-6	14948-22-6	10	3/8	-6	9.5	58	35	22
14946-18-8	14948-18-8	12	1/2	-8	12.7	56	32	18
14946-22-8	14948-22-8	12	1/2	-8	12.7	59	35	22
14946-22-10	14948-22-10	16	5/8	-10	15.9	60	35	22
14946-26-12	14948-26-12	19	3/4	-12	19.1	66	40	26
14946-27-12	14948-27-12	19	3/4	-12	19.1	66	40	27

To select corresponding screw and seals see section Eb.


Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or 48	441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC
46	463 | 492 | 492ST | 492TC | 692 | 692TWIN
48	301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...
	471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

92 Female BSP Parallel Pipe Swivel – Straight (60° Cone)

BS5200-A – DKR





Part Number		Hose I.D.				Thread	A	B	W
46 series	48 series	DN	Inch	Size	mm	BSP	mm	mm	mm
19246-2-4	19248-2-4	6	1/4	-4	6.4	1/8x28	41	17	14
	19248-4-4	6	1/4	-4	6.4	1/4x19	43	19	19
19246-4-4		6	1/4	-4	6.4	1/4x19	46	19	19
19246-6-4	19248-6-4	6	1/4	-4	6.4	3/8x19	44	20	22
19246-8-4	19248-8-4	6	1/4	-4	6.4	1/2x14	49	25	27
19246-4-5	19248-4-5	8	5/16	-5	7.9	1/4x19	43	19	19
19246-6-5	19248-6-5	8	5/16	-5	7.9	3/8x19	44	20	22
19246-4-6	19248-4-6	10	3/8	-6	9.5	1/4x19	43	20	19
19246-6-6	19248-6-6	10	3/8	-6	9.5	3/8x19	43	20	22
19246-8-6	19248-8-6	10	3/8	-6	9.5	1/2x14	45	22	27
19246-6-8	19248-6-8	12	1/2	-8	12.7	3/8x19	45	21	22
19246-8-8	19248-8-8	12	1/2	-8	12.7	1/2x14	45	22	27
19246-10-8	19248-10-8	12	1/2	-8	12.7	5/8x14	44	20	30
19246-12-8	19248-12-8	12	1/2	-8	12.7	3/4x14	47	23	32
19246-8-10	19248-8-10	16	5/8	-10	15.9	1/2x14	48	22	27
19246-10-10	19248-10-10	16	5/8	-10	15.9	5/8x14	45	20	30
19246-12-10	19248-12-10	16	5/8	-10	15.9	3/4x14	47	22	32
19246-8-12	19248-8-12	19	3/4	-12	19.1	1/2x14	49	23	27
19246-10-12	19248-10-12	19	3/4	-12	19.1	5/8x14	47	22	30
19246-12-12	19248-12-12	19	3/4	-12	19.1	3/4x14	49	23	32
19246-16-12	19248-16-12	19	3/4	-12	19.1	1x11	51	25	41
19246-16-16	19248-16-16	25	1	-16	25.4	1x11	55	25	41
	19248-20-16	25	1	-16	25.4	1 1/4x11	63	31	50
19246-20-16		25	1	-16	25.4	1 1/4x11	61	31	50
	19248-20-20	31	1 1/4	-20	31.8	1 1/4x11	79	32	50
19246-20-20		31	1 1/4	-20	31.8	1 1/4x11	68	31	50
	19248-24-24	38	1 1/2	-24	38.1	1 1/2x11	71	33	60
	19248-32-32	51	2	-32	50.8	2x11	84	35	70

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or **48** 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC


46 463 | 492 | 492ST | 492TC | 692 | 692TWIN


48 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...

471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

B1 Female BSP Parallel Pipe Swivel 45° Elbow (60° Cone)

BS 5200-D – DKR 45°





Part Number		Hose I.D.				Thread	A	B	E	W
46 series	48 series	DN	Inch	Size	mm	BSP	mm	mm	mm	mm
	1B148-4-4	6	1/4	-4	6.4	1/4x19	58	35	16	19
1B146-4-4		6	1/4	-4	6.4	1/4x19	59	35	16	19
1B146-6-4	1B148-6-4	6	1/4	-4	6.4	3/8x19	59	35	14	22
1B146-6-5	1B148-6-5	8	5/16	-5	7.9	3/8x19	60	36	15	22
1B146-6-6	1B148-6-6	10	3/8	-6	9.5	3/8x19	69	46	17	22
1B146-8-6	1B148-8-6	10	3/8	-6	9.5	1/2x14	63	40	17	27
1B146-6-8	1B148-6-8	12	1/2	-8	12.7	3/8x19	72	49	21	22
1B146-8-8	1B148-8-8	12	1/2	-8	12.7	1/2x14	72	48	20	27
1B146-10-8	1B148-10-8	12	1/2	-8	12.7	5/8x14	69	46	19	30
1B146-10-10	1B148-10-10	16	5/8	-10	15.9	5/8x14	77	52	22	30
1B146-12-10	1B148-12-10	16	5/8	-10	15.9	3/4x14	74	49	20	32
1B146-12-12	1B148-12-12	19	3/4	-12	19.1	3/4x14	87	61	25	32
1B146-16-12	1B148-16-12	19	3/4	-12	19.1	1x11	88	62	26	41
1B146-16-16	1B148-16-16	25	1	-16	25.4	1x11	107	78	33	41
	1B148-20-20	31	1 1/4	-20	31.8	1 1/4x11	141	94	38	50
1B146-20-20		31	1 1/4	-20	31.8	1 1/4x11	136	98	38	50
	1B148-24-24	38	1 1/2	-24	38.1	1 1/2x11	160	122	52	55
	1B148-32-32	51	2	-32	50.8	2x11	210	161	66	70


Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or 48	441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC
46	463 | 492 | 492ST | 492TC | 692 | 692TWIN
48	301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...
	471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

B2 Female BSP Parallel Pipe Swivel 90° Elbow (60° Cone)

BS 5200-B – DKR 90°





Part Number		Hose I.D.				Thread	A	B	E	W
46 series	48 series	DN	Inch	Size	mm	BSP	mm	mm	mm	mm
1B246-2-4	1B248-2-4	6	1/4	-4	6.4	1/8x28	50	26	30	14
1B246-4-4	1B248-4-4	6	1/4	-4	6.4	1/4x19	50	26	28	19
	1B248-6-4	6	1/4	-4	6.4	3/8x19	51	27	27	22
1B246-6-4		6	1/4	-4	6.4	3/8x19	51	27	28	22
1B246-8-4	1B248-8-4	6	1/4	-4	6.4	1/2x14	51	27	29	27
1B246-6-5	1B248-6-5	8	5/16	-5	7.9	3/8x19	52	28	28	22
1B246-6-6	1B248-6-6	10	3/8	-6	9.5	3/8x19	61	38	33	22
1B246-8-6	1B248-8-6	10	3/8	-6	9.5	1/2x14	60	38	36	27
1B246-6-8	1B248-6-8	12	1/2	-8	12.7	3/8x19	63	40	41	22
1B246-8-8	1B248-8-8	12	1/2	-8	12.7	1/2x14	63	40	41	27
1B246-10-8	1B248-10-8	12	1/2	-8	12.7	5/8x14	67	43	38	30
1B246-10-10	1B248-10-10	16	5/8	-10	15.9	5/8x14	70	45	44	30
1B246-12-10	1B248-12-10	16	5/8	-10	15.9	3/4x14	70	45	42	32
1B246-12-12	1B248-12-12	19	3/4	-12	19.1	3/4x14	80	54	53	32
1B246-16-12	1B248-16-12	19	3/4	-12	19.1	1x11	80	54	54	41
1B246-16-16	1B248-16-16	25	1	-16	25.4	1x11	104	75	69	41
1B246-20-20		31	1 1/4	-20	31.8	1 1/4x11	124	86	80	50
	1B248-20-20	31	1 1/4	-20	31.8	1 1/4x11	129	82	80	50
	1B248-24-24	38	1 1/2	-24	38.1	1 1/2x11	140	102	103	55
	1B248-32-32	51	2	-32	50.8	2x11	185	137	134	70

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or **48** 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC


46 463 | 492 | 492ST | 492TC | 692 | 692TWIN


48 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...

471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

B4 Female BSP Parallel Pipe Swivel – 90° Elbow Block Type (60° Cone)

BS 5200-E – DKR 90°





Part Number		Hose I.D.				Thread	A	B	E	H	W
46 series	48 series	DN	Inch	Size	mm	BSP	mm	mm	mm	mm	mm
1B446-4-4	1B448-4-4	6	1/4	-4	6.4	1/4x19	58	34	22	17	19
1B446-6-4	1B448-6-4	6	1/4	-4	6.4	3/8x19	43	20	22	17	22
1B446-6-6	1B448-6-6	10	3/8	-6	9.5	3/8x19	68	45	23	19	22
1B446-8-6	1B448-8-6	10	3/8	-6	9.5	1/2x14	67	44	27	22	27
1B446-8-8	1B448-8-8	12	1/2	-8	12.7	1/2x14	67	43	27	22	27
1B446-10-10	1B448-10-10	16	5/8	-10	15.9	5/8x14	69	44	27	27	30
1B446-12-12	1B448-12-12	19	3/4	-12	19.1	3/4x14	72	47	33	32	32
1B446-16-16	1B448-16-16	25	1	-16	25.4	1x11	82	52	34	36	41

Short version available upon request (swaging on universal crimpers only)

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or 48 | 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC

46 | 463 | 492 | 492ST | 492TC | 692 | 692TWIN


48 | 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...


471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

EA

BSP Swivel Female with O–Ring (60° Cone)

BS 5200 – ISO 12151-6 – DKOR





Part Number		Hose I.D.				Thread	A	B	W
46 series	48 series	DN	Inch	Size	mm	BSP	mm	mm	mm
1EA46-4-4	1EA48-4-4	6	1/4	-4	6.4	1/4x19	40	17	19
1EA46-6-4	1EA48-6-4	6	1/4	-4	6.4	3/8x19	49	26	22
	1EA48-6-5	8	5/16	-5	7.9	3/8x19	50	25	22
	1EA48-4-6	10	3/8	-6	9.5	1/4x19	44	21	19
1EA46-6-6	1EA48-6-6	10	3/8	-6	9.5	3/8x19	43	20	22
1EA46-8-6	1EA48-8-6	10	3/8	-6	9.5	1/2x14	51	28	27
	1EA48-6-8	12	1/2	-8	12.7	3/8x19	46	22	22
1EA46-8-8	1EA48-8-8	12	1/2	-8	12.7	1/2x14	45	22	27
	1EA48-10-8	12	1/2	-8	12.7	5/8x14	43	20	30
1EA46-10-10	1EA48-10-10	16	5/8	-10	15.9	5/8x14	46	21	30
1EA46-12-10	1EA48-12-10	16	5/8	-10	15.9	3/4x14	54	29	32
1EA46-12-12	1EA48-12-12	19	3/4	-12	19.1	3/4x14	49	23	32
1EA46-16-12	1EA48-16-12	19	3/4	-12	19.1	1x11	61	35	41
1EA46-16-16	1EA48-16-16	25	1	-16	25.4	1x11	61	31	41
	1EA48-20-20	31	1 1/4	-20	31.8	1 1/4x11	78	31	50
	1EA48-24-24	38	1 1/2	-24	38.1	1 1/2x11	72	34	55

Hose fittings are delivered with ozone resistant Nitrile (NBR) O-ring as a standard version. Working temperature from -40 °C up to +105 °C.
Hose fittings with special O-rings (Viton or EPDM) available on request. O-ring dimensions and part-numbers see in section Eb.

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or 48 | 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC

46 | 463 | 492 | 492ST | 492TC | 692 | 692TWIN


48 | 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...


471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

EB

BSP Swivel Female with O–Ring 45° Elbow (60° Cone)

BS 5200 – ISO 12151-6 – DKOR 45°





Part Number		Hose I.D.				Thread	A	B	E	W
46 series	48 series	DN	Inch	Size	mm	BSP	mm	mm	mm	mm
	1EB48-4-4	6	1/4	-4	6.4	1/4x19	57	34	14	19
1EB46-4-4		6	1/4	-4	6.4	1/4x19	59	36	14	19
1EB46-6-6	1EB48-6-6	10	3/8	-6	9.5	3/8x19	69	46	17	22
1EB46-8-8	1EB48-8-8	12	1/2	-8	12.7	1/2x14	71	48	20	27
1EB46-12-10	1EB48-12-10	16	5/8	-10	15.9	3/4x14	78	52	21	32
1EB46-12-12	1EB48-12-12	19	3/4	-12	19.1	3/4x14	89	63	27	32
1EB46-16-16	1EB48-16-16	25	1	-16	25.4	1x11	112	82	33	41
	1EB48-20-20	31	1 1/4	-20	31.8	1 1/4x11	138	91	35	50
	1EB48-24-24	38	1 1/2	-24	38.1	1 1/2x11	146	108	38	55

Hose fittings are delivered with ozone resistant Nitrile (NBR) O-ring as a standard version. Working temperature from -40 °C up to +105 °C.
Hose fittings with special O-rings (Viton or EPDM) available on request. O-ring dimensions and part-numbers see in section Eb.

Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK


46 or 48	441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC
46	463 | 492 | 492ST | 492TC | 692 | 692TWIN
48	301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...
	471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

EC

BSP Swivel Female with O–Ring 90° Elbow (60° Cone)

BS 5200 – ISO 12151-6 – DKOR 90°





Part Number		Hose I.D.				Thread	A	B	E	W
46 series	48 series	DN	Inch	Size	mm	BSP	mm	mm	mm	mm
1EC46-4-4	1EC48-4-4	6	1/4	-4	6.4	1/4x19	50	27	24	19
1EC46-6-4	1EC48-6-4	6	1/4	-4	6.4	3/8x19	51	28	27	22
1EC46-6-6	1EC48-6-6	10	3/8	-6	9.5	3/8x19	60	38	33	22
1EC46-8-6	1EC48-8-6	10	3/8	-6	9.5	1/2x14	60	38	36	27
	1EC48-6-8	12	1/2	-8	12.7	3/8x19	63	39	41	22
1EC46-8-8	1EC48-8-8	12	1/2	-8	12.7	1/2x14	63	40	40	27
1EC46-10-8	1EC48-10-8	12	1/2	-8	12.7	5/8x14	63	40	39	30
1EC46-10-10	1EC48-10-10	16	5/8	-10	15.9	5/8x14	70	45	44	30
1EC46-12-10		16	5/8	-10	15.9	3/4x14	70	45	42	32
	1EC48-12-10	16	5/8	-10	15.9	5/8x14	70	45	42	32
1EC46-12-12	1EC48-12-12	19	3/4	-12	19.1	3/4x14	79	54	55	32
1EC46-16-12	1EC48-16-12	19	3/4	-12	19.1	1x11	80	54	59	41
1EC46-16-16	1EC48-16-16	25	1	-16	25.4	1x11	105	75	71	41
	1EC48-20-20	31	1 1/4	-20	31.8	1 1/4x11	129	82	75	50
	1EC48-24-24	38	1 1/2	-24	38.1	1 1/2x11	140	102	103	55
	1EC48-32-32	51	2	-32	50.8	2x11	185	137	132	70

Hose fittings are delivered with ozone resistant Nitrile (NBR) O-ring as a standard version. Working temperature from -40 °C up to +105 °C.
Hose fittings with special O-rings (Viton or EPDM) available on request. O-ring dimensions and part-numbers see in section Eb.

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or **48** 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC


46 463 | 492 | 492ST | 492TC | 692 | 692TWIN


48 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...

471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

D9 Male BSP Parallel Pipe Rigid – Straight (60° Cone)

BS5200 – AGR





Part Number		Hose I.D.				Thread	A	B	H
46 series	48 series	DN	Inch	Size	mm	BSP	mm	mm	mm
1D946-2-4	1D948-2-4	6	1/4	-4	6.4	1/8x28	46	22	14
1D946-4-4	1D948-4-4	6	1/4	-4	6.4	1/4x19	51	27	19
1D946-6-4	1D948-6-4	6	1/4	-4	6.4	3/8x19	53	31	22
1D946-8-4	1D948-8-4	6	1/4	-4	6.4	1/2x14	54	52	27
1D946-4-5		8	5/16	-5	7.9	1/4x19	50	27	19
	1D948-4-5	8	5/16	-5	7.9	1/4x19	49	27	19
1D946-6-5	1D948-6-5	8	5/16	-5	7.9	3/8x19	55	31	22
1D946-4-6		10	3/8	-6	9.5	1/4x19	49	27	19
	1D948-4-6	10	3/8	-6	9.5	1/4x19	50	27	19
1D946-6-6	1D948-6-6	10	3/8	-6	9.5	3/8x19	54	31	22
1D946-8-6	1D948-8-6	10	3/8	-6	9.5	1/2x14	56	33	27
1D946-6-8	1D948-6-8	12	1/2	-8	12.7	3/8x19	54	30	22
1D946-8-8	1D948-8-8	12	1/2	-8	12.7	1/2x14	57	33	27
1D946-10-8	1D948-10-8	12	1/2	-8	12.7	5/8x14	58	35	30
1D946-12-8	1D948-12-8	12	1/2	-8	12.7	3/4x14	60	36	32
1D946-8-10	1D948-8-10	16	5/8	-10	15.9	1/2x14	58	33	27
1D946-10-10	1D948-10-10	16	5/8	-10	15.9	5/8x14	60	35	30
1D946-12-10	1D948-12-10	16	5/8	-10	15.9	3/4x14	62	37	32
1D946-12-12	1D948-12-12	19	3/4	-12	19.1	3/4x14	62	36	32
1D946-16-12	1D948-16-12	19	3/4	-12	19.1	1x11	67	41	41
1D946-16-16	1D948-16-16	25	1	-16	25.4	1x11	72	42	41
1D946-20-16	1D948-20-16	25	1	-16	25.4	1 1/4x11	75	46	50
1D946-20-20		31	1 1/4	-20	31.8	1 1/4x11	85	47	50
	1D948-20-20	31	1 1/4	-20	31.8	1 1/4x11	92	45	50
	1D948-24-24	38	1 1/2	-24	38.1	1 1/2x11	87	49	60
	1D948-32-32	51	2	-32	50.8	2x11	102	54	70


Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or 48	441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC
46	463 | 492 | 492ST | 492TC | 692 | 692TWIN
48	301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...
	471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

91 Male BSP Taper Pipe – Rigid Straight


BS5200 – AGR-K






Part Number		Hose I.D.				Thread	A	B	H
46 series	48 series	DN	Inch	Size	mm	BSP	mm	mm	mm
19146-4-4	19148-4-4	6	1/4	-4	6.4	1/4x19	49	26	14
	19148-6-4	6	1/4	-4	6.4	3/8x19	51	28	17
19146-4-5	19148-4-5	8	5/16	-5	7.9	1/4x19	49	25	14
19146-6-5	19148-6-5	8	5/16	-5	7.9	3/8x19	48	24	19
	19148-4-6	10	3/8	-6	9.5	1/4x19	46	24	14
19146-6-6	19148-6-6	10	3/8	-6	9.5	3/8x19	52	27	19
19146-8-6	19148-8-6	10	3/8	-6	9.5	1/2x14	57	34	22
	19148-6-8	12	1/2	-8	12.7	3/8x19	48	25	19
19146-8-8	19148-8-8	12	1/2	-8	12.7	1/2x14	57	33	22
	19148-12-10	16	5/8	-10	15.9	3/4x14	63	37	30
19146-12-12	19148-12-12	19	3/4	-12	19.1	3/4x14	63	37	30
19146-16-16	19148-16-16	25	1	-16	25.4	1x11	72	42	36

B5 Female BSP Parallel Pipe Swivel Straight (Flat Seat)





Part Number		Hose I.D.				Thread	A	B	W
46 series	48 series	DN	Inch	Size	mm	BSP	mm	mm	mm
1B546-4-4	1B548-4-4	6	1/4	-4	6.4	1/4x19	41	17	19
1B546-4-5	1B548-4-5	8	5/16	-5	7.9	1/4x19	41	17	19
1B546-6-5	1B548-6-5	8	5/16	-5	7.9	3/8x19	38	14	22
1B546-8-5	1B548-8-5	8	5/16	-5	7.9	1/2x14	44	21	27
1B546-6-6	1B548-6-6	10	3/8	-6	9.5	3/8x19	37	14	22
1B546-8-6	1B548-8-6	10	3/8	-6	9.5	1/2x14	43	20	27
1B546-8-8	1B548-8-8	12	1/2	-8	12.7	1/2x14	43	19	27
1B546-12-8	1B548-12-8	12	1/2	-8	12.7	3/4x14	43	19	32
1B546-12-10	1B548-12-10	16	5/8	-10	15.9	3/4x14	43	18	32
1B546-12-12	1B548-12-12	19	3/4	-12	19.1	3/4x14	44	18	32
1B546-16-16	1B548-16-16	25	1	-16	25.4	1x11	51	21	41

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or **48** 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC


46 463 | 492 | 492ST | 492TC | 692 | 692TWIN


48 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...

471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

01 Male NPTF Pipe Rigid – Straight

SAE J476A / J516 – AGN





Part Number		Hose I.D.				Thread	A	B	H
46 series	48 series	DN	Inch	Size	mm	NPTF	mm	mm	mm
10146-2-4	10148-2-4	6	1/4	-4	6.4	1/8x27	48	24	12
10146-4-4	10148-4-4	6	1/4	-4	6.4	1/4x18	53	29	14
10146-6-4	10148-6-4	6	1/4	-4	6.4	3/8x18	55	31	19
10146-4-5	10148-4-5	8	5/16	-5	7.9	1/4x18	53	29	14
10146-6-5	10148-6-5	8	5/16	-5	7.9	3/8x18	55	31	19
10146-4-6	10148-4-6	10	3/8	-6	9.5	1/4x18	52	29	14
10146-6-6	10148-6-6	10	3/8	-6	9.5	3/8x18	54	31	19
10146-8-6	10148-8-6	10	3/8	-6	9.5	1/2x14	55	32	22
10146-6-8	10148-6-8	12	1/2	-8	12.7	3/8x18	55	32	19
10146-8-8	10148-8-8	12	1/2	-8	12.7	1/2x14	61	38	22
10146-8-10	10148-8-10	16	5/8	-10	15.9	1/2x14	63	38	22
10146-12-10	10148-12-10	16	5/8	-10	15.9	3/4x14	59	34	27
10146-12-12	10148-12-12	19	3/4	-12	19.1	3/4x14	60	34	27
10146-16-16		25	1	-16	25.4	1x11 1/2	75	45	36
	10148-16-16	25	1	-16	25.4	1x11 1/2	75	45	36
	10148-20-20	31	1 1/4	-20	31.8	1 1/4x11 1/2	104	57	46
10146-20-20		31	1 1/4	-20	31.8	1 1/4x11 1/2	86	48	46
	10148-24-24	38	1 1/2	-24	38.1	1 1/2x11 1/2	89	51	50
	10148-32-32	51	2	-32	50.8	2x11 1/2	104	55	65

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or 48 — 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC


46 — 463 | 492 | 492ST | 492TC | 692 | 692TWIN


48 — 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...

471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

03 Male JIC 37° – Rigid Straight

ISO12151-5-S – AGJ





Part Number		Hose I.D.				Thread	A	B	H
46 series	48 series	DN	Inch	Size	mm	UNF	mm	mm	mm
10346-4-4	10348-4-4	6	1/4	-4	6.4	7/16x20	52	29	14
10346-5-4	10348-5-4	6	1/4	-4	6.4	1/2x20	52	29	14
10346-6-4	10348-6-4	6	1/4	-4	6.4	9/16x18	55	31	19
10346-5-5	10348-5-5	8	5/16	-5	7.9	1/2x20	50	26	14
10346-6-5	10348-6-5	8	5/16	-5	7.9	9/16x18	55	31	19
10346-8-5	10348-8-5	8	5/16	-5	7.9	3/4x16	57	33	19
10346-4-6	10348-4-6	10	3/8	-6	9.5	7/16x20	54	31	19
10346-5-6	10348-5-6	10	3/8	-6	9.5	1/2x20	53	30	19
10346-6-6	10348-6-6	10	3/8	-6	9.5	9/16x18	56	31	19
10346-8-6	10348-8-6	10	3/8	-6	9.5	3/4x16	53	30	22
10346-10-6	10348-10-6	10	3/8	-6	9.5	7/8x14	56	33	24
10346-8-8	10348-8-8	12	1/2	-8	12.7	3/4x16	57	34	22
10346-10-8	10348-10-8	12	1/2	-8	12.7	7/8x14	56	32	24
10346-12-8	10348-12-8	12	1/2	-8	12.7	1 1/16x12	62	38	27
10346-10-10	10348-10-10	16	5/8	-10	15.9	7/8x14	63	38	24
10346-12-10	10348-12-10	16	5/8	-10	15.9	1 1/16x12	64	39	27
10346-12-12	10348-12-12	19	3/4	-12	19.1	1 1/16x12	68	42	27
10346-14-12	10348-14-12	19	3/4	-12	19.1	1 3/16x12	68	42	30
10346-16-12	10348-16-12	19	3/4	-12	19.1	1 5/16x12	64	38	36
10346-16-16	10348-16-16	25	1	-16	25.4	1 5/16x12	76	46	36
10346-20-16	10348-20-16	25	1	-16	25.4	1 5/8x12	73	43	46
	10348-20-20	31	1 1/4	-20	31.8	1 5/8x12	101	53	46
10346-20-20		31	1 1/4	-20	31.8	1 5/8x12	86	48	46
	10348-24-24	38	1 1/2	-24	38.1	1 7/8x12	85	47	50
	10348-32-32	51	2	-32	50.8	2 1/2x12	109	61	65

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or **48** 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC


46 463 | 492 | 492ST | 492TC | 692 | 692TWIN


48 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...

471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

05 Male SAE Straight Thread with O–Ring – Rigid Straight

ISO 11926 – SAE J516





Part Number		Hose I.D.				Thread	A	B	H
46 series	48 series	DN	Inch	Size	mm	UNF	mm	mm	mm
	10548-6-6	10	3/8	-6	9.5	9/16 18	47	24	17
10546-8-6	10548-8-6	10	3/8	-6	9.5	3/4x16	48	25	22
10546-8-8	10548-8-8	12	1/2	-8	12.7	3/4x16	52	28	22
10546-10-8	10548-10-8	12	1/2	-8	12.7	7/8x14	49	26	27

To select corresponding O-ring see section Eb.

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or **48** 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC


46 463 | 492 | 492ST | 492TC | 692 | 692TWIN


48 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...

471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

06/68 Female – JIC 37° SAE 45° Dual Flare Swivel – Straight

ISO12151-5-SWS – DKJ





Part Number		Hose I.D.				Thread	A	B	H	W
46 series	48 series	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
16846-4-4	16848-4-4	6	1/4	-4	6.4	7/16x20	52	29	14	17
16846-5-4		6	1/4	-4	6.4	1/2x20	53	30	14	17
	16848-5-4	6	1/4	-4	6.4	1/2x20	54	30	14	17
10646-6-4	10648-6-4	6	1/4	-4	6.4	9/16x18	55	31	14	19
16846-5-5		8	5/16	-5	7.9	1/2x20	54	31	14	17
	16848-5-5	8	5/16	-5	7.9	1/2x20	54	30	14	17
10646-6-5	10648-6-5	8	5/16	-5	7.9	9/16x18	53	29	14	19
16846-8-5	16848-8-5	8	5/16	-5	7.9	3/4x16	57	34	17	22
16846-4-6	16848-4-6	10	3/8	-6	9.5	7/16x20	50	27	14	17
	16848-5-6	10	3/8	-6	9.5	1/2x20	52	29	14	17
16846-5-6		10	3/8	-6	9.5	1/2x20	51	29	14	17
10646-6-6	10648-6-6	10	3/8	-6	9.5	9/16x18	52	30	17	19
16846-8-6	16848-8-6	10	3/8	-6	9.5	3/4x16	56	34	17	22
16846-10-6	16848-10-6	10	3/8	-6	9.5	7/8x14	59	36	22	27
10646-6-8	10648-6-8	12	1/2	-8	12.7	9/16x18	55	32	22	19
16846-8-8	16848-8-8	12	1/2	-8	12.7	3/4x16	56	32	22	22
16846-10-8	16848-10-8	12	1/2	-8	12.7	7/8x14	62	38	22	27
10646-12-8	10648-12-8	12	1/2	-8	12.7	1 1/16x12	62	39	27	32
16846-8-10	16848-8-10	16	5/8	-10	15.9	3/4x16	57	32	22	22
16846-10-10	16848-10-10	16	5/8	-10	15.9	7/8x14	60	35	22	27
10646-12-10	10648-12-10	16	5/8	-10	15.9	1 1/16x12	64	39	27	32
16846-8-12	16848-8-12	19	3/4	-12	19.1	3/4x16	58	32	24	22
16846-10-12	16848-10-12	19	3/4	-12	19.1	7/8x14	61	35	24	27
10646-12-12	10648-12-12	19	3/4	-12	19.1	1 1/16x12	67	41	27	32
10646-14-12	10648-14-12	19	3/4	-12	19.1	1 3/16x12	68	42	30	36
10646-16-12	10648-16-12	19	3/4	-12	19.1	1 5/16x12	71	45	32	41
10646-12-16	10648-12-16	25	1	-16	25.4	1 1/16x12	73	44	32	32
10646-16-16	10648-16-16	25	1	-16	25.4	1 5/16x12	75	46	32	41
10646-20-16	10648-20-16	25	1	-16	25.4	1 5/8x12	80	50	41	50
	10648-16-20	31	1 1/4	-20	31.8	1 5/16x12	97	50	46	41
10646-16-20		31	1 1/4	-20	31.8	1 5/16x12	87	49	41	41
	10648-20-20	31	1 1/4	-20	31.8	1 5/8x12	100	53	46	50
10646-20-20		31	1 1/4	-20	31.8	1 5/8x12	89	51	46	50
	10648-24-24	38	1 1/2	-24	38.1	1 7/8x12	98	60	55	60
	10648-32-32	51	2	-32	50.8	2 1/2x12	120	72	65	75

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or **48** 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC


46 463 | 492 | 492ST | 492TC | 692 | 692TWIN


48 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...

471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

08 Female SAE 45° – Swivel Straight

SAE J516





Part Number		Hose I.D.				Thread	A	B	H	W
46 series	48 series	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
10846-6-6	10848-6-6	10	3/8	-6	9.5	5/8x18	57	34	19	19


Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or 48	441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC
46	463 | 492 | 492ST | 492TC | 692 | 692TWIN
48	301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...
	471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

37/3V Female JIC 37° SAE 45° – Dual Flare Swivel Female 45° Elbow

ISO 12151-5-SWE 45° – DKJ 45°





Part Number		Hose I.D.				Thread	A	B	E	W
46 series	48 series	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
13V46-4-4	13V48-4-4	6	1/4	-4	6.4	7/16x20	53	29	10	17
13V46-5-4	13V48-5-4	6	1/4	-4	6.4	1/2x20	57	33	9	17
13746-6-4	13748-6-4	6	1/4	-4	6.4	9/16x18	55	31	11	19
13V46-5-5	13V48-5-5	8	5/16	-5	7.9	1/2x20	53	29	10	17
13746-6-5	13748-6-5	8	5/16	-5	7.9	9/16x18	58	35	10	19
13746-6-6	13748-6-6	10	3/8	-6	9.5	9/16x18	60	37	11	19
13V46-8-6	13V48-8-6	10	3/8	-6	9.5	3/4x16	67	44	15	22
13V46-10-6	13V48-10-6	10	3/8	-6	9.5	7/8 14	69	46	17	27
13V46-8-8	13V48-8-8	12	1/2	-8	12.7	3/4x16	61	37	15	22
13V46-10-8	13V48-10-8	12	1/2	-8	12.7	7/8x14	70	46	16	27
13V46-10-10	13V48-10-10	16	5/8	-10	15.9	7/8x14	69	44	16	27
13746-12-10	13748-12-10	16	5/8	-10	15.9	1 1/16x12	74	49	21	32
13746-12-12	13748-12-12	19	3/4	-12	19.1	1 1/16x12	83	58	22	32
13746-14-12	13748-14-12	19	3/4	-12	19.1	1 3/16x12	84	58	22	36
13746-16-12	13748-16-12	19	3/4	-12	19.1	1 5/16x12	84	58	24	41
13746-12-16	13748-12-16	25	1	-16	25.4	1 1/16x12	91	61	21	32
13746-16-16	13748-16-16	25	1	-16	25.4	1 5/16x12	99	70	24	41
13746-20-16	13748-20-16	25	1	-16	25.4	1 5/8x12	101	71	26	50
	13748-20-20	31	1 1/4	-20	31.8	1 5/8x12	134	87	30	50
13746-20-20		31	1 1/4	-20	31.8	1 5/8x12	129	91	31	50
	13748-24-24	38	1 1/2	-24	38.1	1 7/8x12	165	127	58	60

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or 48 | 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC


46 | 463 | 492 | 492ST | 492TC | 692 | 692TWIN


48 | 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...

471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

39/3W Female JIC 37° SAE 45° – Dual Flare Swivel Female 90° Elbow

ISO 12151-5-SWES – DKJ 90°





Part Number		Hose I.D.				Thread	A	B	E	W
46 series	48 series	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
13W46-4-4	13W48-4-4	6	1/4	-4	6.4	7/16x20	48	24	21	17
13W46-5-4	13W48-5-4	6	1/4	-4	6.4	1/2x20	57	34	21	17
13946-6-4	13948-6-4	6	1/4	-4	6.4	9/16x18	49	25	23	19
13W46-5-5	13W48-5-5	8	5/16	-5	7.9	1/2x20	49	25	21	17
13946-6-5	13948-6-5	8	5/16	-5	7.9	9/16x18	51	28	23	19
13W46-4-6	13W48-4-6	10	3/8	-6	9.5	7/16x20	46	23	21	17
13946-6-6	13948-6-6	10	3/8	-6	9.5	9/16x18	51	28	23	19
13W46-8-6	13W48-8-6	10	3/8	-6	9.5	3/4x16	59	36	29	22
13W46-10-6	13W48-10-6	10	3/8	-6	9.5	7/8x14	61	38	32	27
13946-6-8	13948-6-8	12	1/2	-8	12.7	9/16x18	54	30	23	19
13W46-8-8	13W48-8-8	12	1/2	-8	12.7	3/4x16	55	31	29	22
13W46-10-8	13W48-10-8	12	1/2	-8	12.7	7/8x14	63	39	32	27
13W46-10-10	13W48-10-10	16	5/8	-10	15.9	7/8x14	64	39	33	27
13946-12-10	13948-12-10	16	5/8	-10	15.9	1 1/16x12	74	49	48	32
13946-12-12	13948-12-12	19	3/4	-12	19.1	1 1/16x12	80	54	48	32
13946-14-12	13948-14-12	19	3/4	-12	19.1	1 3/16x12	80	54	51	36
13946-16-12	13948-16-12	19	3/4	-12	19.1	1 5/16x12	80	54	56	41
13946-12-16	13948-12-16	25	1	-16	25.4	1 1/16x12	87	58	48	32
13946-16-16	13948-16-16	25	1	-16	25.4	1 5/16x12	98	68	56	41
13946-20-16	13948-20-16	25	1	-16	25.4	1 5/8x12	98	68	62	50
	13948-20-20	31	1 1/4	-20	31.8	1 5/8x12	129	82	70	50
13946-20-20		31	1 1/4	-20	31.8	1 5/8x12	124	86	70	50
	13948-24-24	38	1 1/2	-24	38.1	1 7/8x12	140	102	91	60


Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or 48	441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC
46	463 | 492 | 492ST | 492TC | 692 | 692TWIN
48	301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...
	471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

41/3Y Female JIC 37° / 45° Swivel Female 90° Elbow (Long)

ISO 12151-5-SWEL – DKJ 90°L





Part Number		Hose I.D.				Thread	A	B	E	W
46 series	48 series	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
13Y46-4-4	13Y48-4-4	6	1/4	-4	6.4	7/16x20	61	37	46	17
14146-6-4	14148-6-4	6	1/4	-4	6.4	9/16x18	57	34	55	19
14146-6-6	14148-6-6	10	3/8	-6	9.5	9/16x18	57	34	54	19
	13Y48-8-6	10	3/8	-6	9.5	3/4x16	55	32	62	22
13Y46-8-6		10	3/8	-6	9.5	3/4x16	59	36.5	62	22
13Y46-8-8	13Y48-8-8	12	1/2	-8	12.7	3/4x16	59	36	64	22
13Y46-10-10	13Y48-10-10	16	5/8	-10	15.9	7/8x14	61	36	70	27
14146-12-12	14148-12-12	19	3/4	-12	19.1	1 1/16x12	80	54	96	32
14146-16-16	14148-16-16	25	1	-16	25.4	1 5/16x12	98	68	110	41

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or **48** 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC


46 463 | 492 | 492ST | 492TC | 692 | 692TWIN


48 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...

471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

15 ISO 6162-1 Flange Straight

ISO 12151-3-S-L – SFL
(21.0 MPa/ 3000 psi)





Part Number		Hose I.D.				Flange	A	B	F
46 series	48 series	DN	Inch	Size	mm	Inch	mm	mm	mm
11546-8-8	11548-8-8	12	1/2	-8	12.7	1/2	74	50	30
11546-12-8	11548-12-8	12	1/2	-8	12.7	3/4	51	27	38
11546-12-10	11548-12-10	16	5/8	-10	15.9	3/4	55	30	38
11546-12-12	11548-12-12	19	3/4	-12	19.1	3/4	81	55	38
11546-16-12	11548-16-12	19	3/4	-12	19.1	1	56	30	45
11546-20-12	11548-20-12	19	3/4	-12	19.1	1 1/4	77	51	51
11546-16-16	11548-16-16	25	1	-16	25.4	1	84	54	45
11546-20-16	11548-20-16	25	1	-16	25.4	1 1/4	65	35	51
11546-24-16	11548-24-16	25	1	-16	25.4	1 1/2	97	67	60
	11548-16-20	31	1 1/4	-20	31.8	1	111	64	45
	11548-20-20	31	1 1/4	-20	31.8	1 1/4	119	72	51
11546-20-20		31	1 1/4	-20	31.8	1 1/4	114	76	51
	11548-24-20	31	1 1/4	-20	31.8	1 1/2	82	35	60
11546-24-20		31	1 1/4	-20	31.8	1 1/2	72	35	60
	11548-32-20	31	1 1/4	-20	31.8	2	123	76	71
	11548-24-24	38	1 1/2	-24	38.1	1 1/2	117	79	60
	11548-32-24	38	1 1/2	-24	38.1	2	80	42	71
	11548-24-32	51	2	-32	50.8	1 1/2	129	81	60
	11548-32-32	51	2	-32	50.8	2	127	79	71

To select corresponding half-flange and O-ring see section Eb.


Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or 48	441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC
46	463 | 492 | 492ST | 492TC | 692 | 692TWIN
48	301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...
	471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

17 ISO 6162-1 Flange 45° Elbow

ISO 12151-3 – E45 – L – SFL 45°
(21.0 MPa/ 3000 psi)





Part Number		Hose I.D.				Flange	A	B	E	F
46 series	48 series	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
11746-8-8	11748-8-8	12	1/2	-8	12.7	1/2	72	48	20	30
11746-12-8	11748-12-8	12	1/2	-8	12.7	3/4	70	47	21	38
11746-12-10	11748-12-10	16	5/8	-10	15.9	3/4	75	50	24	38
11746-12-12	11748-12-12	19	3/4	-12	19.1	3/4	88	62	26	38
11746-16-12	11748-16-12	19	3/4	-12	19.1	1	88	62	26	45
11746-20-12	11748-20-12	19	3/4	-12	19.1	1 1/4	87	61	25	51
	11748-16-16	25	1	-16	25.4	1	107	78	32	45
11746-16-16		25	1	-16	25.4	1	109	78	32	45
11746-20-16	11748-20-16	25	1	-16	25.4	1 1/4	109	79	32	51
	11748-16-20	31	1 1/4	-20	31.8	1	141	94	38	45
	11748-20-20	31	1 1/4	-20	31.8	1 1/4	141	94	38	51
11746-20-20		31	1 1/4	-20	31.8	1 1/4	136	98	38	51
	11748-24-20	31	1 1/4	-20	31.8	1 1/2	141	94	38	60
11746-24-20		31	1 1/4	-20	31.8	1 1/2	136	98	38	60
	11748-24-24	38	1 1/2	-24	38.1	1 1/2	151	113	44	60
	11748-32-24	38	1 1/2	-24	38.1	2	150	112	44	71
	11748-24-32	51	2	-32	50.8	1 1/2	153	105	36	60
	11748-32-32	51	2	-32	50.8	2	202	153	56	71

To select corresponding half-flange and O-ring see section Eb.

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or **48** 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC


46 463 | 492 | 492ST | 492TC | 692 | 692TWIN


48 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...

471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

19 ISO 6162-1 Flange 90° Elbow

ISO 12151-3 – E– L – SFL 90°
(21.0 MPa/ 3000 psi)





Part Number		Hose I.D.				Flange	A	B	E	F
46 series	48 series	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
11946-8-8	11948-8-8	12	1/2	-8	12.7	1/2	64	41	41	30
11946-12-8	11948-12-8	12	1/2	-8	12.7	3/4	70	47	43	38
11946-12-10	11948-12-10	16	5/8	-10	15.9	3/4	78	53	52	38
11946-16-10	11948-16-10	16	5/8	-10	15.9	1	78	53	53	45
11946-12-12	11948-12-12	19	3/4	-12	19.1	3/4	80	54	58	38
11946-16-12	11948-16-12	19	3/4	-12	19.1	1	80	54	58	45
11946-20-12	11948-20-12	19	3/4	-12	19.1	1 1/4	80	54	54	51
11946-12-16	11948-12-16	25	1	-16	25.4	3/4	98	68	70	38
11946-16-16	11948-16-16	25	1	-16	25.4	1	98	68	70	45
11946-20-16	11948-20-16	25	1	-16	25.4	1 1/4	102	72	70	51
	11948-24-16	25	1	-16	25.4	1 1/2	100	70	62	60
	11948-16-20	31	1 1/4	-20	31.8	1	129	82	90	45
11946-20-20		31	1 1/4	-20	31.8	1 1/4	124	86	90	51
	11948-20-20	31	1 1/4	-20	31.8	1 1/4	130	83	90	51
	11948-24-20	31	1 1/4	-20	31.8	1 1/2	129	82	90	60
11946-24-20		31	1 1/4	-20	31.8	1 1/2	124	86	90	60
	11948-32-20	31	1 1/4	-20	31.8	2	130	83	67	71
	11948-24-24	38	1 1/2	-24	38.1	1 1/2	149	111	104	60
	11948-32-24	38	1 1/2	-24	38.1	2	139	101	104	71
	11948-24-32	51	2	-32	50.8	1 1/2	154	106	104	60
	11948-32-32	51	2	-32	50.8	2	180	132	138	71

To select corresponding half-flange and O-ring see section Eb.

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or **48** 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC


46 463 | 492 | 492ST | 492TC | 692 | 692TWIN


48 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...

471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

6A ISO 6162-2 Flange Straight

ISO 12151-3-S-S – SFS
(42.0 MPa/ 6000 psi)







Part Number		Hose I.D.				Flange	A	B	F
46 series	48 series	DN	Inch	Size	mm	Inch	mm	mm	mm
16A46-8-8	16A48-8-8	12	1/2	-8	12.7	1/2	75	51	32
	16A48-12-10	16	5/8	-10	15.9	3/4	60	35	41
16A46-12-12	16A48-12-12	19	3/4	-12	19.1	3/4	96	70	41
16A46-12-16	16A48-12-16	25	1	-16	25.4	3/4	99	69	41
16A46-16-16	16A48-16-16	25	1	-16	25.4	1	111	81	48
16A46-20-20		31	1 1/4	-20	31.8	1 1/4	122	84	54
	16A48-20-20	31	1 1/4	-20	31.8	1 1/4	130	83	54
	16A48-24-24	38	1 1/2	-24	38.1	1 1/2	139	101	64
	16A48-32-32	51	2	-32	50.8	2	172	124	79

To select corresponding half-flange and O-ring see section Eb.

6F ISO 6162-2 Flange 45° Elbow – Heavy Series

ISO 12151-3 – E45-S – SFS 45°
(42.0 MPa/ 6000 psi)





Part Number		Hose I.D.				Flange	A	B	E	F
46 series	48 series	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
16F46-12-12	16F48-12-12	19	3/4	-12	19.1	3/4	88	62	26	41
16F46-16-16	16F48-16-16	25	1	-16	25.4	1	107	78	32	48
	16F48-20-20	31	1 1/4	-20	31.8	1 1/4	141	94	38	54
	16F48-24-24	38	1 1/2	-24	38.1	1 1/2	150	112	44	64
	16F48-32-32	51	2	-32	50.8	2	200	152	56	79

To select corresponding half-flange and O-ring see section Eb.

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or **48** 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC


46 463 | 492 | 492ST | 492TC | 692 | 692TWIN


48 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...

471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

6N ISO 6162-2 Flange 90° Elbow

ISO 12151-3 – E-S – SFS 90°
(42.0 MPa/ 6000 psi)





Part Number		Hose I.D.				Flange	A	B	E	F
46 series	48 series	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
16N46-8-12	16N48-8-12	19	3/4	-12	19.1	1/2	70	44	40	32
16N46-12-12	16N48-12-12	19	3/4	-12	19.1	3/4	80	54	54	41
16N46-16-12	16N48-16-12	19	3/4	-12	19.1	1	80	54	53	48
16N46-12-16	16N48-12-16	25	1	-16	25.4	3/4	88	58	70	41
16N46-16-16	16N48-16-16	25	1	-16	25.4	1	98	68	70	48
	16N48-20-20	31	1 1/4	-20	31.8	1 1/4	129	82	90	54
16N46-20-20		31	1 1/4	-20	31.8	1 1/4	124	86	90	54
	16N48-24-24	38	1 1/2	-24	38.1	1 1/2	139	101	104	64
	16N48-32-32	51	2	-32	50.8	2	186	138	138	79

To select corresponding half-flange and O-ring see section Eb.

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or 48 | 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC

46 | 463 | 492 | 492ST | 492TC | 692 | 692TWIN


48 | 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...


471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

JC

Female ORFS Swivel – Straight Short

ISO 12151-1 – SWSA
SAE J516 – ORFS





Part Number		Hose I.D.				Thread	A	B	H	W
46 series	48 series	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
1JC46-4-4	1JC48-4-4	6	1/4	-4	6.4	9/16x18	46	22	14	17
1JC46-6-4	1JC48-6-4	6	1/4	-4	6.4	11/16x16	45	23	17	22
1JC46-8-4	1JC48-8-4	6	1/4	-4	6.4	13/16x16	45	22	19	24
1JC46-6-5	1JC48-6-5	8	5/16	-5	7.9	11/16x16	47	23	17	22
1JC46-4-6	1JC48-4-6	10	3/8	-6	9.5	9/16x18	42	19	17	17
1JC46-6-6	1JC48-6-6	10	3/8	-6	9.5	11/16x16	43	21	17	22
1JC46-8-6	1JC48-8-6	10	3/8	-6	9.5	13/16x16	45	22	19	24
1JC46-6-8	1JC48-6-8	12	1/2	-8	12.7	11/16x16	44	20	17	22
1JC46-8-8	1JC48-8-8	12	1/2	-8	12.7	13/16x16	46	22	22	24
1JC46-10-8	1JC48-10-8	12	1/2	-8	12.7	1x14	48	24	24	30
1JC46-12-8	1JC48-12-8	12	1/2	-8	12.7	1 3/16x12	52	29	30	36
1JC46-8-10	1JC48-8-10	16	5/8	-10	15.9	13/16x16	47	22	22	24
1JC46-10-10	1JC48-10-10	16	5/8	-10	15.9	1x14	51	26	24	30
1JC46-12-10	1JC48-12-10	16	5/8	-10	15.9	1 3/16x12	54	28	30	36
1JC46-10-12	1JC48-10-12	19	3/4	-12	19.1	1x14	54	28	24	30
1JC46-12-12	1JC48-12-12	19	3/4	-12	19.1	1 3/16x12	55	29	30	36
1JC46-16-12	1JC48-16-12	19	3/4	-12	19.1	1 7/16x12	59	33	36	41
	1JC48-12-16	25	1	-16	25.4	1 3/16x12	60	30	32	36
1JC46-16-16	1JC48-16-16	25	1	-16	25.4	1 7/16x12	63	33	36	41
1JC46-20-16	1JC48-20-16	25	1	-16	25.4	1 11/16x12	62	32	41	50
1JC46-20-20		31	1 1/4	-20	31.8	1 11/16x12	71	33	41	50
	1JC48-20-20	31	1 1/4	-20	31.8	1 11/16x12	85	36	50	50

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or **48** 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC


46 463 | 492 | 492ST | 492TC | 692 | 692TWIN


48 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...

471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

JS ORFS Swivel Female (Long)

ISO 12151-1-SWSB
SAE J516 – ORFS





Part Number		Hose I.D.				Thread	A	B	H	W
46 series	48 series	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
	1JS48-4-4	6	1/4	-4	6.4	9/16x18	51	29	14	17
1JS46-4-4		6	1/4	-4	6.4	9/16x18	53	29	14	17
	1JS48-6-4	6	1/4	-4	6.4	11/16x16	54	31	17	22
1JS46-6-4		6	1/4	-4	6.4	11/16x16	56	31	17	22
1JS46-6-5	1JS48-6-5	8	5/16	-5	7.9	11/16x16	55	31	17	22
	1JS48-4-6	10	3/8	-6	9.5	9/16x18	53	31	14	17
1JS46-6-6	1JS48-6-6	10	3/8	-6	9.5	11/16x16	52	29	17	22
1JS46-8-6	1JS48-8-6	10	3/8	-6	9.5	13/16x16	58	35	19	24
1JS46-6-8	1JS48-6-8	12	1/2	-8	12.7	11/16x16	52	29	17	22
1JS46-8-8	1JS48-8-8	12	1/2	-8	12.7	13/16x16	57	33	22	24
1JS46-10-8	1JS48-10-8	12	1/2	-8	12.7	1x14	63	39	24	30
1JS46-10-10	1JS48-10-10	16	5/8	-10	15.9	1x14	65	39	24	30
1JS46-12-10	1JS48-12-10	16	5/8	-10	15.9	1 3/16x12	70	45	30	36
	1JS48-10-12	19	3/4	-12	19.1	1x14	65	39	24	30
1JS46-12-12	1JS48-12-12	19	3/4	-12	19.1	1 3/16x12	71	45	30	36
1JS46-16-12	1JS48-16-12	19	3/4	-12	19.1	1 7/16x12	73	47	36	41
1JS46-16-16	1JS48-16-16	25	1	-16	25.4	1 7/16x12	76	46	36	41
	1JS48-20-20	31	1 1/4	-20	31.8	1 11/16x12	102	54	46	50
1JS46-20-20		31	1 1/4	-20	31.8	1 11/16x12	88	50	41	50
	1JS48-24-24	38	1 1/2	-24	38.1	2x12	99	62	50	60

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or **48** 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC


46 463 | 492 | 492ST | 492TC | 692 | 692TWIN


48 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...

471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

J7 Female ORFS – Swivel 45° Elbow

ISO 12151-1 – SWE 45°
SAE J516 – ORFS 45°





Part Number		Hose I.D.				Thread	A	B	E	W
46 series	48 series	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
1J746-4-4	1J748-4-4	6	1/4	-4	6.4	9/16x18	54	31	10	17
1J746-6-4	1J748-6-4	6	1/4	-4	6.4	11/16x16	53	30	11	22
1J746-8-4	1J748-8-4	6	1/4	-4	6.4	13/16x16	59	34	15	24
1J746-6-5	1J748-6-5	8	5/16	-5	7.9	11/16x16	56	32	11	22
1J746-6-6	1J748-6-6	10	3/8	-6	9.5	11/16x16	54	31	11	22
1J746-8-6	1J748-8-6	10	3/8	-6	9.5	13/16x16	59	36	15	24
	1J748-6-8	12	1/2	-8	12.7	11/16	57	33	11	22
1J746-6-8		12	1/2	-8	12.7	11/16x16	57	33	11	22
1J746-8-8	1J748-8-8	12	1/2	-8	12.7	13/16x16	61	38	15	24
1J746-10-8	1J748-10-8	12	1/2	-8	12.7	1x14	65	41	16	30
1J746-12-8	1J748-12-8	12	1/2	-8	12.7	1 3/16x12	77	53	21	36
1J746-10-10	1J748-10-10	16	5/8	-10	15.9	1x14	67	42	16	30
1J746-12-10	1J748-12-10	16	5/8	-10	15.9	1 3/16x12	80	55	21	36
1J746-10-12	1J748-10-12	19	3/4	-12	19.1	1x14	73	47	16	30
1J746-12-12	1J748-12-12	19	3/4	-12	19.1	1 3/16x12	83	57	21	36
1J746-16-12	1J748-16-12	19	3/4	-12	19.1	1 7/16x12	94	68	24	41
1J746-12-16	1J748-12-16	25	1	-16	25.4	1 3/16x12	91	61	21	36
1J746-16-16	1J748-16-16	25	1	-16	25.4	1 7/16x12	99	69	24	41
1J746-20-16	1J748-20-16	25	1	-16	25.4	1 11/16x12	101	71	25	50
	1J748-20-20	31	1 1/4	-20	31.8	1 11/16x12	130	82	27	50
1J746-20-20		31	1 1/4	-20	31.8	1 11/16x12	124	86	26	50
	1J748-24-24	38	1 1/2	-24	38.1	2x12	148	110	40	60

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or **48** 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC


46 463 | 492 | 492ST | 492TC | 692 | 692TWIN


48 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...

471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

J9 Female ORFS – Swivel 90° Elbow – Short Drop

ISO 12151-1 – SWES
SAE J516 – ORFS 90°





Part Number		Hose I.D.				Thread	A	B	E	W
46 series	48 series	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
1J946-4-4	1J948-4-4	6	1/4	-4	6.4	9/16x18	52	29	21	17
1J946-6-4	1J948-6-4	6	1/4	-4	6.4	11/16x16	51	27	23	22
	1J948-8-4	6	1/4	-4	6.4	13/16x16	50	26	29	24
1J946-6-5	1J948-6-5	8	5/16	-5	7.9	11/16x16	53	29	23	22
1J946-4-6	1J948-4-6	10	3/8	-6	9.5	9/16x18	47	24	21	17
1J946-6-6	1J948-6-6	10	3/8	-6	9.5	11/16x16	52	29	23	22
1J946-8-6	1J948-8-6	10	3/8	-6	9.5	13/16x16	53	30	29	24
1J946-6-8	1J948-6-8	12	1/2	-8	12.7	11/16x16	53	29	23	22
1J946-8-8	1J948-8-8	12	1/2	-8	12.7	13/16x16	55	32	29	24
1J946-10-8	1J948-10-8	12	1/2	-8	12.7	1x14	66	42	32	30
1J946-12-8	1J948-12-8	12	1/2	-8	12.7	1 3/16x12	58	34	48	36
1J946-10-10	1J948-10-10	16	5/8	-10	15.9	1x14	65	39	32	30
1J946-12-10	1J948-12-10	16	5/8	-10	15.9	1 3/16x12	71	45	48	36
1J946-10-12	1J948-10-12	19	3/4	-12	19.1	1x14	69	43	32	30
1J946-12-12	1J948-12-12	19	3/4	-12	19.1	1 3/16x12	82	54	48	36
1J946-16-12		19	3/4	-12	19.1	1 7/16x12	88	62	56	41
	1J948-12-16	25	1	-16	25.4	1 3/16 12	88	58	48	36
1J946-12-16		25	1	-16	25.4	1 3/16x12	88	58	48	36
1J946-16-16	1J948-16-16	25	1	-16	25.4	1 7/16x12	98	68	56	41
1J946-20-16	1J948-20-16	25	1	-16	25.4	1 11/16x12	104	74	64	50
1J946-20-20		31	1 1/4	-20	31.8	1 11/16x12	124	86	64	50
	1J948-20-20	31	1 1/4	-20	31.8	1 11/16x12	129	82	64	50
	1J948-24-24	38	1 1/2	-24	38.1	2x12	140	102	82	60


Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or 48	441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC
46	463 | 492 | 492ST | 492TC | 692 | 692TWIN
48	301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...
	471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

J1 Female ORFS – Swivel 90° Elbow – Long Drop

ISO 12151-1 – SWEL
SAE J 516 – ORFS 90° L







Part Number		Hose I.D.				Thread	A	B	E	W
46 series	48 series	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
1J146-4-4	1J148-4-4	6	1/4	-4	6.4	9/16x18	58	35	46	17
	1J148-6-4	6	1/4	-4	6.4	11/16x16	59	36	54	22
1J146-6-6	1J148-6-6	10	3/8	-6	9.5	11/16x16	58	35	54	22
1J146-8-6	1J148-8-6	10	3/8	-6	9.5	13/16x16	59	37	64	24
1J146-8-8	1J148-8-8	12	1/2	-8	12.7	13/16x16	61	37	64	24
	1J148-10-8	12	1/2	-8	12.7	1x14	66	42	70	30
1J146-10-10	1J148-10-10	16	5/8	-10	15.9	1x14	65	40	70	30
1J146-12-12	1J148-12-12	19	3/4	-12	19.1	1 3/16x12	80	54	96	36
	1J148-16-16	25	1	-16	25.4	1 7/16x12	98	68	114	41

J5 Female ORFS – Swivel 90° Elbow – Medium Drop

ISO 12151-1 – SWEM – ORFS 90° M





Part Number		Hose I.D.				Thread	A	B	E	W
46 series	48 series	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
1J546-4-4	1J548-4-4	6	1/4	-4	6.4	9/16x18	59	35	32	17
1J546-6-4	1J548-6-4	6	1/4	-4	6.4	11/16x16	62	39	38	22
1J546-6-6	1J548-6-6	10	3/8	-6	9.5	11/16x16	58	35	38	22
1J546-8-6	1J548-8-6	10	3/8	-6	9.5	13/16x16	60	37	41	24
1J546-8-8	1J548-8-8	12	1/2	-8	12.7	13/16x16	60	37	41	24
	1J548-10-8	12	1/2	-8	12.7	1x14	66	43	47	30
1J546-10-10	1J548-10-10	16	5/8	-10	15.9	1x14	65	39	47	30
1J546-12-12	1J548-12-12	19	3/4	-12	19.1	1 3/16x12	80	54	58	36

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or **48** 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC


46 463 | 492 | 492ST | 492TC | 692 | 692TWIN


48 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...

471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

JM ORFS Male

ISO 12151-1-S – SAE J516







Part Number		Hose I.D.				Thread	A	B	H
46 series	48 series	DN	Inch	Size	mm	UNF	mm	mm	mm
	1JM48-4-4	6	1/4	-4	6.4	9/16x18	44	22	17
1JM46-4-4		6	1/4	-4	6.4	9/16x18	46	22	17
	1JM48-6-4	6	1/4	-4	6.4	11/16x16	46	24	19
1JM46-6-4		6	1/4	-4	6.4	11/16x16	48	24	19
1JM46-6-5	1JM48-6-5	8	5/16	-5	7.9	11/16x16	53	26	19
1JM46-6-6	1JM48-6-6	10	3/8	-6	9.5	11/16x16	47	24	19
1JM46-8-6	1JM48-8-6	10	3/8	-6	9.5	13/16x16	50	27	22
1JM46-8-8	1JM48-8-8	12	1/2	-8	12.7	13/16x16	51	27	22
1JM46-10-8	1JM48-10-8	12	1/2	-8	12.7	1x14	55	32	27
1JM46-10-10	1JM48-10-10	16	5/8	-10	15.9	1x14	57	32	27
1JM46-12-10	1JM48-12-10	16	5/8	-10	15.9	1 3/16x12	59	34	32
1JM46-12-12	1JM48-12-12	19	3/4	-12	19.1	1 3/16x12	61	35	32
1JM46-16-12	1JM48-16-12	19	3/4	-12	19.1	1 7/16x12	64	38	41
1JM46-16-16	1JM48-16-16	25	1	-16	25.4	1 7/16x12	67	37	41
1JM46-20-16	1JM48-20-16	25	1	-16	25.4	1 11/16x12	66	36	46
	1JM48-20-20	31	1 1/4	-20	31.8	1 11/16x12	85	37	46

To select corresponding O-ring see section Eb.

JD Male ORFS Bulkhead with Locknut Straight (with O-ring)

ISO 12151-1 – SAE J516





Part Number		Hose I.D.				Thread	A	B	H	W
46 series	48 series	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
1JD46-4-4	1JD48-4-4	6	1/4	-4	6.4	9/16x18	72	48	22	22
1JD46-6-6	1JD48-6-6	10	3/8	-6	9.5	11/16x16	73	51	27	27
1JD46-8-8	1JD48-8-8	12	1/2	-8	12.7	13/16x16	79	56	30	30
1JD46-10-10	1JD48-10-10	16	5/8	-10	15.9	1x14	86	60	32	36
1JD46-12-12	1JD48-12-12	19	3/4	-12	19.1	1 3/16x12	88	63	36	38
	1JD48-16-16	25	1	-16	25.4	1 7/16x12	94	64	46	46

To select corresponding O-ring see section Eb.

Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK


46 or 48	441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC
46	463 | 492 | 492ST | 492TC | 692 | 692TWIN
48	301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...
	471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

FU

Female BSP Parallel Pipe Swivel – Straight (30° Flare)

ISO 228-1 – JIS B8363 – GUI







Part Number		Hose I.D.				Thread	A	B	H	W
46 series	48 series	DN	Inch	Size	mm	BSP	mm	mm	mm	mm
1FU46-4-4	1FU48-4-4	6	1/4	-4	6.4	1/4x19	50	32	19	19
1FU46-6-6	1FU48-6-6	10	3/8	-6	9.5	3/8x19	58	35	24	22
1FU46-12-12	1FU48-12-12	19	3/4	-12	19.1	3/4x14	71	45	36	36
1FU46-16-16	1FU48-16-16	25	1	-16	25.4	1x11	76	46	41	41

GU

Female BSP Parallel Pipe Swivel – Straight (60° Cone)

ISO 228-1 – JIS B8363 – GUO





Part Number		Hose I.D.				Thread	A	B	H	W
46 series	48 series	DN	Inch	Size	mm	BSP	mm	mm	mm	mm
1GU46-4-4	1GU48-4-4	6	1/4	-4	6.4	1/4x19	51	27	19	19
1GU46-6-6	1GU48-6-6	10	3/8	-6	9.5	3/8x19	58	35	22	22
1GU46-8-8	1GU48-8-8	12	1/2	-8	12.7	1/2x14	55	32	27	27

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or **48** 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC

46 463 | 492 | 492ST | 492TC | 692 | 692TWIN


48 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...


471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

MU

Female Metric – Swivel Straight (30° Flare)

JIS B8363 – MU







Part Number		Hose I.D.				Thread	A	B	H	W
46 series	48 series	DN	Inch	Size	mm	metric	mm	mm	mm	mm
1MU46-4-4	1MU48-4-4	6	1/4	-4	6.4	M14x1.5	45	21	19	19
	1MU48-6-4	6	1/4	-4	6.4	M18x1.5	57	33	24	24
1MU46-6-6	1MU48-6-6	10	3/8	-6	9.5	M18x1.5	59	36	24	24
1MU46-8-8	1MU48-8-8	12	1/2	-8	12.7	M22x1.5	64	40	27	27

MZ

Female Metric – Swivel 90° Elbow (30° Flare)

JIS B8363






Part Number		Hose I.D.				Thread	A	B	E	W
46 series	48 series	DN	Inch	Size	mm	metric	mm	mm	mm	mm
1MZ46-4-4	1MZ48-4-4	6	1/4	-4	6.4	M14x1.5	48	24	23	19
1MZ46-6-6	1MZ48-6-6	10	3/8	-6	9.5	M18x1.5	51	28	29	24
1MZ46-8-8	1MZ48-8-8	12	1/2	-8	12.7	M22x1.5	55	31	31	27


Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or 48	441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC
46	463 | 492 | 492ST | 492TC | 692 | 692TWIN
48	301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...
	471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881


FG Male French Gas Series Rigid – Straight (24° Cone)






Part Number		Hose I.D.				Thread	Tube O.D.	A	B	H
46 series	48 series	DN	Inch	Size	mm	metric	mm	mm	mm	mm
1FG46-13-5	1FG48-13-5	8	5/16	-5	7.9	M20x1.5	13	53	29	22
1FG46-13-6	1FG48-13-6	10	3/8	-6	9.5	M20x1.5	13	52	29	22
1FG46-17-8	1FG48-17-8	12	1/2	-8	12.7	M24x1.5	17	51	27	24
1FG46-21-10	1FG48-21-10	16	5/8	-10	15.9	M30x1.5	21	57	32	30
1FG46-27-12	1FG48-27-12	19	3/4	-12	19.1	M36x1.5	27	59	34	36
1FG46-33-16	1FG48-33-16	25	1	-16	25.4	M45x1.5	33	69	40	46

F2 Female French Gas Series Swivel – 90° Elbow





Part Number		Hose I.D.				Thread	Tube O.D.	A	B	E	W
46 series	48 series	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
1F246-13-5	1F248-13-5	8	5/16	-5	7.9	M20x1.5	13	59	35	30	24
1F246-13-6	1F248-13-6	10	3/8	-6	9.5	M20x1.5	13	60	38	33	24
1F246-17-8	1F248-17-8	12	1/2	-8	12.7	M24x1.5	17	63	39	43	30
1F246-21-10	1F248-21-10	16	5/8	-10	15.9	M30x1.5	21	71	46	45	36

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK


46 or **48** 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC


46 463 | 492 | 492ST | 492TC | 692 | 692TWIN

48 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...

471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881


F4 Female French Gas Series Swivel – Straight (Ball Nose)






Part Number		Hose I.D.				Thread	Tube O.D.	A	B	W
46 series	48 series	DN	Inch	Size	mm	metric	mm	mm	mm	mm
1F446-13-4	1F448-13-4	6	1/4	-4	6.4	M20x1.5	13	48	24	24
1F446-13-5	1F448-13-5	8	5/16	-5	7.9	M20x1.5	13	48	24	24
1F446-13-6	1F448-13-6	10	3/8	-6	9.5	M20x1.5	13	45	22	24
1F446-17-8	1F448-17-8	12	1/2	-8	12.7	M24x1.5	17	49	25	30
1F446-21-10	1F448-21-10	16	5/8	-10	15.9	M30x1.5	21	50	25	36
1F446-27-12	1F448-27-12	19	3/4	-12	19.1	M36x1.5	26	59	33	46
1F446-33-16	1F448-33-16	25	1	-16	25.4	M45x1.5	33	63	33	55

F6 French Male Metric Series (24° Cone)





Part Number		Hose I.D.				Thread	Tube O.D.	A	B	H
46 series	48 series	DN	Inch	Size	mm	metric	mm	mm	mm	mm
1F646-14-6	1F648-14-6	10	3/8	-6	9.5	M20x1.5	14	50	27	22
1F646-20-10	1F648-20-10	16	5/8	-10	15.9	M27x1.5	20	59	33	30

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK


46 or **48** 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC


46 463 | 492 | 492ST | 492TC | 692 | 692TWIN

48 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...

471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881


F9 French Female Metric Series Swivel – (Ball Nose)






Part Number		Hose I.D.				Thread	Tube O.D.	A	B	W
46 series	48 series	DN	Inch	Size	mm	metric	mm	mm	mm	mm
1F946-6-4	1F948-6-4	6	1/4	-4	6.4	M12x1	6	43	20	14
1F946-10-4	1F948-10-4	6	1/4	-4	6.4	M16x1.5	10	45	22	19
1F946-14-6	1F948-14-6	10	3/8	-6	9.5	M20x1.5	14	44	22	24
1F946-20-10	1F948-20-10	16	5/8	-10	15.9	M27x1.5	20	50	25	32
1F946-22-12	1F948-22-12	19	3/4	-12	19.1	M30x1.5	22	53	27	36
1F946-25-12	1F948-25-12	19	3/4	-12	19.1	M33x1.5	25	55	29	41
1F946-30-16	1F948-30-16	25	1	-16	25.4	M39x1.5	30	61	32	50

FA Metric Male for Agriculture Valves





Part Number		Hose I.D.				Thread	A	B	H
46 series	48 series	DN	Inch	Size	mm	metric	mm	mm	mm
1FA46-12-5	1FA48-12-5	8	5/16	-5	7.9	M18x1.5	53	29	19
1FA46-12-6	1FA48-12-6	10	3/8	-6	9.5	M18x1.5	52	30	19
1FA46-12-8	1FA48-12-8	12	1/2	-8	12.7	M18x1.5	53	30	19

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK


46 or **48** 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC

46 463 | 492 | 492ST | 492TC | 692 | 692TWIN

48 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...

471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

CW Power Cleaner Connection






Part Number		Hose I.D.				Thread	Tube O.D.	A	B
46 series	48 series	DN	Inch	Size	mm	metric	mm	mm	mm
1CW46-15-4	1CW48-15-4	6	1/4	-4	6.4	M22x1.5	15	53	29
1CW46-15-5	1CW48-15-5	8	5/16	-5	7.9	M22x1.5	15	53	29
1CW46-15-6	1CW48-15-6	10	3/8	-6	9.5	M22x1.5	15	52	29
1CW46-15-8	1CW48-15-8	12	1/2	-8	12.7	M22x1.5	15	53	29

Rubber hand grip Part-No. WKS-X-XXX in black or blue please find on page Eb-17.

NW Female Kärcher Metric Cleaning Hose Fitting Swivel – Straight





Part Number		Hose I.D.				Thread	A	B
46 series	48 series	DN	Inch	Size	mm	metric	mm	mm
1NW46-15-4	1NW48-15-4	6	1/4	-4	6.4	M22x1.5	52	29
1NW46-15-5	1NW48-15-5	8	5/16	-5	7.9	M22x1.5	52	29
1NW46-15-6	1NW48-15-6	10	3/8	-6	9.5	M22x1.5	48	25

Rubber hand grip Part-No. WKS-X-XXX in black or blue please find on page Eb-17.

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or 48 | 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC


46 | 463 | 492 | 492ST | 492TC | 692 | 692TWIN


48 | 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...

471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

PW

Male Kärcher
Metric Cleaning Hose Fitting
Rigid – Straight





Part Number		Hose I.D.				Tube O.D.	A	B
46 series	48 series	DN	Inch	Size	mm	mm	mm	mm
1PW46-10-4	1PW48-10-4	6	1/4	-4	6.4	10	60	36
1PW46-11-4	1PW48-11-4	6	1/4	-4	6.4	11	60	37
1PW46-10-5	1PW48-10-5	8	5/16	-5	7.9	10	60	36
1PW46-11-5	1PW48-11-5	8	5/16	-5	7.9	11	61	37
1PW46-10-6	1PW48-10-6	10	3/8	-6	9.5	10	60	37

Rubber hand grip Part-No. WKS-X-XXX in black or blue please find on page Eb-17.

1PWxx-**11**-x = with ball bearing as shown above
1PWxx-**10**-x = without ball bearing

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or **48** 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC

46 463 | 492 | 492ST | 492TC | 692 | 692TWIN


48 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...


471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

XU

Female Metric – Swivel Straight (30° Flare)

JIS B8363







Part Number		Hose I.D.				Thread	A	B	H	W
46 series	48 series	DN	Inch	Size	mm	metric	mm	mm	mm	mm
	1XU48-10-10	16	5/8	-10	15.9	M24x1.5	69	44	30	32
	1XU48-12-12	19	3/4	-12	19.1	M30x1.5	73	47	32	36

DK

Male Metric L – Rigid Bulkhead with Locknut (24° Cone)





Part Number		Hose I.D.				Thread	A	B	H	W
46 series	48 series	DN	Inch	Size	mm	metric	mm	mm	mm	mm
1DK46-10-5	1DK48-10-5	8	5/16	-5	7.9	M16x1.5	71	48	22	22
1DK46-15-10	1DK48-15-10	16	5/8	-10	15.9	M22x1.5	81	56	27	30
	1DK48-18-10	16	5/8	-10	15.9	M26x1.5	85	60	36	36
1DK46-18-10		16	5/8	-10	15.9	M26x1.5	85	60	32	36

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK


46 or 48 | 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC


46 | 463 | 492 | 492ST | 492TC | 692 | 692TWIN

48 | 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...

471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

DX Female Metric Swivel (M27x2) O-Ring Light Series





Part Number		Hose I.D.				Thread	A	B	W
46 series	48 series	DN	Inch	Size	mm	metric	mm	mm	mm
1DX46-18-10	1DX48-18-10	16	5/8	-10	15.9	M27x2	61	36	32

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK


46 or **48** 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC


46 463 | 492 | 492ST | 492TC | 692 | 692TWIN

48 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...

471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881


EN UPTC – Male Straight






Part Number		Hose I.D.				Tube O.D.	A	B
46 series	48 series	DN	Inch	Size	mm	mm	mm	mm
1EN46-8-4	1EN48-8-4	6	1/4	-4	6.4	8	49	26
1EN46-10-5	1EN48-10-5	8	5/16	-5	7.9	10	50	26
1EN46-12-6	1EN48-12-6	10	3/8	-6	9.5	12	50	27
1EN46-15-8	1EN48-15-8	12	1/2	-8	12.7	15	53	29
1EN46-18-10	1EN48-18-10	16	5/8	-10	15.9	18	56	31
1EN46-22-12	1EN48-22-12	19	3/4	-12	19.1	22	57	32

EU UPTC – Male 45° Elbow





Part Number		Hose I.D.				Tube O.D.	A	B	E
46 series	48 series	DN	Inch	Size	mm	mm	mm	mm	mm
1EU46-8-4	1EU48-8-4	6	1/4	-4	6.4	8	66	43	23
1EU46-10-5	1EU48-10-5	8	5/16	-5	7.9	10	68	45	23
1EU46-12-6	1EU48-12-6	10	3/8	-6	9.5	12	71	48	23
1EU46-15-8	1EU48-15-8	12	1/2	-8	12.7	15	78	54	25
1EU46-18-10	1EU48-18-10	16	5/8	-10	15.9	18	84	59	32
1EU46-22-12	1EU48-22-12	19	3/4	-12	19.1	22	95	69	33


Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or 48	441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC
46	463 | 492 | 492ST | 492TC | 692 | 692TWIN
48	301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...
	471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

ET

UPTC – Male 90° Elbow





Part Number		Hose I.D.				Tube O.D.	A	B	E
46 series	48 series	DN	Inch	Size	mm	mm	mm	mm	mm
1ET46-8-4	1ET48-8-4	6	1/4	-4	6.4	8	59	36	39
1ET46-10-5	1ET48-10-5	8	5/16	-5	7.9	10	58	35	39
1ET46-12-6	1ET48-12-6	10	3/8	-6	9.5	12	57	34	40
1ET46-15-8	1ET48-15-8	12	1/2	-8	12.7	15	61	38	45
1ET46-18-10	1ET48-18-10	16	5/8	-10	15.9	18	65	39	57
1ET46-22-12	1ET48-22-12	19	3/4	-12	19.1	22	80	54	64

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

46 or 48 | 441 | 441RH | 461LT | 462 | 462ST | 462CLF | 462TC

46 | 463 | 492 | 492ST | 492TC | 692 | 692TWIN

48 | 301SN | 301TC | 304 | 387 | 387ST | 387TC | 421RH | 421SN | 426 | 436 | ...

471TC | 477 | 477ST | 477TC | 487 | 487ST | 487TC | 493 | 811 | 881

Shell

Page Cd-1

10048

Cd-1




No-Skive shell

SAE

Page Cd-1

01

Cd-1




Male NPTF Pipe
Rigid – Straight
SAE J476A / J516 – AGN

Flange

Page Cd-2

15


Cd-2



ISO 6162-1 Flange
Straight
ISO 12151-3-S-L – SFL
(21.0 MPa/ 3000 psi)

Crimp Diameters please find on **www.parker.com/crimpsource-euro**

10048 No-Skive shell





Only for use with adjustable crimpers.

Part Number	Hose I.D.				B
	DN	Inch	Size	mm	mm
10048-40	63	2 1/2	-40	63.5	67
10048-48	76	3	-48	76.2	75

01 Male NPTF Pipe Rigid – Straight

SAE J476A / J516 – AGN






Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	NPTF	mm	mm	mm
K0147-48-40	63	2 1/2	-40	63.5	3-8	135	73	95
K0147-48-48	76	3	-48	76.2	3-8	143	73	95


Approved **fitting series** for **hose types**:

48 462TC

15 ISO 6162-1 Flange Straight

ISO 12151-3-S-L – SFL
(21.0 MPa/ 3000 psi)





Part Number	Hose I.D.				Flange	A	B	F
	DN	Inch	Size	mm	Inch	mm	mm	mm
K1547-40-40	63	2 1/2	-40	63.5	2 1/2	127	65	84
K1547-48-40	63	2 1/2	-40	63.5	3	137	75	102
K1547-48-48	76	3	-48	76.2	3	155	85.5	102

To select corresponding half-flange and O-ring see section Eb.

Approved **fitting series** for **hose types**:

48 462TC

Shell

Page Ce-1

100IF

Ce-1



No-Skive shell

Flange

Page Ce-2 – Ce-3

15


Ce-2



ISO 6162-1 Flange
Straight
ISO 12151-3-S-L – SFL
(21.0 MPa/ 3000 psi)

17


Ce-2



ISO 6162-1 Flange
45° Elbow
ISO 12151-3 – E45 – L – SFL 45°
(21.0 MPa/ 3000 psi)

19

Ce-3



ISO 6162-1 Flange
90° Elbow
ISO 12151-3 – E– L – SFL 90°
(21.0 MPa/ 3000 psi)

Crimp Diameters please find on **www.parker.com/crimpsource-euro**

100IF No-Skive shell



Only for use with adjustable crimpers.


Part Number	Hose I.D.				B
	DN	Inch	Size	mm	mm
100IF-40	63	2 1/2	-40	63,5	63
100IF-48	76	3	-48	76,2	68
100IF-56	90	3 1/2	-56	88,9	100
100IF-64	100	4	-64	101,6	95
100IF-80	127	5	-80	127	110
100IF-96	152	6	-96	152,4	142


Approved **fitting series** for **hose types**:

IF | 811 | 811S

15 ISO 6162-1 Flange Straight

ISO 12151-3-S-L – SFL
(21.0 MPa/ 3000 psi)







Part Number	Hose I.D.				Flange	A	B	F
	DN	Inch	Size	mm	Inch	mm	mm	mm
K15IF-40-40-2P	63	2 1/2	-40	63.5	2 1/2	120	67	84
K15IF-48-48-2P	76	3	-48	76.2	3	166	95	102
K15IF-56-56-2P	90	3 1/2	-56	88.9	3 1/2	183	91	114
K15IF-64-64-2P	100	4	-64	101.6	4	206	103	127
K15IF-80-80-2P	127	5	-80	127	5	221	118	152
K15IF-80-96-2P	152	6	-96	152.4	5	281	151	152

To select corresponding half-flange and O-ring see section Eb.

17 ISO 6162-1 Flange 45° Elbow

ISO 12151-3 – E45 – L – SFL 45°
(21.0 MPa/ 3000 psi)





Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
K17IF-40-40-3P	63	2 1/2	-40	63.5	2 1/2	164	111	47	84
K17IF-48-48-3P	76	3	-48	76.2	3	224	153	53	102
K17IF-56-56-3P	90	3 1/2	-56	88.9	3 1/2	258	166	50	114
K17IF-64-64-3P	100	4	-64	101.6	4	294	191	57	127
K17IF-80-80-3P	127	5	-80	127	5	341	238	92	152
K17IF-80-96-3P	152	6	-96	152.4	5	401	271	92	152


SAE flange halves see in section Eb.
Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

Approved **fitting series** for **hose types**:

IF	811 | 811S

19 ISO 6162-1 Flange 90° Elbow

ISO 12151-3 – E– L – SFL 90°
(21.0 MPa/ 3000 psi)





Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
K19IF-40-40-3P	63	2 1/2	-40	63.5	2 1/2	162	109	111	84
K19IF-48-48-3P	76	3	-48	76.2	3	226	155	131	102
K19IF-56-56-3P	90	3 1/2	-56	88.9	3 1/2	275	183	137	114
K19IF-64-64-3P	100	4	-64	101.6	4	314	211	159	127
K19IF-80-80-3P	127	5	-80	127	5	361	258	241	152
K19IF-80-96-3P	152	6	-96	152.4	5	421	291	241	152

SAE flange halves see in section Eb.
Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

Approved **fitting series** for **hose types**:

IF	811 | 811S





aerospace
climate control
electromechanical
filtration
fluid & gas handling
hydraulics
pneumatics
process control
sealing & shielding





Hydraulic Hoses, Fittings and Equipment

High Pressure



Parker

ENGINEERING YOUR SUCCESS.

High Pressure Hoses and Fittings

Three systems for heavy duty performers

Multispiral Parkrimp *No-Skive*

Crimpable with Parkrimp System



Compact Spiral Interlock *No-Skive*

Crimpable with Parkrimp System



ParLock Interlock Skive

Crimpable with adjustable crimpers



Applications

The definitive hose range for all high pressure applications



Crimper systems you can trust

Parkrimp crimpers
for *No-Skive* one-piece fittings



KarryKrimp® 2



KarryKrimp® 2
Bench Mount



Parkrimp®

Adjustable crimpers
for two-piece ParLock fittings



TH8E-530



TH 8E-380-BM



TH 8E-480-BM



Parkrimp *No-Skive*
one-piece fittings



ParLock
two-piece skive fittings

GLOBALCORE™

The world's first high-performance, cohesive hose and fitting system

722 / 722TC / 722ST *No-Skive* GlobalCore

Resilient 4-wire spiral construction

Primary Applications



Parker's GlobalCore 722 spiral hose provides 28 MPa (4,000 psi) constant working pressure in sizes -6 through -16. Designed for high-pressure, high-impulse applications, 722 hose is offered in Standard, ToughCover and SuperTough cover options.
It is one-half the bend radius of 100R12 hose, making it easy to install and reducing the amount of hose needed. Exceeding the ISO 18752 performance specification, Parker's 722 hose excels in multiple applications around the world.

787 / 787TC *No-Skive* GlobalCore

Lighter weight, high flexibility make installation easy

Primary Applications



Parker's GlobalCore 787 hose provides 35 MPa (5,000 psi) constant working pressure in all sizes. Compared with conventional spiral hose, 787 hose offers measurably greater advantages in routing and installation, product size and weight, inventory savings and much more. The 787 hose exceeds the ISO 18752 performance specification.

797 / 797TC *No-Skive* GlobalCore

Lighter weight, high flexibility make installation easy

Primary Applications




Parker's GlobalCore 797 hose provides 42 MPa (6,000 psi) constant working pressure in all sizes. Compared with conventional spiral hose, 797 hose offers measurably greater advantages in routing and installation, product size and weight, inventory savings and much more. The 797 hose exceeds the ISO 18752 performance specification.

www.parker.com/globalcore


GlobalCore significantly reduces system complexity



- ½ ISO 18752 minimum bend radius
- 28 MPa (4,000 psi) constant working pressure
- Exceeds ISO 18752 performance specification (BC and CC)
- 4-spiral construction for longer life in high-impulse, heavy-duty cycle applications
- TC cover provides 80 times the abrasion resistance compared to Standard rubber cover hoses
- ST cover provides 450 times the abrasion resistance compared to Standard rubber cover hoses



- ½ ISO 18752 minimum bend radius
- 35 MPa (5,000 psi) constant working pressure in all sizes
- Exceeds ISO 18752 performance specification (BC/DC)
- Nearly 30 % smaller O.D. by area than SAE spiral
- Twice the impulse/life – tested to 2,000,000 cycles
- Flex impulse tested, providing a hose superior in both performance and service life
- 30 % less hose weight than SAE spiral



- ½ the bend radius of SAE spiral
- 42 MPa (6,000 psi) constant working pressure in all sizes
- Exceeds ISO 18752 performance specification (BC/CC/DC)
- Nearly 30 % smaller O.D. by area than SAE spiral
- Twice the impulse/life – tested to 2,000,000 cycles
- Flex impulse tested, providing a hose superior in both performance and service life
- 30 % less hose weight than SAE spiral

Full Flange System

Provides full flange mounting option for ISO 6162-1 (35.0 MPa/5000 psi) and ISO 6162-2 (42.0 MPa/ 6000 psi) flanges – system flexibility reduces inventory investment.

The full flange system addresses the needs of customers by:

- Being easier to assemble
- Providing one-piece integrity
- Being easier to handle
- Being easier to route in tight spaces
- Enabling assemblies to be sent to customers with the flange in place
- Easing bent tube installation (displacement angle) with a freely rotating flange



The full flange system can be used repeatedly because of its patent-pending attachment system – the flange is not permanently locked onto the fitting.

- This is not a captive flange – it can easily be removed
- Flange can be reused if necessary
- Flange is not scrapped on a mis-crimp

Fitting Configuration

This fitting configuration is specifically designed for Parker's full flange system, and will accept either a ISO 6162-1 or ISO 6162-2 flange. The X5, X7 and X9 fittings are designed to work with all Parkrimp crimpers. These fittings can replace multiple existing fittings and help to reduce inventory.

Reduction of Inventory

Parker's full flange system requires less inventory than the existing split flange system.
By using the new X5, X7 and X9 fittings, distributors can streamline inventory and can still respond to customer needs. Before the introduction of the full flange system, distributors needed to stock both ISO 6162 fittings to be prepared.


X5



1**X5**77-20-20

Straight
ISO 6162-1 or ISO 6162-2 fitting
*Alternative to **15**, **4A** and **6A***

X7



1**X7**77-20-20

45°
ISO 6162-1 or ISO 6162-2 fitting
*Alternative to **17**, **4F** and **6F***

X9



1**X9**77-20-20

90°
ISO 6162-1 or ISO 6162-2 fitting
*Alternative to **19**, **4N** and **6N***

For more information about Full Flange System please refer to pages *Dd-18, Dd-19, Df-19, Df-20, Eb-4 and Eb-5*

High Pressure GLOBALCORE™

Hoses		Page
722 No-Skive	GlobalCore	Daa-1
722TC No-Skive	GlobalCore	Daa-2
722ST No-Skive	GlobalCore	Daa-3
787 No-Skive	GlobalCore Compact Spiral	Daa-4
787TC No-Skive	GlobalCore Compact Spiral	Daa-5
797 No-Skive	GlobalCore Compact Spiral	Daa-6
797TC No-Skive	GlobalCore Compact Spiral	Daa-7

Fittings Series	77
Chapter	Dd
DIN – Metric	1 – 4
BSP	5 – 8
SAE	9 – 11
Flange	12 – 22
ORFS	23 – 25
French Standard	26
Special Fittings	27

Parker Hannifin assumes no liability for typographical errors or other errors

Parkrimp

GlobalCore

722

Daa-1



No-Skive **GlobalCore**
Exceed ISO 18752-BC

722TC

Daa-2



No-Skive **GlobalCore Tough Cover**
Exceeds ISO 18752-CC

722ST

Daa-3



No-Skive **GlobalCore Super Tough**
Exceed ISO 18752-CC

787

Daa-4



No-Skive
GlobalCore Compact Spiral™
Exceeds ISO 18752-BC

787TC

Daa-5



No-Skive
GlobalCore Compact Spiral™
Exceeds ISO 18752-DC

797

Daa-6



No-Skive
GlobalCore Compact Spiral™
Exceeds ISO 18752-BC

797TC

Daa-7



No-Skive
GlobalCore Compact Spiral™
Sizes -8 to -20 exceed ISO 18752-DC
Sizes -24 and -32 exceed ISO 18752-CC

722

No-Skive GlobalCore

Exceed ISO 18752-BC



- *No-Skive* hose construction
- ½ ISO 18752 minimum bend radius
- 28 MPa constant working pressure
- Exceeds ISO 18752 BC performance specification
- 4-spiral construction for longer life in high-impulse, heavy-duty cycle applications

Primary Applications

General high pressure hydraulic applications

Applicable Specifications

Exceed ISO 18752-BC

Construction

Tube: Synthetic rubber
Reinforcement: Four spirals high-tensile steel wire
Cover: Synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series



Series 43 you'll find in the Medium Pressure chapter Cb

Part Number	Hose I.D.				Hose O.D.	Pressure Rating				min. bend radius	weight
						max. working pressure		min. burst pressure			
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
722-6	10	3/8	-6	9.5	19.9	28.0	4000	112.0	16000	65	0.60
722-8	12	1/2	-8	12.7	22.7	28.0	4000	112.0	16000	90	0.80
722-10	16	5/8	-10	15.9	26.4	28.0	4000	112.0	16000	100	1.10
722-12	19	3/4	-12	19.1	30.7	28.0	4000	112.0	16000	120	1.40
722-16	25	1	-16	25.4	37.8	28.0	4000	112.0	16000	150	1.99

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



722TC

No-Skive GlobalCore Tough Cover

Exceeds ISO 18752-CC



- *No-Skive* hose construction – Compact design
- 1/2 the bend radius of SAE 100R12
- Constant working pressure of 28.0 MPa
- Highly abrasion resistant TOUGH COVER
- MSHA approved
- Hose is suitable for temporary immersion in mineral oil up to 70 °C with frequent inspections

Primary Applications

General high pressure hydraulic applications

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

SAE 100R12 – EN 856 Type R12 –
ISO 3862Type R12

Construction

Tube:	Nitril (NBR)
Reinforcement:	Four spirals high-tensile steel wire
Cover:	High abrasion resistance MSHA approved synthetic rubber

Temperature Range ..... -40 °C up to +125 °C

Exception:	Air ..... max. +70 °C
	Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

43

Series 43 you'll find in the Medium Pressure chapter Cb

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
722TC-6	10	3/8	-6	9.5	19.9	28.0	4000	112.0	16000	65	0.60
722TC-8	12	1/2	-8	12.7	22.7	28.0	4000	112.0	16000	90	0.80
722TC-10	16	5/8	-10	15.9	26.4	28.0	4000	112.0	16000	100	1.10
722TC-12	19	3/4	-12	19.1	30.7	28.0	4000	112.0	16000	120	1.40
722TC-16	25	1	-16	25.4	37.8	28.0	4000	112.0	16000	150	1.99

Replace the hose when any deformation or damage on the hose cover are visible.
The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



722ST

No-Skive GlobalCore Super Tough

Exceeds ISO 18752-CC



- *No-Skive* hose construction
- ½ ISO 18752 minimum bend radius
- 28 MPa constant working pressure
- Exceeds ISO 18752 CC performance specification
- Extreme abrasion resistant SUPER TOUGH cover
- 4-spiral construction for longer life in high-impulse, heavy-duty cycle applications

Primary Applications

General high pressure hydraulic applications

Applicable Specifications

Exceed ISO 18752-CC

Construction

Tube: Synthetic rubber
Reinforcement: Four spirals high-tensile steel wire
Cover: Synthetic rubber with a special polyethylene coating

Temperature Range ..... -40 °C up to +125 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

43

Series 43 you'll find in the Medium Pressure chapter Cb

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
722ST-6	10	3/8	-6	9.5	19.9	28.0	4000	112.0	16000	65	0.60
722ST-8	12	1/2	-8	12.7	22.7	28.0	4000	112.0	16000	90	0.80
722ST-10	16	5/8	-10	15.9	26.4	28.0	4000	112.0	16000	100	1.10
722ST-12	19	3/4	-12	19.1	30.7	28.0	4000	112.0	16000	120	1.40
722ST-16	25	1	-16	25.4	37.8	28.0	4000	112.0	16000	150	1.99

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



787

No-Skive

GlobalCore Compact Spiral™

Exceeds ISO 18752-BC



- 1/2 the bend radius of SAE 100R13
- Constant working pressure of 35.0 MPa
- Reduced O.D. and new construction lead to superior flexibility
- 1/3 less effort to bend
- Weight reduction – up to 26 %

Primary Applications

On- & offshore, construction, injection moulding, mining

Applicable Specifications

Exeeds ISO 18752-BC

Construction

Tube:	Proprietary synthetic rubber
Reinforcement:	Four or six spirals high-tensile steel wire
Cover:	Synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception:	Air	..... max. +70 °C
	Water	..... max. +85 °C

Recommended Fluids

Petroleum based hydraulic fluids and lubricating oils. Wide Compatibility exceeding Column III, with additional chemical resistance, especialy for diesel and biodiesel. For chemical compatibility please contact HPDE_helpdesk@parker.com

Fitting Series



Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
787-8	12	1/2	-8	12.7	21.1	35.0	5000	140.0	20000	90	0.67
787-10	16	5/8	-10	15.9	23.9	35.0	5000	140.0	20000	100	0.80
787-12	19	3/4	-12	19.1	27.9	35.0	5000	140.0	20000	120	1.16
787-16	25	1	-16	25.4	35.7	35.0	5000	140.0	20000	150	1.74
787-20	31	1 1/4	-20	31.8	44.9	35.0	5000	140.0	20000	210	2.89
787-24	38	1 1/2	-24	38.1	52.8	35.0	5000	140.0	20000	255	3.96
787-32	51	2	-32	50.8	67.6	35.0	5000	140.0	20000	318	6.50

Replace the hose when any deformation or damage on the hose cover are visible.
The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



787TC

No-Skive

GlobalCore Compact Spiral™

Exceeds ISO 18752-DC



- 1/2 the bend radius of SAE 100R13
- Constant working pressure of 35.0 MPa
- Reduced O.D. and new construction lead to superior flexibility
- 1/3 less effort to bend
- Weight reduction – up to 26 %
- Highly abrasion resistant TOUGH COVER
- MSHA approved
- Hose is suitable for temporary immersion in mineral oil up to 70 °C with frequent inspections

Primary Applications

On- & offshore, construction, injection moulding, mining

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

Exeeds SAE 100R13 – ISO 3862 Type R13 –
EN 856 Type R13 – ISO 18752-DC

Construction

Tube:	Proprietary synthetic rubber
Reinforcement:	Four or six spirals high-tensile steel wire
Cover:	High abrasion resistance MSHA approved synthetic rubber

Temperature Range ..... -40 °C up to +125 °C

Exception:	Air ..... max. +70 °C
	Water ..... max. +85 °C

Recommended Fluids

Petroleum based hydraulic fluids and lubricating oils.
Wide Compatibility exceeding Column III, with additional chemical resistance, especialy for diesel and biodiesel.
For chemical compatibility please contact
HPDE_helpdesk@parker.com

Fitting Series

77

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
787TC-8	12	1/2	-8	12.7	21.1	35.0	5000	140.0	20000	90	0.67
787TC-10	16	5/8	-10	15.9	23.9	35.0	5000	140.0	20000	100	0.80
787TC-12	19	3/4	-12	19.1	27.9	35.0	5000	140.0	20000	120	1.16
787TC-16	25	1	-16	25.4	35.7	35.0	5000	140.0	20000	150	1.74
787TC-20	31	1 1/4	-20	31.8	44.9	35.0	5000	140.0	20000	210	2.89
787TC-24	38	1 1/2	-24	38.1	52.8	35.0	5000	140.0	20000	255	3.96
787TC-32	51	2	-32	50.8	67.6	35.0	5000	140.0	20000	318	6.50

Replace the hose when any deformation or damage on the hose cover are visible.
The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



797

No-Skive

GlobalCore Compact Spiral™

Exceeds ISO 18752-BC



- 1/2 the bend radius of SAE 100R15
- Constant working pressure of 42.0 MPa
- Reduced O.D. and new construction lead to superior flexibility
- 1/3 less effort to bend
- Weight reduction – up to 26 %

Primary Applications

On- & offshore, construction, injection moulding, mining

Applicable Specifications

Exceeds ISO 18752-BC

Construction

Tube:	Proprietary synthetic rubber
Reinforcement:	Four or six spirals high-tensile steel wire
Cover:	Synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception:	Air	max. +70 °C
	Water	max. +85 °C

Recommended Fluids

Petroleum base hydraulic fluids and lubricating oils.
Wide Compatibility exceeding Column III, with additional chemical resistance, especialy for diesel and biodiesel.
For chemical compatibility please contact HPDE_helpdesk@parker.com

Fitting Series

77

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
797-8	12	1/2	-8	12.7	21.1	42.0	6000	168.0	24000	100	0.67
797-10	16	5/8	-10	15.9	23.9	42.0	6000	168.0	24000	115	0.80
797-12	19	3/4	-12	19.1	27.9	42.0	6000	168.0	24000	135	1.16
797-16	25	1	-16	25.4	35.7	42.0	6000	168.0	24000	165	1.74
797-20	31	1 1/4	-20	31.8	44.9	42.0	6000	168.0	24000	225	2.89
797-24	38	1 1/2	-24	38.1	52.8	42.0	6000	168.0	24000	305	3.96
797-32	51	2	-32	50.8	67.6	42.0	6000	168.0	24000	380	6.50

Replace the hose when any deformation or damage on the hose cover are visible.
The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



797TC

No-Skive

GlobalCore Compact Spiral™

Sizes -8 to -20 exceed ISO 18752-DC
Sizes -24 and -32 exceed ISO 18752-CC



- 1/2 the bend radius of SAE 100R15
- Constant working pressure of 42.0 MPa
- Reduced O.D. and new construction lead to superior flexibility
- 1/3 less effort to bend
- Weight reduction – up to 26 %
- Highly abrasion resistant TOUGH COVER
- MSHA approved
- Hose is suitable for temporary immersion in mineral oil up to 70 °C with frequent inspections

Primary Applications

On- & offshore, construction, injection moulding, mining

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

Exeeds SAE 100R15 – ISO 3862 Type R15 –
ISO 18752-DC and CC

Construction

Tube:	Proprietary synthetic rubber
Reinforcement:	Four or six spirals high-tensile steel wire
Cover:	High abrasion resistance MSHA approved synthetic rubber

Temperature Range ..... -40 °C up to +125 °C

Exception:	Air ..... max. +70 °C
	Water ..... max. +85 °C

Recommended Fluids

Petroleum base hydraulic fluids and lubricating oils.
Wide Compatibility exceeding Column III, with additional chemical resistance, especialy for diesel and biodiesel.
For chemical compatibility please contact
HPDE_helpdesk@parker.com

Fitting Series

77

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
797TC-8	12	1/2	-8	12.7	21.1	42.0	6000	168.0	24000	100	0.67
797TC-10	16	5/8	-10	15.9	23.9	42.0	6000	168.0	24000	115	0.80
797TC-12	19	3/4	-12	19.1	27.9	42.0	6000	168.0	24000	135	1.16
797TC-16	25	1	-16	25.4	35.7	42.0	6000	168.0	24000	165	1.74
797TC-20	31	1 1/4	-20	31.8	44.9	42.0	6000	168.0	24000	225	2.89
797TC-24	38	1 1/2	-24	38.1	52.8	42.0	6000	168.0	24000	305	3.96
797TC-32	51	2	-32	50.8	67.6	42.0	6000	168.0	24000	380	6.50

Replace the hose when any deformation or damage on the hose cover are visible.
The combination of high temperature and high pressure could reduce the hose life.

Parkrimp Hose

Hose layline example



High Pressure

Hoses			Page
Parkrimp	**371LT** No-Skive	3-braids low temperature	Dab-1
	372 No-Skive	3-braids standard	Dab-2
	372RH No-Skive	3-braids railway	Dab-3
	372TC No-Skive	3-braids high abrasion resistance	Dab-4
	701 No-Skive	Standard	Dab-5
	701TC No-Skive	High abrasion resistance	Dab-6
	722ClF No-Skive	Chlorine Free	Dab-7
	722LT No-Skive	Low Temperature	Dab-8
	722TC No-Skive	High abrasion resistance	Dab-9
	722ST No-Skive	Extreme abrasion resistance	Dab-10
	731 No-Skive	Standard	Dab-11
	731TC No-Skive	High abrasion resistance	Dab-12
	774 No-Skive	Phosphate Ester	Dab-13
	F42 No-Skive	Phosphate Ester	Dab-14
ParLock	**H29**	Standard	Dab-15
	H29RH	Railway	Dab-16
	H29TC	High abrasion resistance	Dab-17
	H29ST	Extreme abrasion resistance	Dab-18
	H31	Standard	Dab-19
	H31TC	High abrasion resistance	Dab-20
	H31ST	Extreme abrasion resistance	Dab-21
	R35	Standard	Dab-22
	R35TC/RS35TC-48	High abrasion resistance	Dab-23
	R42	Standard	Dab-24
	R42TC	High abrasion resistance	Dab-25
	R42ST	Extreme abrasion resistance	Dab-26
	R50TC/R56TC	High abrasion resistance	Dab-27
	BPK	Water-Blasting	Dab-28

	Parkrimp			ParLock			
Fittings Series	70	73	77	VS	V4/V6	V5	WB
Chapter	Db	Dc	Dd	De	Df	Dg	Dh
Shell				1	1	1	1
DIN – Metric	1 – 4	1 – 2	1 – 4	2 – 5	2 – 5	2 – 3	2
BSP	5 – 7	3 – 4	5 – 8	6 – 7	6 – 8		3
SAE	8 – 10	5 – 7	9 – 11	8 – 10	9 – 11		4
Flange	11 – 14	8 – 12	12 – 22	11 – 13	12 – 22		
ORFS	15 – 17	13 – 15	23 – 25	14 – 15	23 – 25		
JIS	18						
French Standard	19	16 – 17	26	16	26		
Others	20						
Special Fittings		19	27				

Parker Hannifin assumes no liability for typographical errors or other errors

Parkrimp

3-braids standard

372

Dab-2



No-Skive **Compact**
3-wire braid compact hose with
4SP working pressures

3-braids low temperature

371LT

Dab-1



No-Skive **Compact**
3-wire braid low-temperature compact hose
with 4SP working pressures

3-braids high abrasion resistance

372TC

Dab-4



No-Skive **Compact**
3-wire braid compact hose with
4SP working pressures

3-braids railway

372RH

Dab-3



No-Skive **Compact**
3-wire braid with fire-retardant cover

Parkrimp

Standard

701
Dab-6



No-Skive **Multispiral**
ISO 3862 Type 4SP – EN 856 Type 4SP

731
Dab-11



No-Skive **Multispiral**
ISO 3862 Type 4SH – EN 856 Type 4SH

Low temperature

722LT
Dab-8



No-Skive **Low-temperature spiral**
SAE 100R12/ISO 3862-1 TypeR12 /EN 856 Type R12

Phosphate Ester

774
Dab-13



No-Skive **Multispiral**
For phosphate ester base fluids

F42
Dab-14



No-Skive **Multispiral**
For phosphate ester base fluids

Chlorine Free

722ClF
Dab-7



No-Skive **Chlorine Free**
SAE 100R12 - EN 856 Type R12 - ISO 3862 Type R12

High abrasion resistance

701TC
Dab-6



No-Skive **Multispiral Tough Cover**
ISO 3862 Type 4SP – EN 856 Type 4SP

722TC
Dab-9



No-Skive **Tough Cover**
Exceeds ISO 18752-CC

731TC
Dab-12



No-Skive **Multispiral**
ISO 3862 Type 4SH – EN 856 Type 4SH

Extreme abrasion resistance

722ST
Dab-10



No-Skive **Super Tough**
Exceed ISO 18752-CC

ParLock

Standard

H29
Dab-15

ParLock Multispiral
Exceeds ISO 3862 Type 4SH –
EN 856 Type 4SH

H31
Dab-19

ParLock Multispiral
Exceeds ISO 3862 Type 4SP –
EN 856 Type 4SP

R35
Dab-22

ParLock Multispiral
Exceeds ISO 3862 Type R13 –
Parker Specifications

R42
Dab-24

ParLock Multispiral
Exceeds ISO 3862 Type R15 –
Parker Specifications

High abrasion resistance

H29TC
Dab-17

ParLock Multispiral
Exceeds ISO 3862 Type 4SH –
EN 856 Type 4SH

H31TC
Dab-20

ParLock Multispiral
Exceeds ISO 3862 Type 4SP –
EN 856 Type 4SP

R35TC/RS35TC-48
Dab-23

ParLock Multispiral
Exceeds ISO 3862 Type R13 –
Parker Specifications

R42TC
Dab-25

ParLock Multispiral
Exceeds ISO 3862 Type R15 –
Parker Specifications

R50TC/R56TC
Dab-27

ParLock Multispiral
Exceeds ISO 3862 Type R15 –
Parker Specifications

Extreme abrasion resistance

H29ST
Dab-18

ParLock Multispiral
Exceeds ISO 3862 Type 4SH –
EN 856 Type 4SH

H31ST
Dab-21

ParLock Multispiral
Exceeds ISO 3862 Type 4SP –
EN 856 Type 4SP

R42ST
Dab-26

ParLock Multispiral
Exceeds ISO 3862 Type R15 –
Parker Specifications

Railway

H29RH
Dab-16

ParLock Multispiral
Fire-retardant cover – exceeds
ISO 3862 Type 4SH – EN 856 Type 4SH

Water-Blasting

BPK
Dab-28

Blastopak ParLock Multispiral
DIN EN 1829-2

371LT

No-Skive Compact

3-wire braid low-temperature compact hose with 4SP working pressures



- *No-Skive* hose construction – Compact design
- Excellent ozone resistance
- Temperature range from -50 °C up to +100 °C

Primary Applications

Mobile applications in low temperature environments: Forestry machines, refrigerated warehouses

Applicable Specifications

Parker Specifications

Construction

Tube:	Synthetic rubber
Reinforcement:	Three high-tensile steel wire braids
Cover:	Synthetic rubber

Temperature Range ..... -50 °C up to +100 °C

Exception:	Air	max. +70 °C
	Water	max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

70

Part Number	Hose I.D.				Hose O.D.	Pressure Rating				min. bend radius	weight
						max. working pressure		min. burst pressure			
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
371LT-6	10	3/8	-6	9.5	21.4	44.5	6500	178.0	25800	120	0.73
371LT-8	12	1/2	-8	12.7	24.6	41.5	6000	166.0	24000	160	0.90
371LT-10	16	5/8	-10	15.9	28.2	35.0	5000	140.0	20000	210	1.09
371LT-12	19	3/4	-12	19.1	32.2	35.0	5000	140.0	20000	260	1.36
371LT-16	25	1	-16	25.4	39.7	28.0	4000	112.0	16000	310	1.78

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



372

No-Skive Compact

3-wire braid compact hose with
4SP working pressures



- *No-Skive* hose construction – Compact design
- Nitrile (NBR) inner tube for extended fluid compatibility

Primary Applications

General high pressure small bending radii hydraulic applications

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

Parker Specifications

Construction

Tube: Nitrile (NBR)
Reinforcement: Three high-tensile steel wire braids
Cover: Synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

70

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
372-6	10	3/8	-6	9.5	21.4	44.5	6500	178.0	25800	120	0.73
372-8	12	1/2	-8	12.7	24.6	41.5	6000	166.0	24000	160	0.90
372-10	16	5/8	-10	15.9	28.2	35.0	5000	140.0	20000	210	1.09
372-12	19	3/4	-12	19.1	32.2	35.0	5000	140.0	20000	260	1.36
372-16	25	1	-16	25.4	39.7	28.0	4000	112.0	16000	310	1.78

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example

Parker NO-SKIVE 372-12 WP 35,0 MPa (5075 PSI) | · · 19 mm (3/4) X 3W Made in Italy

372RH

No-Skive Compact

3-wire braid with fire-retardant cover



- *No-Skive* hose construction
- Nitrile (NBR) inner tube – high chemical resistance
- Small bend radii
- Fire-retardant cover
- German Standard: **DIN 5510-2**
- French Standard: **NF F16-101/102 I2/F3**
- British Standard: **BS 6853 - Table 4**

Primary Applications

Dynamic and static high-pressure hydraulic systems

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

Parker specifications
Working pressure and O.D. to EN 856-4SP

Construction

Tube: Nitrile (NBR)
Reinforcement: Three high-tensile steel wire braids
Cover: Fire retardant synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

70

Part Number	Hose I.D.				Hose O.D.	Pressure Rating				min. bend radius	weight
						max. working pressure		min. burst pressure			
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
372RH-6	10	3/8	-6	9.5	21.4	44.5	6500	178.0	25800	120	0.73
372RH-8	12	1/2	-8	12.7	24.6	41.5	6000	166.0	24000	160	0.90
372RH-10	16	5/8	-10	15.9	28.2	35.0	5000	140.0	20000	210	1.09
372RH-12	19	3/4	-12	19.1	32.2	35.0	5000	140.0	20000	260	1.36
372RH-16	25	1	-16	25.4	39.7	28.0	4000	112.0	16000	310	1.78

The combination of high temperature and high pressure could reduce the hose life.

Parkrimp Hose

Hose layline example

Parker RAIL HOSE 372RH-12 WP 35,0 MPa (5075 PSI) | • • 19 mm (3/4) X 3W Made in Italy

372TC

No-Skive Compact

3-wire braid compact hose with
4SP working pressures



- *No-Skive* hose construction – Compact design
- Nitrile (NBR) inner tube for greater fluid compatibility
- Highly abrasion resistant TOUGH COVER
- MSHA approved
- Hose is suitable for temporary immersion in mineral oil up to 70 °C with frequent inspections

Primary Applications

General high pressure hydraulic applications (typically in the mobile industry)

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

Parker specifications – working pressures and outside diameters according to EN 856-4SP

Construction

Tube:	Nitrile (NBR)
Reinforcement:	Three high-tensile steel wire braids
Cover:	Highly abrasion resistant MSHA approved synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception:	Air ..... max. +70 °C
	Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

70

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
372TC-6	10	3/8	-6	9.5	21.4	44.5	6500	178.0	25800	120	0.73
372TC-8	12	1/2	-8	12.7	24.6	41.5	6000	166.0	24000	160	0.90
372TC-10	16	5/8	-10	15.9	28.2	35.0	5000	140.0	20000	210	1.09
372TC-12	19	3/4	-12	19.1	32.2	35.0	5000	140.0	20000	260	1.36
372TC-16	25	1	-16	25.4	39.7	28.0	4000	112.0	16000	310	1.78

Replace the hose when any deformation or damage on the hose cover are visible.
The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



701

No-Skive Multispiral

ISO 3862 Type 4SP – EN 856 Type 4SP



- *No-Skive* hose construction
- Reinforcement of four high tensile steel wires

Primary Applications

General high pressure hydraulic applications

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

ISO 3862 Type 4SP – EN 856 Type 4SP

Construction

Tube: Synthetic rubber
Reinforcement: Four spirals high-tensile steel wire
Cover: Synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

70

Part Number	Hose I.D.				Hose O.D.	Pressure Rating				min. bend radius	weight
						max. working pressure		min. burst pressure			
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
701-6	10	3/8	-6	9.5	21.4	45.0	6500	180.0	26000	180	0.78
701-8	12	1/2	-8	12.7	24.6	41.5	6000	166.0	24000	230	0.93
701-10	16	5/8	-10	15.9	28.2	35.0	5000	140.0	20000	250	1.15
701-12	19	3/4	-12	19.1	32.2	35.0	5000	140.0	20000	300	1.58
701-16	25	1	-16	25.4	39.7	28.0	4000	112.0	16000	340	2.04

The combination of high temperature and high pressure could reduce the hose life.


Hose layline example

Parker NO-SKIVE 701-12 WP 35,0 MPa (5000 PSI) MSHA XXXX 19 mm (3/4) X 4S EN 856-4SP/20/4Q91

701TC

No-Skive Multispiral Tough Cover

ISO 3862 Type 4SP – EN 856 Type 4SP



- *No-Skive* hose construction
- Reinforcement of four high tensile steel wires
- Highly abrasion resistant TOUGH COVER
- MSHA approved
- Hose is suitable for temporary immersion in mineral oil up to 70 °C with frequent inspections

Primary Applications

General high pressure hydraulic applications

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

ISO 3862 Type 4SP – EN 856 Type 4SP

Construction

Tube:	Synthetic rubber
Reinforcement:	Four spirals high-tensile steel wire
Cover:	Highly abrasion resistant MSHA approved synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception:	Air ..... max. +70 °C
	Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series



Part Number	Hose I.D.				Hose O.D.	Pressure Rating				min. bend radius	weight
						max. working pressure		min. burst pressure			
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
701TC-6	10	3/8	-6	9.5	21.4	45.0	6500	180.0	26000	180	0.78
701TC-8	12	1/2	-8	12.7	24.6	41.5	6000	166.0	24000	230	0.93
701TC-10	16	5/8	-10	15.9	28.2	35.0	5000	140.0	20000	250	1.15
701TC-12	19	3/4	-12	19.1	32.2	35.0	5000	140.0	20000	300	1.58
701TC-16	25	1	-16	25.4	39.7	28.0	4000	112.0	16000	340	2.04

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example

Parker NO-SKIVE 701TC-12 WP 35,0 MPa (5000 PSI) MSHA XXXX 19 mm (3/4) X 4S EN 856-4SP/20/4Q91

722ClF

No-Skive Chlorine Free

SAE 100R12 - EN 856 Type R12 -
ISO 3862 Type R12



- *No-Skive* hose construction
  – Compact design
- 1/2 the bend radius of SAE 100R12
- Constant working pressure of 28.0 MPa
- Chlorine free compounds

Primary Applications

Transportation, construction, forestry

Applicable Specifications

SAE 100R12 – EN 856 Type R12 –
ISO 3862Type R12

Construction

Tube: Chlorine free Nitril (NBR)
Reinforcement: Four spirals high-tensile steel wire
Cover: Chlorine free synthetic rubber

Temperature Range ..... -40 °C up to +125 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

43

Series 43 you'll find in the Medium Pressure chapter Cb

Part Number	Hose I.D.				Hose O.D.	Pressure Rating				min. bend radius	weight
						max. working pressure		min. burst pressure			
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
722CLF-6	10	3/8	-6	9.5	19.9	28.0	4000	112	16000	65	0.60
722CLF-8	12	1/2	-8	12.7	22.7	28.0	4000	112	16000	90	0.80
722CLF-10	16	5/8	-10	15.9	26.4	28.0	4000	112	16000	100	1.10
722CLF-12	19	3/4	-12	19.1	30.7	28.0	4000	112	16000	120	1.40
722CLF-16	25	1	-16	25.4	37.8	28.0	4000	112	16000	150	1.99

Replace the hose when any deformation or damage on the hose cover are visible.
The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



722LT

No-Skive Low temperature spiral hose

for extreme cold conditions



- *No-Skive* hose construction
- Temperature Range from -57 °C up to 100 °C
- Constant working pressure of 28.0 MPa
- Compatible with petroleum
- 1/2 the bend radius of SAE 100R12

Primary Applications

Snow grooming equipment, heavy construction equipment, sideboo

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

SAE 100R12 – ISO 3862-1 Type R12 – EN 856 Type R12

Construction

Tube:	Nitrile (NBR)
Reinforcement:	Four spirals high-tensile steel wire
Cover:	Synthetic rubber

Temperature Range ..... -57 °C up to +100 °C

Recommended Fluids

Petroleum based hydraulic fluids and lubricating. Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

43

Series 43 for size -6 up to -20
Size -24 on request
Series 43 you'll find in the Medium Pressure chapter Cb

Part Number	Hose I.D.				Hose O.D.	Pressure Rating				min. bend radius	weight
						max. working pressure		min. burst pressure			
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
722LT-6	10	3/8	-6	9.5	19.9	28.0	4000	112.0	16000	65	0.60
722LT-8	12	1/2	-8	12.7	22.7	28.0	4000	112.0	16000	90	0.80
722LT-10	16	5/8	-10	15.9	26.4	28.0	4000	112.0	16000	100	1.10
722LT-12	19	3/4	-12	19.1	30.7	28.0	4000	112.0	16000	120	1.40
722LT-16	25	1	-16	25.4	37.8	28.0	4000	112.0	16000	150	1.99
722LT-20	31	1 1/4	-20	31.8	46.2	21.0	3000	84.0	12000	210	2.59
722LT-24	38	1 1/2	-24	38.1	52.5	17.5	2500	70.0	10000	250	2.99

Replace the hose when any deformation or damage on the hose cover are visible.
The combination of high temperature and high pressure could reduce the hose life.

722TC

No-Skive Tough Cover

Exceeds ISO 18752-CC



- *No-Skive* hose construction – Compact design
- 1/2 the bend radius of SAE 100R12
- Highly abrasion resistant TOUGH COVER
- MSHA approved
- Hose is suitable for temporary immersion in mineral oil up to 70 °C with frequent inspections

Primary Applications

General high pressure hydraulic applications

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

SAE 100R12 – EN 856 Type R12 –
ISO 3862 Type R12

Construction

Tube: Nitrile (NBR)
Reinforcement: Four spirals high-tensile steel wire
Cover: High abrasion resistance
MSHA approved synthetic rubber

Temperature Range ..... -40 °C up to +125 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

43

Series 43 only for size -20
Size -24 and -32 on request
Series 43 you'll find in the Medium Pressure chapter Cb

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
722TC-20	31	1 1/4	-20	31.8	46	21.0	3000	84.0	12000	210	2.59
722TC-24	38	1 1/2	-24	38.1	53	17.5	2500	70.0	10000	250	2.99
722TC-32	51	2	-32	50.8	66	17.5	2500	70.0	10000	320	4.09

Replace the hose when any deformation or damage on the hose cover are visible.
The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



722ST

No-Skive Super Tough

Exceeds ISO 18752-CC



- *No-Skive* hose construction
- ½ ISO 18752 minimum bend radius
- Exceeds ISO 18752 CC performance specification
- Extreme abrasion resistant SUPER TOUGH cover
- 4-spiral construction for longer life in high-impulse, heavy-duty cycle applications

Primary Applications

General high pressure hydraulic applications

Applicable Specifications

Exceed ISO 18752-CC

Construction

Tube:	Synthetic rubber
Reinforcement:	Four spirals high-tensile steel wire
Cover:	Synthetic rubber with a special polyethylene coating

Temperature Range ..... -40 °C up to +125 °C

Exception:	Air ..... max. +70 °C
	Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

43

Series 43 only for size -20
Size -24 and -32 on request
Series 43 you'll find in the Medium Pressure chapter Cb

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
722ST-20	31	1 1/4	-20	31.8	46	21.0	3000	84.0	12000	210	2.59
722ST-24	38	1 1/2	-24	38.1	53	17.5	2500	70.0	10000	250	2.99
722ST-32	51	2	-32	50.8	66	17.5	2500	70.0	10000	320	4.09

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



731

No-Skive Multispiral

ISO 3862 Type 4SH – EN 856 Type 4SH



- *No-Skive* hose construction
- Reinforcement of four high tensile steel wires

Primary Applications

General high pressure hydraulic applications

Applicable Specifications

ISO 3862 Type 4SH – EN 856 Type 4SH

Construction

Tube: Synthetic rubber
Reinforcement: Four spirals high-tensile steel wire
Cover: Synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

73

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
731-12	19	3/4	-12	19.1	32.0	42.0	6000	168.0	24000	280	1.72
731-16	25	1	-16	25.4	39.0	38.0	5500	152.0	22000	340	2.14
731-20	31	1 1/4	-20	31.8	45.0	32.0	4700	130.0	18800	460	2.96
731-24	38	1 1/2	-24	38.1	53.0	29.0	4200	116.0	16800	560	3.20
731-32	51	2	-32	50.8	68.0	25.0	3600	100.0	14400	700	5.30

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example

Parker NO-SKIVE 731-12 WP 42,0 MPa (6000 PSI) MSHA XXXX 19 mm (3/4) X 4S EN 856-4SH/20/4Q91

731TC

No-Skive Multispiral

ISO 3862 Type 4SH – EN 856 Type 4SH



- *No-Skive* hose construction
- Reinforcement of four high tensile steel wires
- Highly abrasion resistant TOUGH COVER
- MSHA approved
- Hose is suitable for temporary immersion in mineral oil up to 70 °C with frequent inspections

Primary Applications

General high pressure hydraulic applications

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

ISO 3862 Type 4SH – EN 856 Type 4SH

Construction

Tube:	Synthetic rubber
Reinforcement:	Four spirals high-tensile steel wire
Cover:	High abrasion resistance MSHA approved synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception:	Air ..... max. +70 °C
	Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

73

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
731TC-12	19	3/4	-12	19.1	32.0	42.0	6000	168.0	24000	280	1.72
731TC-16	25	1	-16	25.4	39.0	38.0	5500	152.0	22000	340	2.14
731TC-20	31	1 1/4	-20	31.8	45.0	32.0	4700	130.0	18800	460	2.96
731TC-24	38	1 1/2	-24	38.1	53.0	29.0	4200	116.0	16800	560	3.20
731TC-32	51	2	-32	50.8	68.0	25.0	3600	100.0	14400	700	5.30

Replace the hose when any deformation or damage on the hose cover are visible.
The combination of high temperature and high pressure could reduce the hose life.

Hose layline example

Parker TOUGH COVER 731TC-12 WP 42.0 MPa (6000 PSI) MSHA IC 40/26 | • • 19 mm (3/4) X 4S EN856-4SH

774

No-Skive Multispiral

For phosphate ester base fluids



- *No-Skive* hose construction
- Phosphate ester and weather resistant, green, EPDM synthetic rubber cover

Primary Applications

Test stands for aerospace, foundries, steel mills
High pressure hydraulic applications with phosphate ester fluids

Restrictions

Do not allow tube to contact any petroleum base fluids.
Use liquid soap as hose lubricant.

Applicable Specifications

Parker specifications

Construction

Tube:	Phosphate ester resistant EPDM synthetic rubber
Reinforcement:	Four spirals high-tensile steel wire
Cover:	Phosphate ester and weather resistant, green, EPDM synthetic rubber cover

Recommended Fluids

Phosphate ester base hydraulic fluids.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Temperature Range ..... -40 °C up to +80 °C

Fitting Series ..... on request

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
774-12	19	3/4	-12	19.1	31.0	28.0	4000	112.0	16000	240	1.40
774-16	25	1	-16	25.4	38.0	28.0	4000	112.0	16000	300	1.99
774-20	31	1 1/4	-20	31.8	47.0	21.0	3000	84.0	12000	420	2.59
774-24	38	1 1/2	-24	38.1	53.0	17.5	2500	70.0	10000	500	2.99
774-32	51	2	-32	50.8	67.0	17.5	2500	70.0	10000	630	4.09

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example

Parker NO-SKIVE 774-20 WP 21,0 MPa (3000 PSI) 31,5 mm (1 1/4) X 4S 3Q78

F42

No-Skive Multispiral

For phosphate ester base fluids



- *No-Skive* hose construction
- Phosphate ester and weather resistant, green, EPDM synthetic rubber cover
- Constant working pressure of 42.0 MPa

Primary Applications

Test stands for aerospace, foundries, steel mills
High pressure hydraulic applications with phosphate ester fluids

Applicable Specifications

Parker Specification

Restrictions

Do not allow tube to contact any petroleum base fluids.
Use liquid soap as hose lubricant.

Construction

Tube:	Phosphate ester resistant EPDM synthetic rubber
Reinforcement:	Four or six spirals high-tensile steel wire
Cover:	Phosphate ester and weather resistant, green, EPDM synthetic rubber cover

Temperature Range ..... -40 °C up to +80 °C

Exception:	Air	max. +70 °C
	Water	max. +85 °C

Recommended Fluids

Phosphate ester based hydraulic fluids, water-glycol based fluids, air and water.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series



Series 70 only for size -8
Size -12 up to size -20 on request

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
F42-8	12	1/2	-8	12.7	25.0	42.0	6000	168.0	24000	200	0.83
F42-12	19	3/4	-12	19.1	31.9	42.0	6000	168.0	24000	265	1.53
F42-16	25	1	-16	25.4	38.5	42.0	6000	168.0	24000	330	2.08
F42-20	31	1 1/4	-20	31.8	50	42.0	6000	168.0	24000	445	3.96

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



H29

ParLock Multispiral

Exceeds ISO 3862 Type 4SH –
EN 856 Type 4SH



- Interlock technology
- Reinforcement of four high tensile steel wires

Primary Applications

General high pressure hydraulic applications

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

Exceeds ISO 3862 Type 4SH – EN 856 Type 4SH

Construction

Tube:	Synthetic rubber
Reinforcement:	Four spirals high-tensile steel wire
Cover:	Synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception:	Air	..... max. +70 °C
	Water	..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

Internal and external skiving

V4

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
H29-12	19	3/4	-12	19.1	32.2	43.0	6250	172.0	25000	280	1.7
H29-16	25	1	-16	25.4	38.7	40.0	5800	160.0	23200	340	2.2
H29-20	31	1 1/4	-20	31.8	45.5	35.0	5000	140.0	20000	460	2.6
H29-24	38	1 1/2	-24	38.1	53.5	31.0	4500	124.0	18000	560	3.4
H29-32	51	2	-32	50.8	68.1	28.0	4050	112.0	16200	700	4.8

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



H29RH

ParLock Multispiral

Fire-retardant cover – exceeds
ISO 3862 Type 4SH – EN 856 Type 4SH



- Interlock technology
- Reinforcement of four high tensile steel wires
- Fire-retardant cover
- French Standard: **NF F16-101/102 I2/F3**
- British Standard: **BS 6853 - Table 4**

Primary Applications

General high pressure hydraulic applications

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

Exceeds ISO 3862 Type 4SH – EN 856 Type 4SH

Construction

Tube:	Synthetic rubber
Reinforcement:	Four spirals high-tensile steel wire
Cover:	Fire retardant synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception:	Air	..... max. +70 °C
	Water	..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

Internal and external skiving

V4

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
H29RH-16	25	1	-16	25.4	38.7	40.0	5800	160.0	23200	340	2.2
H29RH-20	31	1 1/4	-20	31.8	45.5	35.0	5000	140.0	20000	460	2.6
H29RH-24	38	1 1/2	-24	38.1	53.5	31.0	4500	124.0	18000	560	3.4

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example

Parker RAIL HOSE H29RH-16 WP 40 MPa (5800 PSI) | • • EXCEED ISO3862 - EN856 4SH - 25 mm

H29TC

ParLock Multispiral

Exceeds ISO 3862 Type 4SH –
EN 856 Type 4SH



- Interlock technology
- Reinforcement of four high tensile steel wires
- Highly abrasion resistant TOUGH COVER
- MSHA approved
- Hose is suitable for temporary immersion in mineral oil up to 70 °C with frequent inspections

Primary Applications

General high pressure hydraulic applications

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

Exceeds ISO 3862 Type 4SH – EN 856 Type 4SH

Construction

Tube:	Synthetic rubber
Reinforcement:	Four spirals high-tensile steel wire
Cover:	High abrasion resistance MSHA approved synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception:	Air ..... max. +70 °C
	Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

Internal and external skiving

V4

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
H29TC-12	19	3/4	-12	19.1	32.2	43.0	6250	172.0	25000	280	1.7
H29TC-16	25	1	-16	25.4	38.7	40.0	5800	160.0	23200	340	2.2
H29TC-20	31	1 1/4	-20	31.8	45.5	35.0	5000	140.0	20000	460	2.6
H29TC-24	38	1 1/2	-24	38.1	53.5	31.0	4500	124.0	18000	560	3.4
H29TC-32	51	2	-32	50.8	68.1	28.0	4050	112.0	16200	700	4.8

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



H29ST

ParLock Multispiral

Exceeds ISO 3862 Type 4SH –
EN 856 Type 4SH



- Interlock technology
- Extreme abrasion resistant SUPER TOUGH cover
- Reinforcement of four high tensile steel wires

Primary Applications

General high pressure hydraulic applications

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

Exceeds ISO 3862 Type 4SH – EN 856 Type 4SH

Construction

Tube:	Synthetic rubber
Reinforcement:	Four spirals high-tensile steel wire
Cover:	Synthetic rubber with a special polyethylene coating

Temperature Range ..... -40 °C up to +100 °C

Exception:	Air	max. +70 °C
	Water	max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

Internal and external skiving

V4

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
H29ST-12	19	3/4	-12	19.1	32.2	43.0	6250	172.0	25000	280	1.7
H29ST-16	25	1	-16	25.4	38.7	40.0	5800	160.0	23200	340	2.2
H29ST-20	31	1 1/4	-20	31.8	45.5	35.0	5000	140.0	20000	460	2.6
H29ST-24	38	1 1/2	-24	38.1	53.5	31.0	4500	124.0	18000	560	3.4
H29ST-32	51	2	-32	50.8	68.1	28.0	4050	112.0	16200	700	4.8

Replace the hose when any deformation or damage on the hose cover are visible.
The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



H31

ParLock Multispiral

Exceeds ISO 3862 Type 4SP –
EN 856 Type 4SP



- Interlock technology
- Reinforcement of four high tensile steel wires

Primary Applications

General high pressure hydraulic applications

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

Exceeds ISO 3862 Type 4SP – EN 856 Type 4SP

Construction

Tube:	Synthetic rubber
Reinforcement:	Four spirals high-tensile steel wire
Cover:	Synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception:	Air	..... max. +70 °C
	Water	..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

External skiving (size -4 up to -8) VS

Internal and external skiving (size -10 up to -16) V4

Part Number	Hose I.D.				Hose O.D.	Pressure Rating				min. bend radius	weight
						max. working pressure		min. burst pressure			
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
H31-4	6	1/4	-4	6.4	17.8	50.0	7250	200.0	29000	120	0.73
H31-6	10	3/8	-6	9.5	21.4	44.5	6450	178.0	25800	130	0.91
H31-8	12	1/2	-8	12.7	24.6	41.5	6000	166.0	24000	180	1.08
H31-10	16	5/8	-10	15.9	28.5	39.0	5650	156.0	22600	225	1.39
H31-12	19	3/4	-12	19.1	32.0	35.0	5000	140.0	20300	280	1.73
H31-16	25	1	-16	25.4	39.7	31.0	4500	124.0	18000	355	2.31

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example

Parker H31-12 WP 35,0 MPa (5000 PSI) | • • EXCEED ISO3862 - EN856 4SP - 19 mm (3/4")

H31TC

ParLock Multispiral

Exceeds ISO 3862 Type 4SP –
EN 856 Type 4SP



- Interlock technology
- Reinforcement of four high tensile steel wires
- Highly abrasion resistant TOUGH COVER
- MSHA approved
- Hose is suitable for temporary immersion in mineral oil up to 70 °C with frequent inspections

Primary Applications

General high pressure hydraulic applications

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

Exceeds ISO 3862 Type 4SP – EN 856 Type 4SP

Construction

Tube:	Synthetic rubber
Reinforcement:	Four spirals high-tensile steel wire
Cover:	High abrasion resistance MSHA approved synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception:	Air ..... max. +70 °C
	Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

External skiving (size -4 up to -8) VS

Internal and external skiving (size -10 up to -16) V4

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
H31TC-4	6	1/4	-4	6.4	17.8	50.0	7250	200.0	29000	120	0.73
H31TC-6	10	3/8	-6	9.5	21.4	44.5	6450	178.0	25800	130	0.91
H31TC-8	12	1/2	-8	12.7	24.6	41.5	6000	166.0	24000	180	1.08
H31TC-10	16	5/8	-10	15.9	28.5	39.0	5650	156.0	22600	225	1.39
H31TC-12	19	3/4	-12	19.1	32.0	35.0	5000	140.0	20300	280	1.73
H31TC-16	25	1	-16	25.4	39.7	31.0	4500	124.0	18000	355	2.31

Replace the hose when any deformation or damage on the hose cover are visible.
The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



H31ST

ParLock Multispiral

Exceeds ISO 3862 Type 4SP –
EN 856 Type 4SP



- Interlock technology
- Extreme abrasion resistant SUPER TOUGH cover
- Reinforcement of four high tensile steel wires

Primary Applications

General high pressure hydraulic applications

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

Exceeds ISO 3862 Type 4SP – EN 856 Type 4SP

Construction

Tube: Synthetic rubber
Reinforcement: Four spirals high-tensile steel wire
Cover: Synthetic rubber
with a special polyethylene coating

Temperature Range ..... -40 °C up to +100 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

External skiving (size -4 up to -8) VS
Internal and external skiving (size -10 up to -16) V4

Part Number	Hose I.D.				Hose O.D.	Pressure Rating				min. bend radius	weight
						max. working pressure		min. burst pressure			
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
H31ST-4	6	1/4	-4	6.4	17.8	50.0	7250	200.0	29000	120	0.73
H31ST-6	10	3/8	-6	9.5	21.4	44.5	6450	178.0	25800	130	0.91
H31ST-8	12	1/2	-8	12.7	24.6	41.5	6000	166.0	24000	180	1.08
H31ST-10	16	5/8	-10	15.9	28.5	39.0	5650	156.0	22600	225	1.39
H31ST-12	19	3/4	-12	19.1	32.0	35.0	5000	140.0	20300	280	1.73
H31ST-16	25	1	-16	25.4	39.7	31.0	4500	124.0	18000	355	2.31

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



R35

ParLock Multispiral

Exceeds ISO 3862 Type R13 –
Parker Specifications



- Interlock technology
- Reinforcement of four or six high tensile steel wires
- Constant working pressure of 35.0 MPa

Primary Applications

General high pressure hydraulic applications

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

Exceeds ISO 3862 Type R13 – Parker Specifications

Construction

Tube:	Synthetic rubber
Reinforcement:	Four or six spirals high-tensile steel wire
Cover:	Synthetic rubber

Temperature Range ..... -40 °C up to +125 °C

Exception:	Air ..... max. +70 °C
	Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

Internal and external skiving (size -12, -16, -20) V4

Internal and external skiving (size -24, -32) V6

Part Number	Hose I.D.				Hose O.D.	Pressure Rating				min. bend radius	weight
						max. working pressure		min. burst pressure			
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
R35-12	19	3/4	-12	19.1	32.00	35.0	5000	140.0	20000	220	1.5
R35-16	25	1	-16	25.4	39.35	35.0	5000	140.0	20000	280	2.2
R35-20	31	1 1/4	-20	31.8	45.50	35.0	5000	140.0	20000	380	2.6
R35-24	38	1 1/2	-24	38.1	57.30	35.0	5000	140.0	20000	480	4.8
R35-32	51	2	-32	50.8	71.10	35.0	5000	140.0	20000	600	6.7

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



R35TC/RS35TC-48

ParLock Multispiral

Exceeds ISO 3862 Type R13 – Parker Specifications



- Interlock technology
- Reinforcement of four or six high tensile steel wires
- Constant working pressure of 35.0 MPa
- Highly abrasion resistant TOUGH COVER
- MSHA approved
- Hose is suitable for temporary immersion in mineral oil up to 70 °C with frequent inspections

Primary Applications

General high pressure hydraulic applications

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

Exceeds ISO 3862 Type R13 – Parker Specifications

Construction

Tube: Synthetic rubber
Reinforcement: Four or six spirals high-tensile steel wire
Cover: High abrasion resistance
MSHA approved synthetic rubber

Temperature Range ..... -40 °C up to +125 °C

Exception: Air ..... max. +70 °C
Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series


Internal and external skiving (size -12 up to -20) V4
Internal and external skiving (size -24 up to -48) V6

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
R35TC-12	19	3/4	-12	19.1	32.00	35.0	5000	140.0	20000	220	1.5
R35TC-16	25	1	-16	25.4	39.35	35.0	5000	140.0	20000	280	2.2
R35TC-20	31	1 1/4	-20	31.8	45.50	35.0	5000	140.0	20000	380	2.6
R35TC-24	38	1 1/2	-24	38.1	57.30	35.0	5000	140.0	20000	480	4.8
R35TC-32	51	2	-32	50.8	71.10	35.0	5000	140.0	20000	600	6.7
R35TC-40	63	2 1/2	-40	63.5	84.50	35.0	5000	140.0	20000	800	9.0
RS35TC-48	76	3	-48	76.2	96.00	35.0*	5000*	88.0	12750	900	10.0
RS35TC-48	76	3	-48	76.2	96.00	21.0**	3040**	88.0	12750	900	10.0

Replace the hose when any deformation or damage on the hose cover are visible.
The combination of high temperature and high pressure could reduce the hose life.

* 35 MPa: Static applications according to ISO 6807-D
** 21 MPa: Dynamic hydraulic application design factor > 4:1

Hose layline example



R42

ParLock Multispiral

Exceeds ISO 3862 Type R15 – Parker Specifications



- Interlock technology
- Reinforcement of four or six high tensile steel wires
- Constant working pressure of 42.0 MPa

Primary Applications

General high pressure hydraulic applications

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

Exceeds ISO 3862 Type R15 – Parker Specifications

Construction

Tube:	Synthetic rubber
Reinforcement:	Four or six spirals high-tensile steel wire
Cover:	Synthetic rubber

Temperature Range ..... -40 °C up to +125 °C

Exception:	Air ..... max. +70 °C
	Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

Internal and external skiving (size -10, -12, -16) V4

Internal and external skiving (size -20, -24, -32) V6

Part Number	Hose I.D.				Hose O.D.	Pressure Rating				min. bend radius	weight
						max. working pressure		min. burst pressure			
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
R42-10	16	5/8	-10	15.9	28.50	42.0	6000	168.0	24000	225	1.39
R42-12	19	3/4	-12	19.1	32.00	42.0	6000	168.0	24000	280	1.70
R42-16	25	1	-16	25.4	39.00	42.0	6000	168.0	24000	300	2.30
R42-20	31	1 1/4	-20	31.8	50.75	42.0	6000	168.0	24000	400	3.80
R42-24	38	1 1/2	-24	38.1	57.00	42.0	6000	168.0	24000	500	4.80
R42-32	51	2	-32	50.8	71.50	42.0	6000	168.0	24000	700	7.00

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example

Parker R42-16 WP 42.0 MPa (6000 PSI) I · · ISO 3862 - SAE100R15 - 25 mm (1")

R42TC

ParLock Multispiral

Exceeds ISO 3862 Type R15 – Parker Specifications



- Interlock technology
- Reinforcement of four or six high tensile steel wires
- Constant working pressure of 42.0 MPa
- Highly abrasion resistant TOUGH COVER
- MSHA approved
- Hose is suitable for temporary immersion in mineral oil up to 70 °C with frequent inspections

Primary Applications

General high pressure hydraulic applications

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

Exceeds ISO 3862 Type R15 – Parker Specifications

Construction

Tube:	Synthetic rubber
Reinforcement:	Four or six spirals high-tensile steel wire
Cover:	High abrasion resistance MSHA approved synthetic rubber

Temperature Range ..... -40 °C up to +125 °C

Exception:	Air ..... max. +70 °C
	Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

Internal and external skiving (size -10, -12, -16) V4

Internal and external skiving (size -20, -24, -32) V6

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
R42TC-10	16	5/8	-10	15.9	28.50	42.0	6000	168.0	24000	225	1.39
R42TC-12	19	3/4	-12	19.1	32.00	42.0	6000	168.0	24000	280	1.70
R42TC-16	25	1	-16	25.4	39.00	42.0	6000	168.0	24000	300	2.30
R42TC-20	31	1 1/4	-20	31.8	50.75	42.0	6000	168.0	24000	400	3.80
R42TC-24	38	1 1/2	-24	38.1	57.00	42.0	6000	168.0	24000	500	4.80
R42TC-32	51	2	-32	50.8	71.50	42.0	6000	168.0	24000	700	7.00

Replace the hose when any deformation or damage on the hose cover are visible.
The combination of high temperature and high pressure could reduce the hose life.

Hose layline example

Parker TOUGH COVER R42TC-32 WP 42.0 MPa (6000 PSI) MSHA IC 40/26 I · · ISO 3862 - SAE100R

R42ST

ParLock Multispiral

Exceeds ISO 3862 Type R15 –
Parker Specifications



- Interlock technology
- Extreme abrasion resistant SUPER TOUGH cover
- Reinforcement of four or six high tensile steel wires
- Constant working pressure of 42.0 MPa

Primary Applications

General high pressure hydraulic applications

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

Exceeds ISO 3862 Type R15 – Parker Specifications

Construction

Tube:	Synthetic rubber
Reinforcement:	Four or six spirals high-tensile steel wire
Cover:	Synthetic rubber with a special polyethylene coating

Temperature Range ..... -40 °C up to +125 °C

Exception:	Air	max. +70 °C
	Water	max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series

Internal and external skiving (size -10, -12, -16) V4

Internal and external skiving (size -20, -24, -32) V6

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
R42ST-10	16	5/8	-10	15.9	28.50	42.0	6000	168.0	24000	225	1.39
R42ST-12	19	3/4	-12	19.1	32.00	42.0	6000	168.0	24000	280	1.70
R42ST-16	25	1	-16	25.4	39.00	42.0	6000	168.0	24000	300	2.30
R42ST-20	31	1 1/4	-20	31.8	50.75	42.0	6000	168.0	24000	400	3.80
R42ST-24	38	1 1/2	-24	38.1	57.00	42.0	6000	168.0	24000	500	4.80
R42ST-32	51	2	-32	50.8	71.50	42.0	6000	168.0	24000	700	7.00

The combination of high temperature and high pressure could reduce the hose life.

Hose layline example

Parker SUPER TOUGH R42ST-20 WP 42.0 MPa (6000 PSI) MSHA IC 111/3 I · · 31.5 mm (1 1/4)

R50TC/R56TC

ParLock Multispiral

Exceeds ISO 3862 Type R15 – Parker Specifications



- Interlock technology
- Reinforcement of four or six high tensile steel wires
- Constant working pressure of 50.0 MPa (R50TC) and 56.0 MPa (R56TC)
- Highly abrasion resistant TOUGH COVER
- MSHA approved
- Hose is suitable for temporary immersion in mineral oil up to 70 °C with frequent inspections

Primary Applications

Mobile hydraulic equipment and agricultural machines with typically large constructions.

Type Approvals

Details please find on pages ***Ab-16*** to ***Ab-19***

Applicable Specifications

Exceeds ISO 3862 Type R15 – Parker Specifications

Construction

Tube:	Synthetic rubber
Reinforcement:	Four or six spirals high-tensile steel wire
Cover:	High abrasion resistance MSHA approved synthetic rubber

Temperature Range ..... -40 °C up to +100 °C

Exception:	Air ..... max. +70 °C
	Water ..... max. +85 °C

Recommended Fluids

Petroleum and water-glycol based fluids, lubricating oils, air and water. For air above 1.7 MPa, the hose cover must be pin-pricked.
Consult the chemical compatibility section on pages ***Ab-26*** to ***Ab-34*** for more detailed information.

Fitting Series Internal and external skiving

R56TC-6 and R56TC-8 — V5


R50TC-10 up to -16 — V4

R50TC-20 — V6

Part Number	Hose I.D.				Hose O.D.	Pressure Rating: max. working pressure		Pressure Rating: min. burst pressure		min. bend radius	weight
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
R56TC-6	10	3/8	-6	9.5	21.8	56.0	8100	224.0	32400	130	0.95
R56TC-8	12	1/2	-8	12.7	25.5	56.0	8100	224.0	32400	180	1.25
R50TC-10	16	5/8	-10	15.9	28.50	50.0	7250	200.0	29000	225	1.48
R50TC-12	19	3/4	-12	19.1	32.00	50.0	7250	200.0	29000	270	1.85
R50TC-16	25	1	-16	25.4	38.40	50.0	7250	200.0	29000	300	2.70
R50TC-20	31	1 1/4	-20	31.8	52.60	50.0	7250	200.0	29000	450	5.00

Replace the hose when any deformation or damage on the hose cover are visible.
The combination of high temperature and high pressure could reduce the hose life.

Hose layline example



BPK

Blastopak ParLock Multispiral

DIN EN 1829-2



- Interlock technology
- Reinforcement of four or six spirals of highly tensile steel wire
- DIN EN 1829-2

Primary Applications

Water blasting applications, water cutting applications, cleaning and paint or corrosion removal.
Not recommended for dynamic hydraulic applications

Applicable Specifications

Exceeds ISO 3862 Type R15 – Parker Specifications

Construction

Tube:	Synthetic rubber
Reinforcement:	Four or six spirals high-tensile steel wire
Cover:	Synthetic rubber

Continuous Service Temperature Range

-10 °C up to +70 °C

Max. Service Temperature Range

-40 °C up to +93 °C

Applicable Specifications

DIN EN 1829-2

Recommended Fluids

Water, water-soap emulsion

Fitting Series

Internal and external skiving

WB

Part Number	Hose I.D.				Hose O.D.	Pressure Rating				min. bend radius	weight
						max. working pressure		min. burst pressure			
	DN	Inch	Size	mm	mm	MPa	psi	MPa	psi	mm	kg
BPK-4	6	1/4	-4	6.4	17.6	110.0	15900	275.0	39800	100	0.64
BPK-6	10	3/8	-6	9.5	21.8	110.0	15900	275.0	39800	130	1.10
BPK-8	12	1/2	-8	12.7	25.5	110.0	15900	275.0	39800	200	1.40
BPK-12	20	3/4	-12	19.1	35.2	110.0	15900	275.0	39800	250	2.50
BPK-16	25	1	-16	25.4	41.8	80.0	11600	200.0	29000	300	3.00


Replace the hose when any deformation or damage on the hose cover are visible.
The combination of high temperature and high pressure could reduce the hose life.


Hose layline example

Parker BPK-12 BLASTOPAK WP 1100 bar (16000 psi)

DIN – Metric


Page Db-1 – Db-4


CA Db-1

Female Metric 24° Light Series with O–Ring Swivel – Straight
ISO 12151-2-SWS-L – DKOL

CE Db-1

Female Metric 24° Light Series with O–Ring Swivel – 45° Elbow
ISO 12151-2-SWE 45°-L – DKOL 45°

CF Db-2

Female Metric 24° Light Series with O–Ring Swivel – 90° Elbow
ISO 12151-2-SWE-L – DKOL 90°

D0 Db-2

Male Metric 24° Light Series – Rigid Straight
ISO 12151-2-S-L – CEL


C9 Db-3

Female Metric 24° – Swivel Heavy Series with O-Ring Straight
ISO 12151-2-SWS-S – DKOS

0C Db-3

Female Metric 24° – Swivel Heavy Series with O–Ring 45° Elbow
ISO 12151-2 – SWE 45°-S – DKOS 45°


1C Db-4

Female Metric 24° – Swivel Heavy Series with O–Ring 90° Elbow
ISO 12151-2-SWE-S – DKOS 90°

D2 Db-4

Male Metric 24° – Rigid Heavy Series – Straight
ISO 12151-2-S-S – CES

BSP

Page Db-5 – Db-7


92 Db-5

Female BSP Parallel Pipe Swivel – Straight (60° Cone)
BS5200-A – DKR


B1 Db-5


Female BSP Parallel Pipe Swivel 45° Elbow (60° Cone)
BS 5200-D – DKR 45°

B2 Db-6

Female BSP Parallel Pipe Swivel 90° Elbow (60° Cone)
BS 5200-B – DKR 90°


EA Db-6

BSP Swivel Female with O–Ring (60° Cone)
BS 5200 – ISO 12151-6 – DKOR


EC Db-7

BSP Swivel Female with O–Ring 90° Elbow (60° Cone)
BS 5200 – ISO 12151-6 – DKOR 90°


D9 Db-7

Male BSP Parallel Pipe Rigid – Straight (60° Cone)
BS5200 – AGR


SAE


Page Db-8 – Db-10

01 Db-8

Male NPTF Pipe Rigid – Straight
SAE J476A / J516 – AGN

03 Db-8

Male JIC 37° – Rigid Straight
ISO12151-5-S – AGJ

06 Db-9

Female JIC 37° – Swivel Straight
ISO12151-5-SWS – DKJ


37 Db-10

Female JIC 37° – Swivel 45° Elbow
ISO 12151-5-SWE 45° – DKJ 45°

39/3W Db-10

Female JIC 37° SAE 45° – Dual Flare Swivel Female 90° Elbow
ISO 12151-5-SWES – DKJ 90°

Flange


Page Db-11 – Db-14

15 Db-11




ISO 6162-1 Flange
Straight
ISO 12151-3-S-L – SFL
(21.0 MPa/ 3000 psi)

17 Db-11




ISO 6162-1 Flange
45° Elbow
ISO 12151-3 – E45 – L – SFL 45°
(21.0 MPa/ 3000 psi)

19 Db-12




ISO 6162-1 Flange
90° Elbow
ISO 12151-3 – E– L – SFL 90°
(21.0 MPa/ 3000 psi)

6A Db-12




ISO 6162-2 Flange
Straight
ISO 12151-3-S-S – SFS
(42.0 MPa/ 6000 psi)

6F Db-13




ISO 6162-2 Flange
45° Elbow – Heavy Series
ISO 12151-3 – E45-S – SFS 45°
(42.0 MPa/ 6000 psi)

6N Db-13



ISO 6162-2 Flange
90° Elbow
ISO 12151-3 – E-S – SFS 90°
(42.0 MPa/ 6000 psi)

PY Db-14




Flange – 24° Male
French Gas
Straight

ORFS


Page Db-15 – Db-17

JC Db-15




Female ORFS
Swivel – Straight
Short
ISO 12151-1 – SWSA SAE J516 – ORFS

JS Db-15



ORFS Swivel Female (Long)
ISO 12151-1-SWSB
SAE J516 – ORFS

J7 Db-16



Female ORFS – Swivel
45° Elbow
ISO 12151-1 – SWE 45°
SAE J516 – ORFS 45°

J9 Db-16




Female ORFS – Swivel
90° Elbow – Short Drop
ISO 12151-1 – SWES
SAE J516 – ORFS 90°

J1 Db-17



Female ORFS – Swivel
90° Elbow – Long Drop
ISO 12151-1 – SWEL
SAE J 516 – ORFS 90° L

JM Db-17




ORFS Male
ISO 12151-1-S – SAE J516

JIS

Page Db-18

MU Db-18




Female Metric – Swivel
Straight (30° Flare)
JIS B8363 – MU

French Standard


Page Db-19

FG Db-19



Male French Gas Series
Rigid – Straight (24° Cone)

F4 Db-19




Female French Gas Series
Swivel – Straight
(Ball Nose)

Others


Page Db-20

XU Db-20



Female Metric – Swivel
Straight (30° Flare)
JIS B8363

XY Db-20





Female Metric – Swivel
90° Elbow (30° Flare)
JIS B8363

CA

Female Metric 24° Light Series with O-Ring Swivel – Straight

ISO 12151-2-SWS-L – DKOL






Part Number	Hose I.D.				Thread	Tube O.D.	A	B	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
1CA70-10-6	10	3/8	-6	9.5	M16x1.5	10	53	24	19
1CA70-12-6	10	3/8	-6	9.5	M18x1.5	12	53	24	22
1CA70-15-8	12	1/2	-8	12.7	M22x1.5	15	62	27	27
1CA70-18-8	12	1/2	-8	12.7	M26x1.5	18	57	22	32
1CA70-15-10	16	5/8	-10	15.9	M22x1.5	15	66	27	27
1CA70-18-10	16	5/8	-10	15.9	M26x1.5	18	62	25	32
1CA70-22-10	16	5/8	-10	15.9	M30x2	22	64	24	36
1CA70-18-12	19	3/4	-12	19.1	M26x1.5	18	65	26	32
1CA70-22-12	19	3/4	-12	19.1	M30x2	22	63	24	36
1CA70-28-12	19	3/4	-12	19.1	M36x2	28	66	26	41
1CA70-28-16	25	1	-16	25.4	M36x2	28	78	33	41
1CA70-35-16	25	1	-16	25.4	M45x2	35	76	31	50


Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.
Attention: Hose assembly pressure is reduced; see page Ab-8

CE

Female Metric 24° Light Series with O-Ring Swivel – 45° Elbow

ISO 12151-2-SWE 45°-L – DKOL 45°





Part Number	Hose I.D.				Thread	Tube O.D.	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
1CE70-12-6	10	3/8	-6	9.5	M18x1.5	12	69	40	20	22
1CE70-15-8	12	1/2	-8	12.7	M22x1.5	15	85	50	24	27
1CE70-18-10	16	5/8	-10	15.9	M26x1.5	18	89	49	23	32
1CE70-22-12	19	3/4	-12	19.1	M30x2	22	98	58	26	36
1CE70-28-16	25	1	-16	25.4	M36x2	28	127	80	34	41

Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.
Attention: Hose assembly pressure is reduced; see page Ab-8


Approved **fitting series** for **hose types**:


70 | 371LT | 372 | 372RH | 372TC | 701 | 701 TC | F42-8

CF

Female Metric 24° Light Series with O-Ring Swivel – 90° Elbow

ISO 12151-2-SWE-L – DKOL 90°






Part Number	Hose I.D.				Thread	Tube O.D.	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
1CF70-10-6	10	3/8	-6	9.5	M16x1.5	10	67	38	38	19
1CF70-12-6	10	3/8	-6	9.5	M18x1.5	12	67	38	37	22
1CF70-15-8	12	1/2	-8	12.7	M22x1.5	15	74	39	45	27
1CF70-18-8	12	1/2	-8	12.7	M26x1.5	18	71	36	40	32
1CF70-15-10	16	5/8	-10	15.9	M22x1.5	15	79	42	50	27
1CF70-18-10	16	5/8	-10	15.9	M26x1.5	18	79	42	49	32
1CF70-18-12	19	3/4	-12	19.1	M26x1.5	18	89	49	56	32
1CF70-22-12	19	3/4	-12	19.1	M30x2	22	89	49	55	36
1CF70-28-16	25	1	-16	25.4	M36x2	28	114	68	78	41
1CF70-35-16	25	1	-16	25.4	M45x2	35	115	68	69	50


Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

D0

Male Metric 24° Light Series – Rigid Straight

ISO 12151-2-S-L – CEL





Part Number	Hose I.D.				Thread	Tube O.D.	A	B	H
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
1D070-15-8	12	1/2	-8	12.7	M22x1.5	15	60	26	22
1D070-18-10	16	5/8	-10	15.9	M26x1.5	18	65	28	27
1D070-22-12	19	3/4	-12	19.1	M30x2	22	69	30	30
1D070-28-16	25	1	-16	25.4	M36x2	28	79	32	36


Attention: Hose assembly pressure is reduced; see page Ab-8


Approved **fitting series** for **hose types**:

70 | 371LT | 372 | 372RH | 372TC | 701 | 701 TC | F42-8

C9 Female Metric 24° – Swivel Heavy Series with O-Ring Straight

ISO 12151-2-SWS-S – DKOS







Part Number	Hose I.D.				Thread	Tube O.D.	A	B	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
1C970-8-6	10	3/8	-6	9.5	M16x1.5	8	53	24	19
1C970-12-6	10	3/8	-6	9.5	M20x1.5	12	52	22	24
1C970-14-6	10	3/8	-6	9.5	M22x1.5	14	53	24	27
1C970-12-8	12	1/2	-8	12.7	M20x1.5	12	60	25	24
1C970-16-8	12	1/2	-8	12.7	M24x1.5	16	59	24	30
1C970-20-8	12	1/2	-8	12.7	M30x2	20	59	24	36
1C970-16-10	16	5/8	-10	15.9	M24x1.5	16	66	27	30
1C970-20-10	16	5/8	-10	15.9	M30x2	20	64	27	36
1C970-25-10	16	5/8	-10	15.9	M36x2	25	65	29	46
1C970-20-12	19	3/4	-12	19.1	M30x2	20	66	27	36
1C970-25-12	19	3/4	-12	19.1	M36x2	25	68	28	46
1C970-25-16	25	1	-16	25.4	M36x2	25	78	33	46
1C970-30-16	25	1	-16	25.4	M42x2	30	80	33	50

Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

0C Female Metric 24° – Swivel Heavy Series with O-Ring 45° Elbow

ISO 12151-2 – SWE 45°-S – DKOS 45°





Part Number	Hose I.D.				Thread	Tube O.D.	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
10C70-12-6	10	3/8	-6	9.5	M20x1.5	12	69	40	20	24
10C70-14-6	10	3/8	-6	9.5	M22x1.5	14	76	46	20	27
10C70-16-8	12	1/2	-8	12.7	M24x1.5	16	83	48	24	30
10C70-16-10	16	5/8	-10	15.9	M24x1.5	16	88	49	22	30
10C70-20-10	16	5/8	-10	15.9	M30x2	20	91	52	25	36
10C70-25-10	16	5/8	-10	15.9	M36x2	25	92	56	27	46
10C70-20-12	19	3/4	-12	19.1	M30x2	20	99	60	28	36
10C70-25-12	19	3/4	-12	19.1	M36x2	25	100	61	29	46
10C70-25-16	25	1	-16	25.4	M36x2	25	123	76	33	46
10C70-30-16	25	1	-16	25.4	M42x2	30	126	79	36	50


Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.


Approved **fitting series** for **hose types**:

70 | 371LT | 372 | 372RH | 372TC | 701 | 701 TC | F42-8

1C Female Metric 24° – Swivel Heavy Series with O-Ring 90° Elbow

ISO 12151-2-SWE-S – DKOS 90°







Part Number	Hose I.D.				Thread	Tube O.D.	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
11C70-8-6	10	3/8	-6	9.5	M16x1.5	8	67	38	37	19
11C70-12-6	10	3/8	-6	9.5	M20x1.5	12	67	38	37	24
11C70-14-6	10	3/8	-6	9.5	M22x1.5	14	64	35	37	27
11C70-16-8	12	1/2	-8	12.7	M24x1.5	16	72	37	45	30
11C70-20-8	12	1/2	-8	12.7	M30x2	20	75	40	46	36
11C70-16-10	16	5/8	-10	15.9	M24x1.5	16	79	40	45	30
11C70-20-10	16	5/8	-10	15.9	M30x2	20	79	40	48	36
11C70-25-10	16	5/8	-10	15.9	M36x2	25	85	46	52	46
11C70-20-12	19	3/4	-12	19.1	M30x2	20	89	50	58	36
11C70-25-12	19	3/4	-12	19.1	M36x2	25	89	49	59	46
11C70-30-12	19	3/4	-12	19.1	M42x2	30	89	50	60	50
11C70-25-16	25	1	-16	25.4	M36x2	25	109	64	69	46
11C70-30-16	25	1	-16	25.4	M42x2	30	115	68	76	50

Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

D2 Male Metric 24° – Rigid Heavy Series – Straight

ISO 12151-2-S-S – CES






Part Number	Hose I.D.				Thread	Tube O.D.	A	B	H
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
1D270-12-6	10	3/8	-6	9.5	M20x1.5	12	53	24	22
1D270-14-6	10	3/8	-6	9.5	M22x1.5	14	55	25	22
1D270-16-8	12	1/2	-8	12.7	M24x1.5	16	62	28	24
1D270-20-8	12	1/2	-8	12.7	M30x2	20	67	32	30
1D270-20-10	16	5/8	-10	15.9	M30x2	20	75	32	30
1D270-20-12	19	3/4	-12	19.1	M30x2	20	72	33	30
1D270-25-12	19	3/4	-12	19.1	M36x2	25	74	35	36
1D270-25-16	25	1	-16	25.4	M36x2	25	84	37	36
1D270-30-16	25	1	-16	25.4	M42x2	30	85	40	46

Approved **fitting series** for **hose types**:

70 | 371LT | 372 | 372RH | 372TC | 701 | 701 TC | F42-8

92 Female BSP Parallel Pipe Swivel – Straight (60° Cone)

BS5200-A – DKR







Part Number	Hose I.D.				Thread	A	B	W
	DN	Inch	Size	mm	BSP	mm	mm	mm
19270-6-6	10	3/8	-6	9.5	3/8x19	49	20	22
19270-8-6	10	3/8	-6	9.5	1/2x14	51	22	27
19270-8-8	12	1/2	-8	12.7	1/2x14	57	22	27
19270-10-8	12	1/2	-8	12.7	5/8x14	55	20	30
19270-10-10	16	5/8	-10	15.9	5/8x14	57	21	30
19270-12-10	16	5/8	-10	15.9	3/4x14	61	22	32
19270-12-12	19	3/4	-12	19.1	3/4x14	61	22	32
19270-16-12	19	3/4	-12	19.1	1x11	63	24	41
19270-16-16	25	1	-16	25.4	1x11	72	25	41

B1 Female BSP Parallel Pipe Swivel 45° Elbow (60° Cone)

BS 5200-D – DKR 45°






Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	BSP	mm	mm	mm	mm
1B170-4-6	10	3/8	-6	9.5	1/4x19	68	39	19	19
1B170-6-6	10	3/8	-6	9.5	3/8x19	67	37	17	22
1B170-8-6	10	3/8	-6	9.5	1/2x14	68	39	19	27
1B170-8-8	12	1/2	-8	12.7	1/2x14	79	45	20	27
1B170-10-8	12	1/2	-8	12.7	5/8x14	78	43	19	30
1B170-10-10	16	5/8	-10	15.9	5/8x14	89	50	23	30
1B170-12-10	16	5/8	-10	15.9	3/4x14	88	49	22	32
1B170-12-12	19	3/4	-12	19.1	3/4x14	96	57	25	32
1B170-16-12	19	3/4	-12	19.1	1x11	95	56	24	41
1B170-16-16	25	1	-16	25.4	1x11	121	77	33	41


Approved **fitting series** for **hose types**:

70 371LT | 372 | 372RH | 372TC | 701 | 701 TC | F42-8

B2 Female BSP Parallel Pipe Swivel 90° Elbow (60° Cone)

BS 5200-B – DKR 90°







Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	BSP	mm	mm	mm	mm
1B270-6-6	10	3/8	-6	9.5	3/8x19	66	37	33	22
1B270-8-6	10	3/8	-6	9.5	1/2x14	66	37	35	27
1B270-8-8	12	1/2	-8	12.7	1/2x14	70	35	39	27
1B270-10-8	12	1/2	-8	12.7	5/8x14	74	39	38	30
1B270-10-10	16	5/8	-10	15.9	5/8x14	81	41	46	30
1B270-12-10	16	5/8	-10	15.9	3/4x14	92	52	59	32
1B270-16-10	16	5/8	-10	15.9	1x11	86	46	44	41
1B270-12-12	19	3/4	-12	19.1	3/4x14	89	50	53	32
1B270-16-12	19	3/4	-12	19.1	1x11	89	49	51	41
1B270-16-16	25	1	-16	25.4	1x11	116	69	69	41

EA BSP Swivel Female with O–Ring (60° Cone)

BS 5200 – ISO 12151-6 – DKOR





Part Number	Hose I.D.				Thread	A	B	W
	DN	Inch	Size	mm	BSP	mm	mm	mm
1EA70-8-8	12	1/2	-8	12.7	1/2x14	56	21	27
1EA70-12-12	19	3/4	-12	19.1	3/4x14	63	23	32
1EA70-16-16	25	1	-16	25.4	1x11	77	31	41

Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.


Approved **fitting series** for **hose types**:


70 | 371LT | 372 | 372RH | 372TC | 701 | 701 TC | F42-8

EC

BSP Swivel Female with O–Ring 90° Elbow (60° Cone)

BS 5200 – ISO 12151-6 – DKOR 90°






Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	BSP	mm	mm	mm	mm
1EC70-8-8	12	1/2	-8	12.7	1/2x14	71	36	40	27
1EC70-12-12	19	3/4	-12	19.1	3/4x14	89	49	55	32
1EC70-16-16	25	1	-16	25.4	1x11	115	68	71	41


Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

D9

Male BSP Parallel Pipe Rigid – Straight (60° Cone)

BS5200 – AGR






Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	BSP	mm	mm	mm
1D970-6-6	10	3/8	-6	9.5	3/8x19	57	28	22
1D970-8-6	10	3/8	-6	9.5	1/2x14	60	31	27
1D970-8-8	12	1/2	-8	12.7	1/2x14	62	28	27
1D970-10-8	12	1/2	-8	12.7	5/8x14	70	36	30
1D970-12-8	12	1/2	-8	12.7	3/4x14	69	35	32
1D970-10-10	16	5/8	-10	15.9	5/8x14	75	36	30
1D970-12-10	16	5/8	-10	15.9	3/4x14	72	35	32
1D970-12-12	19	3/4	-12	19.1	3/4x14	72	33	32
1D970-16-12	19	3/4	-12	19.1	1x11	77	38	41
1D970-16-16	25	1	-16	25.4	1x11	85	40	41


Approved **fitting series** for **hose types**:

70 | 371LT | 372 | 372RH | 372TC | 701 | 701 TC | F42-8

01 Male NPTF Pipe Rigid – Straight

SAE J476A / J516 – AGN







Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	NPTF	mm	mm	mm
10170-6-6-SM	10	3/8	-6	9.5	3/8x18	60	31	19
10170-12-8-SM	12	1/2	-8	12.7	3/4x14	68	33	27
10170-8-10-SM	16	5/8	-10	15.9	1/2x14	75	38	24
10170-12-10-SM	16	5/8	-10	15.9	3/4x14	71	34	27
10170-12-12-SM	19	3/4	-12	19.1	3/4x14	79	39	27
10170-16-12-SM	19	3/4	-12	19.1	1x11 1/2	79	39	36
10170-16-16-SM	25	1	-16	25.4	1x11 1/2	93	46	36

03 Male JIC 37° – Rigid Straight

ISO12151-5-S – AGJ






Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	UNF	mm	mm	mm
10370-6-6-SM	10	3/8	-6	9.5	9/16x18	60	31	19
10370-8-6-SM	10	3/8	-6	9.5	3/4x16	59	29	19
10370-8-8-SM	12	1/2	-8	12.7	3/4x16	68	33	22
10370-10-8-SM	12	1/2	-8	12.7	7/8x14	67	32	24
10370-12-8-SM	12	1/2	-8	12.7	1 1/16x12	71	36	27
10370-10-10-SM	16	5/8	-10	15.9	7/8x14	75	38	24
10370-12-10-SM	16	5/8	-10	15.9	1 1/16x12	75	36	27
10370-12-12-SM	19	3/4	-12	19.1	1 1/16x12	82	42	27
10370-16-12-SM	19	3/4	-12	19.1	1 5/16x12	77	38	36
10370-16-16-SM	25	1	-16	25.4	1 5/16x12	94	47	36


Approved **fitting series** for **hose types**:

70 | 371LT | 372 | 372RH | 372TC | 701 | 701 TC | F42-8

06 Female JIC 37° – Swivel Straight

ISO12151-5-SWS – DKJ





Part Number	Hose I.D.				Thread	A	B	H	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
10670-6-6-SM	10	3/8	-6	9.5	9/16x18	58	29	17	19
10670-8-6-SM	10	3/8	-6	9.5	3/4x16	61	32	19	22
10670-8-8-SM*	12	1/2	-8	12.7	3/4x16	67	32	22	22
10670-12-8-SM	12	1/2	-8	12.7	1 1/16x12	71	36	27	32
10670-10-10-SM	16	5/8	-10	15.9	7/8x14	75	35	24	27
10670-12-10-SM	16	5/8	-10	15.9	1 1/16x12	79	39	27	32
10670-12-12-SM	19	3/4	-12	19.1	1 1/16x12	80	41	27	32
10670-14-12-SM	19	3/4	-12	19.1	1 3/16x12	81	42	32	36
10670-16-12-SM	19	3/4	-12	19.1	1 5/16x12	84	45	32	41
10670-12-16-SM	25	1	-16	25.4	1 1/16x12	89	44	36	32
10670-16-16-SM	25	1	-16	25.4	1 5/16x12	94	47	36	41
10670-20-16-SM	25	1	-16	25.4	1 5/8x12	98	52	41	50


* These fittings contain a dual seat that accepts both JIC (37°) and SAE (45°) male configurations.


Approved **fitting series** for **hose types**:

70 | 371LT | 372 | 372RH | 372TC | 701 | 701 TC | F42-8

37 Female JIC 37° – Swivel 45° Elbow

ISO 12151-5-SWE 45° – DKJ 45°







Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
13770-6-6-SM	10	3/8	-6	9.5	9/16x18	61	32	11	19
13770-8-6-SM*	10	3/8	-6	9.5	3/4x16	70	41	14	22
13770-8-8-SM*	12	1/2	-8	12.7	3/4x16	73	38	14	22
13770-10-8-SM*	12	1/2	-8	12.7	7/8x14	78	43	17	27
13770-8-10-SM*	16	5/8	-10	15.9	3/4x16	78	39	15	22
13770-10-10-SM*	16	5/8	-10	15.9	7/8x14	83	42	16	27
13770-12-10-SM	16	5/8	-10	15.9	1 1/16x12	88	48	21	32
13770-12-12-SM	19	3/4	-12	19.1	1 1/16x12	91	52	20	32
13770-16-16-SM	25	1	-16	25.4	1 5/16x12	111	66	24	41
13770-20-16-SM	25	1	-16	25.4	1 5/8x12	114	67	26	50

* These fittings contain a dual seat that accepts both JIC (37°) and SAE (45°) male configurations.

39/3W Female JIC 37° SAE 45° – Dual Flare Swivel Female 90° Elbow

ISO 12151-5-SWES – DKJ 90°





Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
13970-6-6-SM	10	3/8	-6	9.5	9/16x18	57	28	23	19
13W70-8-6-SM	10	3/8	-6	9.5	3/4x16	64	35	29	22
13970-6-8-SM	12	1/2	-8	12.7	9/16x18	64	29	22	19
13970-12-10-SM	16	5/8	-10	15.9	1 1/16x12	87	48	48	32
13970-12-12-SM	19	3/4	-12	19.1	1 1/16x12	89	50	48	32
13970-16-12-SM	19	3/4	-12	19.1	1 5/16x12	89	50	51	41
13970-12-16-SM	25	1	-16	25.4	1 1/16x12	99	54	46	32
13970-16-16-SM	25	1	-16	25.4	1 5/16x12	109	64	56	41
13970-20-16-SM	25	1	-16	25.4	1 5/8x12	111	64	62	50


* These fittings contain a dual seat that accepts both JIC (37°) and SAE (45°) male configurations.


Approved **fitting series** for **hose types**:

70 371LT | 372 | 372RH | 372TC | 701 | 701 TC | F42-8

15 ISO 6162-1 Flange Straight

ISO 12151-3-S-L – SFL
(21.0 MPa/ 3000 psi)







Part Number	Hose I.D.				Flange	A	B	F
	DN	Inch	Size	mm	Inch	mm	mm	mm
11570-8-8	12	1/2	-8	12.7	1/2	89	54	30
11570-10-10	16	5/8	-10	15.9	5/8	116	79	34
11570-12-10	16	5/8	-10	15.9	3/4	69	30	38
11570-12-12	19	3/4	-12	19.1	3/4	98	59	38
11570-16-12	19	3/4	-12	19.1	1	70	31	45
11570-20-12	19	3/4	-12	19.1	1 1/4	75	36	51
11570-12-16	25	1	-16	25.4	3/4	111	66	38
11570-16-16	25	1	-16	25.4	1	108	63	45
11570-20-16	25	1	-16	25.4	1 1/4	82	36	51

SAE flange halves see in section Eb.
Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

17 ISO 6162-1 Flange 45° Elbow

ISO 12151-3 – E45 – L – SFL 45°
(21.0 MPa/ 3000 psi)





Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
11770-8-8	12	1/2	-8	12.7	1/2	79	44	20	30
11770-10-10	16	5/8	-10	15.9	5/8	104	67	24	34
11770-12-10	16	5/8	-10	15.9	3/4	96	57	26	38
11770-12-12	19	3/4	-12	19.1	3/4	98	58	26	38
11770-16-12	19	3/4	-12	19.1	1	97	57	25	45
11770-16-16	25	1	-16	25.4	1	119	73	27	45
11770-20-16	25	1	-16	25.4	1 1/4	121	76	32	51


SAE flange halves see in section Eb.
Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.


Approved **fitting series** for **hose types**:

70 | 371LT | 372 | 372RH | 372TC | 701 | 701 TC | F42-8

19 ISO 6162-1 Flange 90° Elbow

ISO 12151-3 – E– L – SFL 90°
(21.0 MPa/ 3000 psi)







Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
11970-8-8	12	1/2	-8	12.7	1/2	75	40	41	30
11970-12-8	12	1/2	-8	12.7	3/4	77	42	42	38
11970-10-10	16	5/8	-10	15.9	5/8	92	55	55	34
11970-12-10	16	5/8	-10	15.9	3/4	95	65	54	38
11970-12-12	19	3/4	-12	19.1	3/4	89	50	58	38
11970-16-12	19	3/4	-12	19.1	1	90	50	58	45
11970-16-16	25	1	-16	25.4	1	105	55	61	45
11970-20-16	25	1	-16	25.4	1 1/4	113	68	70	51

SAE flange halves see in section Eb.
Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

6A ISO 6162-2 Flange Straight

ISO 12151-3-S-S – SFS
(42.0 MPa/ 6000 psi)





Part Number	Hose I.D.				Flange	A	B	F
	DN	Inch	Size	mm	Inch	mm	mm	mm
16A70-8-8	12	1/2	-8	12.7	1/2	103	68	32
16A70-12-8	12	1/2	-8	12.7	3/4	105	70	41
16A70-8-10	16	5/8	-10	15.9	1/2	107	68	32
16A70-12-10	16	5/8	-10	15.9	3/4	117	78	41
16A70-8-12	19	3/4	-12	19.1	1/2	107	67	32
16A70-12-12	19	3/4	-12	19.1	3/4	105	66	41
16A70-16-12	19	3/4	-12	19.1	1	110	70	48
16A70-12-16	25	1	-16	25.4	3/4	127	82	41
16A70-16-16	25	1	-16	25.4	1	127	82	48
16A70-20-16	25	1	-16	25.4	1 1/4	127	82	54


SAE flange halves see in section Eb.
Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.


Approved **fitting series** for **hose types**:

70 | 371LT | 372 | 372RH | 372TC | 701 | 701 TC | F42-8

6F ISO 6162-2 Flange 45° Elbow – Heavy Series

ISO 12151-3 – E45-S – SFS 45°
(42.0 MPa/ 6000 psi)







Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
16F70-8-8	12	1/2	-8	12.7	1/2	81	46	19	32
16F70-12-8	12	1/2	-8	12.7	3/4	90	55	26	41
16F70-8-10	16	5/8	-10	15.9	1/2	92	53	26	32
16F70-12-10	16	5/8	-10	15.9	3/4	92	55	26	41
16F70-8-12	19	3/4	-12	19.1	1/2	94	54	26	32
16F70-12-12	19	3/4	-12	19.1	3/4	105	66	26	41
16F70-16-12	19	3/4	-12	19.1	1	101	62	26	48
16F70-12-16	25	1	-16	25.4	3/4	118	73	27	41
16F70-16-16	25	1	-16	25.4	1	117	77	27	48
16F70-20-16	25	1	-16	25.4	1 1/4	117	70	31	54

SAE flange halves see in section Eb.
Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

6N ISO 6162-2 Flange 90° Elbow

ISO 12151-3 – E-S – SFS 90°
(42.0 MPa/ 6000 psi)






Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
16N70-8-8	12	1/2	-8	12.7	1/2	74	39	41	32
16N70-12-8	12	1/2	-8	12.7	3/4	79	44	45	41
16N70-8-10	16	5/8	-10	15.9	1/2	95	56	54	32
16N70-12-10	16	5/8	-10	15.9	3/4	92	55	54	41
16N70-16-10	16	5/8	-10	15.9	1	86	46	54	48
16N70-8-12	19	3/4	-12	19.1	1/2	81	42	54	32
16N70-12-12	19	3/4	-12	19.1	3/4	98	58	54	41
16N70-16-12	19	3/4	-12	19.1	1	92	53	53	48
16N70-12-16	25	1	-16	25.4	3/4	113	66	57	41
16N70-16-16	25	1	-16	25.4	1	111	64	70	48
16N70-20-16	25	1	-16	25.4	1 1/4	115	68	68	54

SAE flange halves see in section Eb.
Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

Approved **fitting series** for **hose types**:

70 | 371LT | 372 | 372RH | 372TC | 701 | 701 TC | F42-8

PY Flange – 24° Male French Gas Straight





Part Number	Hose I.D.				A	B
	DN	Inch	Size	mm	mm	mm
1PY70-10-10	16	5/8	-10	15.9	63	24
1PY70-12-12	19	3/4	-12	19.1	69	30
1PY70-16-16	25	1	-16	25.4	87	41


Approved **fitting series** for **hose types**:


70 371LT | 372 | 372RH | 372TC | 701 | 701 TC | F42-8

JC

Female ORFS Swivel – Straight Short

ISO 12151-1 – SWSA
SAE J516 – ORFS







Part Number	Hose I.D.				Thread	A	B	H	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
1JC70-6-6-SM	10	3/8	-6	9.5	11/16x16	49	20	19	22
1JC70-8-6-SM	10	3/8	-6	9.5	13/16x16	51	22	19	24
1JC70-8-8-SM	12	1/2	-8	12.7	13/16x16	56	24	*13/16*	*15/16*
1JC70-10-8-SM	12	1/2	-8	12.7	1x14	58	24	24	30
1JC70-12-8-SM	12	1/2	-8	12.7	1 3/16x12	63	28	32	36
1JC70-8-10-SM	16	5/8	-10	15.9	13/16x16	59	22	22	24
1JC70-10-10-SM	16	5/8	-10	15.9	1x14	64	24	24	30
1JC70-12-10-SM	16	5/8	-10	15.9	1 3/16x12	68	29	32	36
1JC70-8-12-SM	19	3/4	-12	19.1	13/16x16	61	22	27	24
1JC70-12-12-SM	19	3/4	-12	19.1	1 3/16x12	68	29	32	36
1JC70-16-12-SM	19	3/4	-12	19.1	1 7/16x12	72	33	36	41
1JC70-12-16-SM	25	1	-16	25.4	13/16x12	76	31	36	36
1JC70-16-16-SM	25	1	-16	25.4	1 7/16x12	80	35	36	41
1JC70-20-16-SM	25	1	-16	25.4	1 11/16x12	79	34	41	50

JS

ORFS Swivel Female (Long)

ISO 12151-1-SWSB
SAE J516 – ORFS






Part Number	Hose I.D.				Thread	A	B	H	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
1JS70-6-6-SM	10	3/8	-6	9.5	11/16x16	58	29	17	22
1JS70-8-6-SM	10	3/8	-6	9.5	13/16x16	64	35	19	24
1JS70-8-8-SM	12	1/2	-8	12.7	13/16x16	67	33	22	24
1JS70-10-8-SM	12	1/2	-8	12.7	1x14	73.5	38.5	24	30
1JS70-10-10-SM	16	5/8	-10	15.9	1x14	79	39	24	30
1JS70-12-12-SM	19	3/4	-12	19.1	1 3/16x12	84	45	30	36
1JS70-16-12-SM	19	3/4	-12	19.1	1 7/16x12	86	47	36	41
1JS70-16-16-SM	25	1	-16	25.4	1 7/16x12	98	53	36	41
1JS70-20-16-SM	25	1	-16	25.4	1 11/16x12	94	47	41	50


Approved **fitting series** for **hose types**:

70 | 371LT | 372 | 372RH | 372TC | 701 | 701 TC | F42-8

J7 Female ORFS – Swivel 45° Elbow

ISO 12151-1 – SWE 45°
SAE J516 – ORFS 45°







Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
1J770-6-6-SM	10	3/8	-6	9.5	11/16x16	62	33	11	22
1J770-8-6-SM	10	3/8	-6	9.5	13/16x16	64	35	15	24
1J770-6-8-SM	12	1/2	-8	12.7	11/16x16	68	33	11	22
1J770-8-8-SM	12	1/2	-8	12.7	13/16x16	72	37	15	24
1J770-10-8-SM	12	1/2	-8	12.7	1x14	80	46	17	30
1J770-10-10-SM	16	5/8	-10	15.9	1x14	83	44	16	30
1J770-12-10-SM	16	5/8	-10	15.9	1 3/16x12	90	53	21	36
1J770-12-12-SM	19	3/4	-12	19.1	1 3/16x12	92	53	21	36
1J770-16-12-SM	19	3/4	-12	19.1	1 7/16x12	95	56	24	41
1J770-16-16-SM	25	1	-16	25.4	1 7/16x12	113	66	24	41

J9 Female ORFS – Swivel 90° Elbow – Short Drop

ISO 12151-1 – SWES
SAE J516 – ORFS 90°






Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
1J970-6-6-SM	10	3/8	-6	9.5	11/16x16	58	29	23	22
1J970-8-6-SM	10	3/8	-6	9.5	13/16x16	58	29	29	24
1J970-8-8-SM	12	1/2	-8	12.7	13/16x16	70	35	29	24
1J970-10-8-SM	12	1/2	-8	12.7	1x14	73	38	32	30
1J970-12-8-SM	12	1/2	-8	12.7	1 3/16x12	76	41	48	36
1J970-10-10-SM	16	5/8	-10	15.9	1x14	78	39	33	30
1J970-12-10-SM	16	5/8	-10	15.9	1 3/16x12	86	50	48	36
1J970-12-12-SM	19	3/4	-12	19.1	1 3/16x12	89	49	48	36
1J970-16-12-SM	19	3/4	-12	19.1	1 7/16x12	89	49	56	41
1J970-16-16-SM	25	1	-16	25.4	1 7/16x12	111	64	56	41
1J970-20-16-SM	25	1	-16	25.4	1 11/16x12	111	64	64	50


Approved **fitting series** for **hose types**:

70 | 371LT | 372 | 372RH | 372TC | 701 | 701 TC | F42-8

J1 Female ORFS – Swivel 90° Elbow – Long Drop

ISO 12151-1 – SWEL
SAE J 516 – ORFS 90° L







Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
1J170-8-8-SM	12	1/2	-8	12.7	13/16x16	71	36	64	24
1J170-10-8-SM	12	1/2	-8	12.7	1x14	73	38	70	30
1J170-10-10-SM	16	5/8	-10	15.9	1x14	78	39	70	30
1J170-12-10-SM	16	5/8	-10	15.9	1 3/16x12	76	40	96	36
1J170-12-12-SM	19	3/4	-12	19.1	1 3/16x12	89	49	96	36
1J170-16-16-SM	25	1	-16	25.4	1 7/16x12	109	64	114	41

JM ORFS Male

ISO 12151-1-S – SAE J516





Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	UNF	mm	mm	mm
1JM70-6-6-SM	10	3/8	-6	9.5	11/16x16	53	24	19
1JM70-8-6-SM	10	3/8	-6	9.5	13/16x16	56	27	22
1JM70-8-8-SM	12	1/2	-8	12.7	13/16x16	62	27	22
1JM70-10-8-SM	12	1/2	-8	12.7	1x14	66	32	27
1JM70-10-10-SM	16	5/8	-10	15.9	1x14	68	32	27
1JM70-12-10-SM	16	5/8	-10	15.9	1 3/16x12	71	34	32
1JM70-12-12-SM	19	3/4	-12	19.1	1 3/16x12	74	34	32
1JM70-16-12-SM	19	3/4	-12	19.1	1 7/16x12	74	35	41
1JM70-16-16-SM	25	1	-16	25.4	1 7/16x12	84	39	41
1JM70-20-16-SM	25	1	-16	25.4	1 11/16x12	82	37	46

JM fittings are supplied without O-ring.
O-rings see section Eb. Special O-rings are available on request.


Approved **fitting series** for **hose types**:


70 | 371LT | 372 | 372RH | 372TC | 701 | 701 TC | F42-8

MU

Female Metric – Swivel Straight (30° Flare)

JIS B8363 – MU







Part Number	Hose I.D.				Thread	A	B	H	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
1MU70-6-6	10	3/8	-6	9.5	M18x1.5	62	33	24	24
1MU70-8-8	12	1/2	-8	12.7	M22x1.5	72	37	27	27
1MU70-12-12	19	3/4	-12	19.1	M27x2	81	41	36	36

Approved **fitting series** for **hose types**:

70 371LT | 372 | 372RH | 372TC | 701 | 701 TC | F42-8


FG Male French Gas Series Rigid – Straight (24° Cone)






Part Number	Hose I.D.				Thread	Tube O.D.	A	B	H
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
1FG70-13-6	10	3/8	-6	9.5	M20x1.5	13.25	46	24	22
1FG70-17-8	12	1/2	-8	12.7	M24x1.5	16.75	62	27	24
1FG70-21-10	16	5/8	-10	15.9	M30x1.5	21.25	70	30	30
1FG70-27-12	19	3/4	-12	19.1	M36x1.5	26.75	70	30	36
1FG70-33-16	25	1	-16	25.4	M45x1.5	33.50	82	36	46

F4 Female French Gas Series Swivel – Straight (Ball Nose)






Part Number	Hose I.D.				Thread	Tube O.D.	A	B	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
1F470-13-6	10	3/8	-6	9.5	M20x1.5	13	52	22	24
1F470-17-8	12	1/2	-8	12.7	M24x1.5	17	60	25	30
1F470-21-10	16	5/8	-10	15.9	M30x1.5	21	62	25	36
1F470-27-12	19	3/4	-12	19.1	M36x1.5	27	70	31	46


Approved **fitting series** for **hose types**:

70 371LT | 372 | 372RH | 372TC | 701 | 701 TC | F42-8

XU Female Metric – Swivel Straight (30° Flare)

JIS B8363







Part Number	Hose I.D.				Thread	A	B	H	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
1XU70-10-10	16	5/8	-10	15.9	M24x1.5	67	28	30	32
1XU70-12-12	19	3/4	-12	19.1	M30x1.5	68	28	32	36
1XU70-16-16	25	1	-16	25.4	M33x1.5	82	35	36	41

XY Female Metric – Swivel 90° Elbow (30° Flare)

JIS B8363






Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
1XY70-10-10	16	5/8	-10	15.9	M24x1.5	77	41	41	32
1XY70-12-12	19	3/4	-12	19.1	M24x1.5	89	49	52	36

Approved **fitting series** for **hose types**:

70 371LT | 372 | 372RH | 372TC | 701 | 701 TC | F42-8


DIN – Metric


Page Dc-1 – Dc-2

C9
Dc-1

Female Metric 24° – Swivel
Heavy Series with O-Ring
Straight
ISO 12151-2-SWS-S – DKOS

0C
Dc-1


Female Metric 24° – Swivel
Heavy Series with O–Ring
45° Elbow
ISO 12151-2 – SWE 45°-S – DKOS 45°


1C
Dc-2

Female Metric 24° – Swivel
Heavy Series with O–Ring
90° Elbow
ISO 12151-2-SWE-S – DKOS 90°

D2
Dc-2

Male Metric 24° – Rigid
Heavy Series – Straight
ISO 12151-2-S-S – CES

BSP


Page Dc-3 – Dc-4

92
Dc-3

Female BSP Parallel Pipe
Swivel – Straight (60° Cone)
BS5200-A – DKR

B1
Dc-3

Female BSP Parallel Pipe
Swivel
45° Elbow (60° Cone)
BS 5200-D – DKR 45°


B2
Dc-4


Female BSP Parallel Pipe
Swivel
90° Elbow (60° Cone)
BS 5200-B – DKR 90°


D9
Dc-4

Male BSP Parallel Pipe
Rigid – Straight (60° Cone)
BS5200 – AGR


SAE


Page Dc-5 – Dc-7

01
Dc-5

Male NPTF Pipe
Rigid – Straight
SAE J476A / J516 – AGN

03
Dc-5

Male JIC 37° – Rigid
Straight
ISO12151-5-S – AGJ

06
Dc-6

Female JIC 37° – Swivel
Straight
ISO12151-5-SWS – DKJ


37
Dc-6

Female JIC 37° – Swivel
45° Elbow
ISO 12151-5-SWE 45° – DKJ 45°


39
Dc-7

Female JIC 37° – Swivel
90° Elbow
ISO 12151-5-SWES – DKJ 90°


A large range of special hose fittings for the MRO market can be found on page Dc-19


Flange


Page Dc-8 – Dc-12


15/4A Dc-8

ISO 6162-1 Flange
Straight
ISO 12151-3-S-L – SFL
(35.0 MPa/ 5000 psi)


17/4F Dc-8

ISO 6162-1 Flange
45° Elbow
ISO 12151-3 – E45S – L – SFL 45°
(35.0 MPa/ 5000 psi)


19/4N Dc-9

ISO 6162-1 Flange
90° Elbow
ISO 12151-3-E-L – SFL 90°
(35.0 MPa/ 5000 psi)


6A Dc-9

ISO 6162-2 Flange
Straight
ISO 12151-3-S-S – SFS
(42.0 MPa/ 6000 psi)

6F Dc-10

ISO 6162-2 Flange
45° Elbow – Heavy Series
ISO 12151-3 – E45-S – SFS 45°
(42.0 MPa/ 6000 psi)

6N Dc-10

ISO 6162-2 Flange
90° Elbow
ISO 12151-3 – E-S – SFS 90°
(42.0 MPa/ 6000 psi)

XA Dc-11

Caterpillar® Flange
Straight

XF Dc-11

Caterpillar® Flange
45° Elbow


XG Dc-12

Caterpillar® Flange
60° Elbow


XN Dc-12


Caterpillar® Flange
90° Elbow

ORFS

Page Dc-13 – Dc-15


JC Dc-13

Female ORFS
Swivel – Straight
Short
ISO 12151-1 – SWSA SAE J516 – ORFS

JS Dc-13

ORFS Swivel Female (Long)
ISO 12151-1-SWSB
SAE J516 – ORFS

J7 Dc-14

Female ORFS – Swivel
45° Elbow
ISO 12151-1 – SWE 45°
SAE J516 – ORFS 45°


J9 Dc-14


Female ORFS – Swivel
90° Elbow – Short Drop
ISO 12151-1 – SWES
SAE J516 – ORFS 90°


JM Dc-15

ORFS Male
ISO 12151-1-S – SAE J516

French Standard

Page Dc-16 – Dc-17


FG Dc-16

Male French Gas Series
Rigid – Straight (24° Cone)

F2 Dc-16

Female French Gas Series
Swivel – 90° Elbow

F4 Dc-17

Female French Gas Series
Swivel – Straight
(Ball Nose)


Others


Page Dc-18

XU Dc-18

Female Metric – Swivel
Straight (30° Flare)
JIS B8363

C9 Female Metric 24° – Swivel Heavy Series with O-Ring Straight

ISO 12151-2-SWS-S – DKOS







Part Number	Hose I.D.				Thread	Tube O.D.	A	B	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
1C973-20-12	19	3/4	-12	19.1	M30x2	20	81	33	36
1C973-25-12	19	3/4	-12	19.1	M36x2	25	79	31	46
1C973-25-12SW41	19	3/4	-12	19.1	M36x2	25	79	31	41
1C973-30-12	19	3/4	-12	19.1	M42x2	30	82	34	50
1C973-25-16	25	1	-16	25.4	M36x2	25	87	36	46
1C973-30-16	25	1	-16	25.4	M42x2	30	87	36	50
1C973-25-20	31	1 1/4	-20	31.8	M36x2	25	102	38	46
1C973-30-20	31	1 1/4	-20	31.8	M42x2	30	106	42	50
1C973-38-20	31	1 1/4	-20	31.8	M52x2	38	101	37	60
1C973-38-24	38	1 1/2	-24	38.1	M52x2	38	105	42	60

Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

0C Female Metric 24° – Swivel Heavy Series with O-Ring 45° Elbow

ISO 12151-2 – SWE 45°-S – DKOS 45°





Part Number	Hose I.D.				Thread	Tube O.D.	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
10C73-20-12	19	3/4	-12	19.1	M30x2	20	113	65	30	36
10C73-25-12SW41	19	3/4	-12	19.1	M36x2	25	112	64	29	41
10C73-25-12	19	3/4	-12	19.1	M36x2	25	112	64	29	46
10C73-25-16	25	1	-16	25.4	M36x2	25	128	78	33	46
10C73-30-16	25	1	-16	25.4	M42x2	30	137	128	33	50
10C73-25-20	31	1 1/4	-20	31.8	M36x2	25	150	86	33	46
10C73-30-20	31	1 1/4	-20	31.8	M42x2	30	147	83	34	50
10C73-38-20	31	1 1/4	-20	31.8	M52x2	38	161	97	37	60
10C73-38-24	38	1 1/2	-24	38.1	M52x2	38	182	120	49	60


Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.


Approved **fitting series** for **hose types**:

73 | 731 | 731TC

1C Female Metric 24° – Swivel Heavy Series with O-Ring 90° Elbow

ISO 12151-2-SWE-S – DKOS 90°







Part Number	Hose I.D.				Thread	Tube O.D.	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
11C73-20-12	19	3/4	-12	19.1	M30x2	20	101	53	60	36
11C73-25-12SW41	19	3/4	-12	19.1	M36x2	25	101	53	59	41
11C73-25-12	19	3/4	-12	19.1	M36x2	25	101	53	59	46
11C73-25-16	25	1	-16	25.4	M36x2	25	117	67	69	46
11C73-30-16	25	1	-16	25.4	M42x2	30	130	118	67	50
11C73-30-20	31	1 1/4	-20	31.8	M42x2	30	137	73	73	50
11C73-38-20	31	1 1/4	-20	31.8	M52x2	38	151	87	78	60
11C73-38-24	38	1 1/2	-24	38.1	M52x2	38	166	103	101	60
11C73-38-32	51	2	-32	50.8	M52x2	38	224	152	166	60

Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

D2 Male Metric 24° – Rigid Heavy Series – Straight

ISO 12151-2-S-S – CES






Part Number	Hose I.D.				Thread	Tube O.D.	A	B	H
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
1D273-20-12	19	3/4	-12	19.1	M30x2	20	84	35	30
1D273-25-12	19	3/4	-12	19.1	M36x2	25	86	38	36
1D273-30-12	19	3/4	-12	19.1	M42x2	30	90	42	46
1D273-25-16	25	1	-16	25.4	M36x2	25	91	40	36
1D273-30-16	25	1	-16	25.4	M42x2	30	94	42	46
1D273-30-20	31	1 1/4	-20	31.8	M42x2	30	110	46	46
1D273-38-20	31	1 1/4	-20	31.8	M52x2	38	112	46	55


Approved **fitting series** for **hose types**:

73 | 731 | 731TC

92 Female BSP Parallel Pipe Swivel – Straight (60° Cone)

BS5200-A – DKR







Part Number	Hose I.D.				Thread	A	B	W
	DN	Inch	Size	mm	BSP	mm	mm	mm
19273-12-12	19	3/4	-12	19.1	3/4x14	75	27	32
19273-16-16	25	1	-16	25.4	1x11	89	38	41
19273-20-20	31	1 1/4	-20	31.8	1 1/4x11	101	37	50
19273-24-20	31	1 1/4	-20	31.8	1 1/2x11	101	37	55
19273-24-24	38	1 1/2	-24	38.1	1 1/2x11	100	37	55
19273-32-32	51	2	-32	50.8	2x11	113	38	70

B1 Female BSP Parallel Pipe Swivel 45° Elbow (60° Cone)

BS 5200-D – DKR 45°






Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	BSP	mm	mm	mm	mm
1B173-12-12	19	3/4	-12	19.1	3/4x14	110	62	26	32
1B173-16-16	25	1	-16	25.4	1x11	136	84	36	41
1B173-20-20	31	1 1/4	-20	31.8	1 1/4x11	168	104	43	50
1B173-24-24	38	1 1/2	-24	38.1	1 1/2x11	186	123	52	55
1B173-32-32	51	2	-32	50.8	2x11	249	177	70	70


Approved **fitting series** for **hose types**:

73 | 731 | 731TC

B2 Female BSP Parallel Pipe Swivel 90° Elbow (60° Cone)

BS 5200-B – DKR 90°







Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	BSP	mm	mm	mm	mm
1B273-12-12	19	3/4	-12	19.1	3/4x14	106	58	55	32
1B273-16-16	25	1	-16	25.4	1x11	120	70	74	41
1B273-20-20	31	1 1/4	-20	31.8	1 1/4x11	151	87	80	50
1B273-24-20	31	1 1/4	-20	31.8	1 1/2x11	151	87	80	55
1B273-24-24	38	1 1/2	-24	38.1	1 1/2x11	166	103	103	55
1B273-32-32	51	2	-32	50.8	2x11	229	157	121	70

D9 Male BSP Parallel Pipe Rigid – Straight (60° Cone)

BS5200 – AGR






Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	BSP	mm	mm	mm
1D973-12-12	19	3/4	-12	19.1	3/4x14	87	39	32
1D973-16-16	25	1	-16	25.4	1x11	96	43	41
1D973-20-20	31	1 1/4	-20	31.8	1 1/14x11	113	49	50
1D973-24-24	38	1 1/2	-24	38.1	1 1/2x11	114	51	55
1D973-32-32	51	2	-32	50.8	2x11	129	58	70


Approved **fitting series** for **hose types**:

73 | 731 | 731TC

01 Male NPTF Pipe Rigid – Straight

SAE J476A / J516 – AGN







Part Number	Hose I.D.				Thread	A	B	H	
	DN	Inch	Size	mm	NPTF	mm	mm	mm	*Inch*
10173-12-12-SM	19	3/4	-12	19.1	3/4x14	90	42	30	
10173-16-12-SM	19	3/4	-12	19.1	1x11 1/2	96	48	36	
10173-16-16-SM	25	1	-16	25.4	1x11 1/2	100	50	36	
10173-20-20-SM	31	1 1/4	-20	31.8	1 1/4x11 1/2	125	61	46	
10173-24-24-SM	38	1 1/2	-24	38.1	1 1/2x11 1/2	124	62	50	
10173-32-32	51	2	-32	50.8	2x11 1/2	141	73	*2 1/2*	

03 Male JIC 37° – Rigid Straight

ISO12151-5-S – AGJ






Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	UNF	mm	mm	mm
10373-12-12-SM	19	3/4	-12	19.1	1 1/16x12	89	41	30
10373-16-12-SM	19	3/4	-12	19.1	1 5/16x12	93	45	36
10373-16-16-SM	25	1	-16	25.4	1 5/16x12	97	47	36
10373-20-16-SM	25	1	-16	25.4	1 5/8x12	102	52	46
10373-20-20-SM	31	1 1/4	-20	31.8	1 5/8x12	118	54	46
10373-24-20-SM	31	1 1/4	-20	31.8	1 7/8x12	118	54	50
10373-24-24-SM	38	1 1/2	-24	38.1	1 7/8x12	122	59	50
10373-32-32-SM	51	2	-32	50.8	2 1/2x12	143	72	65


Approved **fitting series** for **hose types**:

73 | 731 | 731TC

06 Female JIC 37° – Swivel Straight

ISO12151-5-SWS – DKJ







Part Number	Hose I.D.				Thread	A	B	H	W
	DN	Inch	Size	mm	UNF	mm	mm	mm *Inch*	mm *Inch*
10673-12-12-SM	19	3/4	-12	19.1	1 1/16x12	93	45	30	32
10673-16-12	19	3/4	-12	19.1	1 5/16x12	99	51	36	41
10673-16-16-SM	25	1	-16	25.4	1 5/16x12	103	52	36	41
10673-20-16	25	1	-16	25.4	1 5/16x12	109	59	41	50
10673-16-20-SM	31	1 1/4	-20	31.8	1 5/16x12	116	52	46	41
10673-20-20-SM	31	1 1/4	-20	31.8	1 5/8x12	125	61	46	50
10673-24-20-SM	31	1 1/4	-20	31.8	1 7/8x12	130	66	50	60
10673-24-24-SM	38	1 1/2	-24	38.1	1 7/8x12	128	66	50	60
10673-32-24-SM	38	1 1/2	-24	38.1	2 1/2x12	138	76	65	75
10673-32-32-SM	51	2	-32	50.8	2 1/2x12	150	79	65	75

37 Female JIC 37° – Swivel 45° Elbow

ISO 12151-5-SWE 45° – DKJ 45°






Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
13773-12-12-SM	19	3/4	-12	19.1	1 1/16x12	104	56	22	32
13773-16-12-SM	19	3/4	-12	19.1	1 5/16x12	107	59	24	41
13773-16-16-SM	25	1	-16	25.4	1 5/16x12	119	69	24	41
13773-20-16-SM	25	1	-16	25.4	1 5/8x12	143	92	47	55
13773-20-20-SM	31	1 1/4	-20	31.8	1 5/8x12	171	107	47	50
13773-24-20-SM	31	1 1/4	-20	31.8	1 7/8x12	172	108	48	60
13773-24-24-SM	38	1 1/2	-24	38.1	1 7/8x12	194	132	58	60
13773-32-24-SM	38	1 1/2	-24	38.1	2 1/2x12	208	145	72	75
13773-32-32-SM	51	2	-32	50.8	2 1/2x12	251	179	72	75


Approved **fitting series** for **hose types**:

73 | 731 | 731TC

39 Female JIC 37° – Swivel 90° Elbow

ISO 12151-5-SWES – DKJ 90°






Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
13973-12-12-SM	19	3/4	-12	19.1	1 1/16x12	101	53	48	32
13973-16-12-SM	19	3/4	-12	19.1	1 5/16x12	101	53	56	41
13973-16-16-SM	25	1	-16	25.4	1 5/16x12	118	67	56	41
13973-20-16-SM	25	1	-16	25.4	1 5/8x12	118	67	85	55
13973-20-20-SM	31	1 1/4	-20	31.8	1 5/8x12	150	87	85	50
13973-24-20-SM	31	1 1/4	-20	31.8	1 7/8x12	151	87	102	60
13973-24-24-SM	38	1 1/2	-24	38.1	1 7/8x12	194	119	102	60
13973-32-24-SM	38	1 1/2	-24	38.1	2 1/2x12	168	106	152	75
13973-32-32-SM	51	2	-32	50.8	2 1/2x12	229	157	152	75


Approved **fitting series** for **hose types**:

73 | 731 | 731TC

15/4A ISO 6162-1 Flange Straight

ISO 12151-3-S-L – SFL
(35.0 MPa/ 5000 psi)






Part Number	Hose I.D.				Flange	A	B	F
	DN	Inch	Size	mm	Inch	mm	mm	mm
11573-12-12	19	3/4	-12	19.1	3/4	110	62	38
11573-16-12	19	3/4	-12	19.1	1	110	62	45
11573-12-16	25	1	-16	25.4	3/4	117	67	38
11573-16-16	25	1	-16	25.4	1	117	67	45
14A73-20-16	25	1	-16	25.4	1 1/4	85	34	51
11573-16-20	31	1 1/4	-20	31.8	1	133	69	45
14A73-20-20	31	1 1/4	-20	31.8	1 1/4	141	77	51
14A73-24-20	31	1 1/4	-20	31.8	1 1/2	104	40	60
14A73-20-24	38	1 1/2	-24	38.1	1 1/4	142	80	51
14A73-24-24	38	1 1/2	-24	38.1	1 1/2	166	103	60
14A73-32-24	38	1 1/2	-24	38.1	2	113	50	71
14A73-24-32	51	2	-32	50.8	1 1/2	156	84	60
14A73-32-32	51	2	-32	50.8	2	220	148	71


SAE flange halves see in section Eb.

Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

17/4F ISO 6162-1 Flange 45° Elbow

ISO 12151-3 – E45S – L – SFL 45°
(35.0 MPa/ 5000 psi)





Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
11773-12-12	19	3/4	-12	19.1	3/4	119	71	27	38
11773-16-12	19	3/4	-12	19.1	1	109	64	26	44
11773-12-16	25	1	-16	25.4	3/4	130	80	32	38
11773-16-16	25	1	-16	25.4	1	127	77	32	45
14F73-20-16	25	1	-16	25.4	1 1/4	136	85	32	51
14F73-20-20	31	1 1/4	-20	31.8	1 1/4	160	96	35	51
14F73-24-20	31	1 1/4	-20	31.8	1 1/2	162	102	38	60
14F73-24-24	38	1 1/2	-24	38.1	1 1/2	178	115	44	60
14F73-32-24	38	1 1/2	-24	38.1	2	177	114	43	71
14F73-24-32	51	2	-32	50.8	1 1/2	192	120	53	60
14F73-32-32	51	2	-32	50.8	2	224	153	62	71

SAE flange halves see in section Eb.


Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.


Approved **fitting series** for **hose types**:

73 | 731 | 731TC

19/4N ISO 6162-1 Flange 90° Elbow

ISO 12151-3-E-L – SFL 90°
(35.0 MPa/ 5000 psi)






Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
11973-12-12	19	3/4	-12	19.1	3/4	109	61	58	38
11973-16-12	19	3/4	-12	19.1	1	102	54	58	45
11973-12-16	25	1	-16	25.4	3/4	121	70	70	38
11973-16-16	25	1	-16	25.4	1	118	67	70	45
14N73-20-16	25	1	-16	25.4	1 1/4	128	78	68	51
14N73-24-16	25	1	-16	25.4	1 1/2	132	81	70	60
11973-16-20	31	1 1/4	-20	31.8	1	133	69	70	44
14N73-20-20	31	1 1/4	-20	31.8	1 1/4	155	91	90	51
14N73-24-20	31	1 1/4	-20	31.8	1 1/2	155	91	90	60
14N73-24-24	38	1 1/2	-24	38.1	1 1/2	166	103	93	60
14N73-32-24	38	1 1/2	-24	38.1	2	166	103	92	71
14N73-32-32	51	2	-32	50.8	2	220	148	133	71


SAE flange halves see in section Eb.

Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

6A ISO 6162-2 Flange Straight

ISO 12151-3-S-S – SFS
(42.0 MPa/ 6000 psi)





Part Number	Hose I.D.				Flange	A	B	F
	DN	Inch	Size	mm	Inch	mm	mm	mm
16A73-8-12	19	3/4	-12	19.1	1/2	123	75	32
16A73-12-12	19	3/4	-12	19.1	3/4	130	82	41
16A73-16-12	19	3/4	-12	19.1	1	135	87	48
16A73-20-12	19	3/4	-12	19.1	1 1/4	96	48	54
16A73-12-16	25	1	-16	25.4	3/4	124	73	41
16A73-16-16	25	1	-16	25.4	1	131	81	48
16A73-20-16	25	1	-16	25.4	1 1/4	142	91	54
16A73-16-20	31	1 1/4	-20	31.8	1	147	83	48
16A73-20-20	31	1 1/4	-20	31.8	1 1/4	149	85	54
16A73-24-20	31	1 1/4	-20	31.8	1 1/2	121	57	64
16A73-20-24	38	1 1/2	-24	38.1	1 1/4	158	96	54
16A73-24-24	38	1 1/2	-24	38.1	1 1/2	166	104	64
16A73-32-24	38	1 1/2	-24	38.1	2	129	66	79
16A73-32-32	51	2	-32	50.8	2	194	122	79

SAE flange halves see in section Eb.


Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.


Approved **fitting series** for **hose types**:

73 | 731 | 731TC

6F ISO 6162-2 Flange 45° Elbow – Heavy Series

ISO 12151-3 – E45-S – SFS 45°
(42.0 MPa/ 6000 psi)






Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
16F73-8-12	19	3/4	-12	19.1	1/2	107	59	27	32
16F73-12-12	19	3/4	-12	19.1	3/4	110	62	26	41
16F73-16-12	19	3/4	-12	19.1	1	110	62	26	48
16F73-20-12	19	3/4	-12	19.1	1 1/4	125	77	32	54
16F73-12-16	25	1	-16	25.4	3/4	123	73	32	41
16F73-16-16	25	1	-16	25.4	1	129	79	32	48
16F73-20-16	25	1	-16	25.4	1 1/4	129	79	32	54
16F73-16-20	31	1 1/4	-20	31.8	1	157	93	33	48
16F73-20-20	31	1 1/4	-20	31.8	1 1/4	163	98	38	54
16F73-24-20	31	1 1/4	-20	31.8	1 1/2	163	99	38	63
16F73-20-24	38	1 1/2	-24	38.1	1 1/4	170	107	44	54
16F73-24-24	38	1 1/2	-24	38.1	1 1/2	178	115	44	64
16F73-32-32	51	2	-32	50.8	2	230	158	56	79


SAE flange halves see in section Eb.

Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

6N ISO 6162-2 Flange 90° Elbow

ISO 12151-3 – E-S – SFS 90°
(42.0 MPa/ 6000 psi)





Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
16N73-8-12	19	3/4	-12	19.1	1/2	92	44	58	32
16N73-12-12	19	3/4	-12	19.1	3/4	101	53	58	41
16N73-16-12	19	3/4	-12	19.1	1	111	63	58	48
16N73-20-12	19	3/4	-12	19.1	1 1/4	110	62	63	54
16N73-12-16	25	1	-16	25.4	3/4	109	58	70	41
16N73-16-16	25	1	-16	25.4	1	122	71	70	48
16N73-20-16	25	1	-16	25.4	1 1/4	122	71	70	54
16N73-16-20	31	1 1/4	-20	31.8	1	137	73	90	48
16N73-20-20	31	1 1/4	-20	31.8	1 1/4	172	108	71	54
16N73-24-20	31	1 1/4	-20	31.8	1 1/2	172	108	76	64
16N73-20-24	38	1 1/2	-24	38.1	1 1/4	152	90	104	54
16N73-24-24	38	1 1/2	-24	38.1	1 1/2	166	103	104	64
16N73-32-24	38	1 1/2	-24	38.1	2	166	103	104	79
16N73-24-32	51	2	-32	50.8	1 1/2	188	116	104	64
16N73-32-32	51	2	-32	50.8	2	229	157	138	79


SAE flange halves see in section Eb.


Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

Approved **fitting series** for **hose types**:

73 | 731 | 731TC

XA Caterpillar® Flange Straight







Part Number	Hose I.D.				Flange	A	B	F
	DN	Inch	Size	mm	Inch	mm	mm	mm
1XA73-12-12	19	3/4	-12	19.1	3/4	123	75	41
1XA73-16-12	19	3/4	-12	19.1	1	134	86	48
1XA73-16-16	25	1	-16	25.4	1	138	88	48
1XA73-20-16	25	1	-16	25.4	1 1/4	144	93	54
1XA73-20-20	31	1 1/4	-20	31.8	1 1/4	155	96	54
1XA73-24-20	31	1 1/4	-20	31.8	1 1/2	162	97	64

Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

XF Caterpillar® Flange 45° Elbow






Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
1XF73-12-12	19	3/4	-12	19.1	3/4	123	75	31	41
1XF73-16-12	19	3/4	-12	19.1	1	122	74	31	48
1XF73-16-16	25	1	-16	25.4	1	139	88	36	48
1XF73-20-20	31	1 1/4	-20	31.8	1 1/4	162	98	37	54
1XF73-24-20	31	1 1/4	-20	31.8	1 1/2	182	117	36	64


Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

Approved **fitting series** for **hose types**:

73	731 | 731TC

XG Caterpillar® Flange 60° Elbow







Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
1XG73-12-12	19	3/4	-12	19.1	3/4	41	138	90	42
1XG73-16-16	25	1	-16	25.4	1	48	160	109	50
1XG73-20-16	25	1	-16	25.4	1 1/4	54	153	103	48

Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

XN Caterpillar® Flange 90° Elbow





Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
1XN73-12-12	19	3/4	-12	19.1	3/4	111	63	63	41
1XN73-16-12	19	3/4	-12	19.1	1	111	63	62	48
1XN73-16-16	25	1	-16	25.4	1	128	78	74	48
1XN73-20-16	25	1	-16	25.4	1 1/4	122	71	74	54
1XN73-20-20	31	1 1/4	-20	31.8	1 1/4	172	108	77	54

Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.


Approved **fitting series** for **hose types**:


73 | 731 | 731TC

JC

Female ORFS Swivel – Straight Short

ISO 12151-1 – SWSA
SAE J516 – ORFS







Part Number	Hose I.D.				Thread	A	B	H	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
1JC73-12-12-SM	19	3/4	-12	19.1	1 3/16x12	81	33	30	36
1JC73-16-16-SM	25	1	-16	25.4	1 7/16x12	89	38	36	41
1JC73-20-20-SM	31	1 1/4	-20	31.8	1 11/16x12	106	42	46	50
1JC73-24-24-SM	38	1 1/2	-24	38.1	2x12	117	44	50	60

JS

ORFS Swivel Female (Long)

ISO 12151-1-SWSB
SAE J516 – ORFS






Part Number	Hose I.D.				Thread	A	B	H	W
	DN	Inch	Size	mm	UNF	mm	mm	mm *Inch*	mm *Inch*
1JS73-12-12-SM	19	3/4	-12	19.1	1 3/16x12	94	46	30	36
1JS73-16-12-SM	19	3/4	-12	19.1	1 7/16x12	107	58	36	41
1JS73-16-16-SM	25	1	-16	25.4	1 7/16x12	103	52	36	41
1JS73-20-16-SM	25	1	-16	25.4	1 11/16x12	114	64	41	50
1JS73-20-20-SM	31	1 1/4	-20	31.8	1 11/16x12	117	54	46	50
1JS73-24-24-SM	38	1 1/2	-24	38.1	2x12	120	57	50	60


Approved **fitting series** for **hose types**:

73 | 731 | 731TC

J7 Female ORFS – Swivel 45° Elbow

ISO 12151-1 – SWE 45°
SAE J516 – ORFS 45°







Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
1J773-12-12-SM	19	3/4	-12	19.1	1 3/16x12	105	57	21	36
1J773-16-12-SM	19	3/4	-12	19.1	1 7/16x12	107	59	24	41
1J773-16-16-SM	25	1	-16	25.4	1 7/16x12	119	69	24	41
1J773-20-16-SM	25	1	-16	25.4	1 11/16x12	131	80	26	50
1J773-20-20-SM	31	1 1/4	-20	31.8	1 11/16x12	154	90	30	50
1J773-20-20	31	1 1/4	-20	31.8	1 11/16x12	147	83	25	7/8
1J773-24-20-SM	31	1 1/4	-20	31.8	2x12	164	100	40	60

J9 Female ORFS – Swivel 90° Elbow – Short Drop

ISO 12151-1 – SWES
SAE J516 – ORFS 90°






Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
1J973-12-12-SM	19	3/4	-12	19.1	1 3/16x12	101	53	48	36
1J973-16-12-SM	19	3/4	-12	19.1	1 7/16x12	114	66	56	41
1J973-16-16-SM	25	1	-16	25.4	1 7/16x12	120	70	56	41
1J973-20-16-SM	25	1	-16	25.4	1 11/16x12	127	77	64	50
1J973-20-20	31	1 1/4	-20	31.8	1 11/16x12	148	84	64	7/8
1J973-20-20-SM	31	1 1/4	-20	31.8	1 11/16x12	151	87	69	50
1J973-24-24-SM	38	1 1/2	-24	38.1	2x12	166	103	82	60


Approved **fitting series** for **hose types**:

73 | 731 | 731TC

JM ORFS Male

ISO 12151-1-S – SAE J516






Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	UNF	mm	mm	mm
1JM73-12-12-SM	19	3/4	-12	19.1	1 3/16x12	86	38	32
1JM73-16-12-SM	19	3/4	-12	19.1	1 7/16x12	87	39	41
1JM73-16-16-SM	25	1	-16	25.4	1 7/16x12	93	42	41
1JM73-20-16-SM	25	1	-16	25.4	1 11/16x12	89	39	46
1JM73-20-20-SM	31	1 1/4	-20	31.8	1 11/16x12	106	42	46


JM fittings are supplied without O-ring.
O-rings see section Eb. Special O-rings are available on request.

Approved **fitting series** for **hose types**:

73 | 731 | 731TC


FG Male French Gas Series Rigid – Straight (24° Cone)






Part Number	Hose I.D.				Thread	Tube O.D.	A	B	H
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
1FG73-27-12	19	3/4	-12	19.1	M36x1.5	26.75	82	33	36
1FG73-33-16	25	1	-16	25.4	M45x1.5	33.50	91	39	46

F2 Female French Gas Series Swivel – 90° Elbow







Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
1F273-33-16	25	1	-16	25.4	M45x1.5	122	71	68	55

Approved **fitting series** for **hose types**:

73 | 731 | 731TC

F4 Female French Gas Series Swivel – Straight (Ball Nose)





Part Number	Hose I.D.				Thread	Tube O.D.	A	B	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
1F473-27-12	19	3/4	-12	19.1	M36x1.5	27	83	33	46
1F473-33-16	25	1	-16	25.4	M45x1.5	33	85	34	55


Approved **fitting series** for **hose types**:


73 | 731 | 731TC

XU

Female Metric – Swivel Straight (30° Flare)

JIS B8363





Part Number	Hose I.D.				Thread	A	B	H	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
1XU73-12-12	19	3/4	-12	19.1	M30x1.5	76	28	32	36
1XU73-16-16	25	1	-16	25.4	M33x1.5	85	35	36	41


Approved **fitting series** for **hose types**:

73 | 731 | 731TC

Large range of special hose fittings for the MRO market

The demand for special hose fittings is part of our everyday business.
In order to meet this demand with the authority expected, the Hose Products Division Europe has extended its standard offer with special hose fittings such as an extra drop length, etc.

The following is an overview of our special hose fitting selection:





Further special hose fittings are available on request.


Part Number	Description	Hose I.D. Size	Flange Inch	A mm	B mm	E mm	F mm
11973-12-12-SL100	SAE 5000 psi 90° elbow - drop length 100 mm	-12	3/4	109	61	100	38
11973-12-12-SL150	SAE 5000 psi 90° elbow - drop length 150 mm	-12	3/4	109	61	150	38
11973-12-12-SL180	SAE 5000 psi 90° elbow - drop length 180 mm	-12	3/4	109	61	180	38
11973-16-16-SL100	SAE 5000 psi 90° elbow - drop length 100 mm	-16	1	118	67	100	45
11973-16-16-SL150	SAE 5000 psi 90° elbow - drop length 150 mm	-16	1	118	67	150	45
11973-16-16-SL90	SAE 5000 psi 90° elbow - drop length 90 mm	-16	1	118	67	90	45
14N73-20-20-SL150	SAE 5000 psi 90° elbow - drop length 150 mm	-20	1 1/4	155	91	150	51
16N73-12-12-SL100	SAE 6000 psi 90° elbow - drop length 100 mm	-12	3/4	101	53	100	41
16N73-12-12-SL140	SAE 6000 psi 90° elbow - drop length 140 mm	-12	3/4	101	53	140	41
16N73-12-12-SL150	SAE 6000 psi 90° elbow - drop length 150 mm	-12	3/4	101	53	150	41
16N73-12-12-SL85	SAE 6000 psi 90° elbow - drop length 85 mm	-12	3/4	101	53	85	41
16N73-16-12-SL100	SAE 6000 psi 90° elbow - drop length 100 mm	-12	1	111	63	100	48
16N73-16-12-SL116	SAE 6000 psi 90° elbow - drop length 116 mm	-12	1	111	63	116	48
16N73-16-12-SL120	SAE 6000 psi 90° elbow - drop length 120 mm	-12	1	111	63	120	48
16N73-16-16-SL100	SAE 6000 psi 90° elbow - drop length 100 mm	-16	1	118	67	100	48
16N73-16-16-SL110	SAE 6000 psi 90° elbow - drop length 110 mm	-16	1	122	71	110	48
16N73-16-16-SL116	SAE 6000 psi 90° elbow - drop length 116 mm	-16	1	128	77	116	48
16N73-16-16-SL125	SAE 6000 psi 90° elbow - drop length 125 mm	-16	1	118	67	125	48
16N73-16-16-SL140	SAE 6000 psi 90° elbow - drop length 140 mm	-16	1	122	71	140	48
16N73-16-16-SL175	SAE 6000 psi 90° elbow - drop length 175 mm	-16	1	122	71	175	48
16N73-16-16SL150	SAE 6000 psi 90° elbow - drop length 150 mm	-16	1	117	67	150	48
16N73-20-16-SL120	SAE 6000 psi 90° elbow - drop length 120 mm	-16	1 1/4	122	71	120	54
16N73-20-16-SL160	SAE 6000 psi 90° elbow - drop length 160 mm	-16	1 1/4	122	71	160	54
16N73-20-20-SL100	SAE 6000 psi 90° elbow - drop length 100 mm	-20	1 1/4	155	91	100	54
16N73-20-20-SL180	SAE 6000 psi 90° elbow - drop length 180 mm	-20	1 1/4	155	91	180	54
16N73-20-20SL145	SAE 6000 psi 90° elbow - drop length 145 mm	-20	1 1/4	155	91	145	54
16N73-24-24-SL90	SAE 6000 psi 90° elbow - drop length 90 mm	-24	1 1/2	166	103	90	64

Approved **fitting series** for **hose types**:

73 | 731 | 731TC

DIN – Metric

Page Dd-1 – Dd-4

CA Dd-1

Female Metric 24°
Light Series with O–Ring
Swivel – Straight
ISO 12151-2-SWS-L – DKOL

CE Dd-1

Female Metric 24°
Light Series with O–Ring
Swivel – 45° Elbow
ISO 12151-2-SWE 45°-L – DKOL 45°

CF Dd-2

Female Metric 24°
Light Series with O–Ring
Swivel – 90° Elbow
ISO 12151-2-SWE-L – DKOL 90°

D0 Dd-2

Male Metric 24°
Light Series – Rigid
Straight
ISO 12151-2-S-L – CEL

C9 Dd-3


Female Metric 24° – Swivel
Heavy Series with O-Ring
Straight
ISO 12151-2-SWS-S – DKOS

0C Dd-3

Female Metric 24° – Swivel
Heavy Series with O–Ring
45° Elbow
ISO 12151-2 – SWE 45°-S – DKOS 45°


1C Dd-4


Female Metric 24° – Swivel
Heavy Series with O–Ring
90° Elbow
ISO 12151-2-SWE-S – DKOS 90°


D2 Dd-4

Male Metric 24° – Rigid
Heavy Series – Straight
ISO 12151-2-S-S – CES


BSP


Page Dd-5 – Dd-8


92 Dd-5

Female BSP Parallel Pipe
Swivel – Straight (60° Cone)
BS5200-A – DKR


B1 Dd-5

Female BSP Parallel Pipe
Swivel
45° Elbow (60° Cone)
BS 5200-D – DKR 45°

B2 Dd-6

Female BSP Parallel Pipe
Swivel
90° Elbow (60° Cone)
BS 5200-B – DKR 90°

EA Dd-6

BSP Swivel Female
with O–Ring (60° Cone)
BS 5200 – ISO 12151-6 – DKOR


EB Dd-7

BSP Swivel Female
with O–Ring
45° Elbow (60° Cone)
BS 5200 – ISO 12151-6 – DKOR 45°


EC Dd-7

BSP Swivel Female
with O–Ring
90° Elbow (60° Cone)
BS 5200 – ISO 12151-6 – DKOR 90°


D9 Dd-8

Male BSP Parallel Pipe
Rigid – Straight (60° Cone)
BS5200 – AGR


SAE


Page Dd-9 – Dd-11

01 Dd-9

Male NPTF Pipe
Rigid – Straight
SAE J476A / J516 – AGN

03 Dd-9

Male JIC 37° – Rigid
Straight
ISO12151-5-S – AGJ


06 Dd-10

Female JIC 37° – Swivel
Straight
ISO12151-5-SWS – DKJ


37 Dd-11

Female JIC 37° – Swivel
45° Elbow
ISO 12151-5-SWE 45° – DKJ 45°

39 Dd-11

Female JIC 37° – Swivel
90° Elbow
ISO 12151-5-SWES – DKJ 90°

Flange


Page Dd-12 – Dd-22


15/4A Dd-12

ISO 6162-1 Flange
Straight
ISO 12151-3-S-L – SFL
(35.0 MPa/ 5000 psi)

17/4F Dd-13

ISO 6162-1 Flange
45° Elbow
ISO 12151-3 – E45S – L – SFL 45°
(35.0 MPa/ 5000 psi)

19/4N Dd-14

ISO 6162-1 Flange
90° Elbow
ISO 12151-3-E-L – SFL 90°
(35.0 MPa/ 5000 psi)

6A Dd-15

ISO 6162-2 Flange
Straight
ISO 12151-3-S-S – SFS
(42.0 MPa/ 6000 psi)


6E Dd-16

ISO 6162-2 Flange
30° Elbow
SFS 30°
(42.0 MPa/ 6000 psi)


6F Dd-16

ISO 6162-2 Flange
45° Elbow – Heavy Series
ISO 12151-3 – E45-S – SFS 45°
(42.0 MPa/ 6000 psi)

6N Dd-17

ISO 6162-2 Flange
90° Elbow
ISO 12151-3 – E-S – SFS 90°
(42.0 MPa/ 6000 psi)

X5 Dd-18

Flange – Straight
Full flange system for
ISO 6162-1 or ISO 6162-2

X7 Dd-18

Flange – 45° Elbow
Full flange system for
ISO 6162-1 or ISO 6162-2

X9 Dd-19

Flange – 90° Elbow
Full flange system for
ISO 6162-1 or ISO 6162-2

XA Dd-19

Caterpillar® Flange
Straight

XF Dd-20


Caterpillar® Flange
45° Elbow

XG Dd-20

Caterpillar® Flange
60° Elbow

XN Dd-21

Caterpillar® Flange
90° Elbow

K5 Dd-21

Komatsu® Flange
Straight

K7 Dd-22


Komatsu® Flange
45° Elbow

K9 Dd-22

Komatsu® Flange
90° Elbow

ORFS

Page Dd-23 – Dd-25

JC Dd-23

Female ORFS
Swivel – Straight
Short
ISO 12151-1 – SWSA SAE J516 – ORFS

J7 Dd-23


Female ORFS – Swivel
45° Elbow
ISO 12151-1 – SWE 45°
SAE J516 – ORFS 45°

J9 Dd-24

Female ORFS – Swivel
90° Elbow – Short Drop
ISO 12151-1 – SWES
SAE J516 – ORFS 90°

J1 Dd-24

Female ORFS – Swivel
90° Elbow – Long Drop
ISO 12151-1 – SWEL
SAE J 516 – ORFS 90° L

JM Dd-25

ORFS Male
ISO 12151-1-S – SAE J516

A large range of special hose fittings for the MRO market can be found on page Dd-27

French Standard

Page Dd-26


FG Dd-26

Male French Gas Series
Rigid – Straight (24° Cone)

CA

Female Metric 24° Light Series with O-Ring Swivel – Straight

ISO 12151-2-SWS-L – DKOL






Part Number	Hose I.D.				Thread	Tube O.D.	A	B	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
1CA77-15-8	12	1/2	-8	12.7	M22x1.5	15	63	28	27
1CA77-18-10	16	5/8	-10	15.9	M26x1.5	18	66	27	32
1CA77-18-12	19	3/4	-12	19.1	M26x1.5	18	74	28	32
1CA77-22-12	19	3/4	-12	19.1	M30x2	22	73	27	36
1CA77-22-16	25	1	-16	25.4	M30x2	22	88	33	36
1CA77-28-16	25	1	-16	25.4	M36x2	28	89	35	41
1CA77-35-20	31	1 1/4	-20	31.8	M45x2	35	100	37	50
1CA77-42-24	38	1 1/2	-24	38.1	M52x2	42	106	39	60


Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

CE

Female Metric 24° Light Series with O-Ring Swivel – 45° Elbow

ISO 12151-2-SWE 45°-L – DKOL 45°





Part Number	Hose I.D.				Thread	Tube O.D.	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
1CE77-15-8	12	1/2	-8	12.7	M22x1.5	15	83	48	23	27
1CE77-22-12	19	3/4	-12	19.1	M30x2	22	120	74	29	36
1CE77-28-16	25	1	-16	25.4	M36x2	28	142	88	33	41
1CE77-35-20	31	1 1/4	-20	31.8	M45x2	35	162	98	37	50
1CE77-42-24	38	1 1/2	-24	38.1	M52x2	42	201	134	49	60

Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.


Approved **fitting series** for **hose types**:

77 | 387 | 387ST | 387TC | 487 | 487ST | 487TC size -20 up to -32 | 787 | 787TC | 797 | 797TC

CF

Female Metric 24° Light Series with O-Ring Swivel – 90° Elbow

ISO 12151-2-SWE-L – DKOL 90°






Part Number	Hose I.D.				Thread	Tube O.D.	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
1CF77-15-8	12	1/2	-8	12.7	M22x1.5	15	76	41	44	27
1CF77-18-10	16	5/8	-10	15.9	M26x1.5	18	92	53	49	32
1CF77-18-12	19	3/4	-12	19.1	M26x1.5	18	108	62	56	32
1CF77-22-12	19	3/4	-12	19.1	M30x2	22	108	62	59	36
1CF77-28-16	25	1	-16	25.4	M36x2	28	131	77	69	41
1CF77-35-20	31	1 1/4	-20	31.8	M45x2	35	151	87	79	50
1CF77-42-24	38	1 1/2	-24	38.1	M52x2	42	179	112	101	60

Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

D0

Male Metric 24° Light Series – Rigid Straight

ISO 12151-2-S-L – CEL






Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	metric	mm	mm	mm
1D077-15-8	12	1/2	-8	12.7	M22x1.5	61	27	22
1D077-18-10	16	5/8	-10	15.9	M26x1.5	68	30	27
1D077-22-12	19	3/4	-12	19.1	M30x2	82	36	30
1D077-28-16	25	1	-16	25.4	M30x2	92	38	36


Approved **fitting series** for **hose types**:

77 | 387 | 387ST | 387TC | 487 | 487ST | 487TC size -20 up to -32 | 787 | 787TC | 797 | 797TC

C9 Female Metric 24° – Swivel Heavy Series with O-Ring Straight

ISO 12151-2-SWS-S – DKOS







Part Number	Hose I.D.				Thread	A	B	W
	DN	Inch	Size	mm	metric	mm	mm	mm
1C977-12-8	12	1/2	-8	12.7	M20x1.5	61	26	24
1C977-16-8	12	1/2	-8	12.7	M24x1.5	60	25	30
1C977-16-10	16	5/8	-10	15.9	M24x1.5	67	28	30
1C977-20-10	16	5/8	-10	15.9	M30x2	67	28	36
1C977-20-12	19	3/4	-12	19.1	M30x2	76	30	36
1C977-25-12-SW41	19	3/4	-12	19.1	M36x2	77	31	41
1C977-25-12	19	3/4	-12	19.1	M36x2	76.6	30.6	46
1C977-30-12	19	3/4	-12	19.1	M42x2	83	37	50
1C977-25-16	25	1	-16	25.4	M36x2	89	35	46
1C977-30-16	25	1	-16	25.4	M42x2	89	35	50
1C977-30-20	31	1 1/4	-20	31.8	M42x2	102	39	50
1C977-38-20	31	1 1/4	-20	31.8	M52x2	100	36	60
1C977-38-24	38	1 1/2	-24	38.1	M52x2	106	39	60

Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

0C Female Metric 24° – Swivel Heavy Series with O-Ring 45° Elbow

ISO 12151-2 – SWE 45°-S – DKOS 45°





Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
10C77-16-8	12	1/2	-8	12.7	M24x1.5	83	49	24	30
10C77-12-10	16	5/8	-10	15.9	M20x1.5	104	65	25	24
10C77-16-10	16	5/8	-10	15.9	M24x1.5	111	64	24	30
10C77-20-10	16	5/8	-10	15.9	M30x2	107	68	28	36
10C77-20-12	19	3/4	-12	19.1	M30x2	120	74	30	36
10C77-25-12-SW41	19	3/4	-12	19.1	M36x2	119	73	29	41
10C77-25-12	19	3/4	-12	19.1	M36x2	119	73	29	46
10C77-30-12	19	3/4	-12	19.1	M42x2	121	75	30	50
10C77-25-16	25	1	-16	25.4	M36x2	142	88	33	46
10C77-30-16	25	1	-16	25.4	M42x2	142	88	33	50
10C77-30-20	31	1 1/4	-20	31.8	M42x2	155	91	34	50
10C77-38-20	31	1 1/4	-20	31.8	M52x2	161	97	37	60
10C77-38-24	38	1 1/2	-24	38.1	M52x2	195	128	49	60


Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.


Approved **fitting series** for **hose types**:

77 | 387 | 387ST | 387TC | 487 | 487ST | 487TC size -20 up to -32 | 787 | 787TC | 797 | 797TC

1C Female Metric 24° – Swivel Heavy Series with O-Ring 90° Elbow

ISO 12151-2-SWE-S – DKOS 90°







Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
11C77-16-8	12	1/2	-8	12.7	M24x1.5	77	42	45	30
11C77-16-10	16	5/8	-10	15.9	M24x1.5	92	53	45	30
11C77-20-10	16	5/8	-10	15.9	M30x2	92	53	53	36
11C77-20-10-STB60	16	5/8	-10	15.9	M30x2	115	76	37	36
11C77-20-12	19	3/4	-12	19.1	M30x2	108	62	60	36
11C77-20-12-STB60	19	3/4	-12	19.1	M30x2	134	88	41	36
11C77-25-12	19	3/4	-12	19.1	M36x2	108	62	58.5	46
11C77-25-12-STB60	19	3/4	-12	19.1	M36x2	133	87	40	46
11C77-25-12-SW41	19	3/4	-12	19.1	M36x2	108	62	59	41
11C77-30-12	19	3/4	-12	19.1	M42x2	108	62	61	50
11C77-25-16	25	1	-16	25.4	M36x2	131	77	69	46
11C77-30-16	25	1	-16	25.4	M42x2	131	77	69	50
11C77-30-16-SL120	25	1	-16	25.4	M42x2	131	77	120	50
11C77-30-20	31	1 1/4	-20	31.8	M42x2	145	82	73	50
11C77-38-20	31	1 1/4	-20	31.8	M52x2	151	87	78	60
11C77-38-24	38	1 1/2	-24	38.1	M52x2	179	112	101	60

Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

D2 Male Metric 24° – Rigid Heavy Series – Straight

ISO 12151-2-S-S – CES






Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	metric	mm	mm	mm
1D277-16-8	12	1/2	-8	12.7	M24x1.5	64	30	24
1D277-16-10	16	5/8	-10	15.9	M24x1.5	69	30	24
1D277-20-10	16	5/8	-10	15.9	M30x2	72	34	30
1D277-20-12	19	3/4	-12	19.1	M30x2	84	38	30
1D277-25-12	19	3/4	-12	19.1	M36x2	86	40	36
1D277-25-16	25	1	-16	25.4	M36x2	96	42	36
1D277-30-16	25	1	-16	25.4	M42x2	99	45	46
1D277-30-20	31	1 1/4	-20	31.8	M42x2	110	47	46
1D277-38-20	31	1 1/4	-20	31.8	M52x2	114	51	55
1D277-38-24	38	1 1/2	-24	38.1	M52x2	120	53	55


Approved **fitting series** for **hose types**:

77 | 387 | 387ST | 387TC | 487 | 487ST | 487TC | size -20 up to -32 | 787 | 787TC | 797 | 797TC

92 Female BSP Parallel Pipe Swivel – Straight (60° Cone)

BS5200-A – DKR







Part Number	Hose I.D.				Thread	A	B	W
	DN	Inch	Size	mm	BSP	mm	mm	mm
19277-8-8	12	1/2	-8	12.7	1/2x14	57	23	27
19277-12-12	19	3/4	-12	19.1	3/4x14	73	27	32
19277-16-12	19	3/4	-12	19.1	1x11	85	39	41
19277-12-16	25	1	-16	25.4	3/4x14	83	29	32
19277-16-16	25	1	-16	25.4	1x11	91	37	41
19277-20-20	31	1 1/4	-20	31.8	1 1/4x11	98	34	50

B1 Female BSP Parallel Pipe Swivel 45° Elbow (60° Cone)

BS 5200-D – DKR 45°






Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	BSP	mm	mm	mm	mm
1B177-8-8	12	1/2	-8	12.7	1/2x14	84	49	20	27
1B177-12-12	19	3/4	-12	19.1	3/4x14	116	70	26	32
1B177-16-12	19	3/4	-12	19.1	1x11	124	78	34	41
1B177-16-16	25	1	-16	25.4	1x11	145	91	36	41


Approved **fitting series** for **hose types**:

77 | 387 | 387ST | 387TC | 487 | 487ST | 487TC size -20 up to -32 | 787 | 787TC | 797 | 797TC

B2 Female BSP Parallel Pipe Swivel 90° Elbow (60° Cone)

BS 5200-B – DKR 90°







Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	BSP	mm	mm	mm	mm
1B277-8-8	12	1/2	-8	12.7	1/2x14	76	41	40	27
1B277-12-12	19	3/4	-12	19.1	3/4x14	108	62	55	32
1B277-16-16	25	1	-16	25.4	1x11	131	77	74	41

EA BSP Swivel Female with O-Ring (60° Cone)

BS 5200 – ISO 12151-6 – DKOR





Part Number	Hose I.D.				Thread	A	B	W
	DN	Inch	Size	mm	BSP	mm	mm	mm
1EA77-8-8	12	1/2	-8	12.7	1/2x14	58	23	27
1EA77-10-10	16	5/8	-10	15.9	5/8x14	62	23	30
1EA77-12-10	16	5/8	-10	15.9	3/4x14	63	24	32
1EA77-12-12	19	3/4	-12	19.1	3/4x14	72	26	32
1EA77-16-12	19	3/4	-12	19.1	1x11	82	36	41
1EA77-12-16	25	1	-16	25.4	3/4x14	83	29	32
1EA77-16-16	25	1	-16	25.4	1x11	90	36	41
1EA77-20-20	31	1 1/4	-20	31.8	1 1/4x11	96	33	50
1EA77-24-24	38	1 1/2	-24	38.1	1 1/2	103	36	55
1EA77-32-32	51	2	-32	50.8	2	118	40	70

Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.


Approved **fitting series** for **hose types**:


77 | 387 | 387ST | 387TC | 487 | 487ST | 487TC size -20 up to -32 | 787 | 787TC | 797 | 797TC

EB

BSP Swivel Female with O–Ring 45° Elbow (60° Cone)

BS 5200 – ISO 12151-6 – DKOR 45°






Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	BSP	mm	mm	mm	mm
1EB77-8-8	12	1/2	-8	12.7	1/2x14	80	45	20	27
1EB77-10-10	16	5/8	-10	15.9	5/8x14	101	62	22	30
1EB77-12-10	16	5/8	-10	15.9	3/4x14	103	64	24	32
1EB77-12-12	19	3/4	-12	19.1	3/4x14	117	71	27	32
1EB77-16-12	19	3/4	-12	19.1	1x11	120	74	29	41
1EB77-16-16	25	1	-16	25.4	1x11	144	90	35	41
1EB77-20-20	31	1 1/4	-20	31.8	1 1/4x11	159	95	35	50
1EB77-24-24	38	1 1/2	-24	38.1	1 1/2	196	129	50	55
1EB77-32-32	51	2	-32	50.8	2	255	178	86	70


Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

EC

BSP Swivel Female with O–Ring 90° Elbow (60° Cone)

BS 5200 – ISO 12151-6 – DKOR 90°





Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	BSP	mm	mm	mm	mm
1EC77-8-8	12	1/2	-8	12.7	1/2x14	76	41	40	27
1EC77-10-10	16	5/8	-10	15.9	5/8x14	92	53	44	30
1EC77-12-10	16	5/8	-10	15.9	3/4x14	92	53	47	32
1EC77-12-12	19	3/4	-12	19.1	3/4x14	108	62	55	32
1EC77-16-12	19	3/4	-12	19.1	1x11	108	62	59	41
1EC77-16-16	25	1	-16	25.4	1x11	131	77	72	41
1EC77-20-20	31	1 1/4	-20	31.8	1 1/4x11	151	87	75	50
1EC77-24-24	38	1 1/2	-24	38.1	1 1/2	179	112	103	55
1EC77-32-32	51	2	-32	50.8	2	236	159	147	70


Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.


Approved **fitting series** for **hose types**:

77 | 387 | 387ST | 387TC | 487 | 487ST | 487TC size -20 up to -32 | 787 | 787TC | 797 | 797TC

D9 Male BSP Parallel Pipe Rigid – Straight (60° Cone)

BS5200 – AGR






Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	BSP	mm	mm	mm
1D977-8-8	12	1/2	-8	12.7	1/2x14	68	33	27
1D977-10-10	16	5/8	-10	15.9	5/8x14	74	36	30
1D977-12-12	19	3/4	-12	19.1	3/4x14	87	41	32
1D977-16-12	19	3/4	-12	19.1	1x11	91	45	41
1D977-16-16	25	1	-16	25.4	1x11	91	45	41
1D977-20-16	25	1	-16	25.4	1 1/4x11	103	49	50
1D977-20-20	31	1 1/4	-20	31.8	1 1/4x11	113	50	50
1D977-24-24	38	1 1/2	-24	38.1	1 1/2x11	124	57	55


Approved **fitting series** for **hose types**:

77 | 387 | 387ST | 387TC | 487 | 487ST | 487TC size -20 up to -32 | 787 | 787TC | 797 | 797TC

01 Male NPTF Pipe Rigid – Straight

SAE J476A / J516 – AGN







Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	NPTF	mm	mm	mm
10177-8-8	12	1/2	-8	12.7	1/2x14	69	35	22
10177-8-12	19	3/4	-12	19.1	1/2x14	87	41	30
10177-12-12	19	3/4	-12	19.1	3/4x14	87	41	30
10177-16-16	25	1	-16	25.4	1x11 1/2	103	49	36
10177-20-20	31	1 1/4	-20	31.8	1 1/4x11	116	53	46
10177-24-24	38	1 1/2	-24	38.1	1 1/2x11	124	57	50
10177-32-32	51	2	-32	50.8	2x11	143	66	65

All sizes of 10177 fittings are rated at 35,0 MPa working pressure.

03 Male JIC 37° – Rigid Straight

ISO12151-5-S – AGJ





Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	UNF	mm	mm	mm
10377-8-8	12	1/2	-8	12.7	3/4x16	66.45	32	22
10377-10-8	12	1/2	-8	12.7	7/8x14	69	34	24
10377-12-8	12	1/2	-8	12.7	1 1/16x12	77	42	27
10377-10-10	16	5/8	-10	15.9	7/8x14	76	38	24
10377-12-10	16	5/8	-10	15.9	1 1/16x12	82	43	30
10377-10-12	19	3/4	-12	19.1	7/8x14	87	41	30
10377-12-12	19	3/4	-12	19.1	1 1/16x12	89	43	30
10377-16-12	19	3/4	-12	19.1	1 5/16x12	92	46	36
10377-16-16	25	1	-16	25.4	1 5/16x12	101.4	47	36
10377-20-16	25	1	-16	25.4	1 5/8x12	110	56	50
10377-20-20	31	1 1/4	-20	31.8	1 5/8x12	118	55	50
10377-32-32	51	2	-32	50.8	2 1/2x12	148	71	65


All sizes of 10377 fittings are rated at 35,0 MPa working pressure.


Approved **fitting series** for **hose types**:

77 | 387 | 387ST | 387TC | 487 | 487ST | 487TC size -20 up to -32 | 787 | 787TC | 797 | 797TC

06 Female JIC 37° – Swivel Straight

ISO12151-5-SWS – DKJ





Part Number	Hose I.D.				Thread	A	B	H	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
10677-8-8	12	1/2	-8	12.7	3/4x16	71	37	22	22
10677-10-8	12	1/2	-8	12.7	7/8x14	74	39	22	27
10677-12-8	12	1/2	-8	12.7	1 1/16x12	80	46	30	32
10677-10-10	16	5/8	-10	15.9	7/8x14	81	42	24	27
10677-12-10	16	5/8	-10	15.9	1 1/16x12	84	45	30	32
10677-10-12	19	3/4	-12	19.1	7/8x14	92	46	30	27
10677-12-12	19	3/4	-12	19.1	1 1/16x12	94	48	30	32
10677-14-12	19	3/4	-12	19.1	1 3/16x12	99	53	36	36
10677-16-12	19	3/4	-12	19.1	1 5/16x12	99	53	36	41
10677-12-16	25	1	-16	25.4	1 1/16x12	102	48	36	32
10677-16-16	25	1	-16	25.4	1 5/16x12	106	52	36	41
10677-20-16	25	1	-16	25.4	1 5/8x12	109	55	41	50
10677-16-20	31	1 1/4	-20	31.8	1 5/16x12	120	57	46	41
10677-20-20	31	1 1/4	-20	31.8	1 5/8 12	124	60	46	50
10677-24-20	31	1 1/4	-20	31.8	1 7/8x12	108	44	50	60
10677-24-24	38	1 1/2	-24	38.1	1 7/8x12	136	69	50	60
10677-32-32	51	2	-32	50.8	2 1/2x12	160	83	65	75


All sizes of 10677 fittings are rated at 35,0 MPa working pressure.


Approved **fitting series** for **hose types**:

77 | 387 | 387ST | 387TC | 487 | 487ST | 487TC size -20 up to -32 | 787 | 787TC | 797 | 797TC

37 Female JIC 37° – Swivel 45° Elbow

ISO 12151-5-SWE 45° – DKJ 45°







Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
13777-8-8	12	1/2	-8	12.7	3/4x16	73	38	15	22
13777-10-8	12	1/2	-8	12.7	7/8x14	76	41	16	27
13777-12-8	12	1/2	-8	12.7	1 1/16x12	79	44	21	32
13777-10-10	16	5/8	-10	15.9	7/8x14	93	54	16	27
13777-12-10	16	5/8	-10	15.9	1 1/16x12	100	61	21	32
13777-10-12	19	3/4	-12	19.1	7/8x14	102	56	16	27
13777-12-12	19	3/4	-12	19.1	1 1/16x12	111	65	21	32
13777-16-12	19	3/4	-12	19.1	1 5/16x12	114	68	24	41
13777-16-16	25	1	-16	25.4	1 5/16x12	133	79	24	41
13777-20-20	31	1 1/4	-20	31.8	1 5/8x12	153	90	32	50
13777-24-24	38	1 1/2	-24	38.1	1 7/8x12	201	134	58	60
13777-32-32	51	2	-32	50.8	2 1/2x12	258	181	72	75

All sizes of 13777 fittings are rated at 35,0 MPa working pressure.

39 Female JIC 37° – Swivel 90° Elbow

ISO 12151-5-SWES – DKJ 90°





Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
13977-8-8	12	1/2	-8	12.7	3/4x16	71	36	29	22
13977-10-8	12	1/2	-8	12.7	7/8x14	76	41	32	27
13977-12-8	12	1/2	-8	12.7	1 1/16x12	76	41	48	32
13977-10-10	16	5/8	-10	15.9	7/8x14	88	50	33	27
13977-12-10	16	5/8	-10	15.9	1 1/16x12	92	53	48	32
13977-10-12	19	3/4	-12	19.1	7/8x14	97	51	33	27
13977-12-12	19	3/4	-12	19.1	1 1/16x12	108	62	48	32
13977-16-12	19	3/4	-12	19.1	1 5/16x12	108	62	56	41
13977-16-16	25	1	-16	25.4	1 5/16x12	131	77	74	41
13977-20-20	31	1 1/4	-20	31.8	1 5/8x12	148	84	78	50
13977-24-24	38	1 1/2	-24	38.1	1 7/8x12	175	108	102	60
13977-32-32	51	2	-32	50.8	2 1/2x12	236	159	152	75


All sizes of 13977 fittings are rated at 35,0 MPa working pressure.


Approved **fitting series** for **hose types**:

77	387	387ST	387TC	487	487ST	487TC	size -20 up to -32	787	787TC	797	797TC

15/4A ISO 6162-1 Flange Straight

ISO 12151-3-S-L – SFL
(35.0 MPa/ 5000 psi)





Part Number	Hose I.D.				Flange	A	B	F
	DN	Inch	Size	mm	Inch	mm	mm	mm
11577-8-8	12	1/2	-8	12.7	1/2	90	55	30
11577-12-8	12	1/2	-8	12.7	3/4	67	33	38
11577-10-10	16	5/8	-10	15.9	5/8	99	60	34
11577-12-10	16	5/8	-10	15.9	3/4	75	36	38
11577-12-12	19	3/4	-12	19.1	3/4	107	62	38
11577-16-12	19	3/4	-12	19.1	1	88	42	45
11577-16-16	25	1	-16	25.4	1	119	65	45
14A77-20-16	25	1	-16	25.4	1 1/4	90	36	51
11577-16-20	31	1 1/4	-20	31.8	1	130	66	45
14A77-20-20	31	1 1/4	-20	31.8	1 1/4	138	74	51
14A77-24-20	31	1 1/4	-20	31.8	1 1/2	100	37	60
14A77-20-24	38	1 1/2	-24	38.1	1 1/4	146	79	51
14A77-24-24	38	1 1/2	-24	38.1	1 1/2	140	73	60
14A77-32-24	38	1 1/2	-24	38.1	2	117	50	71
14A77-32-32	51	2	-32	50.8	2	163	86	71


SAE flange halves see in section Eb.
Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.


Approved **fitting series** for **hose types**:

77 | 387 | 387ST | 387TC | 487 | 487ST | 487TC size -20 up to -32 | 787 | 787TC | 797 | 797TC

17/4F ISO 6162-1 Flange 45° Elbow

ISO 12151-3 – E45S – L – SFL 45°
(35.0 MPa/ 5000 psi)





Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
11777-8-8	12	1/2	-8	12.7	1/2	79	45	20	30
11777-12-8	12	1/2	-8	12.7	3/4	81	47	22	38
11777-10-10	16	5/8	-10	15.9	5/8	103	64	24	34
11777-12-12	19	3/4	-12	19.1	3/4	116	70	26	38
11777-16-12	19	3/4	-12	19.1	1	116	70	26	45
11777-16-16	25	1	-16	25.4	1	141	87	32	45
14F77-20-16	25	1	-16	25.4	1 1/4	141	87	32	51
14F77-20-20	31	1 1/4	-20	31.8	1 1/4	162	99	38	51
14F77-24-20	31	1 1/4	-20	31.8	1 1/2	162	99	38	60
14F77-24-24	38	1 1/2	-24	38.1	1 1/2	187	120	44	60
14F77-32-24	38	1 1/2	-24	38.1	2	182	115	44	71
14F77-32-32	51	2	-32	50.8	2	211	134	56	71

SAE flange halves see in section Eb.


Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.


Approved **fitting series** for **hose types**:

77 | 387 | 387ST | 387TC | 487 | 487ST | 487TC size -20 up to -32 | 787 | 787TC | 797 | 797TC

19/4N ISO 6162-1 Flange 90° Elbow

ISO 12151-3-E-L – SFL 90°
(35.0 MPa/ 5000 psi)





Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
11977-8-8	12	1/2	-8	12.7	1/2	76	41	41	30
11977-12-8	12	1/2	-8	12.7	3/4	80	45	42	38
11977-10-10	16	5/8	-10	15.9	5/8	92	53	53	34
11977-12-12	19	3/4	-12	19.1	3/4	108	62	58	38
11977-16-12	19	3/4	-12	19.1	1	108	62	58	45
11977-16-16	25	1	-16	25.4	1	131	77	70	45
14N77-20-16	25	1	-16	25.4	1 1/4	131	77	69	51
11977-16-20	31	1 1/4	-20	31.8	1	151	87	90	45
14N77-20-20	31	1 1/4	-20	31.8	1 1/4	151	87	90	51
14N77-24-20	31	1 1/4	-20	31.8	1 1/2	151	87	90	60
14N77-24-24	38	1 1/2	-24	38.1	1 1/2	175	108	104	60
14N77-32-24	38	1 1/2	-24	38.1	2	170	103	104	71
14N77-32-32	51	2	-32	50.8	2	206	129	138	71


SAE flange halves see in section Eb.
Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.


Approved **fitting series** for **hose types**:

77 | 387 | 387ST | 387TC | 487 | 487ST | 487TC size -20 up to -32 | 787 | 787TC | 797 | 797TC

6A ISO 6162-2 Flange Straight

ISO 12151-3-S-S – SFS
(42.0 MPa/ 6000 psi)





Part Number	Hose I.D.				Flange	A	B	F
	DN	Inch	Size	mm	Inch	mm	mm	mm
16A77-8-8	12	1/2	-8	12.7	1/2	89.85	55.2	32
16A77-12-8	12	1/2	-8	12.7	3/4	69.4	34.75	41
16A77-12-10	16	5/8	-10	15.9	3/4	75	36	41
16A77-16-10	16	5/8	-10	15.9	1	80	41	48
16A77-8-12	19	3/4	-12	19.1	1/2	106	60	32
16A77-12-12	19	3/4	-12	19.1	3/4	114.2	68.2	41
16A77-16-12	19	3/4	-12	19.1	1	88.2	42	48
16A77-20-12	19	3/4	-12	19.1	1 1/4	93	47	54
16A77-12-16	25	1	-16	25.4	3/4	126	72	41
16A77-16-16	25	1	-16	25.4	1	113	59	48
16A77-20-16	25	1	-16	25.4	1 1/4	103	49	54
16A77-16-20	31	1 1/4	-20	31.8	1	145	82	48
16A77-20-20	31	1 1/4	-20	31.8	1 1/4	146	82	54
16A77-24-20	31	1 1/4	-20	31.8	1 1/2	118	55	64
16A77-20-24	38	1 1/2	-24	38.1	1 1/4	154	87	54
16A77-24-24	38	1 1/2	-24	38.1	1 1/2	162	96	64
16A77-32-24	38	1 1/2	-24	38.1	2	133	66	79
16A77-32-32	51	2	-32	50.8	2	182	105	79


SAE flange halves see in section Eb.
Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.


Approved **fitting series** for **hose types**:

77 | 387 | 387ST | 387TC | 487 | 487ST | 487TC size -20 up to -32 | 787 | 787TC | 797 | 797TC

6E ISO 6162-2 Flange 30° Elbow

SFS 30°
(42.0 MPa/ 6000 psi)







Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
16E77-12-12	19	3/4	-12	19.1	3/4	121	75	16	41
16E77-16-12	19	3/4	-12	19.1	1	122	76	16	48
16E77-16-16	25	1	-16	25.4	1	136	82	19	48
16E77-20-16	25	1	-16	25.4	1 1/4	149	95	19	54
16E77-20-20	31	1 1/4	-20	31.8	1 1/4	167	104	22	54
16E77-24-24	38	1 1/2	-24	38.1	1 1/2	190	123	30	64
16E77-32-32	51	2	-32	50.8	2	223	145	32	79

SAE flange halves see in section Eb.
Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

6F ISO 6162-2 Flange 45° Elbow – Heavy Series

ISO 12151-3 – E45-S – SFS 45°
(42.0 MPa/ 6000 psi)





Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
16F77-8-8	12	1/2	-8	12.7	1/2	79	44	19	32
16F77-12-8	12	1/2	-8	12.7	3/4	85.8	51	26	41
16F77-8-10	16	5/8	-10	15.9	1/2	105	66	26	32
16F77-12-10	16	5/8	-10	15.9	3/4	104	66	26	41
16F77-16-10	16	5/8	-10	15.9	1	105	66	26	48
16F77-12-12	19	3/4	-12	19.1	3/4	116.2	70	26	41
16F77-16-12	19	3/4	-12	19.1	1	116	70	26	48
16F77-12-16	25	1	-16	25.4	3/4	132	78	32	41
16F77-16-16	25	1	-16	25.4	1	141	87	32	48
16F77-20-16	25	1	-16	25.4	1 1/4	142	88	32	54
16F77-16-20	31	1 1/4	-20	31.8	1	159	95	38	48
16F77-20-20	31	1 1/4	-20	31.8	1 1/4	162	99	38	54
16F77-24-20	31	1 1/4	-20	31.8	1 1/2	162	99	38	64
16F77-20-24	38	1 1/2	-24	38.1	1 1/4	179	112	44	54
16F77-24-24	38	1 1/2	-24	38.1	1 1/2	182	115	44	64
16F77-32-24	38	1 1/2	-24	38.1	2	187	120	44	79
16F77-32-32	51	2	-32	50.8	2	211	134	56	79


SAE flange halves see in section Eb.
Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.


Approved **fitting series** for **hose types**:

77 | 387 | 387ST | 387TC | 487 | 487ST | 487TC size -20 up to -32 | 787 | 787TC | 797 | 797TC

6N ISO 6162-2 Flange 90° Elbow

ISO 12151-3 – E-S – SFS 90°
(42.0 MPa/ 6000 psi)





Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
16N77-8-8	12	1/2	-8	12.7	1/2	77.05	42	41	32
16N77-12-8	12	1/2	-8	12.7	3/4	81.05	47	45	41
16N77-8-10	16	5/8	-10	15.9	1/2	92	53	54	32
16N77-12-10	16	5/8	-10	15.9	3/4	92	53	54	41
16N77-16-10	16	5/8	-10	15.9	1	92	53	54	48
16N77-12-12	19	3/4	-12	19.1	3/4	108.2	62	58	41
16N77-16-12	19	3/4	-12	19.1	1	108	62	58	48
16N77-20-12	19	3/4	-12	19.1	1 1/4	108	62	63	54
16N77-12-16	25	1	-16	25.4	3/4	118	64	70	41
16N77-16-16	25	1	-16	25.4	1	131	77	70	48
16N77-20-16	25	1	-16	25.4	1 1/4	135	81	70	54
16N77-16-20	31	1 1/4	-20	31.8	1	145	82	90	48
16N77-20-20	31	1 1/4	-20	31.8	1 1/4	151	87	90	54
16N77-24-20	31	1 1/4	-20	31.8	1 1/2	151	87	90	64
16N77-20-24	38	1 1/2	-24	38.1	1 1/4	156	89	104	54
16N77-24-24	38	1 1/2	-24	38.1	1 1/2	175	108	104	64
16N77-32-24	38	1 1/2	-24	38.1	2	175	108	104	79
16N77-32-32	51	2	-32	50.8	2	206	129	138	79

SAE flange halves see in section Eb.


Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.


Approved **fitting series** for **hose types**:

77 | 387 | 387ST | 387TC | 487 | 487ST | 487TC size -20 up to -32 | 787 | 787TC | 797 | 797TC

X5 Flange – Straight

Full flange system for
ISO 6162-1 or ISO 6162-2







Part Number	Hose I.D.				A	B
	DN	Inch	Size	mm	mm	mm
1X577-12-12	19	3/4	-12	19.1	103	57
1X577-16-12	19	3/4	-12	19.1	103.2	57
1X577-16-16	25	1	-16	25.4	113	59
1X577-20-16	25	1	-16	25.4	113	59
1X577-24-16	25	1	-16	25.4	113	59
1X577-20-20	31	1 1/4	-20	31.8	124	57
1X577-24-24	38	1 1/2	-24	38.1	129	62
1X577-32-32	51	2	-32	50.8	154	77

Full flange system see Eb-2.

X7 Flange – 45° Elbow

Full flange system for
ISO 6162-1 or ISO 6162-2





Part Number	Hose I.D.				A	B	E
	DN	Inch	Size	mm	mm	mm	mm
1X777-12-12	19	3/4	-12	19.1	118.4	72.6	28.5
1X777-16-12	19	3/4	-12	19.1	118.4	72.4	28.5
1X777-16-16	25	1	-16	25.4	141	87	32
1X777-20-16	25	1	-16	25.4	147	93	38
1X777-16-20	31	1 1/4	-20	31.8	146	82	38
1X777-20-20	31	1 1/4	-20	31.8	159	96	38
1X777-24-20	31	1 1/4	-20	31.8	165	102	44
1X777-24-24	38	1 1/2	-24	38.1	183	116	45


Full flange system see Eb-2.


Approved **fitting series** for **hose types**:

77 | 387 | 387ST | 387TC | 487 | 487ST | 487TC size -20 up to -32 | 787 | 787TC | 797 | 797TC

X9 Flange – 90° Elbow

Full flange system for
ISO 6162-1 or ISO 6162-2






Part Number	Hose I.D.				A	B	E
	DN	Inch	Size	mm	mm	mm	mm
1X977-8-8	12	1/2	-8	12.7	81	45	43
1X977-12-12	19	3/4	-12	19.1	107.5	61.7	60.5
1X977-16-12	19	3/4	-12	19.1	107.6	61.8	60.5
1X977-12-16	25	1	-16	25.4	110	56	70
1X977-16-16	25	1	-16	25.4	131	77	70
1X977-20-16	25	1	-16	25.4	131	77	70
1X977-16-20	31	1 1/4	-20	31.8	130	67	90
1X977-20-20	31	1 1/4	-20	31.8	148	84	90
1X977-24-20	31	1 1/4	-20	31.8	148	84	90
1X977-24-24	38	1 1/2	-24	38.1	170	103	104
1X977-32-32	51	2	-32	50.8	221	144	138

Full flange system see Eb-2.

XA Caterpillar® Flange Straight






Part Number	Hose I.D.				Flange	A	B	F
	DN	Inch	Size	mm	Inch	mm	mm	mm
1XA77-12-12	19	3/4	-12	19.1	3/4	114	68	41
1XA77-16-12	19	3/4	-12	19.1	3/4	88	42	48
1XA77-16-16	25	1	-16	25.4	1	141	87	48
1XA77-20-16	25	1	-16	25.4	1	104	50	54
1XA77-20-20	31	1 1/4	-20	31.8	1 1/4	152	88	54
1XA77-24-20	31	1 1/4	-20	31.8	1 1/2	121	57	64
1XA77-24-24	38	1 1/2	-24	38.1	1 1/2	176	109	64
1XA77-32-24	38	1 1/2	-24	38.1	2	133	66	79
1XA77-32-32	51	2	-32	50.8	2	192	115	79

Approved **fitting series** for **hose types**:

77 | 387 | 387ST | 387TC | 487 | 487ST | 487TC size -20 up to -32 | 787 | 787TC | 797 | 797TC


XF Caterpillar® Flange 45° Elbow





Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
1XF77-12-12	19	3/4	-12	19.1	3/4	122	76	31	41
1XF77-16-16	25	1	-16	25.4	1	145	91	36	48
1XF77-20-20	31	1 1/4	-20	31.8	1 1/4	161	98	37	54
1XF77-24-20	31	1 1/4	-20	31.8	1 1/2	161	98	37	64

XG Caterpillar® Flange 60° Elbow






Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
1XG77-12-12	19	3/4	-12	19.1	3/4	137	91	42	41
1XG77-16-16	25	1	-16	25.4	1	163	109	50	48
1XG77-20-20	31	1 1/4	-20	31.8	1 1/4	200	136	51	54

Approved **fitting series** for **hose types**:

77 | 387 | 387ST | 387TC | 487 | 487ST | 487TC size -20 up to -32 | 787 | 787TC | 797 | 797TC


XN Caterpillar® Flange 90° Elbow





Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
1XN77-12-12	19	3/4	-12	19.1	3/4	108	62	63	41
1XN77-16-12	19	3/4	-12	19.1	1	108	62	63	48
1XN77-16-16	25	1	-16	25.4	1	131	77	74	48
1XN77-20-16	25	1	-16	25.4	1 1/4	120	66	74	54
1XN77-20-20	31	1 1/4	-20	31.8	1 1/4	151	87	94	54
1XN77-24-20	31	1 1/4	-20	31.8	1 1/2	151	87	77	64
1XN77-24-24	38	1 1/2	-24	38.1	1 1/2	160	103	106	79
1XN77-32-24	38	1 1/2	-24	38.1	2	169	103	106	79

K5 Komatsu® Flange Straight






Part Number	Hose I.D.				A	B
	DN	Inch	Size	mm	mm	mm
1K577-16-16	25	1	-16	25.4	119	65

Approved **fitting series** for **hose types**:

77 | 387 | 387ST | 387TC | 487 | 487ST | 487TC size -20 up to -32 | 787 | 787TC | 797 | 797TC


K7 Komatsu® Flange 45° Elbow





Part Number	Hose I.D.				A	B	E
	DN	Inch	Size	mm	mm	mm	mm
1K777-12-12	19	3/4	-12	19.1	116	70	26
1K777-16-16	25	1	-16	25.4	143	89	32
1K777-20-20	31	1 1/4	-20	31.8	159	96	38

K9 Komatsu® Flange 90° Elbow





Part Number	Hose I.D.				A	B	E
	DN	Inch	Size	mm	mm	mm	mm
1K977-12-12	19	3/4	-12	19.1	108	62	58
1K977-16-16	25	1	-16	25.4	127	73	70
1K977-20-20	31	1 1/4	-20	31.8	148	84	90


Approved **fitting series** for **hose types**:


77 | 387 | 387ST | 387TC | 487 | 487ST | 487TC size -20 up to -32 | 787 | 787TC | 797 | 797TC

JC

Female ORFS Swivel – Straight Short

ISO 12151-1 – SWSA
SAE J516 – ORFS






Part Number	Hose I.D.				Thread	A	B	H	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
1JC77-8-8	12	1/2	-8	12.7	13/16x16	60	25	22	24
1JC77-10-8	12	1/2	-8	12.7	1x14	65	31	24	30
1JC77-12-8	12	1/2	-8	12.7	1 3/16x12	64	29	30	36
1JC77-10-10	16	5/8	-10	15.9	1x14	70	31	24	30
1JC77-12-10	16	5/8	-10	15.9	13/16x16	69	30	30	36
1JC77-10-12	19	3/4	-12	19.1	1x14	79	33	30	30
1JC77-12-12	19	3/4	-12	19.1	1 3/16x12	78.5	32.5	30	36
1JC77-16-12	19	3/4	-12	19.1	1 7/16x12	81	35.3	36	41
1JC77-12-16	25	1	-16	25.4	1 3/16x12	92	38	36	36
1JC77-16-16	25	1	-16	25.4	1 7/16x12	91	37.1	36	41
1JC77-20-16	25	1	-16	25.4	1 11/16x12	90	36	41	50
1JC77-20-20	31	1 1/4	-20	31.8	1 11/16x12	107	44	46	50
1JC77-24-24	38	1 1/2	-24	38.1	2x12	109	43	50	60
1JC77-32-32	51	2	-32	50.8	2 1/2x12	143	66	65	75


All sizes of 1JC77 fittings are rated at 35,0 MPa working pressure.

J7

Female ORFS – Swivel 45° Elbow

ISO 12151-1 – SWE 45°
SAE J516 – ORFS 45°






Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
1J777-8-8	12	1/2	-8	12.7	13/16x16	72.7	38	15	24
1J777-10-10	16	5/8	-10	15.9	1x14	93	54	16	30
1J777-12-10	16	5/8	-10	15.9	1 3/16x12	98	59	21	36
1J777-12-12	19	3/4	-12	19.1	1 3/16x12	111	65	21	36
1J777-16-12	19	3/4	-12	19.1	1 7/16x12	114	68	24	41
1J777-16-16	25	1	-16	25.4	1 7/16x12	133	79	24	41
1J777-20-20	31	1 1/4	-20	31.8	1 11/16x12	145	81	25	50
1J777-24-20	31	1 1/4	-20	31.8	2x12	148	84	27	60
1J777-24-24	38	1 1/2	-24	38.1	2x12	176	109	42	60


Approved **fitting series** for **hose types**:

77 | 387 | 387ST | 387TC | 487 | 487ST | 487TC size -20 up to -32 | 787 | 787TC | 797 | 797TC

J9 Female ORFS – Swivel 90° Elbow – Short Drop

ISO 12151-1 – SWES
SAE J516 – ORFS 90°






Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
1J977-8-8	12	1/2	-8	12.7	13/16x16	70.65	36	29	24
1J977-10-10	16	5/8	-10	15.9	1x14	97	50	32	30
1J977-12-10	16	5/8	-10	15.9	1 3/16x12	89	50	48	36
1J977-10-12	19	3/4	-12	19.1	1x14	97	51	32	30
1J977-12-12	19	3/4	-12	19.1	1 3/16x12	108	62	48	36
1J977-16-12	19	3/4	-12	19.1	1 7/16x12	108	62	56	41
1J977-16-16	25	1	-16	25.4	1 7/16x12	131	77	56	41
1J977-20-20	31	1 1/4	-20	31.8	1 11/16x12	146	82	64	50
1J977-24-24	38	1 1/2	-24	38.1	2x12	163	96	69	60

J1 Female ORFS – Swivel 90° Elbow – Long Drop

ISO 12151-1 – SWEL
SAE J 516 – ORFS 90° L






Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
1J177-12-12	19	3/4	-12	19.1	1 3/16x12	108	62	96	36
1J177-16-16	25	1	-16	25.4	1 7/16x12	131	77	114	41


Approved **fitting series** for **hose types**:

77 | 387 | 387ST | 387TC | 487 | 487ST | 487TC size -20 up to -32 | 787 | 787TC | 797 | 797TC

JM ORFS Male

ISO 12151-1-S – SAE J516






Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	UNF	mm	mm	mm
1JM77-8-8	12	1/2	-8	12.7	13/16x16	62.5	27.85	22
1JM77-12-8	12	1/2	-8	12.7	1 3/16x12	69.6	34.95	32
1JM77-10-10	16	5/8	-10	15.9	1x14	71.65	33	27
1JM77-12-10	16	5/8	-10	15.9	1 3/16x12	76	37	30
1JM77-12-12	19	3/4	-12	19.1	1 3/16x12	83	37	32
1JM77-16-12	19	3/4	-12	19.1	1 7/16x12	83.6	37.8	41
1JM77-16-16	25	1	-16	25.4	1 7/16x12	96	40.9	41
1JM77-20-16	25	1	-16	25.4	1 11/16x12	93	39.2	46
1JM77-20-20	31	1 1/4	-20	31.8	1 11/16x12	110	46	50
1JM77-24-20	31	1 1/4	-20	31.8	2 12	116	52	60

JM fittings are supplied without O-ring.
Find O-rings in section E. Special O-rings are available on request.

Approved **fitting series** for **hose types**:

77 | 387 | 387ST | 387TC | 487 | 487ST | 487TC size -20 up to -32 | 787 | 787TC | 797 | 797TC

FG Male French Gas Series Rigid – Straight (24° Cone)





Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	metric	mm	mm	mm
1FG77-27-12	19	3/4	-12	19.1	M36x1.5	82	36	36
1FG77-33-16	25	1	-16	25.4	M45x1.5	97	43	46


Approved **fitting series** for **hose types**:

77 | 387 | 387ST | 387TC | 487 | 487ST | 487TC size -20 up to -32 | 787 | 787TC | 797 | 797TC

Large range of special hose fittings for the MRO market

The demand for special hose fittings is part of our everyday business.
In order to meet this demand with the authority expected, the Hose Products Division Europe has extended its standard offer with special hose fittings such as an extra drop length, etc.

The following is an overview of our special hose fitting selection:





Further special hose fittings are available on request.


Part Number	Description	Hose I.D. Size	Flange Inch	A mm	B mm	E mm	F mm
11977-12-12-SL100	SAE 5000 psi 90° elbow - drop length 100 mm	-12	3/4	108	62	100	38
11977-12-12-SL150	SAE 5000 psi 90° elbow - drop length 150 mm	-12	3/4	108	62	150	38
11977-16-12-SL100	SAE 5000 psi 90° elbow - drop length 100 mm	-12	1	108	62	100	45
11977-16-12-SL150	SAE 5000 psi 90° elbow - drop length 150 mm	-12	1	108	62	150	45
11977-16-16-SL150	SAE 5000 psi 90° elbow - drop length 150 mm	-16	1	131	77	150	45
14N77-24-24-SL150	SAE 5000 psi 90° elbow - drop length 150 mm	-24	1 1/2	175	108	150	60
16A77-20-20-RL186	SAE 6000 psi - straight - Special	-20	1 1/4	175	112		54
16F77-12-16-STB10	SAE 6000 psi - 10° elbow	-16	3/4	143	89	6	41
16F77-20-16-RL110	SAE 6000 psi - 45° elbow - Special	-16	1 1/4	164	110	32	54
16N77-12-12-SL100	SAE 6000 psi 90° elbow - drop length 100 mm	-12	3/4	108	62	100	41
16N77-12-12-SL230	SAE 6000 psi 90° elbow - drop length 230 mm	-12	3/4	108	62	230	41
16N77-12-12-SL72	SAE 6000 psi 90° elbow - drop length 72 mm	-12	3/4	108	62	72	41
16N77-12-12-SL85	SAE 6000 psi 90° elbow - drop length 85 mm	-12	3/4	108	62	85	41
16N77-12-12-STB115	SAE 6000 psi - 115° elbow	-12	3/4	116	70	72	41
16N77-12-12-STB180	SAE 6000 psi - 180° elbow	-12	3/4	101	55	150	41
16N77-12-16-SL55	SAE 6000 psi 90° elbow - drop length 85 mm	-16	3/4	118	64	55	41
16N77-12-16-SL95	SAE 6000 psi 90° elbow - drop length 95 mm	-16	3/4	118	64	95	41
16N77-16-16-SL100	SAE 6000 psi 90° elbow - drop length 100 mm	-16	1	131	77	100	48
16N77-16-16-SL110	SAE 6000 psi 90° elbow - drop length 110 mm	-16	1	131	77	110	48
16N77-16-16-SL120	SAE 6000 psi 90° elbow - drop length 120 mm	-16	1	131	77	120	48
16N77-16-16-SL150	SAE 6000 psi 90° elbow - drop length 150 mm	-16	1	131	77	150	48
16N77-16-16-SL175	SAE 6000 psi 90° elbow - drop length 175 mm	-16	1	135	81	175	48
16N77-16-16-STB120	SAE 6000 psi 120° elbow	-16	1	110	56	85	48
16N77-16-16-STB63-SL75	SAE 6000 psi 63° elbow - drop length 75 mm	-16	1	167	113	75	48
16N77-20-16-SL120	SAE 6000 psi 90° elbow - drop length 120 mm	-16	1 1/4	135	81	120	54
16N77-20-16-SL130	SAE 6000 psi 90° elbow - drop length 130 mm	-16	1 1/4	135	81	130	54
16N77-20-16-STB110-SL150	SAE 6000 psi 110° elbow - drop length 150 mm	-16	1 1/4	128	74	150	54
16N77-20-16-STB70-SL70	SAE 6000 psi 70° elbow - drop length 70 mm	-16	1 1/4	157	103	70	54
16N77-20-20-SL115-RL220	SAE 6000 psi 90° elbow - drop length 220 mm	-20	1 1/4	220	156	115	54
16N77-20-20-SL120	SAE 6000 psi 90° elbow - drop length 120 mm	-20	1 1/4	151	87	120	54
16N77-20-20-SL150-RL150	SAE 6000 psi 90° elbow - drop length 150 mm	-20	1 1/4	238	175	150	54
16N77-20-20-SL150-RL220	SAE 6000 psi 90° elbow - drop length 150 mm	-20	1 1/4	220	156	150	54
16N77-20-20-SL195-RL320	SAE 6000 psi 90° elbow - drop length 195 mm	-20	1 1/4	320	256	195	54
16N77-20-20-SL230-RL250	SAE 6000 psi 90° elbow - drop length 230 mm	-20	1 1/4	338	275	230	54
16N77-20-20-SL230-RL320	SAE 6000 psi 90° elbow - drop length 230 mm	-20	1 1/4	320	256	230	54
16377-16-16	SAE 6000 psi 135° elbow	-16	1	122	68	88	48
16377-20-20	SAE 6000 psi 135° elbow	-20	1 1/4	132	69	109	54
16377-24-24	SAE 6000 psi 135° elbow	-24	1 1/2	124	57	129	64

Approved **fitting series** for **hose types**:

77 | 387 | 387ST | 387TC | 487 | 487ST | 487TC size -20 up to -32 | 787 | 787TC | 797 | 797TC


Shell


Page De-1

VS
De-1

Interlock
Outside Skive

DIN – Metric


Page De-2 – De-5


CA
De-2

Female Metric 24°
Light Series with O–Ring
Swivel – Straight
ISO 12151-2-SWS-L – DKOL

CE
De-2

Female Metric 24°
Light Series with O–Ring
Swivel – 45° Elbow
ISO 12151-2-SWE 45°-L – DKOL 45°

CF
De-3


Female Metric 24°
Light Series with O–Ring
Swivel – 90° Elbow
ISO 12151-2-SWE-L – DKOL 90°


D0
De-3

Male Metric 24°
Light Series – Rigid
Straight
ISO 12151-2-S-L – CEL

C9
De-4

Female Metric 24° – Swivel
Heavy Series with O-Ring
Straight
ISO 12151-2-SWS-S – DKOS

0C
De-4


Female Metric 24° – Swivel
Heavy Series with O–Ring
45° Elbow
ISO 12151-2 – SWE 45°-S – DKOS 45°

1C
De-5

Female Metric 24° – Swivel
Heavy Series with O–Ring
90° Elbow
ISO 12151-2-SWE-S – DKOS 90°

D2
De-5

Male Metric 24° – Rigid
Heavy Series – Straight
ISO 12151-2-S-S – CES

BSP

Page De-6 – De-7


92
De-6

Female BSP Parallel Pipe
Swivel – Straight (60° Cone)
BS5200-A – DKR

B1
De-6

Female BSP Parallel Pipe
Swivel
45° Elbow (60° Cone)
BS 5200-D – DKR 45°


B2
De-7


Female BSP Parallel Pipe
Swivel
90° Elbow (60° Cone)
BS 5200-B – DKR 90°


D9
De-7

Male BSP Parallel Pipe
Rigid – Straight (60° Cone)
BS5200 – AGR


SAE


Page De-8 – De-10

01
De-8

Male NPTF Pipe
Rigid – Straight
SAE J476A / J516 – AGN

03
De-8

Male JIC 37° – Rigid
Straight
ISO12151-5-S – AGJ


06/68
De-9

Female – JIC 37°
SAE 45° Dual Flare
Swivel – Straight
ISO12151-5-SWS – DKJ

37/3V
De-9

Female JIC 37°
SAE 45° – Dual Flare
Swivel Female 45° Elbow
ISO 12151-5-SWE 45° – DKJ 45°

39/3W
De-10

Female JIC 37°
SAE 45° – Dual Flare
Swivel Female 90° Elbow
ISO 12151-5-SWES – DKJ 90°

Flange

Page De-11 – De-13


15
De-11

ISO 6162-1 Flange
Straight
ISO 12151-3-S-L – SFL
(21.0 MPa/ 3000 psi)


17
De-11


ISO 6162-1 Flange
45° Elbow
ISO 12151-3 – E45 – L – SFL 45°
(21.0 MPa/ 3000 psi)

19
De-12

ISO 6162-1 Flange
90° Elbow
ISO 12151-3 – E– L – SFL 90°
(21.0 MPa/ 3000 psi)


6A
De-12

ISO 6162-2 Flange
Straight
ISO 12151-3-S-S – SFS
(42.0 MPa/ 6000 psi)

6F
De-13

ISO 6162-2 Flange
45° Elbow – Heavy Series
ISO 12151-3 – E45-S – SFS 45°
(42.0 MPa/ 6000 psi)

6N
De-13

ISO 6162-2 Flange
90° Elbow
ISO 12151-3 – E-S – SFS 90°
(42.0 MPa/ 6000 psi)

ORFS

Page De-14 – De-15

JC
De-14

Female ORFS
Swivel – Straight
Short
ISO 12151-1 – SWSA
SAE J516 – ORFS

J7
De-14


Female ORFS – Swivel
45° Elbow
ISO 12151-1 – SWE 45°
SAE J516 – ORFS 45°


J9
De-15

Female ORFS – Swivel
90° Elbow – Short Drop
ISO 12151-1 – SWES
SAE J516 – ORFS 90°


French Standard

Page De-16

FG
De-16

Male French Gas Series
Rigid – Straight (24° Cone)

F4
De-16

Female French Gas Series
Swivel – Straight
(Ball Nose)

VS Interlock Outside Skive



Only for use with adjustable crimpers.

Part Number	Hose I.D.				B
	DN	Inch	Size	mm	mm
100VS-4	6	1/4	-4	6.4	38
100VS-6	10	3/8	-6	9.5	36
100VS-8	12	1/2	-8	12.7	41


Approved **fitting series** for **hose types**:


VS | -4 to -8 | H31 | H31TC | H31ST |

CA

Female Metric 24° Light Series with O-Ring Swivel – Straight

ISO 12151-2-SWS-L – DKOL






Part Number	Hose I.D.				Thread	Tube O.D.	A	B	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
KCAVS-10-6	10	3/8	-6	9.5	M16x1.5	10	64	25	19
KCAVS-12-6	10	3/8	-6	9.5	M18x1.5	12	61	23	22
KCAVS-15-8	12	1/2	-8	12.7	M22x1.5	15	70	27	27


Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

CE

Female Metric 24° Light Series with O-Ring Swivel – 45° Elbow

ISO 12151-2-SWE 45°-L – DKOL 45°





Part Number	Hose I.D.				Thread	Tube O.D.	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
KCEVS-12-6	10	3/8	-6	9.5	M18x1.5	12	93	55	19	22
KCEVS-15-8	12	1/2	-8	12.7	M22x1.5	15	103	61	23	27

Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.


Approved **fitting series** for **hose types**:


VS | -4 to -8 | H31 | H31TC | H31ST |

CF

Female Metric 24° Light Series with O-Ring Swivel – 90° Elbow

ISO 12151-2-SWE-L – DKOL 90°






Part Number	Hose I.D.				Thread	Tube O.D.	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
KCFVS-12-6	10	3/8	-6	9.5	M18x1.5	12	83	45	36	22
KCFVS-15-8	12	1/2	-8	12.7	M22x1.5	15	92	50	44	27


Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

D0

Male Metric 24° Light Series – Rigid Straight

ISO 12151-2-S-L – CEL






Part Number	Hose I.D.				Thread	Tube O.D.	A	B	H
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
KD0VS-12-6	10	3/8	-6	9.5	M18x1.5	12	64	25	19
KD0VS-15-8	12	1/2	-8	12.7	M22x1.5	15	71	28	22


Approved **fitting series** for **hose types**:

VS | -4 to -8 | H31 | H31TC | H31ST |

C9 Female Metric 24° – Swivel Heavy Series with O-Ring Straight

ISO 12151-2-SWS-S – DKOS







Part Number	Hose I.D.				Thread	Tube O.D.	A	B	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
KC9VS-8-4	6	1/4	-4	6.4	M16x1.5	8	61	23	19
KC9VS-10-4	6	1/4	-4	6.4	M18x1.5	10	62	24	22
KC9VS-8-6	10	3/8	-6	9.5	M16x1.5	8	64	25	19
KC9VS-12-6	10	3/8	-6	9.5	M20x1.5	12	63	25	24
KC9VS-14-6	10	3/8	-6	9.5	M22x1.5	14	63	24	27
KC9VS-16-8	12	1/2	-8	12.7	M24x1.5	16	71	29	30
KC9VS-20-8	12	1/2	-8	12.7	M30x2	20	71	29	36

Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

0C Female Metric 24° – Swivel Heavy Series with O-Ring 45° Elbow

ISO 12151-2 – SWE 45°-S – DKOS 45°





Part Number	Hose I.D.				Thread	Tube O.D.	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
K0CVS-8-4	6	1/4	-4	6.4	M16x1.5	8	88	50	16	19
K0CVS-10-4	6	1/4	-4	6.4	M18x1.5	10	88	50	16	22
K0CVS-12-6	10	3/8	-6	9.5	M20x1.5	12	94	56	20	24
K0CVS-14-6	10	3/8	-6	9.5	M22x1.5	14	94	56	20	27
K0CVS-16-8	12	1/2	-8	12.7	M24x1.5	16	105	62	24	30


Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.


Approved **fitting series** for **hose types**:

VS | -4 to -8 | H31 | H31TC | H31ST |

1C Female Metric 24° – Swivel Heavy Series with O-Ring 90° Elbow

ISO 12151-2-SWE-S – DKOS 90°







Part Number	Hose I.D.				Thread	Tube O.D.	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
K1CVS-8-4	6	1/4	-4	6.4	M16x1.5	8	79	41	29	19
K1CVS-10-4	6	1/4	-4	6.4	M18x1.5	10	79	41	29	22
K1CVS-12-6	10	3/8	-6	9.5	M20x1.5	12	83	45	37	24
K1CVS-14-6	10	3/8	-6	9.5	M22x1.5	12	83	45	37	27
K1CVS-16-8	12	1/2	-8	12.7	M24x1.5	16	93	51	45	30

Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

D2 Male Metric 24° – Rigid Heavy Series – Straight

ISO 12151-2-S-S – CES






Part Number	Hose I.D.				Thread	Tube O.D.	A	B	H
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
KD2VS-12-6	10	3/8	-6	9.5	M20x1.5	12	66	27	22
KD2VS-14-6	10	3/8	-6	9.5	M22x1.5	14	68	30	22
KD2VS-16-8	12	1/2	-8	12.7	M24x1.5	16	74	31	24


Approved **fitting series** for **hose types**:

VS | -4 to -8 | H31 | H31TC | H31ST |

92 Female BSP Parallel Pipe Swivel – Straight (60° Cone)

BS5200-A – DKR







Part Number	Hose I.D.				Thread	A	B	W
	DN	Inch	Size	mm	BSP	mm	mm	mm
K92VS-6-6	10	3/8	-6	9.5	3/8x19	60	22	22
K92VS-8-6	10	3/8	-6	9.5	1/2x14	62	23	27
K92VS-8-8	12	1/2	-8	12.7	1/2x14	67	24	27
K92VS-10-8	12	1/2	-8	12.7	5/8x14	65	23	30

B1 Female BSP Parallel Pipe Swivel 45° Elbow (60° Cone)

BS 5200-D – DKR 45°






Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	BSP	mm	mm	mm	mm
KB1VS-6-6	10	3/8	-6	9.5	3/8x19	90	52	17	22
KB1VS-8-6	10	3/8	-6	9.5	1/2x14	91	53	17	27
KB1VS-8-8	12	1/2	-8	12.7	1/2x14	100	58	20	27
KB1VS-10-8	12	1/2	-8	12.7	5/8x14	99	57	19	30


Approved **fitting series** for **hose types**:

VS | -4 to -8 | H31 | H31TC | H31ST |

B2 Female BSP Parallel Pipe Swivel 90° Elbow (60° Cone)

BS 5200-B – DKR 90°







Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	BSP	mm	mm	mm	mm
KB2VS-6-6	10	3/8	-6	9.5	3/8x19	82	44	33	22
KB2VS-8-6	10	3/8	-6	9.5	1/2x14	83	45	36	27
KB2VS-8-8	12	1/2	-8	12.7	1/2x14	92	50	40	27
KB2VS-10-8	12	1/2	-8	12.7	5/8x14	92	50	38	30

D9 Male BSP Parallel Pipe Rigid – Straight (60° Cone)

BS5200 – AGR






Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	BSP	mm	mm	mm
KD9VS-4-4	6	1/4	-4	6.4	1/4x19	67	28	19
KD9VS-6-6	10	3/8	-6	9.5	3/8x19	71	33	22
KD9VS-8-8	12	1/2	-8	12.7	1/2x14	78	36	27


Approved **fitting series** for **hose types**:

VS | -4 to -8 | H31 | H31TC | H31ST |

01 Male NPTF Pipe Rigid – Straight

SAE J476A / J516 – AGN







Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	NPTF	mm	mm	mm
K01VS-6-6	10	3/8	-6	9.5	3/8x18	71	33	19
K01VS-8-8	12	1/2	-8	12.7	1/2x14	83	40	22

03 Male JIC 37° – Rigid Straight

ISO12151-5-S – AGJ






Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	UNF	mm	mm	mm
K03VS-6-6	10	3/8	-6	9.5	9/16x18	71	32	19
K03VS-8-6	10	3/8	-6	9.5	3/4x16	69	31	22
K03VS-8-8	12	1/2	-8	12.7	3/4x16	79	36	22
K03VS-10-8	12	1/2	-8	12.7	7/8x14	77	35	24


Approved **fitting series** for **hose types**:

VS | -4 to -8 | H31 | H31TC | H31ST |

06/68 Female – JIC 37° SAE 45° Dual Flare Swivel – Straight

ISO12151-5-SWS – DKJ







Part Number	Hose I.D.				Thread	A	B	H	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
K68VS-4-4	6	1/4	-4	6.4	7/16 20	66	28	14	17
K06VS-6-6	10	3/8	-6	9.5	9/16x18	69	31	17	19
K68VS-8-6	10	3/8	-6	9.5	3/4x16	74	35	17	22
K06VS-12-6	10	3/8	-6	9.5	1 1/16x12	78	40	27	32
K68VS-8-8	12	1/2	-8	12.7	3/4x16	77	35	22	22
K68VS-10-8	12	1/2	-8	12.7	7/8x14	83	41	22	27
K06VS-12-8	12	1/2	-8	12.7	1 1/16x12	83	41	27	32

37/3V Female JIC 37° SAE 45° – Dual Flare Swivel Female 45° Elbow

ISO 12151-5-SWE 45° – DKJ 45°






Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
K37VS-6-6	10	3/8	-6	9.5	9/16x18	83	45	11	19
K3VVS-8-6	10	3/8	-6	9.5	3/4x16	87	49	15	22
K3VVS-8-8	12	1/2	-8	12.7	3/4x16	93	51	15	22
K3VVS-10-8	12	1/2	-8	12.7	7/8x14	94	52	16	27
K37VS-12-8	12	1/2	-8	12.7	1 1/16x12	99	57	21	32


Approved **fitting series** for **hose types**:

VS | -4 to -8 | H31 | H31TC | H31ST |

39/3W Female JIC 37° SAE 45° – Dual Flare Swivel Female 90° Elbow

ISO 12151-5-SWES – DKJ 90°






Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
K39VS-6-6	10	3/8	-6	9.5	9/16x18	80	42	23	19
K3WVS-8-6	10	3/8	-6	9.5	3/4x16	80	42	29	22
K3WVS-8-8	12	1/2	-8	12.7	3/4x16	87	45	29	22
K3WVS-10-8	12	1/2	-8	12.7	7/8x14	87	45	32	27


Approved **fitting series** for **hose types**:

VS | -4 to -8 | H31 | H31TC | H31ST |

15 ISO 6162-1 Flange Straight

ISO 12151-3-S-L – SFL
(21.0 MPa/ 3000 psi)







Part Number	Hose I.D.				Flange	A	B	F
	DN	Inch	Size	mm	Inch	mm	mm	mm
K15VS-8-8	12	1/2	-8	12.7	1/2	102	59	30
K15VS-12-8	12	1/2	-8	12.7	3/4	77	34	38

SAE flange halves see in section Eb.

17 ISO 6162-1 Flange 45° Elbow

ISO 12151-3 – E45 – L – SFL 45°
(21.0 MPa/ 3000 psi)





Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
K17VS-8-8	12	1/2	-8	12.7	1/2	100	57	20	30
K17VS-12-8	12	1/2	-8	12.7	3/4	101	58	21	38


SAE flange halves see in section Eb.


Approved **fitting series** for **hose types**:

VS | -4 to -8 | H31 | H31TC | H31ST |

19 ISO 6162-1 Flange 90° Elbow

ISO 12151-3 – E– L – SFL 90°
(21.0 MPa/ 3000 psi)







Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
K19VS-8-8	12	1/2	-8	12.7	1/2	92	50	41	30
K19VS-12-8	12	1/2	-8	12.7	3/4	92	50	42	38

SAE flange halves see in section Eb.

6A ISO 6162-2 Flange Straight

ISO 12151-3-S-S – SFS
(42.0 MPa/ 6000 psi)





Part Number	Hose I.D.				Flange	A	B	F
	DN	Inch	Size	mm	Inch	mm	mm	mm
K6AVS-8-8	12	1/2	-8	12.7	1/2	105	63	32
K6AVS-12-8	12	1/2	-8	12.7	3/4	79	36	41


SAE flange halves see in section Eb.


Approved **fitting series** for **hose types**:

VS | -4 to -8 | H31 | H31TC | H31ST |

6F ISO 6162-2 Flange 45° Elbow – Heavy Series

ISO 12151-3 – E45-S – SFS 45°
(42.0 MPa/ 6000 psi)







Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
K6FVS-8-8	12	1/2	-8	12.7	1/2	94	52	19	32
K6FVS-12-8	12	1/2	-8	12.7	3/4	106	64	26	41

SAE flange halves see in section Eb.

6N ISO 6162-2 Flange 90° Elbow

ISO 12151-3 – E-S – SFS 90°
(42.0 MPa/ 6000 psi)





Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
K6NVS-8-8	12	1/2	-8	12.7	1/2	87	45	41	32
K6NVS-12-8	12	1/2	-8	12.7	3/4	92	50	45	41

SAE flange halves see in section Eb.


Approved **fitting series** for **hose types**:


VS | -4 to -8 | H31 | H31TC | H31ST |

JC

Female ORFS Swivel – Straight Short

ISO 12151-1 – SWSA
SAE J516 – ORFS







Part Number	Hose I.D.				Thread	A	B	H	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
KJCVS-6-6	10	3/8	-6	9.5	11/16x16	60	22	17	22
KJCVS-8-6	10	3/8	-6	9.5	13/16x16	62	23	19	24
KJCVS-8-8	12	1/2	-8	12.7	13/16x16	67	24	22	24
KJCVS-10-8	12	1/2	-8	12.7	1x14	69	26	24	30

J7

Female ORFS – Swivel 45° Elbow

ISO 12151-1 – SWE 45°
SAE J516 – ORFS 45°






Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
KJ7VS-6-6	10	3/8	-6	9.5	11/16x16	83	45	11	22
KJ7VS-8-6	10	3/8	-6	9.5	13/16x16	89	51	15	24
KJ7VS-8-8	12	1/2	-8	12.7	13/16x16	93	51	15	24
KJ7VS-10-8	12	1/2	-8	12.7	1x14	96	53	16	30


Approved **fitting series** for **hose types**:

VS | -4 to -8 | H31 | H31TC | H31ST |

J9 Female ORFS – Swivel 90° Elbow – Short Drop

ISO 12151-1 – SWES
SAE J516 – ORFS 90°







Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
KJ9VS-6-6	10	3/8	-6	9.5	11/16x16	80	42	23	22
KJ9VS-8-6	10	3/8	-6	9.5	13/16x16	83	45	29	24
KJ9VS-8-8	12	1/2	-8	12.7	13/16x16	87	45	29	24
KJ9VS-10-8	12	1/2	-8	12.7	1x14	88	46	30	30

Approved **fitting series** for **hose types**:

VS | -4 to -8 | H31 | H31TC | H31ST |


FG Male French Gas Series Rigid – Straight (24° Cone)






Part Number	Hose I.D.				Thread	Tube O.D.	A	B	H
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
KFGVS-13-6	10	3/8	-6	9.5	M20x1.5	13.25	69	31	22
KFGVS-17-8	12	1/2	-8	12.7	M24x1.5	16.75	72	30	24

F4 Female French Gas Series Swivel – Straight (Ball Nose)






Part Number	Hose I.D.				Thread	Tube O.D.	A	B	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
KF4VS-13-6	10	3/8	-6	9.5	M20x1.5	13.25	62	24	24
KF4VS-17-8	12	1/2	-8	12.7	M24x1.5	16.75	70	27	30


Approved **fitting series** for **hose types**:

VS | -4 to -8 | H31 | H31TC | H31ST |

Shell


Page Df-1


V4
Df-1

Interlock
In-/Outside Skive
4 Wire Hoses


V6
Df-1

Interlock
In-/Outside Skive
6 Wire Hoses


DIN – Metric

Page Df-2 – Df-5

CA
Df-2

Female Metric 24°
Light Series with O–Ring
Swivel – Straight
ISO 12151-2-SWS-L – DKOL

CE
Df-2

Female Metric 24°
Light Series with O–Ring
Swivel – 45° Elbow
ISO 12151-2-SWE 45°-L – DKOL 45°

CF
Df-3

Female Metric 24°
Light Series with O–Ring
Swivel – 90° Elbow
ISO 12151-2-SWE-L – DKOL 90°

C9
Df-3

Female Metric 24° – Swivel
Heavy Series with O-Ring
Straight
ISO 12151-2-SWS-S – DKOS

0C
Df-4

Female Metric 24° – Swivel
Heavy Series with O–Ring
45° Elbow
ISO 12151-2 – SWE 45°-S – DKOS 45°

1C
Df-4


Female Metric 24° – Swivel
Heavy Series with O–Ring
90° Elbow
ISO 12151-2-SWE-S – DKOS 90°

D2
Df-5

Male Metric 24° – Rigid
Heavy Series – Straight
ISO 12151-2-S-S – CES

BSP

Page Df-6 – Df-8

92
Df-6

Female BSP Parallel Pipe
Swivel – Straight (60° Cone)
BS5200-A – DKR

B1
Df-6


Female BSP Parallel Pipe
Swivel
45° Elbow (60° Cone)
BS 5200-D – DKR 45°

B2
Df-7

Female BSP Parallel Pipe
Swivel
90° Elbow (60° Cone)
BS 5200-B – DKR 90°


D9
Df-7


Male BSP Parallel Pipe
Rigid – Straight (60° Cone)
BS5200 – AGR


91
Df-8

Male BSP Taper Pipe – Rigid
Straight
BS5200 – AGR-K


SAE

Page Df-9 – Df-11

01
Df-9

Male NPTF Pipe
Rigid – Straight
SAE J476A / J516 – AGN

03
Df-9

Male JIC 37° – Rigid
Straight
ISO12151-5-S – AGJ

06
Df-10

Female JIC 37° – Swivel
Straight
ISO12151-5-SWS – DKJ


37
Df-10

Female JIC 37° – Swivel
45° Elbow
ISO 12151-5-SWE 45° – DKJ 45°


39
Df-11


Female JIC 37° – Swivel
90° Elbow
ISO 12151-5-SWES – DKJ 90°


Flange


Page Df-12 – Df-22

15/4A
Df-12

ISO 6162-1 Flange
Straight
ISO 12151-3-S-L – SFL
(35.0 MPa/ 5000 psi)

17/4F
Df-13

ISO 6162-1 Flange
45° Elbow
ISO 12151-3 – E45S – L – SFL 45°
(35.0 MPa/ 5000 psi)


19/4N
Df-14

ISO 6162-1 Flange
90° Elbow
ISO 12151-3-E-L – SFL 90°
(35.0 MPa/ 5000 psi)


6A
Df-15

ISO 6162-2 Flange
Straight
ISO 12151-3-S-S – SFS
(42.0 MPa/ 6000 psi)

6F
Df-16

ISO 6162-2 Flange
45° Elbow – Heavy Series
ISO 12151-3 – E45-S – SFS 45°
(42.0 MPa/ 6000 psi)

6N
Df-17


ISO 6162-2 Flange
90° Elbow
ISO 12151-3 – E-S – SFS 90°
(42.0 MPa/ 6000 psi)


8A
Df-18

Flange – Straight
8000 psi


8F
Df-18

Flange – 45° Elbow
8000 psi


8N
Df-19


Flange – 90° Elbow
8000 psi


X5
Df-19

Flange – Straight
Full flange system for
ISO 6162-1 or ISO 6162-2


X7
Df-20

Flange – 45° Elbow
Full flange system for
ISO 6162-1 or ISO 6162-2


X9
Df-20

Flange – 90° Elbow
Full flange system for
ISO 6162-1 or ISO 6162-2

PY
Df-21

Flange – 24° Male
French Gas
Straight

XA
Df-21

Caterpillar® Flange
Straight


XF
Df-22

Caterpillar® Flange
45° Elbow


XG
Df-22

Caterpillar® Flange
60° Elbow

XN
Df-23

Caterpillar® Flange
90° Elbow

ORFS

Page Df-23 – Df-25

JC
Df-24

Female ORFS
Swivel – Straight
Short
ISO 12151-1 – SWSA


JS
Df-24

ORFS Swivel Female (Long)
ISO 12151-1-SWSB
SAE J516 – ORFS

J7
Df-25

Female ORFS – Swivel
45° Elbow
ISO 12151-1 – SWE 45°
SAE J516 – ORFS 45°


J9
Df-25

Female ORFS – Swivel
90° Elbow – Short Drop
ISO 12151-1 – SWES
SAE J516 – ORFS 90°

JM
Df-26

ORFS Male
ISO 12151-1-S – SAE J516

French Standard

Page Df-26


FG
Df-27

Male French Gas Series
Rigid – Straight (24° Cone)

F4
Df-27

Female French Gas Series
Swivel – Straight
(Ball Nose)

V4 Interlock In-/Outside Skive

4 Wire Hoses




Only for use with adjustable crimpers. Minimum of 320 tons crimping force recommended.

Part Number	Hose I.D.				B
	DN	Inch	Size	mm	mm
100V4-10	16	5/8	-10	15.9	49
100V4-12	19	3/4	-12	19.1	60
100V4-16	25	1	-16	25.4	75
100V4-20	31	1 1/4	-20	31.8	88
100V4-24	38	1 1/2	-24	38.1	94
100V4-32	51	2	-32	50.8	99

V6 Interlock In-/Outside Skive

6 Wire Hoses




Only for use with adjustable crimpers. Minimum of 340 tons crimping force required.


Part Number	Hose I.D.				B
	DN	Inch	Size	mm	mm
100V6-20	31	1 1/4	-20	31.8	90
100V6-24	38	1 1/2	-24	38.1	96
100V6-32	51	2	-32	50.8	110
100V6-40	63	2 1/2	-40	63.5	134
100V6-48	76	3	-48	76.2	110

CA

Female Metric 24° Light Series with O-Ring Swivel – Straight

ISO 12151-2-SWS-L – DKOL






Part Number	Hose I.D.				Thread	Tube O.D.	A	B	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
KCAV4-22-12	19	3/4	-12	19.1	M30x2	22	89	28	36
KCAV4-28-16	25	1	-16	25.4	M36x2	28	103	31	41
KCAV6-35-20	31	1 1/4	-20	31.8	M45x2	35	130	39	50
KCAV4-35-20	31	1 1/4	-20	31.8	M45x2	35	120	32	50
KCAV4-42-24	38	1 1/2	-24	38.1	M52x2	42	128	35	60
KCAV6-42-24	38	1 1/2	-24	38.1	M52x2	42	138	42	60


Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

CE

Female Metric 24° Light Series with O-Ring Swivel – 45° Elbow

ISO 12151-2-SWE 45°-L – DKOL 45°





Part Number	Hose I.D.				Thread	Tube O.D.	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
KCEV4-22-12	19	3/4	-12	19.1	M30x2	22	137	75	29	36
KCEV4-35-20	31	1 1/4	-20	31.8	M45x2	35	197	109	37	50
KCEV6-35-20	31	1 1/4	-20	31.8	M45x2	35	188	97	37	50
KCEV6-42-24	38	1 1/2	-24	38.1	M52x2	42	226	130	49	60

Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK


V4 | -10 up to -16 | H31 | H31TC | H31ST | R42 | R42TC | R42ST | -12 up to -20 | R35 | R35TC | H29 | all sizes | H29TC | H29ST | H29RH |


V6 | -24 up to -48 | R35 | R35TC | RS35TC-48 | -20 up to -32 | R42 | R42ST | R42TC |

CF

Female Metric 24° Light Series with O-Ring Swivel – 90° Elbow

ISO 12151-2-SWE-L – DKOL 90°






Part Number	Hose I.D.				Thread	Tube O.D.	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
KCFV4-22-16	25	1	-16	25.4	M30x2	22	150	77	70	36
KCFV4-35-20	31	1 1/4	-20	31.8	M45x2	35	186	98	79	50
KCFV6-35-20	31	1 1/4	-20	31.8	M45x2	35	177	86	79	50
KCFV6-42-24	38	1 1/2	-24	38.1	M52x2	42	209	113	101	60


Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

C9

Female Metric 24° – Swivel Heavy Series with O-Ring Straight

ISO 12151-2-SWS-S – DKOS





Part Number	Hose I.D.				Thread	Tube O.D.	A	B	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
KC9V4-20-10	16	5/8	-10	15.9	M30x2	20	87	27	36
KC9V4-20-12	19	3/4	-12	19.1	M30x2	20	88	26	36
KC9V4-25-12	19	3/4	-12	19.1	M36x2	25	91	30.3	46
KC9V4-30-12	19	3/4	-12	19.1	M42x2	30	95	33	50
KC9V4-25-16	25	1	-16	25.4	M36x2	25	103	30	46
KC9V4-30-16	25	1	-16	25.4	M42x2	30	108	35	50
KC9V4-38-16	25	1	-16	25.4	M52x2	38	110	37	60
KC9V6-30-20	31	1 1/4	-20	31.8	M42x2	30	131.5	41.5	50
KC9V4-30-20	31	1 1/4	-20	31.8	M42x2	30	123	35	50
KC9V6-38-20	31	1 1/4	-20	31.8	M52x2	38	135	44	60
KC9V4-38-20	31	1 1/4	-20	31.8	M52x2	38	126	38	60
KC9V6-38-24	38	1 1/2	-24	38.1	M52x2	38	139	43	60
KC9V4-38-24	38	1 1/2	-24	38.1	M52x2	38	129	36	60
KC9V6-54-32	51	2	-32	50.8	M68x2	54	175	65	80

Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK


V4 | -10 up to -16 | H31 | H31TC | H31ST | R42 | R42TC | R42ST | -12 up to -20 | R35 | R35TC | H29 | all sizes | H29TC | H29ST | H29RH |

V6 | -24 up to -48 | R35 | R35TC | RS35TC-48 | -20 up to -32 | R42 | R42ST | R42TC |

0C Female Metric 24° – Swivel Heavy Series with O-Ring 45° Elbow

ISO 12151-2 – SWE 45°-S – DKOS 45°







Part Number	Hose I.D.				Thread	Tube O.D.	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
K0CV4-20-10	16	5/8	-10	15.9	M30x2	20	124	65	26	36
K0CV4-20-12	19	3/4	-12	19.1	M30x2	20	138	76	30	36
K0CV4-25-12	19	3/4	-12	19.1	M36x2	25	137	76	29	46
K0CV4-25-16	25	1	-16	25.4	M36x2	25	161	88	33	46
K0CV4-30-16	25	1	-16	25.4	M42x2	30	162	88.7	33	50
K0CV6-30-20	31	1 1/4	-20	31.8	M42x2	30	184	93	34	50
K0CV4-30-20	31	1 1/4	-20	31.8	M42x2	30	193	105	34	50
K0CV4-38-20	31	1 1/4	-20	31.8	M52x2	38	197	108.7	37	60
K0CV6-38-20	31	1 1/4	-20	31.8	M52x2	38	187	96.3	37	60
K0CV6-38-24	38	1 1/2	-24	38.1	M52x2	38	226	130	49	60
K0CV4-38-24	38	1 1/2	-24	38.1	M52x2	38	227	133	49	60

Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

1C Female Metric 24° – Swivel Heavy Series with O-Ring 90° Elbow

ISO 12151-2-SWE-S – DKOS 90°





Part Number	Hose I.D.				Thread	Tube O.D.	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
K1CV4-20-10	16	5/8	-10	15.9	M30x2	20	112	52.3	50	36
K1CV4-20-12	19	3/4	-12	19.1	M30x2	20	125	63	60	36
K1CV4-25-12	19	3/4	-12	19.1	M36x2	25	126	65	59	46
K1CV4-25-16	25	1	-16	25.4	M36x2	25	150	77	69	46
K1CV4-30-16	25	1	-16	25.4	M42x2	30	151	77.7	69	50
K1CV4-38-16	25	1	-16	25.4	M52x2	38	150	77	68	60
K1CV4-30-20	31	1 1/4	-20	31.8	M42x2	30	183	95	73	50
K1CV6-30-20	31	1 1/4	-20	31.8	M42x2	30	169	78	69	50
K1CV4-38-20	31	1 1/4	-20	31.8	M52x2	38	187	98.7	78	60
K1CV6-38-20	31	1 1/4	-20	31.8	M52x2	38	177	86.3	78	60
K1CV4-38-24	38	1 1/2	-24	38.1	M52x2	38	210	117	101	60
K1CV6-38-24	38	1 1/2	-24	38.1	M52x2	38	209	113	101	60

Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK


V4 | -10 up to -16 | H31 | H31TC | H31ST | R42 | R42TC | R42ST | -12 up to -20 | R35 | R35TC | H29 | all sizes | H29TC | H29ST | H29RH |

V6 | -24 up to -48 | R35 | R35TC | RS35TC-48 | -20 up to -32 | R42 | R42ST | R42TC |

D2 Male Metric 24° – Rigid Heavy Series – Straight

ISO 12151-2-S-S – CES





Part Number	Hose I.D.				Thread	Tube O.D.	A	B	H
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
KD2V4-20-12	19	3/4	-12	19.1	M30x2	20	93	31	30
KD2V4-25-12	19	3/4	-12	19.1	M36x2	25	98	36.3	36
KD2V4-25-16	25	1	-16	25.4	M36x2	25	110.3	37.7	46
KD2V4-30-16	25	1	-16	25.4	M42x2	30	115	41.7	46
KD2V6-30-20	31	1 1/4	-20	31.8	M42x2	30	140	59	46
KD2V6-38-20	31	1 1/4	-20	31.8	M52x2	38	142	51	55
KD2V4-38-20	31	1 1/4	-20	31.8	M52x2	38	135	46.7	55
KD2V6-38-24	38	1 1/2	-24	38.1	M52x2	38	151	55	55
KD2V4-38-24	38	1 1/2	-24	38.1	M52x2	38	139	46	55

Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK


V4 | -10 up to -16 | H31 | H31TC | H31ST | R42 | R42TC | R42ST | -12 up to -20 | R35 | R35TC | H29 | all sizes | H29TC | H29ST | H29RH |

V6 | -24 up to -48 | R35 | R35TC | RS35TC-48 | -20 up to -32 | R42 | R42ST | R42TC |

92 Female BSP Parallel Pipe Swivel – Straight (60° Cone)

BS5200-A – DKR







Part Number	Hose I.D.				Thread	A	B	W
	DN	Inch	Size	mm	BSP	mm	mm	mm
K92V4-10-10	16	5/8	-10	15.9	5/8x14	80	20.3	30
K92V4-12-12	19	3/4	-12	19.1	3/4x14	85	23.3	32
K92V4-16-12	19	3/4	-12	19.1	1x11	93	31.3	41
K92V4-16-16	25	1	-16	25.4	1x11	105	32	41
K92V6-20-20	31	1 1/4	-20	31.8	1 1/4x11	127	36	50
K92V4-20-20	31	1 1/4	-20	31.8	1 1/4x11	118	30	50
K92V6-24-24	38	1 1/2	-24	38.1	1 1/2x11	134	38	55
K92V4-24-24	38	1 1/2	-24	38.1	1 1/2x11	124	30.9	55
K92V6-32-32	51	2	-32	50.8	2x11	151	41	70
K92V4-32-32	51	2	-32	50.8	2x11	131	34.2	70

B1 Female BSP Parallel Pipe Swivel 45° Elbow (60° Cone)

BS 5200-D – DKR 45°





Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	BSP	mm	mm	mm	mm
KB1V4-12-12	19	3/4	-12	19.1	3/4x14	134	72.3	26	32
KB1V4-16-16	25	1	-16	25.4	1x11	164	91	36	41
KB1V6-20-20	31	1 1/4	-20	31.8	1 1/4x11	194	103	43	50
KB1V4-20-20	31	1 1/4	-20	31.8	1 1/4x11	198	109.7	38	50
KB1V6-24-24	38	1 1/2	-24	38.1	1 1/2x11	229	133	52	55
KB1V4-24-24	38	1 1/2	-24	38.1	1 1/2x11	230	137	52	55
KB1V6-32-32	51	2	-32	50.8	2x11	288	178	70	70
KB1V4-32-32	51	2	-32	50.8	2x11	277	180	70	70

Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK


V4 | -10 up to -16 | H31 | H31TC | H31ST | R42 | R42TC | R42ST | -12 up to -20 | R35 | R35TC | H29 | all sizes | H29TC | H29ST | H29RH |

V6 | -24 up to -48 | R35 | R35TC | RS35TC-48 | -20 up to -32 | R42 | R42ST | R42TC |

B2 Female BSP Parallel Pipe Swivel 90° Elbow (60° Cone)

BS 5200-B – DKR 90°







Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	BSP	mm	mm	mm	mm
KB2V4-12-12	19	3/4	-12	19.1	3/4x14	125	63.3	55	32
KB2V4-16-16	25	1	-16	25.4	1x11	150	77	74	41
KB2V6-20-20	31	1 1/4	-20	31.8	1 1/4x11	177	86	80	50
KB2V4-20-20	31	1 1/4	-20	31.8	1 1/4x11	186	98.7	80	50
KB2V6-24-24	38	1 1/2	-24	38.1	1 1/2x11	209	113	103	55
KB2V4-24-24	38	1 1/2	-24	38.1	1 1/2x11	210	116.9	103	55
KB2V6-32-32	51	2	-32	50.8	2x11	268	157	149	70
KB2V4-32-32	51	2	-32	50.8	2x11	257	160	149	70

D9 Male BSP Parallel Pipe Rigid – Straight (60° Cone)

BS5200 – AGR





Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	BSP	mm	mm	mm
KD9V4-10-10	16	5/8	-10	15.9	5/8x14	94	35	30
KD9V4-12-12	19	3/4	-12	19.1	3/4x14	99	37.3	32
KD9V4-16-16	25	1	-16	25.4	1x11	115	42.7	41
KD9V6-20-20	31	1 1/4	-20	31.8	1 1/4x11	139	48	50
KD9V4-20-20	31	1 1/4	-20	31.8	1 1/4x11	134	46.2	50
KD9V6-24-24	38	1 1/2	-24	38.1	1 1/2x11	155	58	55
KD9V4-24-24	38	1 1/2	-24	38.1	1 1/2x11	142	48.4	55
KD9V6-32-32	51	2	-32	50.8	2x11	168	58	70
KD9V4-32-32	51	2	-32	50.8	2x11	148	50	70

Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK


V4 | -10 up to -16 | H31 | H31TC | H31ST | R42 | R42TC | R42ST | -12 up to -20 | R35 | R35TC | H29 | all sizes | H29TC | H29ST | H29RH |

V6 | -24 up to -48 | R35 | R35TC | RS35TC-48 | -20 up to -32 | R42 | R42ST | R42TC |

91 Male BSP Taper Pipe – Rigid Straight

BS5200 – AGR-K





Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	BSP	mm	mm	mm
K91V4-12-12	19	3/4	-12	19.1	3/4x14	99	37	30
K91V4-16-16	25	1	-16	25.4	1x11	113	40	36
K91V4-20-20	31	1 1/4	-20	31.8	1 1/4x11	138	50	46
K91V4-24-24	38	1 1/2	-24	38.1	1 1/2x11	144	59	55
K91V4-32-32	51	2	-32	50.8	2x11	154	56	65

Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK


V4 | -10 up to -16 | H31 | H31TC | H31ST | R42 | R42TC | R42ST | -12 up to -20 | R35 | R35TC | H29 | all sizes | H29TC | H29ST | H29RH |

V6 | -24 up to -48 | R35 | R35TC | RS35TC-48 | -20 up to -32 | R42 | R42ST | R42TC |

01 Male NPTF Pipe Rigid – Straight

SAE J476A / J516 – AGN






Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	NPTF	mm	mm	mm
K01V4-12-12	19	3/4	-12	19.1	3/4x14	100	38.3	30
K01V4-16-16	25	1	-16	25.4	1x11 1/2	116.5	43.9	36
K01V6-20-20	31	1 1/4	-20	31.8	1 1/4x11 1/2	151	60.2	46
K01V4-20-20	31	1 1/4	-20	31.8	1 1/4x11 1/2	146	58.2	46
K01V4-24-24	38	1 1/2	-24	38.1	1 1/2x11 1/2	148.4	55.3	50
K01V6-24-24	38	1 1/2	-24	38.1	1 1/2x11 1/2	159	62.7	50
K01V6-32-32	51	2	-32	50.8	2x11 1/2	181	70	65
K01V4-32-32	51	2	-32	50.8	2x11 1/2	159.8	62.3	65
K01V6-48-40	63	2 1/2	-40	63.5	3 8	213	77	95
K01V6-48-48	76	3	-48	76.2	3 8	180	73	95

03 Male JIC 37° – Rigid Straight

ISO12151-5-S – AGJ





Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	UNF	mm	mm	mm
K03V4-12-12	19	3/4	-12	19.1	1 1/16x12	101	39.3	30
K03V4-16-12	19	3/4	-12	19.1	1 5/16x12	103	41.3	36
K03V4-16-16	25	1	-16	25.4	1 5/16x12	117	44.1	36
K03V4-20-16	25	1	-16	25.4	1 5/8x12	122	49.5	46
K03V6-20-20	31	1 1/4	-20	31.8	1 5/8x12	147	56	46
K03V4-20-20	31	1 1/4	-20	31.8	1 5/8x12	139	50.7	46
K03V4-24-20	31	1 1/4	-20	31.8	1 7/8x12	139	51	50
K03V6-24-24	38	1 1/2	-24	38.1	1 7/8x12	156	60	50
K03V4-24-24	38	1 1/2	-24	38.1	1 7/8x12	146	52.6	50
K03V6-32-32	51	2	-32	50.8	2 1/2x12	182	72	65
K03V4-32-32	51	2	-32	50.8	2 1/2x12	161	64	65

Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK


V4 | -10 up to -16 | H31 | H31TC | H31ST | R42 | R42TC | R42ST | -12 up to -20 | R35 | R35TC | H29 | all sizes | H29TC | H29ST | H29RH |

V6 | -24 up to -48 | R35 | R35TC | RS35TC-48 | -20 up to -32 | R42 | R42ST | R42TC |

06 Female JIC 37° – Swivel Straight

ISO12151-5-SWS – DKJ







Part Number	Hose I.D.				Thread	A	B	H	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
K06V4-12-12	19	3/4	-12	19.1	1 1/16x12	105	43	30	32
K06V4-16-12	19	3/4	-12	19.1	1 5/16x12	109	48	36	41
K06V4-16-16	25	1	-16	25.4	1 5/16x12	122	50	36	41
K06V4-20-16	25	1	-16	25.4	1 5/8x12	125	52	41	50
K06V4-20-20	31	1 1/4	-20	31.8	1 5/8x12	146	58	46	50
K06V6-20-20	31	1 1/4	-20	31.8	1 5/8x12	154	63	46	50
K06V6-24-20	31	1 1/4	-20	31.8	1 7/8x12	159	68	50	60
K06V4-24-20	31	1 1/4	-20	31.8	1 7/8x12	150	63	50	60
K06V6-24-24	38	1 1/2	-24	38.1	1 7/8x12	163	67	50	60
K06V4-24-24	38	1 1/2	-24	38.1	1 7/8x12	152	59	50	60
K06V4-32-32	51	2	-32	50.8	2 1/2x12	168	70	65	75
K06V6-32-32	51	2	-32	50.8	2 1/2x12	188	77	65	75

37 Female JIC 37° – Swivel 45° Elbow

ISO 12151-5-SWE 45° – DKJ 45°





Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
K37V4-12-12	19	3/4	-12	19.1	1 1/16x12	129	67	22	32
K37V4-16-16	25	1	-16	25.4	1 5/16x12	152	79.7	24	41
K37V6-20-20	31	1 1/4	-20	31.8	1 5/8x12	192	101	42	50
K37V4-20-20	31	1 1/4	-20	31.8	1 5/8x12	201	113	42	50
K37V6-24-24	38	1 1/2	-24	38.1	1 7/8x12	235	139	58	60
K37V4-24-24	38	1 1/2	-24	38.1	1 7/8x12	227	133.9	49	60
K37V6-32-32	51	2	-32	50.8	2 1/2x12	290	180	72	75
K37V4-32-32	51	2	-32	50.8	2 1/2x12	279	182	72	75

Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK


V4 | -10 up to -16 | H31 | H31TC | H31ST | R42 | R42TC | R42ST | -12 up to -20 | R35 | R35TC | H29 | all sizes | H29TC | H29ST | H29RH |

V6 | -24 up to -48 | R35 | R35TC | RS35TC-48 | -20 up to -32 | R42 | R42ST | R42TC |

39 Female JIC 37° – Swivel 90° Elbow

ISO 12151-5-SWES – DKJ 90°





Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
K39V4-12-12	19	3/4	-12	19.1	1 1/16x12	125	63.3	48	32
K39V4-16-12	19	3/4	-12	19.1	1 5/16x12	125	63.3	56	41
K39V4-16-16	25	1	-16	25.4	1 5/16x12	150	77.7	56	41
K39V4-20-16	25	1	-16	25.4	1 5/8x12	150	77	62	50
K39V4-20-20	31	1 1/4	-20	31.8	1 5/8x12	186	98	85	50
K39V6-20-20	31	1 1/4	-20	31.8	1 5/8x12	177	86	85	50
K39V4-24-20	31	1 1/4	-20	31.8	1 7/8x12	186	98	80	60
K39V6-24-24	38	1 1/2	-24	38.1	1 7/8x12	209	113	102	60
K39V4-24-24	38	1 1/2	-24	38.1	1 7/8x12	210	116.9	102	60
K39V6-32-32	51	2	-32	50.8	2 1/2x12	268	157	152	75
K39V4-32-32	51	2	-32	50.8	2 1/2x12	257	160	152	75

Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK


V4 | -10 up to -16 | H31 | H31TC | H31ST | R42 | R42TC | R42ST | -12 up to -20 | R35 | R35TC | H29 | all sizes | H29TC | H29ST | H29RH |

V6 | -24 up to -48 | R35 | R35TC | RS35TC-48 | -20 up to -32 | R42 | R42ST | R42TC |

15/4A ISO 6162-1 Flange Straight

ISO 12151-3-S-L – SFL
(35.0 MPa/ 5000 psi)





Part Number	Hose I.D.				Flange	A	B	F
	DN	Inch	Size	mm	Inch	mm	mm	mm
K15V4-12-12	19	3/4	-12	19.1	3/4	119	58	38
K15V4-16-12	19	3/4	-12	19.1	1	100	38.3	45
K15V4-12-16	25	1	-16	25.4	3/4	134.8	62.2	38
K15V4-16-16	25	1	-16	25.4	1	133	61	45
K4AV4-20-16	25	1	-16	25.4	1 1/4	101	28	51
K15V6-16-20	31	1 1/4	-20	31.8	1	161	70	44
K15V4-16-20	31	1 1/4	-20	31.8	1	152	64	45
K4AV6-20-20	31	1 1/4	-20	31.8	1 1/4	167	76	51
K4AV4-20-20	31	1 1/4	-20	31.8	1 1/4	160	72	51
K4AV4-24-20	31	1 1/4	-20	31.8	1 1/2	126	38.7	60
K4AV6-24-20	31	1 1/4	-20	31.8	1 1/2	165	74	60
K4AV4-20-24	38	1 1/2	-24	38.1	1 1/4	167	73	51
K4AV6-24-24	38	1 1/2	-24	38.1	1 1/2	201	105	60
K4AV4-24-24	38	1 1/2	-24	38.1	1 1/2	190	97	60
K4AV6-32-24	38	1 1/2	-24	38.1	2	159	63	71
K4AV4-32-24	38	1 1/2	-24	38.1	2	149	56	71
K4AV6-32-32	51	2	-32	50.8	2	210	100	71
K4AV4-32-32	51	2	-32	50.8	2	189	92	71

Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK


V4 | -10 up to -16 | H31 | H31TC | H31ST | R42 | R42TC | R42ST | -12 up to -20 | R35 | R35TC | H29 | all sizes | H29TC | H29ST | H29RH |

V6 | -24 up to -48 | R35 | R35TC | RS35TC-48 | -20 up to -32 | R42 | R42ST | R42TC |

17/4F ISO 6162-1 Flange 45° Elbow

ISO 12151-3 – E45S – L – SFL 45°
(35.0 MPa/ 5000 psi)





Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
K17V4-12-12	19	3/4	-12	19.1	3/4	133	72	26	38
K17V4-16-12	19	3/4	-12	19.1	1	133	72	26	45
K4FV4-20-12	19	3/4	-12	19.1	1 1/4	133	71	25	51
K17V4-16-16	25	1	-16	25.4	1	160	87	32	45
K4FV4-20-16	25	1	-16	25.4	1 1/4	160	87	32	51
K17V6-16-20	31	1 1/4	-20	31.8	1	188	97	38	44
K17V4-16-20	31	1 1/4	-20	31.8	1	198	109.7	38	45
K4FV6-20-20	31	1 1/4	-20	31.8	1 1/4	188	97	38	51
K4FV4-20-20	31	1 1/4	-20	31.8	1 1/4	198	109.7	38	51
K4FV6-24-20	31	1 1/4	-20	31.8	1 1/2	188	97	38	60
K4FV4-24-20	31	1 1/4	-20	31.8	1 1/2	198	109.7	38	60
K4FV6-20-24	38	1 1/2	-24	38.1	1 1/4	201	105	44	51
K4FV6-24-24	38	1 1/2	-24	38.1	1 1/2	221	125	44	60
K4FV4-24-24	38	1 1/2	-24	38.1	1 1/2	222	128.9	44	60
K4FV6-32-24	38	1 1/2	-24	38.1	2	221	125	44	71
K4FV4-32-24	38	1 1/2	-24	38.1	2	222	128.9	44	71
K4FV4-32-32	51	2	-32	50.8	2	269	171	62	71
K4FV6-32-32	51	2	-32	50.8	2	280	169	62	71

Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK


V4 | -10 up to -16 | H31 | H31TC | H31ST | R42 | R42TC | R42ST | -12 up to -20 | R35 | R35TC | H29 | all sizes | H29TC | H29ST | H29RH |

V6 | -24 up to -48 | R35 | R35TC | RS35TC-48 | -20 up to -32 | R42 | R42ST | R42TC |

19/4N ISO 6162-1 Flange 90° Elbow

ISO 12151-3-E-L – SFL 90°
(35.0 MPa/ 5000 psi)





Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
K19V4-12-12	19	3/4	-12	19.1	3/4	125	63.3	58	38
K19V4-16-12	19	3/4	-12	19.1	1	125	63.3	58	45
K19V4-16-16	25	1	-16	25.4	1	150	77.7	70	45
K4NV4-20-16	25	1	-16	25.4	1 1/4	150	77	69	51
K19V4-16-20	31	1 1/4	-20	31.8	1	186	98	90	45
K19V6-16-20	31	1 1/4	-20	31.8	1	177	86	90	44
K4NV6-20-20	31	1 1/4	-20	31.8	1 1/4	177	86	90	51
K4NV4-20-20	31	1 1/4	-20	31.8	1 1/4	186	98.2	90	51
K4NV4-24-20	31	1 1/4	-20	31.8	1 1/2	186	98	90	60
K4NV4-24-20-SL110	31	1 1/4	-20	31.8	1 1/2	186	98	110	60
K4NV6-24-20	31	1 1/4	-20	31.8	1 1/2	177	86	90	60
K4NV6-20-24	38	1 1/2	-24	38.1	1 1/4	184	88	104	51
K4NV4-20-24	38	1 1/2	-24	38.1	1 1/4	197	103	104	51
K4NV6-24-24	38	1 1/2	-24	38.1	1 1/2	209	113	104	60
K4NV4-24-24-SL200	38	1 1/2	-24	38.1	1 1/2	210	116.9	200	60
K4NV4-24-24-SL150	38	1 1/2	-24	38.1	1 1/2	210	116.9	150	60
K4NV4-24-24	38	1 1/2	-24	38.1	1 1/2	210	116.9	104	60
K4NV4-32-24	38	1 1/2	-24	38.1	2	210	116.9	104	71
K4NV6-32-24	38	1 1/2	-24	38.1	2	209	113	104	71
K4NV4-24-32	51	2	-32	50.8	1 1/2	227	130	138	60
K4NV6-32-32	51	2	-32	50.8	2	268	157	138	71
K4NV4-32-32	51	2	-32	50.8	2	257	160.2	138	71

Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK


V4 | -10 up to -16 | H31 | H31TC | H31ST | R42 | R42TC | R42ST | -12 up to -20 | R35 | R35TC | H29 | all sizes | H29TC | H29ST | H29RH |

V6 | -24 up to -48 | R35 | R35TC | RS35TC-48 | -20 up to -32 | R42 | R42ST | R42TC |

6A ISO 6162-2 Flange Straight

ISO 12151-3-S-S – SFS
(42.0 MPa/ 6000 psi)





Part Number	Hose I.D.				Flange	A	B	F
	DN	Inch	Size	mm	Inch	mm	mm	mm
K6AV4-8-10	16	5/8	-10	15.9	1/2	121	62	32
K6AV4-12-10	16	5/8	-10	15.9	3/4	94	33.8	41
K6AV4-12-12	19	3/4	-12	19.1	3/4	126	64.4	41
K6AV4-16-12	19	3/4	-12	19.1	1	100	38	48
K6AV4-12-16	25	1	-16	25.4	3/4	150	77	41
K6AV4-16-16	25	1	-16	25.4	1	148	75	48
K6AV4-20-16	25	1	-16	25.4	1 1/4	116	44	54
K6AV4-24-16	25	1	-16	25.4	1 1/2	118	45	64
K6AV6-16-20	31	1 1/4	-20	31.8	1	175	84	48
K6AV4-16-20	31	1 1/4	-20	31.8	1	166	78	48
K6AV4-20-20	31	1 1/4	-20	31.8	1 1/4	166	78	54
K6AV6-20-20	31	1 1/4	-20	31.8	1 1/4	175	83	54
K6AV4-24-20	31	1 1/4	-20	31.8	1 1/2	139	51	64
K6AV6-24-20	31	1 1/4	-20	31.8	1 1/2	147	56	64
K6AV6-20-24	38	1 1/2	-24	38.1	1 1/4	185	89	54
K6AV4-20-24	38	1 1/2	-24	38.1	1 1/4	174	81	54
K6AV4-24-24	38	1 1/2	-24	38.1	1 1/2	192	99	64
K6AV6-24-24	38	1 1/2	-24	38.1	1 1/2	202	106	64
K6AV4-32-24	38	1 1/2	-24	38.1	2	184	91	79
K6AV6-32-24	38	1 1/2	-24	38.1	2	194	98	79
K6AV6-24-32	51	2	-32	50.8	1 1/2	219	108.3	64
K6AV4-24-32	51	2	-32	50.8	1 1/2	198	101	64
K6AV4-32-32	51	2	-32	50.8	2	212	115	79
K6AV6-32-32	51	2	-32	50.8	2	233	122	79
K6AV6-32-40	63	2 1/2	-40	63.5	2	252	117	79
K6AV6-40-40	63	2 1/2	-40	63.5	2 1/2	253	118	108
K6AV6-48-40	63	2 1/2	-40	63.5	3	250	115	132
K6AV6-48-48	76	3	-48	76.2	3	240	133	132

Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK


V4 | -10 up to -16 | H31 | H31TC | H31ST | R42 | R42TC | R42ST | -12 up to -20 | R35 | R35TC | H29 | all sizes | H29TC | H29ST | H29RH |

V6 | -24 up to -48 | R35 | R35TC | RS35TC-48 | -20 up to -32 | R42 | R42ST | R42TC |

6F ISO 6162-2 Flange 45° Elbow – Heavy Series

ISO 12151-3 – E45-S – SFS 45°
(42.0 MPa/ 6000 psi)





Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
K6FV4-8-10	16	5/8	-10	15.9	1/2	123	63.3	26	32
K6FV4-12-10	16	5/8	-10	15.9	3/4	123	63.3	26	41
K6FV4-12-12	19	3/4	-12	19.1	3/4	133	72	26	41
K6FV4-12-12-SL55	19	3/4	-12	19.1	3/4	162	101	55	41
K6FV4-16-12	19	3/4	-12	19.1	1	133	71.3	26	48
K6FV4-16-12-SL55	19	3/4	-12	19.1	1	162	101	55	48
K6FV4-12-16	25	1	-16	25.4	3/4	155	78	32	41
K6FV4-16-16-SL55	25	1	-16	25.4	1	183	110	55	48
K6FV4-16-16	25	1	-16	25.4	1	160	87	32	48
K6FV4-20-16-SL55	25	1	-16	25.4	1 1/4	184	112	55	54
K6FV4-20-16	25	1	-16	25.4	1 1/4	161	88.7	32	54
K6FV6-16-20	31	1 1/4	-20	31.8	1	188	97	38	48
K6FV4-16-20	31	1 1/4	-20	31.8	1	198	109.7	38	48
K6FV6-20-20	31	1 1/4	-20	31.8	1 1/4	189	97.3	38	54
K6FV4-20-20-SL60	31	1 1/4	-20	31.8	1 1/4	220	132	60	54
K6FV4-20-20	31	1 1/4	-20	31.8	1 1/4	198	109.7	38	54
K6FV6-20-20-SL60	31	1 1/4	-20	31.8	1 1/4	210	119	60	54
K6FV6-24-20	31	1 1/4	-20	31.8	1 1/2	189	97.3	38	64
K6FV4-24-20	31	1 1/4	-20	31.8	1 1/2	198	109.7	38	64
K6FV4-24-20-SL60	31	1 1/4	-20	31.8	1 1/2	220	132	60	64
K6FV6-20-24	38	1 1/2	-24	38.1	1 1/4	209	113.3	44	54
K6FV4-24-24-SL70	38	1 1/2	-24	38.1	1 1/2	248	155	70	64
K6FV6-24-24	38	1 1/2	-24	38.1	1 1/2	221	125.3	44	64
K6FV6-24-24-SL70	38	1 1/2	-24	38.1	1 1/2	247	151	70	64
K6FV4-24-24	38	1 1/2	-24	38.1	1 1/2	222	128.9	44	64
K6FV6-32-24	38	1 1/2	-24	38.1	2	221	125.3	44	79
K6FV4-32-24	38	1 1/2	-24	38.1	2	222	128.9	44	79
K6FV6-24-32	51	2	-32	50.8	1 1/2	260	149.3	56	64
K6FV4-32-32	51	2	-32	50.8	2	263	166	56	79
K6FV6-32-32	51	2	-32	50.8	2	274	163.3	56	79
K6FV4-32-32-SL70	51	2	-32	50.8	2	277	180	70	79

Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK


V4 | -10 up to -16 | H31 | H31TC | H31ST | R42 | R42TC | R42ST | -12 up to -20 | R35 | R35TC | H29 | all sizes | H29TC | H29ST | H29RH |

V6 | -24 up to -48 | R35 | R35TC | RS35TC-48 | -20 up to -32 | R42 | R42ST | R42TC |

6N ISO 6162-2 Flange 90° Elbow

ISO 12151-3 – E-S – SFS 90°
(42.0 MPa/ 6000 psi)





Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
K6NV4-8-10	16	5/8	-10	15.9	1/2	111	51	54	32
K6NV4-12-10	16	5/8	-10	15.9	3/4	111	50.3	54	41
K6NV4-12-12	19	3/4	-12	19.1	3/4	125	63.3	58	41
K6NV4-12-12-SL100	19	3/4	-12	19.1	3/4	125	63	100	41
K6NV4-16-12-SL100	19	3/4	-12	19.1	1	125	63	100	48
K6NV4-16-12	19	3/4	-12	19.1	1	125	63.3	58	48
K6NV4-12-16-SL55	25	1	-16	25.4	3/4	140	67	55	41
K6NV4-12-16	25	1	-16	25.4	3/4	140	67	70	41
K6NV4-16-16-SL100	25	1	-16	25.4	1	150	77	100	48
K6NV4-16-16	25	1	-16	25.4	1	150	77.7	70	48
K6NV4-20-16-SL115	25	1	-16	25.4	1 1/4	154	81	115	54
K6NV4-20-16	25	1	-16	25.4	1 1/4	154	81	70	54
K6NV4-16-20	31	1 1/4	-20	31.8	1	186	98.7	90	48
K6NV6-16-20	31	1 1/4	-20	31.8	1	177	86	90	48
K6NV6-20-20	31	1 1/4	-20	31.8	1 1/4	177	86.3	90	54
K6NV4-20-20-SL120	31	1 1/4	-20	31.8	1 1/4	186	98	120	54
K6NV6-20-20-SL120	31	1 1/4	-20	31.8	1 1/4	177	86	120	54
K6NV4-20-20	31	1 1/4	-20	31.8	1 1/4	186	98.7	90	54
K6NV4-20-20-SL330	31	1 1/4	-20	31.8	1 1/4	186	98	330	54
K6NV4-24-20	31	1 1/4	-20	31.8	1 1/2	186	98.7	90	64
K6NV6-24-20	31	1 1/4	-20	31.8	1 1/2	177	86.3	90	64
K6NV4-24-20-SL135	31	1 1/4	-20	31.8	1 1/2	186	98	135	64
K6NV6-20-24	38	1 1/2	-24	38.1	1 1/4	192	96.3	104	54
K6NV4-20-24	38	1 1/2	-24	38.1	1 1/4	197	103.9	104	54
K6NV4-24-24-SL140	38	1 1/2	-24	38.1	1 1/2	210	117	140	64
K6NV4-24-24-SL160	38	1 1/2	-24	38.1	1 1/2	210	117	160	64
K6NV4-24-24-SL200	38	1 1/2	-24	38.1	1 1/2	210	117	200	64
K6NV4-24-24	38	1 1/2	-24	38.1	1 1/2	210	116.9	104	64
K6NV6-24-24	38	1 1/2	-24	38.1	1 1/2	210	113.3	104	64
K6NV6-32-24	38	1 1/2	-24	38.1	2	209	113.3	104	79
K6NV4-32-24	38	1 1/2	-24	38.1	2	210	116.9	104	79
K6NV6-24-32	51	2	-32	50.8	1 1/2	236	125.3	104	64
K6NV4-24-32	51	2	-32	50.8	1 1/2	221	124	104	64
K6NV4-32-32	51	2	-32	50.8	2	257	160	138	79
K6NV6-32-32	51	2	-32	50.8	2	268	157.3	138	79

Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK


V4 | -10 up to -16 | H31 | H31TC | H31ST | R42 | R42TC | R42ST | -12 up to -20 | R35 | R35TC | H29 | all sizes | H29TC | H29ST | H29RH |

V6 | -24 up to -48 | R35 | R35TC | RS35TC-48 | -20 up to -32 | R42 | R42ST | R42TC |

8A Flange – Straight

8000 psi







Part Number	Hose I.D.				Flange	A	B	F
	DN	Inch	Size	mm	Inch	mm	mm	mm
K8AV4-12-10	16	5/8	-10	15.9	3/4	130	71	41
K8AV4-12-12	19	3/4	-12	19.1	3/4	132	71	41
K8AV4-16-12	19	3/4	-12	19.1	1	143	82	48
K8AV4-16-16	25	1	-16	25.4	1	148	75	48
K8AV4-20-16	25	1	-16	25.4	1 1/4	111	39	54
K8AV6-20-20	31	1 1/4	-20	31.8	1 1/4	190	88	54

8F Flange – 45° Elbow

8000 psi





Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
K8FV4-12-10	16	5/8	-10	15.9	3/4	123	64	26	41
K8FV4-12-12	19	3/4	-12	19.1	3/4	138	76	26	41
K8FV4-16-12	19	3/4	-12	19.1	1	143	81	32	48
K8FV4-16-16	25	1	-16	25.4	1	178	105	35	48
K8FV4-20-16	25	1	-16	25.4	1 1/4	178	105	35	54
K8FV6-20-20	31	1 1/4	-20	31.8	1 1/4	194	103	38	54

Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK


V4 | -10 up to -16 | H31 | H31TC | H31ST | R42 | R42TC | R42ST | -12 up to -20 | R35 | R35TC | H29 | all sizes | H29TC | H29ST | H29RH |

V6 | -24 up to -48 | R35 | R35TC | RS35TC-48 | -20 up to -32 | R42 | R42ST | R42TC |

8N Flange – 90° Elbow

8000 psi







Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
K8NV4-12-10	16	5/8	-10	15.9	3/4	111	51	58	41
K8NV4-12-12	19	3/4	-12	19.1	3/4	133	71	70	41
K8NV4-16-12	19	3/4	-12	19.1	1	133	71	70	48
K8NV4-16-16	25	1	-16	25.4	1	170	97	75	48
K8NV4-20-16	25	1	-16	25.4	1 1/4	170	97	90	54
K8NV6-20-20	31	1 1/4	-20	31.8	1 1/4	182	91	90	54

X5 Flange – Straight

Full flange system for
ISO 6162-1 or ISO 6162-2





Part Number	Hose I.D.				Flange	A	B
	DN	Inch	Size	mm	Inch	mm	mm
KX5V6-20-20	31	1 1/4	-20	31.8	1 1/4	152.3	61.3
KX5V6-24-24	38	1 1/2	-24	38.1	1 1/2	159.3	63.3
KX5V6-32-32	51	2	-32	50.8	2	188	78
KX5V6-40-40	63	2 1/2	-40	63.5	2 1/2	233	83
KX5V6-48-40	63	2 1/2	-40	63.5	3	233	98
KX5V6-48-48	76	3	-48	76.2	3	200	84

Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK


V4 | -10 up to -16 | H31 | H31TC | H31ST | R42 | R42TC | R42ST | -12 up to -20 | R35 | R35TC | H29 | all sizes | H29TC | H29ST | H29RH |

V6 | -24 up to -48 | R35 | R35TC | RS35TC-48 | -20 up to -32 | R42 | R42ST | R42TC |

X7 Flange – 45° Elbow

Full flange system for
ISO 6162-1 or ISO 6162-2







Part Number	Hose I.D.				Flange	A	B	E
	DN	Inch	Size	mm	Inch	mm	mm	mm
KX7V6-20-20	31	1 1/4	-20	31.8	1 1/4	190	99	39
KX7V6-24-24	38	1 1/2	-24	38.1	1 1/2	221	125	44
KX7V6-32-32	51	2	-32	50.8	2	275	164.5	57

X9 Flange – 90° Elbow

Full flange system for
ISO 6162-1 or ISO 6162-2





Part Number	Hose I.D.				Flange	A	B	E
	DN	Inch	Size	mm	Inch	mm	mm	mm
KX9V6-20-20	31	1 1/4	-20	31.8	1 1/4	176.8	85.5	90
KX9V6-24-24	38	1 1/2	-24	38.1	1 1/2	209.3	113	104
KX9V6-32-32	51	2	-32	50.8	2	268	157	138


Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK

V4 | -10 up to -16 | H31 | H31TC | H31ST | R42 | R42TC | R42ST | -12 up to -20 | R35 | R35TC | H29 | all sizes | H29TC | H29ST | H29RH |

V6 | -24 up to -48 | R35 | R35TC | RS35TC-48 | -20 up to -32 | R42 | R42ST | R42TC |


PY Flange – 24° Male French Gas Straight






Part Number	Hose I.D.				A	B
	DN	Inch	Size	mm	mm	mm
KPYV4-12-12	19	3/4	-12	19.1	92	30
KPYV4-16-16	25	1	-16	25.4	112	39

XA Caterpillar® Flange Straight





Part Number	Hose I.D.				Flange	A	B	F
	DN	Inch	Size	mm	Inch	mm	mm	mm
KXAV4-12-12	19	3/4	-12	19.1	3/4	132	71	41
KXAV4-16-12	19	3/4	-12	19.1	1	144	82	48
KXAV4-16-16	25	1	-16	25.4	1	155	82	48
KXAV4-20-16	25	1	-16	25.4	1 1/4	160	88	54
KXAV6-20-20	31	1 1/4	-20	31.8	1 1/4	181	90	54
KXAV6-24-20	31	1 1/4	-20	31.8	1 1/2	188	97	64
KXAV6-24-24	38	1 1/2	-24	38.1	1 1/2	207	111	64


Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK

V4 | -10 up to -16 | H31 | H31TC | H31ST | R42 | R42TC | R42ST | -12 up to -20 | R35 | R35TC | H29 | all sizes | H29TC | H29ST | H29RH |

V6 | -24 up to -48 | R35 | R35TC | RS35TC-48 | -20 up to -32 | R42 | R42ST | R42TC |


XF Caterpillar® Flange 45° Elbow






Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
KXFV4-12-12	19	3/4	-12	19.1	3/4	138	76	31	41
KXFV4-16-16	25	1	-16	25.4	1	164	91	36	48
KXFV4-20-16	25	1	-16	25.4	1 1/4	164	92	35	54
KXFV6-20-20	31	1 1/4	-20	31.8	1 1/4	187	96	37	54
KXFV6-24-20	31	1 1/4	-20	31.8	1 1/2	187	96	37	64
KXFV6-24-24	38	1 1/2	-24	38.1	1 1/2	216	120	39	64

XG Caterpillar® Flange 60° Elbow





Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
KXGV4-16-12	19	3/4	-12	19.1	1	152	91	42	48
KXGV4-16-16	25	1	-16	25.4	1	182	109	50	48
KXGV4-20-16	25	1	-16	25.4	1 1/4	184	112	50	54
KXGV6-20-20	31	1 1/4	-20	31.8	1 1/4	206	115	55	54
KXGV6-24-20	31	1 1/4	-20	31.8	1 1/2	208	117	52	64
KXGV6-24-24	38	1 1/2	-24	38.1	1 1/2	266	170	52	64


Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK

V4 | -10 up to -16 | H31 | H31TC | H31ST | R42 | R42TC | R42ST | -12 up to -20 | R35 | R35TC | H29 | all sizes | H29TC | H29ST | H29RH |

V6 | -24 up to -48 | R35 | R35TC | RS35TC-48 | -20 up to -32 | R42 | R42ST | R42TC |

XN Caterpillar® Flange 90° Elbow





Part Number	Hose I.D.				Flange	A	B	E	F
	DN	Inch	Size	mm	Inch	mm	mm	mm	mm
KXNV4-12-12	19	3/4	-12	19.1	3/4	125	63	63	41
KXNV4-16-12	19	3/4	-12	19.1	1	125	63	62	48
KXNV4-16-16	25	1	-16	25.4	1	150	77	74	48
KXNV4-20-16	25	1	-16	25.4	1 1/4	154	81	74	54
KXNV6-20-20	31	1 1/4	-20	31.8	1 1/4	177	86	77	54
KXNV6-24-20	31	1 1/4	-20	31.8	1 1/2	177	86	77	64
KXNV6-24-24	38	1 1/2	-24	38.1	1 1/2	209	113	106	64

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK


V4 | -10 up to -16 | H31 | H31TC | H31ST | R42 | R42TC | R42ST | -12 up to -20 | R35 | R35TC | H29 | all sizes | H29TC | H29ST | H29RH |


V6 | -24 up to -48 | R35 | R35TC | RS35TC-48 | -20 up to -32 | R42 | R42ST | R42TC |

JC

Female ORFS Swivel – Straight Short

ISO 12151-1 – SWSA
SAE J516 – ORFS







Part Number	Hose I.D.				Thread	A	B	H	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
KJCV4-12-12	19	3/4	-12	19.1	1 3/16x12	93	31.3	30	36
KJCV4-16-12	19	3/4	-12	19.1	1 7/16x12	93	31	36	41
KJCV4-12-16	25	1	-16	25.4	1 3/16x12	101	29	36	36
KJCV4-16-16	25	1	-16	25.4	1 7/16x12	108	36	36	41
KJCV4-20-16	25	1	-16	25.4	1 11/16x12	120	47	41	50
KJCV6-20-20	31	1 1/4	-20	31.8	1 11/16x12	132	41	46	50
KJCV4-20-20	31	1 1/4	-20	31.8	1 11/16x12	127	39	46	50
KJCV6-24-20	31	1 1/4	-20	31.8	2x12	133	42	50	60
KJCV6-24-24	38	1 1/2	-24	38.1	2x12	140	44	50	60
KJCV4-24-24	38	1 1/2	-24	38.1	2x12	131	37.9	50	60

JS

ORFS Swivel Female (Long)

ISO 12151-1-SWSB
SAE J516 – ORFS





Part Number	Hose I.D.				Thread	A	B	H	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
KJSV4-16-16	25	1	-16	25.4	1 7/16x12	121	49	36	41
KJSV4-20-16	25	1	-16	25.4	1 11/16x12	120	47.7	41	50
KJSV4-20-20	31	1 1/4	-20	31.8	1 11/16x12	137	49.7	41	50

Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK


V4 | -10 up to -16 | H31 | H31TC | H31ST | R42 | R42TC | R42ST | -12 up to -20 | R35 | R35TC | H29 | all sizes | H29TC | H29ST | H29RH |

V6 | -24 up to -48 | R35 | R35TC | RS35TC-48 | -20 up to -32 | R42 | R42ST | R42TC |

J7 Female ORFS – Swivel 45° Elbow

ISO 12151-1 – SWE 45°
SAE J516 – ORFS 45°







Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
KJ7V4-12-12	19	3/4	-12	19.1	1 3/16x12	128	66.3	21	36
KJ7V4-16-12	19	3/4	-12	19.1	1 7/16x12	131	70	24	41
KJ7V4-16-16	25	1	-16	25.4	1 7/16x12	152	79	24	41
KJ7V4-20-16	25	1	-16	25.4	1 11/16x12	154	81	26	50
KJ7V4-20-20	31	1 1/4	-20	31.8	1 11/16x12	189	101.7	30	50
KJ7V6-20-20	31	1 1/4	-20	31.8	1 11/16x12	179	87.8	33	50
KJ7V6-24-20	31	1 1/4	-20	31.8	2x12	190	99	40	60
KJ7V6-24-24	38	1 1/2	-24	38.1	2x12	216	120	40	60
KJ7V4-24-24	38	1 1/2	-24	38.1	2x12	218	124.9	40	60

J9 Female ORFS – Swivel 90° Elbow – Short Drop

ISO 12151-1 – SWES
SAE J516 – ORFS 90°





Part Number	Hose I.D.				Thread	A	B	E	W
	DN	Inch	Size	mm	UNF	mm	mm	mm	mm
KJ9V4-12-12	19	3/4	-12	19.1	1 3/16x12	125	63.3	48	36
KJ9V4-16-12	19	3/4	-12	19.1	1 7/16x12	125	63	56	41
KJ9V4-16-16	25	1	-16	25.4	1 7/16x12	150	77.7	56	41
KJ9V4-20-16	25	1	-16	25.4	1 11/16x12	150	77	64	50
KJ9V4-20-20	31	1 1/4	-20	31.8	1 11/16x12	186	98	69	50
KJ9V6-20-20	31	1 1/4	-20	31.8	1 11/16x12	177	86	79	50
KJ9V6-24-20	31	1 1/4	-20	31.8	2x12	177	86	70	60
KJ9V6-24-24	38	1 1/2	-24	38.1	2x12	202	106	87	60
KJ9V4-24-24	38	1 1/2	-24	38.1	2x12	210	116.9	82	60

Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK


V4 | -10 up to -16 | H31 | H31TC | H31ST | R42 | R42TC | R42ST | -12 up to -20 | R35 | R35TC | H29 | all sizes | H29TC | H29ST | H29RH |

V6 | -24 up to -48 | R35 | R35TC | RS35TC-48 | -20 up to -32 | R42 | R42ST | R42TC |

JM ORFS Male

ISO 12151-1-S – SAE J516





Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	UNF	mm	mm	mm
KJMV4-12-12	19	3/4	-12	19.1	1 3/16x12	95	33.3	32
KJMV4-16-12	19	3/4	-12	19.1	1 7/16x12	98.7	37	41


Approved **fitting series** for **hose types**:


Also available in stainless steel. Details can be found in CAT 4400.1/UK

V4 | -10 up to -16 | H31 | H31TC | H31ST | R42 | R42TC | R42ST | -12 up to -20 | R35 | R35TC | H29 | all sizes | H29TC | H29ST | H29RH |

V6 | -24 up to -48 | R35 | R35TC | RS35TC-48 | -20 up to -32 | R42 | R42ST | R42TC |


FG Male French Gas Series Rigid – Straight (24° Cone)





Part Number	Hose I.D.				Thread	Tube O.D.	A	B	H
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
KFGV4-27-12	19	3/4	-12	19.1	M36x1.5	26.75	94	32.3	36
KFGV4-33-16	25	1	-16	25.4	M45x1.5	33.5	111	38.7	46

F4 Female French Gas Series Swivel – Straight (Ball Nose)





Part Number	Hose I.D.				Thread	Tube O.D.	A	B	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
KF4V4-27-12	19	3/4	-12	19.1	M36x1.5	26.75	95	33	46

Approved **fitting series** for **hose types**:

Also available in stainless steel. Details can be found in CAT 4400.1/UK

V4 | -10 up to -16 | H31 | H31TC | H31ST | R42 | R42TC | R42ST | -12 up to -20 | R35 | R35TC | H29 | all sizes | H29TC | H29ST | H29RH |


V6 | -24 up to -48 | R35 | R35TC | RS35TC-48 | -20 up to -32 | R42 | R42ST | R42TC |

Shell

Page Dg-1

V5

Dg-1




Interlock
In-/Outside Skive
R56TC Hose

DIN – Metric

Page Dg-2 – Dg-3

C9

Dg-2



Female Metric 24° – Swivel
Heavy Series with O-Ring
Straight
ISO 12151-2-SWS-S – DKOS

0C

Dg-2



Female Metric 24° – Swivel
Heavy Series with O–Ring
45° Elbow
ISO 12151-2 – SWE 45°-S – DKOS 45°

1C

Dg-3




Female Metric 24° – Swivel
Heavy Series with O–Ring
90° Elbow
ISO 12151-2-SWE-S – DKOS 90°

V5

Interlock
In-/Outside Skive

R56TC Hose



Only for use with adjustable crimpers.


Part Number	Hose I.D.				B
	DN	Inch	Size	mm	mm
100V5-6	10	3/8	-6	9.5	47
100V5-8	12	1/2	-8	12.7	53


Approved **fitting series** for **hose types**:

V5 | R56TC |

C9 Female Metric 24° – Swivel Heavy Series with O-Ring Straight

ISO 12151-2-SWS-S – DKOS







Part Number	Hose I.D.				Thread	Tube O.D.	A	B	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
KC9V5-14-6	10	3/8	-6	9.5	M22x1.5	14	72	23	27
KC9V5-16-8	12	1/2	-8	12.7	M24x1.5	16	79	26	30

Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

0C Female Metric 24° – Swivel Heavy Series with O–Ring 45° Elbow

ISO 12151-2 – SWE 45°-S – DKOS 45°





Part Number	Hose I.D.				Thread	Tube O.D.	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
K0CV5-14-6	10	3/8	-6	9.5	M22x1.5	14	102	53	20	27
K0CV5-16-8	12	1/2	-8	12.7	M24x1.5	16	1112	60	24	30


Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.


Approved **fitting series** for **hose types**:

V5 | R56TC |

1C Female Metric 24° – Swivel Heavy Series with O-Ring 90° Elbow

ISO 12151-2-SWE-S – DKOS 90°





Part Number	Hose I.D.				Thread	Tube O.D.	A	B	E	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm	mm
K1CV5-14-6	10	3/8	-6	9.5	M22x1.5	14	91	42	37	27
K1CV5-16-8	12	1/2	-8	12.7	M24x1.5	16	101	48	45	30

Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.

Approved **fitting series** for **hose types**:


V5 | R56TC |

Shell

Page Dh-1

100WB

Dh-1




Interlock
In-/Outside Skive
BPK Hose

DIN – Metric

Page Dh-2

C9

Dh-2




Female Metric 24° – Swivel
Heavy Series with O-Ring
Straight
ISO 12151-2-SWS-S – DKOS

BSP

Page Dh-3

92

Dh-3




Female BSP Parallel Pipe
Swivel – Straight (60° Cone)
BS5200-A – DKR

SAE

Page Dh-4

01


Dh-4



Male NPTF Pipe
Rigid – Straight
SAE J476A / J516 – AGN

100WB Interlock In-/Outside Skive

BPK Hose



Only for use with adjustable crimpers.


Part Number	Hose I.D.				B
	DN	Inch	Size	mm	mm
100WB-4	6	1/4	-4	6.3	55.0
100WB-6	10	3/8	-6	9.5	47.0
100WB-8	12	1/2	-8	12.7	52.5
100WB-12	20	3/4	-12	19.1	61.0
100WB-16	25	1	-16	25.4	74.5


Approved **fitting series** for **hose types**:

WB | BPK |

C9 Female Metric 24° – Swivel Heavy Series with O-Ring Straight

ISO 12151-2-SWS-S – DKOS





Part Number	Hose I.D.				Thread	Tube O.D.	A	B	W
	DN	Inch	Size	mm	metric	mm	mm	mm	mm
KC9WB-10-4	6	1/4	-4	6.3	M18x1.5	10	72	21	22
KC9WB-14-6	10	3/8	-6	9.5	M22x1.5	14	72	23	27
KC9WB-16-8	12	1/2	-8	12.7	M24x1.5	16	85	32	30
KC9WB-25-12	20	3/4	-12	19.1	M36x2	25	95	34	46
KC9WB-30-16	25	1	-16	25.4	M42x2	30	108	36	50


Fittings with standard O-ring seals can be used for temperatures from -40 °C up to +105 °C.
O-rings see section Eb. Special O-rings are available on request.


Approved **fitting series** for **hose types**:

| WB | BPK |

92 Female BSP Parallel Pipe Swivel – Straight (60° Cone)

BS5200-A – DKR






Part Number	Hose I.D.				Thread	A	B	W
	DN	Inch	Size	mm	BSP	mm	mm	mm
K92WB-4-4	6	1/4	-4	6.3	1/4x19	70	19	19
K92WB-6-6	10	3/8	-6	9.5	3/8x19	72	23	22
K92WB-8-8	12	1/2	-8	12.7	1/2x14	79	26	27


Approved **fitting series** for **hose types**:

| WB | BPK |

01 Male NPTF Pipe Rigid – Straight

SAE J476A / J516 – AGN





Part Number	Hose I.D.				Thread	A	B	H
	DN	Inch	Size	mm	NPTF	mm	mm	mm
K01WB-4-4	6	1/4	-4	6.3	1/4x18	79	28	14
K01WB-6-4	6	1/4	-4	6.3	3/8x18	82	31	19
K01WB-6-6	10	3/8	-6	9.5	3/8x18	77	28	19
K01WB-8-8	12	1/2	-8	12.7	1/2x14	90	37	22
K01WB-12-12	20	3/4	-12	19.1	3/4x14	98	36	30
K01WB-16-16	25	1	-16	25.4	1x11-1/2	114	41	36

Approved **fitting series** for **hose types**:

WB	BPK





aerospace
climate control
electromechanical
filtration
fluid & gas handling
hydraulics
pneumatics
process control
sealing & shielding





Hydraulic Hoses, Fittings and Equipment

Machines, Tooling, Accessories




Parker

ENGINEERING YOUR SUCCESS.

Hydraulic Hose Assembly Workshop Equipment


– meeting the demands of professional hose assembly manufacture

Hose assemblies must be manufactured in conformity with all the relevant EN/ISO standards and with the requirements of various work safety and trade associations. Hose Products Division Europe has selected and developed a complete range of machines and tooling to ensure effective and safe production of hose assemblies. This can be achieved only when equipment designed for the purpose is used.



The programme includes the right tools for ready-to-install Parkrimp No-Skive and ParLock hose assemblies:

- Cutting hoses
- Crimping hoses
- Marking hose assemblies
- Cleaning hose assemblies
- Testing hose assemblies



TH 7-12
7-stage hose reel



85CE-061L + 85CE-1PE
KarryKrimp 2 Bench Mount



TH3E-EM6-M
Hose Cutting Machine



TH 5-3
Hose Assembly Test Bench



TH 4-4 U
Hand Marking Tools



TH 6-6
Cleaning System



TH8E-535-BM
Adjustable Crimper

It's so easy to crimp your own hose assemblies

Please visit us at
www.easy-crimping.com

Parkrimp® *No-Skive*

The system for fast and leak-free assemblies

Hose fittings have an impact on the overall efficiency and safety of a hydraulic system.
The No-Skive concept was launched by Parker Hannifin some 30 years ago but continuous development and the use of modern materials and production techniques have resulted in a state-of-the-art hose to fitting connection. Much easier handling and a high level of safety are available with No-Skive crimp fittings. Parker offers No-Skive fittings in one and two pieces as part of a package consisting of quality hose, No-Skive fittings, hose crimpers and tooling.



Parkrimp *No-Skive* one-piece fittings





Parkrimp® *No-Skive*

- No skiving tool needed
- No need to remove the cover
- Crimps one-piece fittings
- Parkalign positions the fittings in the dies perfectly every time
- Quick and easy: no gauges to set on the machine
- Portable machines for field repair
- Meets EN safety regulations

Modular Design = Portable + Bench Mount

Parkrimp crimpers for *No-Skive* one-piece fittings

The modular design enables the customer to choose between the portability that Parker KarryKrimp crimpers have always offered, and the option to make these same crimpers bench mount units.
The modular design gives users the flexibility of a portable crimper with the advantage of increased productivity when connected to the Bench Power Unit 85CE-1PE.



KarryKrimp® 1

KarryKrimp® 1
Bench Mount



KarryKrimp® 2


KarryKrimp® 2
Bench Mount

ParLock Hose and Fittings

The high-performance skiving system

Certain customers and applications stipulate the usage of multispiral hose assemblies with external/internal skive-type fittings. With the ParLock hose and fitting range, Parker meets this demanding market requirement. Parker adjustable crimpers for two-piece fittings ensure precise, leak-free and tear-proof assembly of hose and fitting.

- High flex-impulse applications
- High vibration applications
- The ParLock design is approved by the German Accident Prevention & Insurance Association (Berufsgenossenschaft) conforming to EN 201 (approved for injection-moulding machine applications)



ParLock two-piece skive fittings





TH2-13-3PH
Hose skiving machine

Adjustable crimpers
for two-piece ParLock fittings



TH8E-530



TH 8E-380-BM



TH 8E-480-BM

ParLock System


- A full range of multispiral hoses to ISO 3862 (4SP to R15)
- Field-tested, proven reliability
- Hose and fitting combinations giving performance that exceeds ISO/EN requirements
- Approved hose and fitting compatibility “one manufacturer, one source”

Hose Whip Restraint

Safety Restraining System for Pressure Hoses

- Prevents whipping of a pressurized hose in the event of the hose separating from its fitting
- The system consists of two parts – a hose collar and a cable assembly





Parker's Hose Whip Restraint System is designed to prevent whipping of a pressurized hose in the event of the hose separating from its fitting. The Hose Whip Restraint System provides an additional level of safety and helps prevent damage to nearby equipment or injury to operators near the failed hose by limiting the whip or travel of the pressurized hose after it breaks free from its hose fitting. Serious damage or injury can occur from whipping hoses, especially at higher pressures.

The system consists of two parts – a hose collar and a cable assembly. The hose collar (WRCxx) is selected based on the outside diameter of the hose, and the cable assembly is selected based on the type of hose connection. Two types of cable assemblies are available – one for flange-type connections (WRFxxx), and the other for port adapters (WRAxxx).


The Hose Whip Restraint is not to be used in place of proper hose crimping procedures. Exceeding the maximum operating pressure of the hose jeopardizes the proper operation of the Hose Whip Restraint System.



Cable Assemblies
for hoses using flange-style connections
ISO 6162-1 (35.0 MPa/5000 psi) and
ISO 6162-2 (42.0 MPa/ 6000 psi)



Cable Assemblies
for hoses attached with port adapters



Hose collars
for Hose Whip Restraint System

For more information about hose whip restraint please refer to page *Eb-19.*

Machines, Tooling, Accessories

Machines	
Parkrimp® Crimping Presses	Ea-1 – Ea-4
Accessories for Parkrimp® Crimping Presses	Ea-5
Parkrimp® Die Sets	Ea-6
Hose Cutting Machines	Ea-7 – Ea-13
Marking Machines	Ea-14 – Ea-15
Cleaning Systems	Ea-16 – Ea-19
Hose Assembly Test Bench	Ea-20
Hose Reels	Ea-21 – Ea-22
Adjustable Crimping Presses	Ea-23 – Ea-25
Hose Skiving Machines	Ea-26 – Ea-28
Skiving Tools for Hose Skiving Machines	Ea-29
Accessories	
Flange Half	Eb-1
Bolts for Flange Halves ISO 6162-1 and ISO 6162-2	Eb-2 – Eb-3
Full Flange System	Eb-4
Bolts for Full Flange System	Eb-5
Banjo Bolt	Eb-6
O-Rings	Eb-7 – Eb-8
Worm Drive Hose Clamps	Eb-9 – Eb-10
Hose Protection	Eb-11 – Eb-21
Hose Whip Restraint	Eb-22
Containment Grips	Eb-23
Thread Identification Kit	Eb-23
Parker „Hoze-Oil“	Eb-24
OilOn	Eb-24
Push-Lok® Assembly Oil	Eb-24
Push-Lok® Assembly Tool	Eb-24
Assembly Instructions	
KarryKrimp® 1 / KarryKrimp® 2	Ec-1
Parkrimp® 2	Ec-2
Your Crimp Source online	Ed-1

Parker Hannifin assumes no liability for typographical errors or other errors

KarryKrimp® 1



Modular portable crimper for braided hoses

- Crimps
  – 1 and 2 steel wire or textile braided hoses..... size -4 up to size -20
- Available in modular design with all Parkrimp system advantages
- The same unit offers portability and bench mountability
- Easily portable for outside work
- Used for service with hand pump or airhydraulic and electrical pump
- Portable, compact rugged design
- Pivoting pusher design for easy die change out
- Increased height enables longer bent tube fittings to be crimped

Primary Applications

Small workshops, repair shops, mobile service vehicles.

Fittings Series

26, 43, 46, 48

Restrictions

Not suitable for multispiral hoses, 2-piece fittings, stainless steel fittings and serial production of hose assemblies in size -12 and above.

Technical / Order Data

KarryKrimp 1	Dimensions	H 760 x W 335 x D 330 mm
	Weight	28 kg
	Part Number	**82CE-061L**

Included standard equipment

Crimp head		**Part Number**	**82CE-CHD**
Stand assembly		**Part Number**	**85C-STD**
Hose assembly		**Part Number**	**85C-00L**
Die rings	silver	**Part Number**	**82C-R01**
	black	**Part Number**	**82C-R02**

Accessories see page ***Ea-5***

KarryKrimp® 2

Modular portable crimper
for braided and multispiral hoses

- Crimps
  - 1 and 2 steel wire or textile braided hoses ..... up to size -20
  - 3 steel wire braided hoses ..... up to size -16
  - 4 layer multispiral hoses ..... up to size -16
  - compact spiral hoses ..... up to size -12
- Available in modular design with all Parkrimp system advantages
- The same unit offers portability and bench mountability
- Easily portable for outside work
- Portable, compact rugged design
- Pivoting pusher design for easy die change out



Primary Applications

Small workshops, repair shops, mobile service vehicles.
Crimps both steel and stainless steel fittings.

Fittings Series

26, 43, 46, 48, 70, 71, 73, 77, 78

Restrictions

Not suitable for 2-piece fittings.

Technical / Order Data

KarryKrimp 2		Dimensions	H 805 x W 340 x D 350 mm
		Weight	46 kg
		Part Number	**85CE-061L**

Included standard equipment

Crimp head		**Part Number**	**85CE-CHD**
Stand assembly		**Part Number**	**85C-STD**
Hose assembly		**Part Number**	**85C-00L**
Die rings	silver	**Part Number**	**85C-R01**
	black	**Part Number**	**85C-R02**

Accessories see page ***Ea-5***

KarryKrimp Bench Mount

Modular crimpers with
Bench Power Unit for workshops

- In addition to the portable versions, the sole crimping units can be used with the Bench Power Unit for workshop versions
- Faster cycle times for increased productivity
- Increased height for longer elbows or bent tube fittings
- The crimpers and the Bench Power Unit are supplied separately



Modular Design = Portable + Bench Mount

The modular design enables the customer to choose between the portability that Parker KarryKrimp crimpers have always offered, and the option to make these same crimpers bench mount units.
The modular design gives users the flexibility of a portable crimper with the advantage of increased productivity when connected to the Bench Power Unit 85CE-1PE.





Technical / Order Data

Bench Power Unit 85CE-1PE



Working pressure	70 MPa
Dimensions	L 425 x W 525 x H 460 mm
Weight	62 kg
Usable oil capacity	8000 ccm
Electrical power	230 V / 50/60 Hz / 10 A
Part Number	**85CE-1PE**

Parkrimp® 2

Bench-mounted crimper for all Parkrimp *No-Skive* hose types from size -4 up to size -32, including 4 and 6 layer multispiral hoses

- Crimps
  - 1 and 2 steel wire or textile braided hoses ..... up to size -32
  - 3 steel wire braided compact ..... up to size -16
  - 4 and 6 layer multispiral hoses ..... up to size -32
  - Compact Spiral hoses ..... up to size -32
- Used for service with 400 V hydraulic power unit



Primary Applications

Workshops and repair shops (for small series).
Crimps both steel and stainless steel fittings.

Fittings Series

26, 43, 46, 48, 70, 71, 73, 77, 78, 79, S6

Restrictions

Not suitable for 2-piece fittings.

Technical / Order Data

Parkrimp 2 with power unit, bench-mounted, but without die sets, connector plug and oil	Electrical power		400 V / 4.4 kW / 8.9 A / 50 Hz
	Dimensions		H 1170 x W 530 x D 985 mm
	Weight	without packaging	370 kg
		with packaging	430 kg
	Part Number		**83CE-083U**

Included standard equipment

Adaptor bowl	**Part Number**	**83C-0CB**
Die ring	**Part Number**	**83C-R02**
Die plate	**Part Number**	**83C-R02H**

Accessories for KarryKrimp® 1 and KarryKrimp® 2

For use with Karrykrimp 1 crimping press

Hand pump
82C-2HP



Working pressure	max. 70 MPa
Dimensions	L 530 x W 121 x H 178 mm
Weight	4.1 kg
Usable oil capacity	900 ccm
Lever force	42 kg
Part Number	**82C-2HP**

For use with KarryKrimp 1 and KarryKrimp 2 crimping presses

Hand pump
85CE-0HP



Working pressure	max. 70 MPa
Dimensions	L 580 x W 150 x H 195 mm
Weight	10.7 kg
Usable oil capacity	2200 ccm
Lever force	35 kg
Part Number	**85CE-0HP**

Turbo air pump
85C-0AP



Working pressure	70 MPa
Dimensions	L 350 x W 170 x H 210 mm
Weight	8.2 kg
Usable oil capacity	2080 ccm
Connection	air 1/4-18 NPTF thread
Part Number	**85C-0AP**

Power pump
82CE-0EP



Working pressure	70 MPa with 3/2 hand valve
Dimensions	L 244 x W 244 x H 362 mm
Weight	10.0 kg
Usable oil capacity	1900 ccm
Connection	230 V / 50/60 Hz / 10 A
Part Number	**82CE-0EP**

Air Hydraulic pump
85CE-XAM

Optional: Manual lever
Part Number
85CE-XA-LK1



Working pressure	70 MPa
Dimensions	L 351 x W 260 x H 152 mm
Weight	8.8 kg
Usable oil capacity	1000 ccm
Connection	air: 1/4-18 NPTF female oil: 3/8-18 NPTF female; 90° swivel
Part Number	**85CE-XAM**

Bench Power Unit
85CE-1PE



Working pressure	70 MPa
Dimensions	L 425 x W 525 x H 460 mm
Weight	62 kg
Usable oil capacity	8000 ccm
Electrical power	230 V / 50/60 Hz / 10 A
Part Number	**85CE-1PE**

Hose Assembly 85C-00L
Hose assembly to connect pump to the press



Working pressure	max. 70 MPa
Length	1830 mm
Port size	3/8-18 NPT male, coupling 3/8”
Part Number	**85C-00L**

Parkrimp® Die Sets

Parker`s Colour-Coded Die Sets

- Chain link keeps segments together
- No loose parts to mismatch or misplace
- The crimp die provides 360-degree gripping power for greater impulse life



Note: *Please consult the pages Ec for assembly instructions. Die sets with the "H" suffix are used for jump sizes and certain metric fittings to permit insertion and removal of fittings. Die sets 80C-XX 8 segments are chained together. Die sets 83C-XX consist of two chained halves. Exceptions 83C-D06, -D08, -D10, -D12, -D16

Hose I.D. size	Hose I.D. DN	Die sets	Part Number 26 series	43 series	46 series	48 series	70 series	73 series	77 series
-4	6	red	80C-E04	80C-A04	80C-B04	80C-C04			
-5	8	violett	80C-E05	80C-A05	80C-B05	80C-C05			
-6	10	yellow	80C-E06	80C-A06	80C-B06	80C-C06	83C-D06		
-8	12	blue	80C-E08	80C-A08	80C-B08	80C-C08	83C-D08		80C-CS08
-10	16	orange	80C-E10	80C-A10	80C-B10	80C-C10	83C-D10		80C-CS10
-12	20	green	80C-E12	80C-A12	80C-B12	80C-C12	83C-D12	83C-L12 or 80C-L12	80C-CS12
-16	25	black	80C-E16	80C-A16 or 83C-A16H	80C-B16	80C-C16	83C-D16 or 83C-D16H	83C-L16 or 80C-L16	83C-CS16
-20	32	white	83C-E20	80C-A20 or 83C-A20H*	80C-B20	80C-C20 or 83C-C20H*		83C-L20	83C-CS20
-24	40	red	83C-E24	83C-A24		83C-C24		83C-L24	83C-CS24
-32	50	green	83C-E32	83C-A32		83C-C32		83C-L32	83C-CS32

EM 10.P

Hose Cutting Machine

- Cuts
  - 1 steel wire or textile braided hoses ..... up to size -16
  - 2 steel wire braided hoses ..... up to size -12
- Can be used on a workbench or in a vice bench
- Cutting blade covered during use
- Equipped with an electrical safety switch



Primary Applications

Repair shops or mobile service vehicles, preferably in combination with KarryKrimp 1

Restrictions

Not suitable for multispiral hoses or large bore industrial hoses.


Technical / Order Data

Hose Cutting Machine EM 10.P with cutting blade, smooth TM 160 x 2,5 x 20	Electric motor	circular saw motor 230 V
	Electric power	50/60 Hz / 1200 W / 6100 rpm
	Electrical insulation	according VDE KI.II 0740
	Radioshielding	according VDE 0875
	Cutting blade	160 x 2.5 x 20 mm (HSS)
	Dimensions	L 360 x W 340 x H 310 mm
	Weight	8 kg
	Part Number	**EM 10.P**
Cutting blade, smooth	**Part Number**	**TM 160 x 2,5 x 20**

TH 3-2-12VDC

Hose Cutting Machine

- Cuts
  - 1 and 2 steel wire or textile braided hoses ..... up to size -20
  - 4 steel wire multispiral hoses ..... up to size -16
- For mobile service vehicles with 12 V connection



Primary Applications

Mobile service vehicles

Restrictions

Not suitable for large bore hoses.

Technical / Order Data

Hose Cutting Machine TH 3-2-12VDC with cutting blade, serrated	Electric motor	12 V / 2.4 kW
	Cutting blade	250 x 2 x 40 mm
	Dimensions	W 567 x D 470 x H 365 mm
	Weight	30 kg
	Part Number	**TH3-2-12VDC**
Cutting blade, serrated 250 x 2 x 40 mm	**Part Number**	**TM250x2x40Z**

TH 3E-EM3

Hose Cutting Machine



- Cuts
  - 1 and 2 steel wire or textile braided hoses ..... up to size -20
  - 4 steel wire multispiral hoses ..... up to size -20
  - Industrial hoses ..... up to size -32
- According to the CE safety standards the blade stops within 10 seconds after switching off the brake motor
- Faster and safer cut using less energy, cutting motor with a larger shaft oversize bearing to gurantee less vibration created by radial forces
- Cutting blades approved on considered material

Primary Applications

Repair shops or mobile service vehicles

Restrictions

Not suitable for large bore industrial hoses.

Technical / Order Data

Hose Cutting Machine TH 3E-EM3 with cutting blade, serrated TMG275x3x30	Electrical power	3 kW
	Cutting blade	275 x 3 x 30 mm
	Dimensions	W 540 x D 440 x H 300 mm
	Weight	50 kg
	Part Number	**TH 3E-EM3**
Cutting blade, serrated 275 x 3 x 30 mm	**Part Number**	**TMG275x3x30**

TH 3E-EM6-M

Hose Cutting Machine

- Cuts
  - 1 and 2 steel wire or textile braided hoses ..... up to size -32
  - Compact Spiral hoses ..... up to size -20
  - 6 steel wire multispiral hoses ..... up to size -32
- Cutting blade covered during use
- Motor with surface brake and thermo protection



Primary Applications

Service in hose workshops and for small series production

Restrictions

Cutting 6 layer multispiral hoses will reduce the service life of the blade.

Technical / Order Data

Hose Cutting Machine TH 3E-EM6-M with cutting blade, serrated TMG350x3x30	Electrical power	400 V / 4.4 kW / 50 Hz
	Exhaust system Ø	60 mm
	Cutting blade	350 x 3 x 30 mm
	Dimensions	L 745 x W 690 x H 430 mm
	Weight	75 kg
	Part Number	**TH3E-EM6-M**
Cutting blade, serrated 350 x 3 x 30 mm	**Part Number**	**TMG350x3x30**

TH 3E-115

Hose Cutting Machine

- Cuts
  - all industrial hose types ..... up to 75 mm O.D.
  - 1, 2 and 3 steel wire or textile braided hoses ..... up to size -40
  - 4/6 steel wire multispiral hoses .... up to size -32
- According to the CE safety standards the blade stops within 10 seconds after switching off the brake motor
- Faster and safer cut using less energy, cutting motor with a larger shaft oversize bearing to gurantee less vibration created by radial forces
- Cutting blades approved on considered material
- Easiest cutting of big dimensioned hoses with more energy efficient machines



Primary Applications

Service and series production at workshops.

Technical / Order Data

Hose Cutting Machine TH 3E-115 3-phase, 400 Volt	Electrical power	230/400 V / 7.5 kW / 25 A / 50 Hz
	Exhaust system Ø	108 mm
	Cutting blade	520 x 4 x 40 mm
	Dimensions	L 1210 x W 650 x H 1650 mm
	Weight	245 kg
	Part Number	**TH3E-115**
Cutting blade, serrated 520 x 4 x 40 mm	**Part Number**	**TMG520 x 4 x 40**

TH 3E-110

Hose Cutting Machine



- Cuts
  - 1 and 2 steel wire or textile braided hoses ..... up to size -48
  - 4 steel wire multispiral hoses ..... up to size -48
  - 6 steel wire multispiral hoses ..... up to size -48
  - Industrial hoses ..... up to size -64
- According to the CE safety standards the blade stops within 10 seconds after switching off the brake motor
- Faster and safer cut using less energy, cutting motor with a larger shaft oversize bearing to gurantee less vibration created by radial forces
- Cutting blades approved on considered material
- Easiest cutting of big dimensioned hoses with more energy efficient machines

Primary Applications

Service and series production at workshops


Technical / Order Data

Hose Cutting Machine TH 3E-110 with cutting blade, serrated TMG520x4x120	Electrical power	7.5 kW
	Exhaust system Ø	100 mm
	Cutting blade	520 x 4 x 120
	Dimensions	W 800 x D 780 x H 1700 mm
	Weight	280 kg
	Part Number	**TH3E-110**
Cutting blade, serrated 520 x 4 x 120 mm	**Part Number**	**TMG520x4x120**

TH 4-7, TH 4-8

Marking Machines

- Manually or pneumatically driven
- Suitable for marking all 1- and 2-piece fittings series ..... up to size -32




Primary Applications

Smaller workshops and mobile service vehicles

Technical / Order Data

Marking Machine TH 4-8 manual excl. QC-adapter, type case and type holder	Colour	zinc plated
	Dimensions	L 500 x W 200 x H 500 mm
	Weight	28 kg
	Part Number	**TH4-8**
Marking Machine TH 4-7 pneumatic excl. QC-adapter, type case and type holder	Colour	zinc plated
	Air pressure	min. 0.6 MPa
	Dimensions	L 500 x W 380 x H 500 mm
	Weight	35 kg
	Part Number	**TH4-7**
Type case 3 mm	**Part Number**	**TH4-9**
Type print holder 2 lines	**Part Number**	**TH4-9-1**
QC-adapter for type print holder	**Part Number**	**TH4-10**

Type holder
2 lines



QC-adapter



Type case

Type case TH 4-9 content
AAABBCCDDEEEEFFGGHHIIIJJKK
LLLMMNNNOOOOPPQRRRSSSTT
UUUVVWXXYZ//..,,11112222333344
445556667778889990000 and 20 pcs of blanks
+ mirror

TH 4-4 U, TH 4E-11

Hand Marking Tools

- Hand marking tool for marking the crimp shells of 1- and 2-piece fittings up to size -32
- Permanent and easy marking in hose assembling workshops
- Type holder with two lines makes it possible to print additional information on the shell or fittings

TH 4E-11

- The cost efficient alternative



Primary Applications

Workshops and mobile service vehicles

Technical / Order Data

Hand Marking Tool TH 4-4 U including type case and quick-change stamping tool	Marking area	Ø O.D. 11.5 mm - 100 mm
	Dimensions	L 250 x W 340 x H 450 mm
	Type holder	2 lines
	Weight	35 kg
	Part Number	**TH4-4U**
Type case for TH 4-4 U	**Part Number**	**UPTS 100**
Quick-change stamping tool for TH 4-4 U single line	**Part Number**	**UPTH-11b-PW3**
Type holder for TH 4-4 U 2 lines	**Part Number**	**UPTH-22b**

Hand Marking Tool TH 4E-11 including type case and type holder	Marking area	Ø O.D. 8 mm - 80 mm
	Dimensions	L 285 x W 265 x H 410 mm
	Type holder	1 line
	Weight	12 kg
	Part Number	**TH4E-11**
Type case for TH 4E-11	**Part Number**	**TH4E-11-TC**
Type holder for TH 4E-11	**Part Number**	**TH4E-11-TH**



Stamping tool
UPTH-11b-PW3


Type case UPTS 100 content
Letters: 1x P, 1x N, 3x letters empty
Numbers: 6 x 1; 5 x 2,3,4,5; 4 x 6; 3 x 7,8,9; 4 x 0
Neutral: 1x 15 mm, 1x 30 mm + brush, tweezers, key

Type case TH4E-11-TC content
Letters: 1x P, 1x N, 3x letters empty
Numbers: 6 x 1; 5 x 2,3,4,5; 4 x 6; 3 x 7,8,9; 4 x 0
Neutral: 1x 15 mm, 1x 30 mm + brush, tweezers, key

TH 6-6

Cleaning System

- Cleaning device for hose and hose assemblies for hoses ..... up to size -20
- Assemblies flushed with fluid and blown out with air
- Defined cleanliness levels can be achieved
- Air connection min. 0.7 MPa required






Technical / Order Data

Cleaning Machine TH 6-6	Air pressure	min. 0.7 MPa
	Flow	8 l/min
	Air consumption	max. 100 Nl/min
	Length (depending on I.D.)	max. 2.5 m
	Dimensions	L 960 x W 435 x H 940 mm
	Weight	55 kg
	with cleaning fluid	93 kg
	Part Number	**TH6-6**
Filter set without cartridges	**Part Number**	**H899959**
Filter cartridges 5 µm	**Part Number**	**600.4**
Neutral cleaning fluid additive (30 litre drum)	**Part Number**	**H899771**

TH 6-7

Cleaning System

- Quick and simple system using compressed air to clean hoses
- Delivered with two plastic nozzles for hoses from ..... size -4 up to -32



Primary Applications

The hose is pressed against the nozzle and thereby opens a valve to allow the compressed air to blow through the hose and blow out loose particles.

Technical / Order Data

Cleaning System TH 6-7 with two plastic nozzles in 30 and 55 mm	Air pressure	min. 0.6 MPa
	Air connection	1/2" BSP
	Dimensions	L 120 x W 50 x H 100 mm
	Weight	0.3 kg
	Part Number	**TH6-7**
Nozzle 30 mm	**Part Number**	**TH6-7-30**
Nozzle 55 mm	**Part Number**	**TH6-7-55**

TH 6-10-EL-7

Ultra Clean Kit

- Cleaning of hoses from .....size -4 up to -20
- Reduces downtime and risk of hose failure
- Has a quarter-turn locking ring for easy nozzle change and projectile loading
- Durable brass and aluminium internals, strong plastic handle, and anodized aluminium firing head and locking ring



Economy Kit
TH6-10-EL-7

Primary Applications

Workshops and mobile service vehicles

Restrictions

5 micron filter and regulator with gauge are strongly suggested

Technical / Order Data

Ultra Clean Kit TH 6-10-EL-7 with case, launcher in size -20, nozzles in size -4, -6, -8, -10, -12, -16 and -20 (1 each)

Air pressure	min. 0.55 MPa
	max. 0.75 MPa
Air connection	1/2“ I.D. air hose
Dimensions	L 407 x W 134 x H 343 mm
Weight	4 kg
Part Number	**TH6-10-EL-7**

Nozzles and Projectiles for Ultra Clean Kit TH6-10-EL-7

Hose Size	Nozzle **Part Number**	Projectile **Part Number**
-4	**TH6-10-H06**	**TH6-10-P10**
-5	**TH6-10-H08**	**TH6-10-P12**
-6	**TH6-10-H10**	**TH6-10-P14**
-8	**TH6-10-H13**	**TH6-10-P18**
-10	**TH6-10-H16**	**TH6-10-P22**
-12	**TH6-10-H19**	**TH6-10-P26**
-16	**TH6-10-H25**	**TH6-10-P33**
-20	**TH6-10-H32**	**TH6-10-P40**

TH 6-10-HL-9-2

Ultra Clean Kit

- Cleaning of hoses from ..... size -4 up to -32
- Reduces downtime and risk of hose failure
- Full-flow quick release coupling and unique 360° rotary plug for proper air flow and non-fatigue operator use
- Aluminium, fully anodized for harsh environments and heavy use
- Unique safety release bar that locks the faceplate into a closed position for firing Ultra Clean projectiles



Standard Kit
TH6-10-HL-9-2

Primary Applications

Workshops and mobile service vehicles

Restrictions

5 micron filter and regulator with gauge are strongly suggested

Technical / Order Data

Ultra Clean Kit TH 6-10-HL-9-2 with case, launcher in size -32, nozzles in size -4, -6, -8, -10, -12, -16, -20, -24 and -32 (1 each)

Air pressure	min. 0.55 MPa
	max. 0.75 MPa
Air connection	1/2“ I.D. air hose
Dimensions	L 407 x W 134 x H 343 mm
Weight	5 kg
Part Number	**TH6-10-HL-9-2**

Nozzles and Projectiles for Ultra Clean Kit TH6-10-HL-9-2

Hose Size	Nozzle **Part Number**	Projectile **Part Number**
-4	**TH6-10-H06**	**TH6-10-P10**
-5	**TH6-10-H08**	**TH6-10-P12**
-6	**TH6-10-H10**	**TH6-10-P14**
-8	**TH6-10-H13**	**TH6-10-P18**
-10	**TH6-10-H16**	**TH6-10-P22**
-12	**TH6-10-H19**	**TH6-10-P26**
-16	**TH6-10-H25**	**TH6-10-P33**
-20	**TH6-10-H32**	**TH6-10-P40**
-24	**TH6-10-H38**	**TH6-10-P50**
-32	**TH6-10-H50**	**TH6-10-P60**

TH 5-3

Hose Assembly Test Bench up to 145.0 MPa

- Totally sealed test chamber
- Safety interlock – pressure automatically decreases within 1/10 sec. when the test chamber is opened
- Rapid fill and automatic air bleeding of the test piece
- Weight-compensated protection cover with safety windows
- Bio-degradable water-oil emulsion as test medium
- Simple operation



Primary Applications

Service and series production in workshops.
The hose assembly test bench makes the efficient and safe final inspection of hose assemblies practical and fast. Static pressure testing of other hydraulic components is also possible.

Restrictions

This test bench is not designed for burst pressure testing. Due to the limited flexibility of large bore multispiral hoses it is not ideal for size -24 and size -32 pressure testing.

Technical / Order Data

Hose Assembly Test Bench TH 5-3 incl. HD adapter set	Test pressure		12.0 - 145.0 MPa
	Drive		intensifier
	Compressed air rating		0.7 MPa, 20 Nl/min
	Pressure regulator		manual
	Test medium		water-oil emulsion
	Safety control unit		yes
	Tank capacity		100 l
	Colour		black / silver
	Dimensions		L 2210 x W 840 x H 1260 mm
	Weight	empty	210 kg
		with medium	310 kg
	Accessories		filter 100 µm, air service unit
	Part Number		**TH5-3**
Hose Assembly Test Bench TH 5-3 with result recording unit	**Part Number**		**TH5-3-BM**
HD adapter set	**Part Number**		**405.906**
Corrosion protection, 10 l	**Part Number**		**H899770**

TH 7-12

7-stage hose reel

- Seven-stage reel for hoses from size -4 up to -20
- Every stage (except bottom stage) can be swung out horizontally so that new rolls can easily be inserted



Technical / Order Data

Hose Reel TH 7-12
for service and series production in workshops

Reel dimensions	
Int. Ø min. / max.	250 mm / 1010 mm
Height max.	300 mm
Max. load per reel	80 kg
Colour	zinc plated
Dimensions	L 1270 x W 1000 x H 2230 mm
Weight	148 kg
Part Number	**TH7-12**

TH 7-13

1-stage hose reel

- One-stage reel for hoses from ....size -4 up to -32
- Table adjustable to fit the center of the coil



Technical / Order Data


Hose Reel TH 7-13
for service and series production in workshops

Reel dimensions	
Int. Ø min. / max.	adjustable 150 - 500 mm
Max. load of reel	500 kg
Colour	zinc plated / grey
Dimensions	L 1200 x W 1200 x H 830 mm
Weight	40 kg
Part Number	**TH7-13**

TH 7-14

Horizontal motorized hose reel

- Motorized reel for hoses from .....size -4 up to -32
- Variable speed control in both directions
- Ideal for cutting long lengths where coiling is neccessary



Technical / Order Data


Hose Reel TH 7-14
for service and series production in workshops

Reel dimensions	
Int. Ø min. / max.	adjustable 150 - 500 mm
Max. load of reel	500 kg
Electric power	230 V / 10 A / 50 Hz
Colour	zinc plated / light grey
Dimensions	W 1200 x H 830 mm
Weight	65 kg
Part Number	**TH7-14**

TH 7-15

Vertical motorized hose reel

- Motorized reel for hoses from .....size -4 up to -20
- Variable speed control in both directions
- Ideal for cutting long lengths where coiling is neccessary
- Very easy to unload



Technical / Order Data

Hose Reel TH 7-15
for service and series production in workshops

Reel dimensions	
Int. Ø min. / max.	adjustable 250 - 800 mm
Max. load of reel	100 kg
Electric power	230 V / 10 A / 50 Hz
Colour	zinc plated
Dimensions	W 600 x H 1400 mm
Weight	75 kg
Part Number	**TH7-15**

TH 8E-530, TH 8E-535-BM

Strong Crimping Press

- Crimps
  – all Parker *No-Skive* fittings ..... up to size -32
- Easy installation on the workbench in the workshop area or in the van
- For die sets series 239L and 266 (adapter die set PB266.239L required)



Primary Applications

Hose assembly workshops with small series production and services at certified distributors, ParkerStores and hose workshops in the maintenance areas at OEM customers

Restrictions

Not for ParLock hose fittings in size -20, -24 and -32 (fittings series V4 and V6).

All TH 8E-530 and TH 8E-535 with – adapter die set PB266.239L – die set packet (14 mm – 74 mm) PBSET-TH8E-53X – quick change tool QDC239.3 Attention: Delivery without oil or connecting plug	Crimp force	200 t
	Crimp range	94 mm
	Noise level	69 dBA
	Colour	black/silver
TH 8E-530	Electrical power	400 V / 50 Hz / 3 PH / 4 kW
	Control system	micrometer
	Dimensions	L 700 x W 600 x H 735 mm
	Oil quantity	50 l
	Weight	248 kg
	Part Number	**TH8E-530**
TH 8E-530-BM	Electrical power	400 V / 50 Hz / 3 PH / 4 kW
	Control system	B-Touch
	Dimensions	L 700 x W 600 x H 735 mm
	Oil quantity	50 l
	Weight	255 kg
	Part Number	**TH8E-530-BM**
TH 8E-530-12VDC	Electrical power	12 V DC
	Control system	micrometer
	Part Number	**TH8E-530-12VDC**
TH 8E-535-BM	Electrical power	400 V / 50 Hz / 3 PH / 5.5 kW
	Control system	B-Touch
	Dimensions	L 690 x W 600 x H 1053 mm
	Oil quantity	55 l
	Weight	375 kg
	Part Number	**TH8E-535-BM**
Adapter die set	**Part Number**	**PB266.239L**
Die rack	**Part Number**	**QDS239S**
Die set packet, diameter from 14 – 74 mm	**Part Number**	**PBSET-TH8E-53X**
Quick change tool	**Part Number**	**QDC239.3**

TH 8-800-BM

Strong Crimping Press

- Crimps
  – all Parker *No-Skive* fittings ..... up to size -32
  – Industrial hose ..... up to 4" (DN 100)
  – SAE 100 R13 / SAE 100 R15 hose with Parker *No-Skive* fittings ..... up to size -32
  – SAE 100 R15 hose with ParLock fittings V4 and V6 ... up to size -20
- Adjustable crimper electronic system B and 3 different crimp programs, manual opening and closing, semi-automatic opening and closing, semi-automatic opening and closing with foot switch or depth stop
- It is possible to crimp small diameters with an adapter die set



Primary Applications

Hose assembly workshops with small series production and services at certified distributors, ParkerStores and hose workshops in the maintenance areas at OEM customers

Restrictions

Not for ParLock hose fittings in size -24 and size-32 (fittings series V4 and V6).
There could be interference with long drop elbow fittings.

Technical / Order Data

Crimping Press TH 8-800-BM with
– adapter die set PB237.239.2L2
– quick change tool QDC239.3
– die set packet (12 mm – 74 mm) PBSET-TH8-800

Attention: Delivery without oil or connecting plug

	Electrical power		400 V / 50 Hz / 3 PH / 4 kW
	Crimp force		220 t
	Control system		B-Touch
	Crimp range		139 mm
	Noise level		69 dB (A)
	Colour		black/silver
	Dimensions		L 690 x W 600 x H 1400 mm
	Oil tank capacity		55 l
	Weight	without oil	390 kg
		with oil	445 kg
	Part Number		**TH8-800-BM**
Adapter die set	**Part Number**		**PB237.239.2L2**
Depth stop	**Part Number**		**TA800/A**
Die rack	**Part Number**		**QDS239S**
Die set packet, diameter from 12 – 74 mm	**Part Number**		**PBSET-TH8-800**
Foot switch	**Part Number**		**FU-HMX**
Mirror set	**Part Number**		**SHS-800**
Quick change tool	**Part Number**		**QDC239.3**

TH 8E-380-BM

Heavy-Duty Crimping Press

- Crimps
  - all Parkrimp and ParLock hose types including 4 and 6 spiral steel wire
  - DIN 4SP/4SH, SAE 100 R13 / R15 Multispiral hoses ..... up to size -32
  - all Parker industrial hoses ..... up to 4" (DN 100)



Primary Applications

Heavy-duty crimper for crimping multispiral hoses in workshops for series production. Suitable for all standard Parker hoses.

Restrictions

Special hose assemblies with 2 elbows in extremly long version.

Technical / Order Data

	Electrical power	400 V / 50 Hz / 3 PH / 5.5 kW
TH 8E-380-BM with • Adapter die set package PB237.239.2L2 • Quick change tool QDC239.3 • Die set package PBSET-TH8-380 For V4 and V6 fittings above size -16 long die sets are required (e.g. PB 237L-57) Attention: Delivery without oil and connecting plug	Crimp force	340 t
	Control system	Control B + Touch
	Crimp range	161 mm
	Type of dies	237L / 239L
	Open / Close speed	23 mm/s
	Noise level	69 dB (A)
	Dimensions	L 1600 x W 600 x H 1600 mm
	Weight without oil / with oil	750 kg / 840 kg
	Part Number	**TH8E-380-BM**
Adapter die set package 237/239L	**Part Number**	**PB237.239.2L2**
Depth Stop Automatic	**Part Number**	**TA380/A**
Die rack	**Part Number**	**QDS239S**
Die set package PB 239L Ø 14, 17, 20, 24, 28, 32, 36, 40, 44, 50 PB 237L Ø 54, 57, 62, 67, 71, 74, 78	**Part Number**	**PBSET-TH8E-380**
Die set package optional PB 237L Ø 84, 86, 90, 96, 103, 106, 111, 116, 121, 126, 131		**PBSET-237L-IH**
Foot switch	**Part Number**	**FU-HMX**
Mirror set	**Part Number**	**SHS310/370**
Quick change tool	**Part Number**	**QDC239.3**
Workplace lamp	**Part Number**	**TH8-LUS**

TH 8E-480-BM

Heavy-Duty Crimping Press

- Crimps
  - all Parkrimp and ParLock hose types including 4 and 6 spiral steel wire
  - DIN 4SP/4SH, SAE 100 R13 / R15 Multispiral hoses ..... up to size -48
  - all Parker industrial hoses ..... up to 8”
- Compact design
- Safe positioning on the fixed 6 o´clock die
- Slide bearings on the crimp tool, no service and 20% less friction



Primary Applications

Heavy Duty Crimping Press for service and series production at workshops

Technical / Order Data

TH 8E-480-BM with
• Quick change tool QDC239.3

Attention: Delivery without oil and connecting plug

	Electrical power	220-480 V / 50/60 Hz / 3 PH / 5.5 kW
	Crimp force	450 t
	Control system	B-Touch
	Crimp range	310 mm
	Open speed	20 mm/s
	Crimp speed	1.5 mm/s
	Close speed	23 mm/s
	Noise level	62 dB (A)
	Dimensions	L 730 x W 1590 x H 2015 mm
	Weight without oil	2600 kg
	Oil capacity	300 l
	Part Number	**TH8E-480-BM**
Adapter die set PB245.237L	**Part Number**	**PB245.237L**
Adapter die set PB237.239.2L2	**Part Number**	**PB237.239.2L2**
Quick change tool	**Part Number**	**QDC239.3**
Workplace lamp	**Part Number**	**TH8-LUS**

TH 2-9

Hose Skiving Machine

- Efficient skiving of hydraulic hoses (external and internal) from .....size -4 up to -32
- Easily controlled by a footpedal
- Waste collection bin



Primary Applications

For small series and service application.

Restrictions

Not recommended for series production.

Technical / Order Data

Hose Skiving Machine TH 2-9 without skiving tools	Hose capacity, external skiving	
	4 and 6 layer	size -4 up to -32
	Hose capacity, internal skiving	
	4 and 6 layer	size -6 up to -32
	Speed	125 rpm
	Colour	light grey
	Dimensions	L 600 x W 410 x H 390 mm
	Weight	35 kg
Hose Skiving Machine TH 2-9-3PH 3 phases, 400 V	Electrical power	3 PH / 400 V / 50 Hz / 16 A / 0.37 kW
	Part Number	**TH2-9-3PH**
Hose Skiving Machine TH 2-9-1PH 1 phase, 230 V	Electrical power	1 PH / 230 V / 50 Hz / 10 A / 0.37 kW
	Part Number	**TH2-9-1PH**



Internal skiving tool



External skiving tool
with one external tool

Skiving tools see page ***Ea-29***

TH 2-10-3PH

Hose Skiving Machine

- Efficient skiving of hydraulic hoses (external and internal) from .....size -4 up to -32
- Semi-automatic electro-pneumatic control-system
- Adjustable pressure and speed
- Automatic self-centering system
- Waste collection bin



Primary Applications

Mainly for hose assembly workshop production for medium and large series.

Restrictions

Work cycle for internal and external skiving takes place separately, not in one step.

Technical / Order Data

Hose Skiving Machine TH 2-10-3PH
without skiving tools

Hose capacity, external skiving	
4 and 6 layer	size -4 up to -32
Hose capacity, internal skiving	
4 and 6 layer	size -6 up to -32
Speed	315 rpm
Air pressure	min. 0.7 MPa
Colour	light grey
Electrical power	3 PH / 400 V / 50 Hz / 16 A / 1.2 kW
Dimensions	L 680 x W 1200 x H 1080 mm
Weight	132 kg
Part Number	**TH2-10-3PH**



Internal skiving tool



External skiving tool
with two external tools

Skiving tools see page ***Ea-29***

TH 2-13-3PH

Twin-Skive Machine

- Twin-skiving of hydraulic hoses (external and internal) from .....size -4 up to -32 in one operation
- Semi-automatic electro-pneumatic control-system
- Automatic self-centring system
- Adjustable pressure and speed
- Waste collection bin
- Eliminates work-related injuries



Primary Applications

For hose assembly workshops for series production.


Restrictions

Max. hose outside diameter 75 mm for external skiving.

Technical / Order Data

Hose Skiving Machine TH 2-13-3PH
without skiving tools

Hose capacity, external skiving	
4 and 6 layer	size -4 up to -32
Hose capacity, internal skiving	
4 and 6 layer	size -6 up to -32
Speed	400 / 315 rpm
Air pressure	min. 0.7 MPa
Colour	light grey
Electrical power	3 PH / 400 V / 50 Hz / 16 A / 2 x 0.75
Dimensions	L 680 x W 1200 x H 1080 mm
Weight	150 kg
Part Number	**TH2-13-3PH**



Skiving tool

Skiving tools see page ***Ea-29***

Skiving Tools for TH 2-9, TH 2-10-3PH and TH 2-13-3PH

Internal skiving tool for TH 2-9 and TH 2-10-3PH

Internal skiving tool
TH 2-9 and TH 2-10-3PH




A: Internal skiving knife

Size	Internal skiving tool (without knife) **Part Number**	Internal skiving knife **Part Number**
-10	**TH2-12NT-10**	**TH2-12NK-1012**
-12	**TH2-12NT-12**	
-16	**TH2-12NT-16**	**TH2-12NK-1620**
-20	**TH2-12NT-20**	
-24	**TH2-12NT-24**	**TH2-12NK-2432**
-32	**TH2-12NT-32**	

External skiving tool for TH 2-9 and TH 2-10-3PH


External skiving tool
TH 2-9 and TH 2-10-3PH



A: External skiving tool holder
B: Mandrel for external skiving
C: Holder for skiving tool
D: External skiving knife

Size	Mandrel Size **Part Number**	External skiving tool (without knife) **Part Number**	Additional arm **Part Number**	External skiving knife **Part Number**
-4	**TH2-11M-4**	short arm **TH2-11ES**	short arm **TH2-11ES-1** TH2-10-3PH only	**TH2-11EK**
-6	**TH2-11M-6**			
-8	**TH2-11M-8**			
-10	**TH2-11M-10**			
-12	**TH2-11M-12**			
-16	**TH2-11M-16**	long arm **TH2-11EL**	long arm **TH2-11EL-1** TH2-10-3PH only	
-20	**TH2-11M-20**			
-24	**TH2-11M-24**			
-32	**TH2-11M-32**			

Internal and external skiving tool for TH 2-13-3PH




Skiving tool
A: Tooling holder complete
B: Mandrel for internal skiving
C: Holder for external skiving knife
D: External skiving knife
E: Internal skiving knife

Internal and external skiving tool
TH 2-13-3PH

Size	Mandrel Size **Part Number**	Internal skiving knife **Part Number**	External skiving toolholder **Part Number**	Additional arm **Part Number**	External skiving knife **Part Number**
-8	**TH2-13M-8**	**TH2-12NK-8**	**TH2-13ET**	short arm **TH2-13ES-1**	**TH2-11EK**
-10	**TH2-13M-10**	**TH2-12NK-1012**			
-12	**TH2-13M-12**				
-16	**TH2-13M-16**	**TH2-12NK-1620**		long arm **TH2-13EL-1**	
-20	**TH2-13M-20**				
-24	**TH2-13M-24**	**TH2-12NK-2432**			
-32	**TH2-13M-32**				

Flange Halves



M1H – ISO 6162-1 Flange Half – Standard Series

(for use with 15, 17 and 19 flanges)

Part Number	Flange			A	B	C	max. dynamic working pressure	
	DN	Inch	Size	mm	mm	mm	MPa	psi
M1H-8	13	1/2	-8	38.1	8.8	8.9	34.5	5000
M1H-12	19	3/4	-12	47.6	11.1	10.6	34.5	5000
M1H-16	25	1	-16	52.4	13.1	10.6	34.5	5000
M1H-20	32	1-1/4	-20	58.7	15.1	10.6	28.0	4000
M1H-24	38	1-1/2	-24	69.9	17.9	13.3	21.0	3000
M1H-32	51	2	-32	77.8	21.5	13.5	21.0	3000
M1H-40	64	2-1/2	-40	88.9	25.4	13.5	17.5	2538
M1H-48	76	3	-48	106.4	31.0	16.7	16.0	2321
M1H-56	89	3-1/2	-56	120.7	35.0	16.7	3.5	508
M1H-64	102	4	-64	130.2	38.9	16.7	3.5	508
M1H-80	127	5	-80	152.4	46.1	16.7	3.5	508

50H – ISO 6162-1 Flange Half 5000 psi

(for use with 4A, 4F and 4N flanges)

Part Number	Flange			A	B	C	max. dynamic working pressure	
	DN	Inch	Size	mm	mm	mm	MPa	psi
50H-20	32	1-1/4	-20	58.7	15.1	12.0	34.5	5000
50H-24	38	1-1/2	-24	69.9	17.9	13.5	34.5	5000
50H-32	51	2	-32	77.8	21.5	13.5	34.5	5000

M2H – ISO 6162-2 Flange Half 6000 psi

(for use with 6A, 6F and 6N flanges)

Part Number	Flange			A	B	C	max. dynamic working pressure	
	DN	Inch	Size	mm	mm	mm	MPa	psi
M2H-8	13	1/2	-8	40.5	9.1	8.9	42.0	6000
M2H-12	19	3/4	-12	50.8	11.9	10.6	42.0	6000
M2H-16	25	1	-16	57.2	13.9	13.0	42.0	6000
M2H-20	32	1-1/4	-20	66.7	15.9	13.0	42.0	6000
M2H-24	38	1-1/2	-24	79.4	18.2	16.7	42.0	6000
M2H-32	51	2	-32	96.8	22.2	20.6	42.0	6000
M2H-40	64	2-1/2	-40	123.8	29.3	25.0	42.0	6000
M2H-48	76	3	-48	152.4	35.7	31.0	42.0	6000

8FH – ISO 6162-2 Flange Half 8000 psi

(for use with 8A, 8F and 8N flanges)

Part Number	Flange			A	B	C	max. dynamic working pressure	
	DN	Inch	Size	mm	mm	mm	MPa	psi
8FH-12-SM	19	3/4	-12	50.8	11.9	11.0	56.0	8000
8FH-16-SM	25	1	-16	57.2	13.9	13.0	56.0	8000
8FH-20-SM	32	1-1/4	-20	66.7	15.9	13.0	56.0	8000
8FH-20-SM-M14	32	1-1/4	-20	66.7	15.9	15.0	56.0	8000

Bolts for Flange Halves ISO 6162-1

M1H – ISO 6162-1 Flange Half – Standard Series

(for use with 15, 17 and 19 flanges)

Part Number	DN	Inch	Size	G Thread metric *Inch*	A mm *Inch*	max. dynamic working pressure MPa	psi
ZYLS8X25VZX	13	1/2	-8	M8x1.25	25	34.5	5000
UNC5/16-18X11/4	13	1/2	-8	*UNC5/16-18*	*11/4*	34.5	5000
ZYLS10X30VZX	19	3/4	-12	M10x1.5	30	34.5	5000
UNC3/8-16X11/4	19	3/4	-12	*UNC3/8-16*	*11/4*	34.5	5000
ZYLS10X30VZX	25	1	-16	M10x1.5	30	34.5	5000
UNC3/8-16X11/4	25	1	-16	*UNC3/8-16*	*11/4*	34.5	5000
ZYLS10X30VZX	32	1-1/4	-20	M10x1.5	30	28.0	4000
UNC7/16-14X11/2	32	1-1/4	-20	*UNC7/16-14*	*11/2*	28.0	4000
ZYLS12X35VZX	38	1-1/2	-24	M12x1.75	35	21.0	3000
UNC1/2-13X11/2	38	1-1/2	-24	*UNC1/2-13*	*11/2*	21.0	3000
ZYLS12X35VZX	51	2	-32	M12x1.75	35	21.0	3000
UNC1/2-13X11/2	51	2	-32	*UNC1/2-13*	*11/2*	21.0	3000
ZYLS12X40VZX	64	2-1/2	-40	M12x1.75	40	17.5	2538
UNC1/2-13X13/4	64	2-1/2	-40	*UNC1/2-13*	*13/4*	17.5	2538
ZYLS16X50VZX	76	3	-48	M16x2	50	16.0	2321
UNC5/8-11X13/4	76	3	-48	*UNC5/8-11*	*13/4*	16.0	2321
ZYLS16X50VZX	89	3-1/2	-56	M16x2	50	3.5	508
UNC5/8-11X2	89	3-1/2	-56	*UNC5/8-11*	*2*	3.5	508
ZYLS16X50VZX	102	4	-64	M16x2	50	3.5	508
UNC5/8-11X2	102	4	-64	*UNC5/8-11*	*2*	3.5	508
ZYLS16X55VZX	127	5	-80	M16x2	55	3.5	508
UNC5/8-11X21/4	127	5	-80	*UNC5/8-11*	*21/4*	3.5	508

- metric bolts according to ISO 4762-10.9 (DIN 912-10.9)
- UNC bolts according to ANSI / ASME B18.3

50H – ISO 6162-1 Flange Half 5000 psi

(for use with 4A, 4F and 4N flanges)

Part Number	DN	Inch	Size	G Thread metric *Inch*	A mm *Inch*	max. dynamic working pressure MPa	psi
-	32	1-1/4	-20	-	-	34.5	5000
UNC7/16-14X11/2	32	1-1/4	-20	*UNC7/16-14*	*11/2*	34.5	5000
-	38	1-1/2	-24	-	-	34.5	5000
UNC1/2-13X11/2	38	1-1/2	-24	*UNC1/2-13*	*11/2*	34.5	5000
-	51	2	-32	-	-	34.5	5000
UNC1/2-13X11/2	51	2	-32	UNC1/2-13	11/2	34.5	5000

- metric bolts according to ISO 4762-10.9 (DIN 912-10.9)
- UNC bolts according to ANSI / ASME B18.3

Assembly torque see page **Ab-24**

Bolts for Flange Halves ISO 6162-2

M2H – ISO 6162-2 Flange Half 6000 psi

(for use with 6A, 6F and 6N flanges)

Part Number	DN	Inch	Size	G Thread metric *Inch*	A mm *Inch*	max. dynamic working pressure MPa	psi
ZYLS8X25VZX	13	1/2	-8	M8x1.25	25	42.0	6000
UNC5/16-18X11/4	13	1/2	-8	*UNC5/16-18*	*1-1/4*	42.0	6000
ZYLS10X35VZX	19	3/4	-12	M10x1.5	35	42.0	6000
UNC3/8-16X11/2	19	3/4	-12	*UNC3/8-16*	*1-1/2*	42.0	6000
ZYLS12X45VZX	25	1	-16	M12x1.75	45	42.0	6000
UNC7/16-14X13/4	25	1	-16	*UNC7/16-14*	*1-3/4*	42.0	6000
ZYLS12X45VZX	32	1-1/4	-20	M12x1.75	45	42.0	6000
UNC1/2-13X13/4	32	1-1/4	-20	*UNC1/2-13*	*1-3/4*	42.0	6000
ZYLS16X55VZX	38	1-1/2	-24	M16x2	55	42.0	6000
UNC5/8-11X21/4	38	1-1/2	-24	*UNC5/8-11*	*2-1/4*	42.0	6000
ZYLS20X65VZX	51	2	-32	*M20x2.5*	*65*	42.0	6000
UNC3/4-10X23/4	51	2	-32	*UNC3/4-10*	*2-3/4*	42.0	6000
ZYLS24X75VZX	64	2-1/2	-40	M24x3	75	42.0	6000
-	64	2-1/2	-40	-	-	42.0	6000
ZYLS30X90VZX	76	3	-48	M30x3.5	90	42.0	6000
-	76	3	-48	-	-	42.0	6000

- metric bolts according to ISO 4762-10.9 (DIN 912-10.9)
- UNC bolts according to ANSI / ASME B18.3

8FH – ISO 6162-2 Flange Half 8000 psi

(for use with 8A, 8F and 8N flanges)

Part Number	DN	Inch	Size	G Thread metric *Inch*	A mm *Inch*	max. dynamic working pressure MPa	psi
-	19	3/4	-12	M10x1.5	45	56.0	8000
-	25	1	-16	M12x1.75	50	56.0	8000
-	32	1-1/4	-20	M12x1.75	50	56.0	8000
-	32	1-1/4	-20	M14x2	50	56.0	8000
-	51	2	-32	-	-	34.5	5000

- metric bolts according to ISO 4762-10.9 (DIN 912-10.9)
- UNC bolts according to ANSI / ASME B18.3

Assembly torque see page **Ab-25**

Full Flange System

Provides full flange mounting option for ISO 6162-1 (35.0 MPa/5000 psi) and ISO 6162-2 (42.0 MPa/ 6000 psi) flanges – system flexibility reduces inventory investment.



Once the hose fitting is crimped to the hose, the flange is placed over the fitting end and then is held in place with the retaining ring. When the flange engages the retaining ring, the flange is held securely and is ready to be bolted to the port. Installation to the port is easy – there is no fumbling with the flange halves, and the flange can be rotated for ease of assembly to the port. The full flange system can be used repeatedly because of its patent-pending attachment system – the flange is not permanently locked onto the fitting.

Flange System

ISO 6162-1 (35.0 MPa/ 5000 psi)*

SAE Flange Size	max. dynamic working pressure		Flange	Seal	Retaining Ring
Inch	MPa	psi	Part Number	Part Number	Part Number
3/4	35.0	5000	R-312-CFX	XRG-12	R12X
1	35.0	5000	R-316-CFX	XRG-16	R16X
1 1/4	35.0	5000	R-320-CFX	XRG-20	R20X
1 1/2	35.0	5000	R-324-CFX	XRG-24	R24X
2	35.0	5000	R-332-CFX	XRG-32	R32X
2 1/2	35.0	5000	R-340-CFX	XRG-40	R40X
3	21.0	3000	R-348-CFX	XRG-48	R48X

Flange System

ISO 6162-2 (42.0 MPa/ 6000 psi)*

SAE Flange Size	max. dynamic working pressure		Flange	Seal	Retaining Ring
Inch	MPa	psi	Part Number	Part Number	Part Number
3/4	42.0	6000	R-612-CFX	XRG-12	R12X
1	42.0	6000	R-616-CFX	XRG-16	R16X
1 1/4	42.0	6000	R-620-CFX	XRG-20	R20X
1 1/2	42.0	6000	R-624-CFX	XRG-24	R24X
2	42.0	6000	R-632-CFX	XRG-32	R32X
2 1/2	35.0	5000	R-640-CFX	XRG-40	R40X
3	21.0	3000	R-648-CFX	XRG-48	R48X

* 2 1/2 inch max. 35.0 MPa/ 5000 psi
3 inch max. 21.0 MPa/ 3000 psi

The stainless steel retaining rings and O-rings are recommended for one-time use.

Bolts for Full Flange System ISO 6162

ISO 6162-1 Retaining Ring Flange System

(for use with X5, X7 and X9 flanges)

Part Number	Flange Part Number	SAE Flange Size Inch	G Thread metric *Inch*	A mm *Inch*	max. dynamic working pressure MPa	psi
ZYLS10X40VZX	R-312-CFX	3/4	M10x1.5	40	35.0	5000
UNC3/8-16X11/4	R-312-CFX	3/4	*UNC3/8-16*	*1-1/4*	*35.0*	5000
ZYLS10X40VZX	R-316-CFX	1	M10x1.5	40	35.0	5000
UNC3/8-16X11/4	R-316-CFX	1	*UNC3/8-16*	*1-1/4*	*35.0*	5000
ZYLS10X40VZX	R-320-CFX	1-1/4	M10x1.5	40	28.0	4000
UNC7/16-14X11/2	R-320-CFX	1-1/4	*UNC7/16-14*	*1-1/2*	*28.0*	4000
ZYLS12X50VZX	R-324-CFX	1-1/2	M12x1.75	50	28.0	4000
UNC1/2-13X11/2	R-324-CFX	1-1/2	*UNC1/2-13*	*1-1/2*	*28.0*	4000
ZYLS12X55VZX	R-332-CFX	2	M12x1.75	55	28.0	4000
UNC1/2-13X11/2	R-332-CFX	2	*UNC1/2-13*	*1-1/2*	*28.0*	4000
ZYLS12X65VZX	R-340-CFX	2-1/2	M12x1.75	65	21.0	3000
UNC1/2-13X13/4	R-340-CFX	2-1/2	*UNC1/2-13*	*1-3/4*	*21.0*	3000
ZYLS16X80VZX	R-348-CFX	3	M16x2	80	21.0	3000
UNC5/8-11X13/4	R-348-CFX	3	*UNC5/8-11*	*1-3/4*	21.0	3000

- metric bolts according to ISO 4762-10.9 (DIN 912-10.9)
- UNC bolts according to ANSI / ASME B18.3

ISO 6162-2 Retaining Ring Flange System


(for use with X5, X7 and X9 flanges)

Part Number	Flange Part Number	SAE Flange Size Inch	G Thread metric *Inch*	A mm *Inch*	max. dynamic working pressure MPa	psi
ZYLS10X45VZX	R-612-CFX	3/4	M10x1.5	45	42.0	6000
UNC3/8-16X11/2	R-612-CFX	3/4	*UNC3/8-16*	*1-1/2*	42.0	6000
ZYLS12X45VZX	R-616-CFX	1	M12x1.75	45	42.0	6000
UNC7/16-14X11/2	R-616-CFX	1	*UNC7/16-14*	*1-1/2*	42.0	6000
ZYLS14X50VZX	R-620-CFX	1-1/4	M14x2	50	42.0	6000
UNC1/2-13X13/4	R-620-CFX	1-1/4	*UNC1/2-13*	*1-3/4*	42.0	6000
ZYLS16X60VZX	R-624-CFX	1-1/2	M16x2	60	42.0	6000
UNC5/8-11X21/4	R-624-CFX	1-1/2	*UNC5/8-11*	*2-1/4*	42.0	6000
ZYLS20X70VZX	R-632-CFX	2	M20x2.5	70	42.0	6000
UNC3/4-10X23/4	R-632-CFX	2	*UNC3/4-10*	*2-3/4*	42.0	6000
ZYLS24X90VZX	R-640-CFX	2-1/2	M24x3	90	42.0	6000
-	R-640-CFX	2-1/2	-	-	42.0	6000
ZYLS30X100VZX	R-648-CFX	3	M30x3.5	100	42.0	6000
-	R-648-CFX	3	-	-	42.0	6000

- metric bolts according to ISO 4762-10.9 (DIN 912-10.9)
- UNC bolts according to ANSI / ASME B18.3

Assembly torque see page **Ab-24, Ab-25**

Banjo Bolt



AM/AR – Banjo Bolt (DIN 7643)

Single Part Number	Double Part Number	I.D. Banjo mm	G Thread metric *Inch*	L Single mm	L1 Double mm	H mm
AM-03	A2M3	8	M8x1	17	26	12
AM-04	A2M4	10	M10x1	19	30	14
AR-04		10	*1/8*	19		14
AM-06	A2M6	12	M12x1.5	24	38	17
AM-08	A2M8	14	M14x1.5	26	41	19
AR-08		14	*1/4*	26		19
AR-08C		14	*1/4*	26		19
AM-10	A2M10	16	M16x1.5	28	46	22
AR-10		17	*3/8*	29		22
AM-13		18	M18x1.5	32		24
AM-16		22	M22x1.5	39		27
AR-16		22	*1/2*	39		27
AM-20		26	M26x1.5	45		32
AR-20		27	*3/4*	45		32



Complete banjo fitting

853009 – Copper Ring (Form A DIN 7603)

Copper Ring Part Number	I.D. Banjo mm	G Thread metric *Inch*
853009-8	8	M8x1
853009-10	10	M10x1
853009-10	10	*1/8*
853009-12	12	M12x1.5
853009-14	14	M14x1.5
853009-14	14	*1/4*
853009-16	16	M16x1.5
853009-17	17	*3/8*
853009-18	18	M18x1.5
853009-21	21	*1/2*
853009-22	22	M22x1.5
853009-26	26	M26x1.5

Banjo fitting, bolt, double bolt, copper ring



O-Rings

Fittings are supplied with O-rings made from ozone-resistant Nitrile (NBR) rubber compound suitable for temperatures — from -40 °C up to +120 °C

On request: Viton® (FPM) compound — from -25 °C up to +200 °C

Ethylene-Propylene (EPDM) compound — from -55 °C up to +150 °C

711509 – O-rings for SAE fittings (05 end configuration)

O-Ring	D	W	Thread UNF	
Part Number	mm	mm	UNF	Size
711509-1	8.92	1.83	7/16x20	-4
711509-2	10.52	1.83	1/2x20	-5
711509-3	11.89	1.98	9/16x18	-6
711509-4	16.36	2.21	3/4x16	-8
711509-5	19.18	2.45	7/8x14	-10
711509-6	23.47	2.95	1-1/16x12	-12
711509-7	29.74	2.95	1-5/16x12	-16
711509-8	37.47	3.00	1-5/8x12	-20

2-0 – O-rings for ORFS male (JD and JM end configuration)

O-Ring	D	W	Thread UNF	
Part Number	mm	mm	UNF	Size
2-011N552-90	7.65	1.78	9/16x18	-4
2-012N552-90	9.25	1.78	11/16x16	-6
2-014N552-90	12.42	1.78	13/16x16	-8
2-016N552-90	15.60	1.78	1x14	-10
2-018N552-90	18.77	1.78	1-3/16x12	-12
2-021N552-90	23.52	1.78	1-7/16x12	-16
2-025N552-90	29.87	1.78	1-11/16x12	-20
2-029N552-90	37.82	1.78	2x12	-24

EARG/VURG/VERG – O-rings for BSP fittings

O-Ring	D	W	Thread BSP	
Part Number	mm	mm	BSP	Size
EARG-4	6.0	1.0	1/4x19	-4
C9RG-10	8.5	1.5	3/8x19	-6
VURG-4	12.0	1.5	1/2x14	-8
EARG-10	13.1	1.6	5/8x14	-10
VERG-14	17.0	1.5	3/4x14	-12
VERG-19	21.0	1.5	1x11	-16
EARG-20	29.5	1.5	1-1/4x11	-20

O-Rings

2-2 – O-rings for SAE flanges

O-Ring Part Number	D mm	W mm	Flange Inch	Flange Size
2-210N552-90	18.64	3.53	*1/2*	-8
2-214N552-90	24.99	3.53	*3/4*	-12
2-219N552-90	32.92	3.53	*1*	-16
2-222N552-90	37.69	3.53	*1 1/4*	-20
2-225N552-90	47.22	3.53	*1 1/2*	-24
2-228N552-90	56.74	3.53	*2*	-32
2-232N552-90	69.44	3.53	*2 1/2*	-40
2-237N552-90	85.32	3.53	*3*	-48

CARG – O-rings for metric 24° female swivel hose-end fittings

O-Ring Part Number	D mm	W mm	Light series metric	Heavy series metric	Tube O.D. mm
CARG-6	4.5	1.5	M12x1.5	M14x1.5	6
C9RG-8	6.5	1.5	M14x1.5	M16x1.5	8
C9RG-10	8.5	1.5	M16x1.5	M18x1.5	10
C9RG-12	10.5	1.5	M18x1.5	M20x1.5	12
C9RG-14	12.0	2.0		M22x1.5	14
CARG-15	12.5	2.0	M22x1.5		15
C9RG-16	14.0	2.0		M24x1.5	16
CARG-18	16.0	2.0	M26x1.5		18
C9RG-20	17.0	2.5		M30x2	20
CARG-22	20.0	2.0	M30x2		22
C9RG-25	22.0	2.5		M36x2	25
CARG-28	26.0	2.0	M36x2		28
C9RG-30	27.0	2.5		M42x2	30
CARG-35	32.0	2.5	M45x2		35
C9RG-38	35.0	2.5		M52x2	38
CARG-42	39.0	2.5	M52x2		42

XARG – Flange "D" rings Caterpillar® and 8000 psi style flanges

O-Ring Part Number	D mm	W mm	Flange Inch	Flange Size
XARG-12	25.4	5.0	*3/4*	-12
XARG-16	31.9	5.0	*1*	-16
XARG-20	38.2	5.0	*1 1/4*	-20
XARG-24	44.7	5.0	*1 1/2*	-24
XARG-32	63.9	5.0	*2*	-32

Worm Drive Hose Clamps

With cross slotted hex head screw
(DIN 3017) for all applications


- Bands and housings of AISI 300 series stainless steel
- Unique interlock construction locks directly into band which tightens under tension
- Shouldered hex head, slotted screw
  No spot welds to rupture under stress or corrode
- Rounded band edges
- High efficiency giving high pressure sealing
- Wide clamping range, giving more flexibility to the user



Miniature Worm Drive Hose Clamps

These small, tough, precision-engineered hose clamps provide:

- Low profile
- Narrow housing
- No protrusions
- Highest sealing
- High working pressure at low torque
- Easy to install in confined areas





Band width 5/16" - 8 mm

Miniature Standard "M" Series

For all clamping applications meeting normal environmental conditions. Hex head screw made of zinc plated carbon steel.

Miniature Stainless "MS-N" Series


Preferred for those environmental conditions which require the extra protection provided by this 100% stainless steel hose clamp. Hex head screw of AISI 305 series made of stainless steel.


"M" series	D Stretch area		"MS" series
Part Number	mm	Inch	Part Number
M 0200	6 - 16	0.25 - 0.62	MS 0200 N
M 0300	8 - 22	0.30 - 0.87	MS 0300 N
M 0400	16 - 32	0.66 - 1.25	MS 0400 N
M 0500	16 - 38	0.66 - 1.50	MS 0500 N
M 0600	19 - 45	0.66 - 1.75	MS 0600 N
M 0700	25 - 50	1.00 - 2.00	MS 0700 N
M 0800	35 - 60	1.38 - 2.38	MS 0800 N
M 0900	45 - 70	1.75 - 2.75	MS 0900 N
M 1000	58 - 82	2.25 - 3.25	MS 1000 N
M 1100	64 - 90	2.50 - 3.50	MS 1100 N
M 1200	77 - 100	3.00 - 4.00	MS 1200 N


For your safety
Hose clamps are intended to ensure the sealing of flexible hoses carrying fluids under pressure; we therefore recommend that you choose the appropriate hose clamp, adhere to the assembly torques indicated and correctly position the hose clamp onto the fitting. Any deformation of the hose requires tightening of the clamp. We disclaim all responsibility for any product failure that might ensue should these recommendations be ignored.

Worm Drive Hose Clamps

With cross slotted hex head screw (DIN 3017) for all applications









Band width 9/16" - 14 mm

Standard "S" Series

Band and housing of stainless steel for all clamping applications, meeting normal environmental conditions. Hex head screw made of zinc plated carbon steel.

Stainless "SS-N" Series

Preferred for those environmental conditions which require the extra protection provided by this 100% stainless steel hose clamp. Hex head screw of AISI 305 series made of stainless steel.

"S" series	"SS" series	D Stretch area		
Part Number	Part Number	size	mm	Inch
S0600	SS0600N	-6	10 - 22	0.38 - 0.87
S0800	SS0800N	-8	11 - 25	0.44 - 1.00
S1000	SS1000N	-10	13 - 27	0.50 - 1.06
S1200	SS1200N	-12	13 - 32	0.50 - 1.25
S1600	SS1600N	-16	19 - 38	0.75 - 1.50
S2000	SS2000N	-20	19 - 44	0.75 - 1.75
S2400	SS2400N	-24	26 - 50	1.00 - 2.00
S2800	SS2800N	-28	34 - 57	1.32 - 2.25
S3200	SS3200N	-32	40 - 64	1.57 - 2.50
S3600	SS3600N	-36	23 - 70	0.88 - 2.75
S4000	SS4000N	-40	29 - 76	1.13 - 3.00
S4400	SS4400N	-44	34 - 82	1.32 - 3.25
S4800	SS4800N	-48	42 - 90	1.63 - 3.50
S5200	SS5200N	-52	48 - 95	1.88 - 3.75
S5600	SS5600N	-56	54 - 100	2.13 - 4.00
S6400	SS6400N	-64	67 - 114	2.63 - 4.50
S7200	SS7200N	-72	76 - 127	3.00 - 5.00
S8000	SS8000N	-80	92 - 140	3.63 - 5.50
S8800	SS8800N	-88	108 - 152	4.25 - 6.00
S9600	SS9600N	-96	120 - 165	4.74 - 6.50
S1040	SS1040N	-104	129 - 178	5.06 - 7.00

Numerous applications in all fields
Automobile industry, ship building, automation systems, agricultural machinery, packaging machines, machine tools, mechanical handling equipment, welding equipment, construction equipment, petrochemical industry, mining, metallurgy.

Protected hose assemblies live longer

In places where the hose assembly is exposed to severe mechanical strain, additional hose protectors such as guards, sleeves etc. have proven to be a good solution. The spring guards or armor guards, for example, prevent kinking of the hose and are the ideal protection against extreme abrasion or possible damage from the outside. Before the fitting is crimped to the hose, the guard needs to be pushed onto the hose – so please remember to order the guards together with your order of hose assembly components.

For some applications it is an advantage to bundle hose assemblies with plastic hose protector coils or sleeves so that they make compact units. For this purpose we recommend using PolyGuard protectors, ParKoil hose protectors and Partek Wraps. Partek Wraps hose sleeves are designed for bundling hose assemblies after installation.

Parker offers a broad range of accessories to work smarter, faster and better!

Spring Guard & Armour Guard (SG & AG)

Parker spring guard and armour guard are two products that prolong the life of your hose lines that are exposed to rugged operating conditions. They distribute bending radii to avoid kinking in hose lines and protect hose from abrasion and deep cuts. Guards are constructed of steel wire and plated to resist rust. See page **Eb-12** and **Eb-13**

PolyGuard & Parkoil (HG & PG)

Protect and bundle your hoses with these spiral guards that minimize kinking and cannot rust. Both the PolyGuard and Parkoil install without removing the hose. See page **Eb-18** and **Eb-19**

Partek (AS & PS)

Nylon woven protective sleeving gives you tough hose abrasion resistance with two versions of coverage – standard “AS” and a lighter “PS” – both providing protection and bundling capability. See page **Eb-14** and **Eb-15**

Minesleeve (DMS)

Best abrasion resistance without adding stiffness to hose assemblies and exceeds the MSHA specifications for flame resistance and flame propergation. See page **Eb-16**

Firesleeve (FS-F)

A flame-resistant sheath that protects your hose from extremely high temperature conditions. See page **Eb-17**

Partek Wrap (PS-BV)

The need for a protective hose sleeve is not always considered while designing for a hose’s application. Many hose assembly installations would benefit from a sleeve, but it is not obvious until all the other hoses and components are in place. Partek Wrap enables the hose sleeve to be installed after the hose assemblies have been positioned and secured in place. The Partek Wrap can be used as extra abrasion protection or to wrap multiple hoses or cables together. See page **Eb-20**

Hose Shields (HP-B)

Hose protection shields extend hose life by protecting the hose from abrasion that occurs when hose rubs against other hose, metal or concrete. Parker hose shields are resistant to oil, lubricants, gasoline, most solvents and can withstand ambient temperatures from -40 °C to +150 °C. Easily installed and secured by cable ties without disconnecting any hose lines. See page **Eb-21**



SG – Spring Guard

Spring Guards protects the hose cover against abrasion and are constructed of steel wire and plated to resist rust.



Hose / Part Number / I.D. mm	SG-060	SG-066	SG-072	SG-084	SG-097	SG-106	SG-113	SG-122	SG-131	SG-155	SG-166	SG-182	SG-209	SG-220	SG-232	SG-270
	15.20	16.75	18.25	21.30	24.60	26.90	28.70	30.95	33.25	39.35	42.15	46.20	53.05	55.85	58.90	68.55
201, 206, 221FR, 225, 235	-4	-5	-6	-8	-10		-12		-16	-20		-24			-32	
213, 285, 293	-4/-5	-6		-8	-10	-12			-16	-20		-24		-32		
301SN, 301TC, 302, 304		-4	-5	-6	-8	-10		-12		-16			-20		-24	
351TC, 402, 421RH, 421SN, 422, 424, 426, 436, 441, 441RH, 451TC, 461LT, 462, 462TC,463, 471TC, 472TC, 492, 493, 611, 611HT, 681, 681DB, 692	-4	-5	-6	-8	-10		-12			-16		-20	-24			-32
372, 372RH, 371LT, 701					-6	-8		-10	-12	-16			-20		-24	
601	-4		-5	-6	-8				-12	-16		-20				
774, 721TC, 772LT				-6	-8		-10		-12	-16			-20	-24		-32
731, 781, 782TC, P35, 791TC, 792TC									-12		-16		-20		-24	
801, 804, 821FR, 831, 836, 837BM	-4/-5		-6	-8	-10		-12		-16							
811, 881, H29, H29ST, H29TC, H29RH									-12	-16		-20		-24		-32
H31, H31ST, H31TC			-4		-6	-8		-10	-12		-16					
R35, R35TC									-12		-16	-20			-24	
R42, R42ST, R42TC								-10	-12		-16		-20		-24	
R50TC / R56TC					-6	-8		-10	-12		-16		-20			
787TC, 797TC			-6	-8		-10		-12		-16		-20		-24		-32
412	-4/-6															
477	-4	-5	-6	-8		-10			-12	-16						

AG – Armour Guard

For extreme abrasion or possible damage from the outside, the corrosion-protected steel flat coil sleeve is recommended.



Hose / Part Number / I.D. mm	AG-060	AG-066	AG-072	AG-084	AG-097	AG-106	AG-113	AG-122	AG-131	AG-155	AG-161	AG-166	AG-182	AG-209	AG-232	AG-270	AG-292	AG-319
	15.20	16.75	18.25	21.30	24.60	26.90	28.70	30.95	33.25	39.35	40.85	42.15	46.20	53.05	58.90	68.55	74.20	81.00
201, 206, 221FR, 225, 235	-4	-5	-6	-8	-10		-12		-16	-20			-24		-32		-40	
213, 285, 293	-4/-5	-6		-8	-10	-12			-16	-20			-24				-40	
301SN, 301TC, 302, 304		-4	-5	-6	-8	-10		-12		-16				-20	-24		-32	
351TC, 402, 421RH, 421SN, 422, 424, 426, 436, 441, 441RH, 451TC, 461LT, 462, 462TC, 463, 471TC, 472TC, 492, 493, 611, 611HT, 681, 681DB, 692	-4	-5	-6	-8	-10		-12			-16			-20	-24		-32		-40
372, 372RH, 371LT, 701					-6	-8		-10	-12	-16				-20	-24			
601	-4		-5	-6	-8				-12	-16			-20					
774, 721TC, 772LT				-6	-8		-10		-12	-16				-20		-32		
731, 781, 782TC, P35, 791TC, 792TC									-12			-16		-20	-24		-32	
801, 804, 821FR, 831, 836, 837BM	-4/-5		-6	-8	-10		-12		-16									
811, 881, H29, H29ST, H29TC, H29RH									-12	-16			-20			-32		-40
H31, H31ST, H31TC			-4		-6	-8		-10	-12		-16							
R35, R35TC									-12		-16		-20		-24		-32	
R42, R42ST, R42TC								-10	-12		-16			-20	-24		-32	
R50TC, R56TC					-6	-8		-10	-12		-16			-20				
787TC, 797TC			-6	-8		-10		-12		-16			-20		-24	-32		
412	-4/-6																	
477	-4	-5	-6	-8		-10			-12	-16								

AS – Partek® Nylon Protective Sleeve

Parker's Partek Nylon Protective Sleeving gives you tough hose abrasion protection two ways. First, per the ISO 6945 specification, Partek has a unique tubular weave nylon construction, Partek "AS" is strong enough to withstand greater than 200,000 abrasion cycles without wearing through the fabric at any location.
In addition, this weave also gives an exceptionally smooth interior wall, allowing rubber hose to move freely inside the sleeve. This provides easy installation and prevents any internal abrasion problems. Partek sleeving is available in either black or yellow and in sizes to fit most hydraulic hose. Partek, the quick and easy solution to hose protection in high-abrasion areas.



Temperature Range ..... -55 °C up to +120 °C

Part Number		I.D. round		I.D. flat	
black	yellow	mm	Inch	mm	Inch
AS-B-11	AS-Y-11	19	0.75	27	1.07
AS-B-13	AS-Y-13	24	0.93	34	1.34
AS-B-15	AS-Y-15	29	1.13	42	1.66
AS-B-17	AS-Y-17	31	1.22	46	1.82
AS-B-19	AS-Y-19	34	1.35	51	2.02
AS-B-22	AS-Y-22	36	1.43	54	2.13
AS-B-27	AS-Y-27	41	1.63	62	2.45
AS-B-33	AS-Y-33	46	1.81	70	2.75
AS-B-35	AS-Y-35	56	2.19	85	3.33
AS-B-37	AS-Y-37	60	2.38	92	3.63
AS-B-39	AS-Y-39	67	2.63	102	4.02
AS-B-45	AS-Y-45	73	2.88	113	4.43
AS-B-47	AS-Y-47	80	3.13	122	4.80
AS-B-53	AS-Y-53	86	3.38	132	5.20
AS-B-58	AS-Y-58	92	3.63	142	5.59
AS-B-64	AS-Y-64	102	4.00	157	6.18

PS – Partek® Nylon Protective Sleeve



Parker's Partek Nylon Protective Sleeving gives you tough hose abrasion protection two ways. First, per the ISO 6945 specification, Partek has a unique tubular weave nylon construction, Partek "PS" is strong enough to withstand greater than 50,000 abrasion cycles without wearing through the fabric at any location. In addition, this weave also gives an exceptionally smooth interior wall, allowing rubber hose to move freely inside the sleeve. This provides easy installation and prevents any internal abrasion problems. Partek sleeving is available in either black or yellow and in sizes to fit most hydraulic hose. Partek, the quick and easy solution to hose protection in high-abrasion areas.

Temperature Range ..... -55 °C up to +120 °C

Part Number	I.D. round		I.D. flat	
	mm	Inch	mm	Inch
PS-B-12	19	0.75	27	1.08
PS-B-13	23	0.91	34	1.32
PS-B-15	27	1.06	40	1.56
PS-B-17	31	1.22	46	1.82
PS-B-22	36	1.42	54	2.14
PS-B-33	46	1.81	70	2.75
PS-B-35	56	2.19	85	3.33
PS-B-37	60	2.38	92	3.63
PS-B-39	67	2.63	102	4.02
PS-B-45	73	2.88	113	4.43
PS-B-47	80	3.13	122	4.8
PS-B-80	127	5.00	197	7.75
PS-B-88	140	5.50	217	8.54

DMS – Minesleeve



Parker Minesleeve offers the best abrasion resistance without adding stiffness to hose assemblies and exceeds the MSHA specifications for flame resistance and flame propergation. Burst tests performed according to SAE J343 on hose assemblies coveres with Mineslesve (DMS) show an oil spill retention capability of 7 times greater than similar products. Also suitable for bundling small hose assemblies, tubing or wires.

- Abrasion resistance
  – offers the best abrasion resistance without adding stiffness to hose assemblies
- Fire & flame resistance
  – exceeds US MSHA specifications for flame resistance & flame propergation
- Electrical conductivity
  – tests performed to ISO 8031 on hose assemblies covered with minesleeve show electrical conductivity values well below the specification requirements
- Oil spill retention
  – burst tests performed according to SAE J343 on hose assemblies covered with minesleeve how an oil spill retention capability of 7 times greater than similar products, also suitable for undling small hose assemblies, tubing or wires
- Approvals: MSHA & UK COAL

Temperature Range ..... -50 °C up to +120 °C

Part Number	I.D. round		I.D. flat	
	mm	Inch	mm	Inch
DMS-23	23	0.91	39	1.54
DMS-27	27	1.06	45	1.77
DMS-31	31	1.22	52	2.05
DMS-36	36	1.42	57	2.24
DMS-47	47	1.85	77	3.03
DMS-55	55	2.17	89	3.5
DMS-66	66	2.60	107	4.21
DMS-85	85	3.35	136	5.35
DMS-93	93	3.66	149	5.87
DMS-127	127	5.00	197	7.75

FS-F – Fire Sleeves

Parker Firesleeve is a flame resistant sheath that protects the hose from extreme temperature conditions. Firesleeve easily slides over hoses and readily expands over fitting. When fitting the fire sleeve to hose assemblies with reusable or crimped fittings, a fire sleeve clamp must be used.



- Certification:
  - UL 1441 Certified
  - VW1 Flame Test Certified
  - MSHA Certified for use in underground mines
  - SAE AS1072E
  - GL-Germanischer Lloyd Certified for 800 °C for 30 min.
  - BS EN 373 Molten Splash Tested
  - BS EN 388 Abrasion Tested
  - BS EN ISO 6940 Flame Resistance Tested
  - BS EN ISO 6530 Oil Resistance Tested
  - BS 2576 Tensile Strength Tested
  - DIN 54837/5510-2 Rail Vehicle Certified for Resistance to Combustibility
  - DIN 5659-2/5510-2 Rail Vehicle Certified for Toxicity
  - MIL-C-24576A
  - PJA and P96 Thermal Conductivity
- Braided fiberglass sleeve with orange, bonded and seamless silicone rubber cover
- Conforms to SAE Aerospace Standard 1072A Type 2A

Temperature Range ..... -54 °C up to +260 °C

Part Number	min. I.D.		max. O.D.		Suction Hose (R4)			1-/2-Wire Braided			Multispiral		
	mm	Inch	mm	Inch	inch	mm	size	inch	mm	size	inch	mm	size
FS-F-10	15	0.58	25	0.97				1/4	6	-4			
FS-F-11	17	0.65	26	1.03				1/4 5/16	6 8	-4 -5			
FS-F-12	18	0.71	28	1.09				5/16	8	-5			
FS-F-14	21	0.84	31	1.22				3/8	10	-6			
FS-F-16	24	0.96	35	1.38				1/2	13	-8	1/4 3/8	6 10	-4 -6
FS-F-18	27	1.08	38	1.50				1/2 5/8	13 16	-8 -10	1/2	13	-8
FS-F-20	31	1.21	40	1.59				3/4	19	-12	1/2 5/8	13 16	-8 -10
FS-F-22	34	1.34	44	1.75	3/4	19	-12				3/4	19	-12
FS-F-24	37	1.46	48	1.90				1	25	-16			
FS-F-28	43	1.71	52	2.06	1	25	-16	1	25	-16	1	25	-16
FS-F-30	47	1.84	56	2.19									
FS-F-32	50	1.96	59	2.32	1 1/4	32	-20	1 1/4	32	-20			
FS-F-38	59	2.34	70	2.74			-24	1 1/4 1 1/2	32 38	-20 -24	1 1/4 1 1/2	32 38	-20 -24
FS-F-40	63	2.46	71	2.79							1 1/2	38	-24
FS-F-48	75	2.96	86	3.40	2	51	-32	2	51	-32	2	51	-32
FS-F-60	94	3.71	105	4.15	2 1/2 3	65 76	-40 -48	2 1/2 3	65 76	-40 -48	2 1/2	65	-40

HG – PolyGuard Hose Protector

Heavy duty polyethylene provides protection in rugged operating conditions, great for bundling high-pressure hose lines



- Shields hose from abrasion and cuts
- Easy to install without removing hose lines: no clamps needed
- Minimises risk of kinking
- Resistant to air, water, oil, gasoline, hydraulic fluid and most solvents
- Ideal for bundling plastic tubing or hose lines
- Cannot rust or corrode
- Color: black

Caution: This material will support combustion

Temperature Range ..... -40 °C up to +93 °C

Part Number	min. I.D.		1-/2-wire braided			Multispiral			Suction hose (R4)		
	mm	Inch	*Inch*	mm	Size	*Inch*	mm	Size	*Inch*	mm	Size
HG-075	18.3 - 19.8	0.72 - 0.78	*1/2* *5/8*	13 16	-8 -10	*1/4* *3/8*	6 10	-4 -6	-	-	-
HG-100	24.6 - 26.2	0.97 - 1.03	*3/4*	19	-12	*1/2* *5/8*	13 16	-8 -10	*3/4*	19	-12
HG-125	31.0 - 32.5	1.22 - 1.28	*1*	25	-16	*3/4*	19	-12	-	-	-
HG-150	37.30 - 38.9	1.47 - 1.53	*1 1/4*	32	-20	*1*	25	-16	*1* *1 1/4*	25 32	-16 -20
HG-200	50.0 - 51.6	1.97 - 2.03	*1 1/2* *2* *2 1/2*	32 38 51	-24 -32 -40	*1 1/4* *1 1/2* *2*	32 38 51	-20 -24 -32	*1 1/2* *2* *2 1/2*	32 38 51	-24 -32 -40
HG-350	88.1 - 89.7	3.47 - 3.53	*3*	76	-48	*2 1/2* *3*	65 76	-40 -48	*3*	76	-48

PG – ParKoil Hose Protector

Lower-cost protection for applications that call for a tighter bend radius and are less demanding



- Shields hose from abrasion and cuts
- Easy to install without removing hose lines: no clamps needed
- Minimises risk of kinking
- Resistant to air, water, oil, gasoline, hydraulic fluid and most solvents
- Ideal for bundling plastic tubing or hose lines
- Cannot rust or corrode
- Color: black

Caution: This material will support combustion

Temperature Range ..... -17 °C up to +93 °C

Part Number	min. I.D.		1-/2-wire braided			Multispiral			Suction hose (R4)		
	mm (± 1.25)	Inch (± 0.05)	*Inch*	mm	Size	*Inch*	mm	Size	*Inch*	mm	Size
PG-038	9.65	0.38	*3/16*	5	-3	-	-	-	-	-	-
PG-050	12.70	0.50	*1/4* *5/16*	6 8	-4 -5	-	-	-	-	-	-
PG-062	15.75	0.62	*3/8*	10	-6	*1/4*	6	-4	-	-	-
PG-075	19.05	0.75	*1/2*	13	-8	*3/8*	10	-6			
PG-088	22.35	0.88	*5/8*	16	-10	*1/2*	13	-8			
PG-100	25.40	1.00	*3/4*	19	-12	*5/8*	16	-10			
PG-119	30.25	1.19	-	-	-	*3/4*	19	-12	*3/4*	19	-12
PG-138	35.05	1.38	*1* *1 1/4*	25 32	-16 -20	*1* *1 1/4*	25 32	-16 -20	*1*	25	-16
PG-188	47.75	1.88	*1 1/2* *2*	38 51	-24 -32	*1 1/2* *2*	38 51	-24 -32	*1 1/2* *2*	38 51	-24 -32

PS – Partek Wrap

Nylon hose sleeve designed for bundling hose assemblies after installation


- Post-assembly installation
- Light weight and high flexibility
- Urethane-coated 1050 ballistic Nylon
- Ambient temperature range of -51 °C to 93 °C
- Fast and easy installation
- Designed for added abrasion resistance or bundling of multiple hoses
- Can be cut to size with household scissors



Part Number	I.D. round		I.D. flat	
	mm	Inch	mm	Inch
PS-BV-200	50	2	80	3.2
PS-BV-300	75	3	80	3.2
PS-BV-400	100	4	162	6.5
PS-BV-500	125	5	203	8.1
PS-BV-600	150	6	243	9.7
PS-BV-700	175	7	283	11.3
PS-BV-800	200	8	325	13.0

WKS Rubber hand grip

For *No-Skive* high pressure water cleaning hoses



Hand Grip		Hose I.D.				L	D1	D2
Part Number	Colour	DN	Inch	Size	mm	mm	mm	mm
WKS-4-BLK	black	6	1/4	-4	6.4	120	15.0	24
WKS-4-BLU	blue	6	1/4	-4	6.4	120	15.0	24
WKS-5-BLK	black	8	5/16	-5	7.9	150	17.0	34
WKS-5-BLU	blue	8	5/16	-5	7.9	150	17.0	34
WKS-6-BLK	black	10	3/8	-6	9.5	150	19.5	34
WKS-6-BLU	blue	10	3/8	-6	9.5	150	19.5	34
WKS-8-BLK	black	12	1/2	-8	12.7	150	22.5	34
WKS-8-BLU	blue	12	1/2	-8	12.7	150	22.5	34
WKS-8-GRA	grey	12	1/2	-8	12.7	150	22.5	34

HP-B – Hose Shield

Hose protection shields extend hose life by protecting the hose from abrasion that occurs when hose rubs against other hose, metal or concrete. Parker hose shields are resistant to oil, lubricants, gasoline, most solvents and can withstand ambient temperatures from -40 °C to +150 °C. Easily installed and secured by cable ties without disconnecting any hose lines.



- Use with hose from size -4 up to size -32
- Eliminate hose abrasion on concrete, metal or any rough surface
- Guard against hose deterioration on mobile hydraulic equipment
- Let Parker fill all your hydraulic and pneumatic hose product needs

Hose Shields KIT HP-B-13X18-KIT with – 2 x HP-13 RFL Hose Protectors, length 101 mm (4”) – 2 x HP-15 RFL Hose Protectors, length 152 mm (6”) – 4 x HP-18 RFL Hose Protectors, length 203 mm (8”) – 30 x HT-12 Tie Wraps – 30 x HT-16 Tie Wraps – 15 x HT-22 Tie Wraps	**Part Number**	**HP-B-13X18-KIT**
Counter Display HP-B-13-RFL with – 10 x HP-B-13 Hose Protectors, length 101 mm (4”) – 30 x HT-12 Tie Wraps	**Part Number**	**HP-B-13-RFL**
Counter Display HP-B-15-RFL with – 10 x HP-B-15 Hose Protectors, length 152 mm (6”) – 30 x HT-16 Tie Wraps	**Part Number**	**HP-B-15-RFL**
Counter Display HP-B-18-RFL with – 5 x HP-B-18 Hose Protectors, length 203 mm (8”) – 15 x HT-18 Tie Wraps	**Part Number**	**HP-B-18-RFL**
Hose Protector, length 101 mm (4”)	**Part Number**	**HP-B-13**
Hose Protector, length 152 mm (6”)	**Part Number**	**HP-B-15**
Hose Protector, length 203 mm (8”)	**Part Number**	**HP-B-18**

Hose Whip Restraint




Safety Restraining System for Pressure Hoses

- Prevents whipping of a pressurized hose in the vent of the hose separating from its fitting
- The system consists of two parts – a hose collar and a cable assembly

Hose collars

for Hose Whip Restraint System



Part Number	A		B	
	Inch	mm	Inch	mm
WRC1212	0.47	12	0.492	12.5
WRC1313	0.51	13	0.531	13.5
WRC1415	0.55	14	0.591	15
WRC1718	0.67	17	0.709	18
WRC1819	0.71	18	0.748	19
WRC2021	0.79	20	0.827	21
WRC2223	0.87	22	0.906	23
WRC2425	0.95	24	0.984	25
WRC2526	0.98	25	1.024	26
WRC2728	1.06	27	1.102	28
WRC2829	1.10	28	1.142	29
WRC3031	1.18	30	1.220	31
WRC3435	1.34	34	1.378	35
WRC3637	1.42	36	1.457	37
WRC3839	1.50	38	1.535	39
WRC4445	1.73	44	1.772	45
WRC4547	1.77	45	1.850	47
WRC4850	1.89	48	1.969	50
WRC5153	2.01	51	2.087	53
WRC5456	2.13	54	2.205	56
WRC5759	2.25	57	2.330	59
WRC6365	2.48	63	2.559	65
WRC6971	2.72	69	2.795	71
WRC7577	3.00	75	3.030	77
WRC8486	3.30	84	3.380	86
WRC8789	3.42	87	3.500	89

Cable Assemblies

for hoses attached with port adapters



Part Number	A		C	
	Inch	mm	Inch	mm
WRA145	0.57	14.5	11.81	300
WRA170	0.67	17.0	11.81	300
WRA185	0.73	18.5	11.81	300
WRA205	0.81	20.5	11.81	300
WRA225	0.89	22.5	11.81	300
WRA245	0.96	24.5	11.81	300
WRA265	1.04	26.5	11.81	300
WRA305	1.20	30.5	11.81	300
WRA340	1.34	34.0	17.72	450
WRA365	1.44	36.5	17.72	450
WRA425	1.67	42.5	17.72	450
WRA455	1.79	45.5	17.72	450
WRA490	1.93	49.0	17.72	450
WRA525	2.07	52.5	17.72	450
WRA600	2.36	60.0	17.72	450

Cable Assemblies


for hoses using flange-style connections (code 61 and code 62 flanges)



Part Number	A		C	
	Inch	mm	Inch	mm
WRF085	0.33	8.5	11.81	300
WRF105	0.41	10.5	17.72	450
WRF125	0.49	12.5	17.72	450
WRF145	0.57	14.5	17.72	450
WRF165	0.65	16.5	17.72	450
WRF205	0.81	20.5	17.72	450

HS – Containment Grips

- Material: electrogalvanized steel wire



Part Number	Hose I.D.				Ø	Working load	Breaking load	Total length l1	Length of loops l2
	DN	Inch	Size	mm	mm	kN	kN	mm	mm
HS-03	5	3/16	-3	4.8	9 - 15	3	9	600	200
HS-05	8	5/16	-5	7.9	12 - 20	6	18	600	200
HS-08	12	1/2	-8	12.7	20 - 30	11	33	600	200
HS-12	20	3/4	-12	19.0	30 - 40	11	33	600	200
HS-16	25	1	-16	25.4	40 - 50	16	48	600	200

Thread Identification Kit

The thread identification tools are useful to help you identify international threads such as:

- European threads (Metric, BSPP, BSPT threads) and
- U.S. threads (NPT and SAE straight threads UNF)



Technical / Order Data

Thread identification kit with thread gauges, a set of callipers, thread profiles and instruction booklet	**Part Number**	English	**H905375-GB**
	Part Number	German	**H905375-DE**
	Part Number	French	**H905375-FR**

The components of the thread ID Kit are not high-precision gauges but simple instruments for workshop use.

Parker „Hoze-Oil“

Parker´s hose assembly lubricant is pressure and temperature resistant. The lubrication effect will help to insert Parker No-Skive hose and fittings. If necessary simply wet the fitting end with a drop of hoze oil.




Volume	1 l
Part Number	**Hoze-Oil**

OilOn TH 11-3

Oiling pad for lubrication of fittings

The perfect way to lubricate the fitting, making it easier to insert into the hose. A foam rubber sponge that evenly disperses the oil onto the fitting, in an effective and easy manner.



Material	steel/plastic
Dimensions	L 130 x W 130 x H 70 mm
Part Number	**TH11-3**

Push-Lok® Assembly Oil H896137

Water-oil emulsion for easier assembly of Parker Push-Lok® fittings. This product is very useful in combination with 830M, 837BM and 837PU hoses as the Push-Lok® assembly oil is free from wetting disturbing substances, e.g. silicone (Labs-free).




Volume	1 l
Part Number	**H896137**

Push-Lok® Assembly Tool


Tool designed for assembly of Push-Lok® fittings and hoses in all sizes. Toggle actions greatly reduce effort necessary to hold hose and press in fitting. Only a few pounds of force is needed on either handle to quickly assemble any size.

Assembly Tool 611050G



Overall length	320 mm
Weight	2.2 kg
Part Number	**611050G**


Assembly Tool 611050HV
“Rigid version”




Dimensions	L 500 x W 90 x H 300 mm
Weight	7.5 kg
Part Number	**611050HV**

KarryKrimp® 1 / KarryKrimp® 2


KarryKrimp 1 crimps Parkrimp® fittings 26, 43, 46, 48 series size -4 up to -20
KarryKrimp 2 crimps Parkrimp® fittings 26, 43, 46, 48, 70, 73 and 77 series




1. Mark the hose insertion depth acc. crimptable with a marker and push hose into fitting until the mark on the hose is even with the end of the shell. If necessary simply wet the fitting end with a drop of hoze oil. Do not lubricate if using spiral hose.




2. Pull pin and drop hinged die-train in place. Pay attention to die segment location.




3. Insert fitting into the dies. Release, fitting will self position.




3. (a) Position the fitting on the die step.



4. Place die ring on top of the dies.



5. Position cylinder and replace pin. Pump until die ring contacts base plate.



6. Release pressure – remove finished assembly.


Parkrimp® 2

Parkrimp® fittings 26, 43, 46, 48, 70, 73 and 77 series


For one-piece die sets 80C- ... and 83C- ... size -4 to -16




With the pusher in the full up position, lift the back half of the split die ring. Lock it in the up position by pushing the slide pin in (the slide pin is located inside the pusher at the back).




Carefully insert the adapter bowl into the base bowl. The adapter bowl must be tilted toward the back of the crimper during insertion.




Insert the proper size and series die set into the adapter bowl.
Note: die sets are colour coded by size and have the fitting series and dash size stamped on the top.
Pay attention to die segment location.



When swaging 43 series fittings on 100R2, 100R3, 100R4 and 100R9 type hose, the black spacer ring must be placed.




Lower the back half of the split die ring onto the dies by pulling the slide pin forward.




Insert the front half of the split die ring aligning the pin in the half with the hole in the front half.


For two-piece die sets 83C-... size -20 to -32



Insert the proper size die set into the die bowl (the die sets are in two halves of four dies each; Place one half in the back and one half in the front to facilitate removal of bent tube fittings).




Lower the back half of the split die ring onto the dies by pulling the slide pin forward.




Insert the front half of the split die ring aligning the pin in the half with the hole in the front half.



Parkalign® feature
Position hose from below in dies.
Rest bottom of coupling on die step.




Turn on the pump by pressing the button on the left hand switch box. Lower the pusher by pressing the lower button on the right hand switch box. When the die ring contacts the base plate, the swaging is complete.



Push the black button at the top of the switch box to open dies and remove the finished assembly.
You do not have to remove any tooling to remove or insert straight fittings. The front half of the split die ring and the front die train must be removed to insert and remove bent tube fittings.

Your crimp source online keeps you always up-to- date

Crimpsource online is your tool for a fast, easy and exact assembly of hose products in Europe



Find the correct crimp specification on the push of a button!

www.parker.com/crimpsource-euro

Part Number	Page
201	B2a-1
206	B2a-2
213	B2a-3
285	B2a-5
293	B2a-6
304	Cab-3
372	Dab-2
412	Cab-4
426	Cab-9
436	Cab-10
441	Cab-11
462	Cab-14
463	Cab-18
477	Cab-20
487	Caa-4
492	Cab-23
493	Cab-26
601	B2a-7
681	B2a-9
692	Cab-27
701	Dab-5
722	Daa-1
731	Dab-11
774	Dab-13
787	Daa-4
797	Daa-6
801	B1a-1
804	B1a-2
811	Cab-29
831	B1a-5
836	B1a-6
881	Cab-31
10048	Cd-1
10126	B2b-5
10143	Cb-9
10146	Cc-21
10148	Cc-21
10170	Db-8
10173	Dc-5
10177	Dd-9
10343	Cb-9
10346	Cc-22
10348	Cc-22
10370	Db-8
10373	Dc-5
10377	Dd-9
10546	Cc-23
10548	Cc-23
10626	B2b-5

Part Number	Page
10643	Cb-10
10646	Cc-24
10648	Cc-24
10670	Db-9
10673	Dc-6
10677	Dd-10
10826	B2b-6
10846	Cc-25
10846	Cc-25
10848	Cc-25
10848	Cc-25
11543	Cb-12
11546	Cc-29
11548	Cc-29
11570	Db-11
11573	Dc-8
11577	Dd-12
11743	Cb-12
11746	Cc-30
11748	Cc-30
11770	Db-11
11773	Dc-8
11777	Dd-13
11943	Cb-13
11946	Cc-31
11948	Cc-31
11970	Db-12
11973	Dc-9
11977	Dd-14
13726	B2b-6
13743	Cb-10
13746	Cc-26
13748	Cc-26
13770	Db-10
13773	Dc-6
13777	Dd-11
13926	B2b-7
13943	Cb-11
13946	Cc-27
13948	Cc-27
13970	Db-10
13973	Dc-7
13977	Dd-11
14146	Cc-28
14148	Cc-28
14926	B2b-2
14946	Cc-11
14948	Cc-11
16826	B2b-5

Part Number	Page
16846	Cc-24
16848	Cc-24
19126	B2b-4
19146	Cc-20
19148	Cc-20
19226	B2b-3
19243	Cb-5
19246	Cc-12
19248	Cc-12
19270	Db-5
19273	Dc-3
19277	Dd-5
30182	B1b-11
30282	B1b-11
30382	B1b-12
30682	B1b-12
30882	B1b-13
33482	B1b-10
33782	B1b-13
33982	B1b-14
34982	B1b-6
36882	B1b-12
38282	B1b-17
39182	B1b-10
39282	B1b-8
405.906	Ea-19
711509	Eb-7
853009	Eb-6
16E77	Dd-16
100IF	Ce-1
100V4	Df-1
100V5	Dg-1
100V6	Df-1
100VS	De-1
100WB	Dh-1
10C43	Cb-3
10C46	Cc-8
10C48	Cc-8
10C70	Db-3
10C73	Dc-1
10C77	Dd-3
11C43	Cb-4
11C46	Cc-9
11C48	Cc-9
11C70	Db-4
11C73	Dc-2
11C77	Dd-4
13V26	B2b-6
13V46	Cc-26

Part Number	Page
13V48	Cc-26
13W26	B2b-7
13W43	Cb-11
13W46	Cc-27
13W48	Cc-27
13W70	Db-10
13Y46	Cc-28
13Y48	Cc-28
14A73	Dc-8
14A77	Dd-12
14F73	Dc-8
14F77	Dd-13
14N73	Dc-9
14N77	Dd-14
15S26	B2b-9
15T26	B2b-9
16A43	Cb-13
16A46	Cc-32
16A48	Cc-32
16A70	Db-12
16A73	Dc-9
16A77	Dd-15
16F46	Cc-32
16F48	Cc-32
16F70	Db-13
16F73	Dc-10
16F77	Dd-16
16N43	Cb-14
16N46	Cc-33
16N48	Cc-33
16N70	Db-13
16N73	Dc-10
16N77	Dd-17
1B126	B2b-3
1B143	Cb-5
1B146	Cc-13
1B148	Cc-13
1B170	Db-5
1B173	Dc-3
1B177	Dd-5
1B226	B2b-4
1B243	Cb-6
1B246	Cc-14
1B248	Cc-14
1B270	Db-6
1B273	Dc-4
1B277	Dd-6
1B446	Cc-15
1B448	Cc-15

Part Number	Page
1B546	Cc-20
1B548	Cc-20
1C348	Cc-5
1C448	Cc-5
1C548	Cc-6
1C648	Cc-11
1C943	Cb-3
1C946	Cc-7
1C948	Cc-7
1C970	Db-3
1C973	Dc-1
1C977	Dd-3
1CA26	B2b-1
1CA43	Cb-1
1CA46	Cc-1
1CA48	Cc-1
1CA70	Db-1
1CA77	Dd-1
1CE26	B2b-1
1CE43	Cb-1
1CE46	Cc-2
1CE48	Cc-2
1CE70	Db-1
1CE77	Dd-1
1CF26	B2b-2
1CF43	Cb-2
1CF46	Cc-3
1CF48	Cc-3
1CF70	Db-2
1CF77	Dd-2
1CW46	Cc-45
1CW48	Cc-45
1D043	Cb-2
1D046	Cc-4
1D048	Cc-4
1D070	Db-2
1D077	Dd-2
1D243	Cb-4
1D246	Cc-10
1D248	Cc-10
1D270	Db-4
1D273	Dc-2
1D277	Dd-4
1D943	Cb-8
1D946	Cc-19
1D948	Cc-19
1D970	Db-7
1D973	Dc-4
1D977	Dd-8
1DK46	Cc-47
1DK48	Cc-47
1DX46	Cc-48
1DX48	Cc-48
1EA43	Cb-6
1EA46	Cc-16
1EA48	Cc-16
1EA70	Db-6
1EA77	Dd-6
1EB43	Cb-7
1EB46	Cc-17
1EB48	Cc-17
1EB77	Dd-7
1EC43	Cb-7
1EC46	Cc-18
1EC48	Cc-18
1EC70	Db-7
1EC77	Dd-7
1EN46	Cc-49
1EN48	Cc-49
1ET46	Cc-50
1ET48	Cc-50
1EU46	Cc-49
1EU48	Cc-49
1F246	Cc-42
1F248	Cc-42
1F273	Dc-16
1F446	Cc-43
1F448	Cc-43
1F470	Db-19
1F473	Dc-17
1F646	Cc-43
1F648	Cc-43
1F946	Cc-44
1F948	Cc-44
1FA46	Cc-44
1FA48	Cc-44
1FG46	Cc-42
1FG48	Cc-42
1FG70	Db-19
1FG73	Dc-16
1FG77	Dd-26
1FU46	Cc-40
1FU48	Cc-40
1GU46	Cc-40
1GU48	Cc-40
1J146	Cc-38
1J148	Cc-38
1J170	Db-17
1J177	Dd-24
1J546	Cc-38
1J548	Cc-38
1J743	Cb-16
1J746	Cc-36
1J748	Cc-36
1J770	Db-16
1J773	Dc-14
1J777	Dd-23
1J943	Cb-16
1J946	Cc-37
1J948	Cc-37
1J970	Db-16
1J973	Dc-14
1J977	Dd-24
1JC26	B2b-8
1JC43	Cb-15
1JC46	Cc-34
1JC48	Cc-34
1JC70	Db-15
1JC73	Dc-13
1JC77	Dd-23
1JD46	Cc-39
1JD48	Cc-39
1JM43	Cb-17
1JM46	Cc-39
1JM48	Cc-39
1JM70	Db-17
1JM73	Dc-15
1JM77	Dd-25
1JS43	Cb-15
1JS46	Cc-35
1JS48	Cc-35
1JS70	Db-15
1JS73	Dc-13
1K577	Dd-21
1K777	Dd-22
1K977	Dd-22
1MU46	Cc-41
1MU48	Cc-41
1MU70	Db-18
1MZ46	Cc-41
1MZ48	Cc-41
1NW46	Cc-45
1NW48	Cc-45
1PW46	Cc-46
1PW48	Cc-46
1PY70	Db-14
1X577	Dd-18
1X777	Dd-18
1X977	Dd-19
1XA73	Dc-11
1XA77	Dd-19
1XF73	Dc-11
1XF77	Dd-20
1XG73	Dc-12
1XG77	Dd-20
1XN73	Dc-12
1XN77	Dd-21
1XU48	Cc-47
1XU70	Db-20
1XU73	Dc-18
1XY70	Db-20
2-0__N552-90	Eb-7
2-2__N552-90	Eb-8
221FR	B2a-4
301SN	Cab-1
301TC	Cab-2
33V82	B1b-13
33W82	B1b-14
35C82	B1b-17
36C82	B1b-18
371LT	Dab-1
372RH	Dab-3
372TC	Dab-4
37C82	B1b-18
387ST	Caa-3
387TC	Caa-2
39B82	B1b-6
39C82	B1b-7
3AF82	B1b-16
3B182	B1b-8
3B282	B1b-9
3C382	B1b-3
3C482	B1b-4
3C582	B1b-5
3CA82	B1b-1
3CE82	B1b-1
3CF82	B1b-2
3D082	B1b-2
3D982	B1b-9
3FF82	B1b-16
3JC82	B1b-15
412ST	Cab-5
421RH	Cab-6
421SN	Cab-7
421WC	Cab-8
441RH	Cab-12

Part Number	Page
461LT	Cab-13
462CIF	Cab-15
462ST	Cab-17
462TC	Cab-16
471TC	Cab-19
477ST	Cab-22
477TC	Cab-21
487ST	Caa-6
487TC	Caa-5
492ST	Cab-25
492TC	Cab-24
50H	Eb-1
600.4	Ea-15
611050G	B1b-19
611050G	Eb-24
611050HV	B1b-19
611050HV	Eb-24
611HT	B2a-8
681DB	B2a-10
692Twin	Cab-28
701TC	Dab-6
722CIF	Dab-7
722LT	Dab-8
722ST	Daa-3
722ST	Dab-10
722TC	Daa-2
722TC	Dab-9
731TC	Dab-12
787TC	Daa-5
797TC	Daa-7
80C-A04	Ea-6
80C-A05	Ea-6
80C-A06	Ea-6
80C-A08	Ea-6
80C-A10	Ea-6
80C-A12	Ea-6
80C-A16	Ea-6
80C-A20	Ea-6
80C-B04	Ea-6
80C-B05	Ea-6
80C-B06	Ea-6
80C-B08	Ea-6
80C-B10	Ea-6
80C-B12	Ea-6
80C-B16	Ea-6
80C-B20	Ea-6
80C-C04	Ea-6
80C-C05	Ea-6
80C-C06	Ea-6

Part Number	Page
80C-C08	Ea-6
80C-C10	Ea-6
80C-C12	Ea-6
80C-C16	Ea-6
80C-C20	Ea-6
80C-CS08	Ea-6
80C-CS10	Ea-6
80C-CS12	Ea-6
80C-E04	Ea-6
80C-E05	Ea-6
80C-E06	Ea-6
80C-E08	Ea-6
80C-E10	Ea-6
80C-E12	Ea-6
80C-E16	Ea-6
80C-L12	Ea-6
80C-L16	Ea-6
811S	Cab-30
821FR	B1a-3
82C-2HP	Ea-5
82CE-061L	Ea-1
82CE-0EP	Ea-5
82CE-CHD	Ea-1
82C-R01	Ea-1
82C-R02	Ea-1
830M	B1a-4
837BM	B1a-7
837PU	B1a-8
838M	B1a-9
83C-0CB	Ea-4
83C-A16H	Ea-6
83C-A20H	Ea-6
83C-A24	Ea-6
83C-A32	Ea-6
83C-C20H	Ea-6
83C-C24	Ea-6
83C-C32	Ea-6
83C-CS16	Ea-6
83C-CS20	Ea-6
83C-CS24	Ea-6
83C-CS32	Ea-6
83C-D06	Ea-6
83C-D06	Ea-6
83C-D08	Ea-6
83C-D08	Ea-6
83C-D10	Ea-6
83C-D10	Ea-6
83C-D12	Ea-6
83C-D12	Ea-6

Part Number	Page
83C-D16	Ea-6
83C-D16	Ea-6
83C-D16H	Ea-6
83C-D16H	Ea-6
83C-D20	Ea-6
83C-D20H	Ea-6
83C-D24	Ea-6
83C-D32	Ea-6
83CE-083U	Ea-4
83C-E20	Ea-6
83C-E24	Ea-6
83C-E32	Ea-6
83C-L12	Ea-6
83C-L16	Ea-6
83C-L20	Ea-6
83C-L24	Ea-6
83C-L32	Ea-6
83C-L32	Ea-6
83C-R02	Ea-4
83C-R02H	Ea-4
85C-00L	Ea-1
85C-00L	Ea-2
85C-00L	Ea-5
85C-0AP	Ea-5
85CE-061L	Ea-2
85CE-0HP	Ea-5
85CE-1PE	Ea-5
85CE-CHD	Ea-2
85CE-XAM	Ea-5
85C-R01	Ea-2
85C-R02	Ea-2
85C-STD	Ea-1
85C-STD	Ea-2
8FH	Eb-1
AG	Eb-13
AM	Eb-6
AR	Eb-6
AS-B	Eb-14
AS-Y	Eb-14
BPK	Dab-28
C9RG	Eb-7
CARG	Eb-8
DMS	Eb-16
EARG	Eb-7
EM10.P	Ea-7
F42	Dab-14
FS-F	Eb-17
FU-HMX	Ea-23
FU-HMX	Ea-24

Part Number	Page
H29	Dab-15
H29RH	Dab-16
H29ST	Dab-18
H29TC	Dab-17
H31	Dab-19
H31ST	Dab-21
H31TC	Dab-20
H896137	B1b-19
H896137	Eb-24
H899770	Ea-19
H899771	Ea-15
H899959	Ea-15
H905375	Eb-24
HG	Eb-18
Hoze-Oil	Eb-24
HP-B	Eb-21
HS	Eb-23
K0147	Cd-1
K01V4	Df-9
K01V6	Df-9
K01VS	De-8
K01WB	Dh-4
K03V4	Df-9
K03V6	Df-9
K03VS	De-8
K06V4	Df-10
K06V6	Df-10
K06VS	De-9
K0CV4	Df-4
K0CV5	Dg-2
K0CV6	Df-4
K0CVS	De-4
K1547	Cd-2
K15IF	Ce-2
K15V4	Df-12
K15V6	Df-12
K15VS	De-11
K17IF	Ce-2
K17V4	Df-13
K17V6	Df-13
K17VS	De-11
K19IF	Ce-3
K19V4	Df-14
K19V6	Df-14
K19VS	De-12
K1CV4	Df-4
K1CV5	Dg-3
K1CV6	Df-4
K1CVS	De-5

Part Number	Page
K37V4	Df-10
K37V6	Df-10
K37VS	De-9
K39V4	Df-11
K39V6	Df-11
K39VS	De-10
K3VVS	De-9
K3WVS	De-10
K4AV4	Df-12
K4AV6	Df-12
K4FV4	Df-13
K4FV6	Df-13
K4NV4	Df-14
K4NV6	Df-14
K68VS	De-9
K6AV4	Df-15
K6AV6	Df-15
K6AVS	De-12
K6FV4	Df-16
K6FV6	Df-16
K6FVS	De-13
K6NV4	Df-17
K6NV6	Df-17
K6NVS	De-13
K8AV4	Df-18
K8AV6	Df-18
K8FV4	Df-18
K8FV6	Df-18
K8NV4	Df-19
K8NV6	Df-19
K91V4	Df-8
K92V4	Df-6
K92V6	Df-6
K92VS	De-6
K92WB	Dh-3
KB1V4	Df-6
KB1V6	Df-6
KB1VS	De-6
KB2V4	Df-7
KB2V6	Df-7
KB2VS	De-7
KC9V4	Df-3
KC9V5	Dg-2
KC9V6	Df-3
KC9VS	De-4
KC9WB	Dh-2
KCAV4	Df-2
KCAV6	Df-2
KCAVS	De-2
KCEV4	Df-2
KCEV6	Df-2
KCEVS	De-2
KCFV4	Df-3
KCFV6	Df-3
KCFVS	De-3
KD0VS	De-3
KD2V4	Df-5
KD2V6	Df-5
KD2VS	De-5
KD9V4	Df-7
KD9V6	Df-7
KD9VS	De-7
KF4V4	Df-27
KF4VS	De-16
KFGV4	Df-27
KFGVS	De-16
KJ7V4	Df-25
KJ7V6	Df-25
KJ7VS	De-14
KJ9V4	Df-25
KJ9V6	Df-25
KJ9VS	De-15
KJCV4	Df-24
KJCV6	Df-24
KJCVS	De-14
KJMV4	Df-26
KJSV4	Df-24
KPYV4	Df-21
KX5V6	Df-19
KX7V6	Df-20
KX9V6	Df-20
KXAV4	Df-21
KXAV6	Df-21
KXFV4	Df-22
KXFV6	Df-22
KXGV4	Df-22
KXGV6	Df-22
KXNV4	Df-23
KXNV6	Df-23
M____	Eb-9
M1H	Eb-1
M2H	Eb-1
MS____N	Eb-9
PB237.239.2L2	Ea-23
PB237.239.2L2	Ea-24
PB237.239.2L2	Ea-25
PB245.237L	Ea-25
PB266.239L	Ea-22
PBSET-237L-IH	Ea-24
PBSET-TH8-800	Ea-23
PBSET-TH8E-380	Ea-24
PBSET-TH8E-53X	Ea-22
PG	Eb-19
PS-B	Eb-15
PS-BV	Eb-20
QDC239.3	Ea-22
QDC239.3	Ea-23
QDC239.3	Ea-24
QDC239.3	Ea-25
QDS239S	Ea-22
QDS239S	Ea-23
QDS239S	Ea-24
R-___CFX	Eb-3
R35	Dab-22
R35TC	Dab-23
R42	Dab-24
R42ST	Dab-26
R42TC	Dab-25
R50TC	Dab-27
R56TC	Dab-27
RS35TC-48	Dab-23
S____	Eb-10
SG	Eb-12
SHS310/370	Ea-24
SHS-800	Ea-23
SS____N	Eb-10
TA380/A	Ea-24
TA800/A	Ea-23
TH11-3	Eb-24
TH2-10-3PH	Ea-27
TH2-11EK	Ea-29
TH2-11EK	Ea-29
TH2-11EL	Ea-29
TH2-11EL-1	Ea-29
TH2-11ES	Ea-29
TH2-11ES-1	Ea-29
TH2-11M-10	Ea-29
TH2-11M-12	Ea-29
TH2-11M-16	Ea-29
TH2-11M-20	Ea-29
TH2-11M-24	Ea-29
TH2-11M-32	Ea-29
TH2-11M-4	Ea-29
TH2-11M-6	Ea-29
TH2-11M-8	Ea-29
TH2-12NK-1012	Ea-29
TH2-12NK-1012	Ea-29
TH2-12NK-1620	Ea-29
TH2-12NK-1620	Ea-29
TH2-12NK-2432	Ea-29
TH2-12NK-2432	Ea-29
TH2-12NK-8	Ea-29
TH2-12NT-10	Ea-29
TH2-12NT-12	Ea-29
TH2-12NT-16	Ea-29
TH2-12NT-20	Ea-29
TH2-12NT-24	Ea-29
TH2-12NT-32	Ea-29
TH2-13-3PH	Ea-28
TH2-13EL-1	Ea-29
TH2-13ES-1	Ea-29
TH2-13ET	Ea-29
TH2-13M-10	Ea-29
TH2-13M-12	Ea-29
TH2-13M-16	Ea-29
TH2-13M-20	Ea-29
TH2-13M-24	Ea-29
TH2-13M-32	Ea-29
TH2-13M-8	Ea-29
TH2-9-1PE	Ea-26
TH2-9-3PH	Ea-26
TH3-2-12VDC	Ea-8
TH3E-110	Ea-12
TH3E-115	Ea-11
TH3E-EM3	Ea-9
TH3E-EM6-M	Ea-10
TH4-10	Ea-13
TH4-4U	Ea-14
TH4-7	Ea-13
TH4-8	Ea-13
TH4-9	Ea-13
TH4-9-1	Ea-13
TH4E-11	Ea-14
TH4E-11-TC	Ea-14
TH4E-11-TH	Ea-14
TH5-3	Ea-19
TH5-3-BM	Ea-19
TH6-10-EL-7	Ea-17
TH6-10-H06	Ea-17
TH6-10-H06	Ea-18
TH6-10-H08	Ea-17
TH6-10-H08	Ea-18
TH6-10-H10	Ea-17
TH6-10-H10	Ea-18
TH6-10-H13	Ea-17
TH6-10-H13	Ea-18

Part Number	Page
TH6-10-H16	Ea-17
TH6-10-H16	Ea-18
TH6-10-H19	Ea-17
TH6-10-H19	Ea-18
TH6-10-H25	Ea-17
TH6-10-H25	Ea-18
TH6-10-H32	Ea-17
TH6-10-H32	Ea-18
TH6-10-H38	Ea-18
TH6-10-H50	Ea-18
TH6-10-HL-9-2	Ea-18
TH6-10-P10	Ea-17
TH6-10-P10	Ea-18
TH6-10-P12	Ea-17
TH6-10-P12	Ea-18
TH6-10-P14	Ea-17
TH6-10-P14	Ea-18
TH6-10-P18	Ea-17
TH6-10-P18	Ea-18
TH6-10-P22	Ea-17
TH6-10-P22	Ea-18
TH6-10-P26	Ea-17
TH6-10-P26	Ea-18
TH6-10-P33	Ea-17
TH6-10-P33	Ea-18
TH6-10-P40	Ea-17
TH6-10-P40	Ea-18
TH6-10-P50	Ea-18
TH6-10-P60	Ea-18
TH6-6	Ea-15
TH6-7	Ea-16
TH6-7-30	Ea-16
TH6-7-55	Ea-16
TH7-12	Ea-20
TH7-13	Ea-20
TH7-14	Ea-21
TH7-15	Ea-21
TH8-800-BM	Ea-23
TH8E-380-BM	Ea-24
TH8E-480-BM	Ea-25
TH8E-530	Ea-22
TH8E-530-12VDC	Ea-22
TH8E-530-BM	Ea-22
TH8E-535-BM	Ea-22
TH8-LUS	Ea-24
TH8-LUS	Ea-25
TM160x2,5x20	Ea-7
TM250x2x40Z	Ea-8
TMG275x3x30	Ea-9
TMG350x3x30	Ea-10
TMG520x4x120	Ea-12
TMG520x4x40	Ea-11
UNC__	Eb-2
UPTH-11b-PW3	Ea-14
UPTH-22b	Ea-14
UPTS100	Ea-14
VERG	Eb-7
VURG	Eb-7
WKS	Eb-20
WRA	Eb-22
WRC	Eb-22
WRF	Eb-22
XARG	Eb-8
XRG	Eb-3
ZYLS___VZX	Eb-2

Parker's Motion & Control Technologies

At Parker, we're guided by a relentless drive to help our customers become more productive and achieve higher levels of profitability by engineering the best systems for their requirements. It means looking at customer applications from many angles to find new ways to create value. Whatever the motion and control technology need, Parker has the experience, breadth of product and global reach to consistently deliver. No company knows more about motion and control technology than Parker. For further information call free on 00800 27 27 5374.



AEROSPACE

Key Markets

- Aircraft engines
- Business & general aviation
- Commercial transports
- Land-based weapons systems
- Military aircraft
- Missiles & launch vehicles
- Regional transports
- Unmanned aerial vehicles

Key Products

- Flight control systems & components
- Fluid conveyance systems
- Fluid metering delivery & atomization devices
- Fuel systems & components
- Hydraulic systems & components
- Inert nitrogen generating systems
- Pneumatic systems & components
- Wheels & brakes



CLIMATE CONTROL

Key Markets

- Agriculture
- Air conditioning
- Food, beverage & dairy
- Life sciences & medical
- Precision cooling
- Processing
- Transportation

Key Products

- CO^2 controls
- Electronic controllers
- Filter driers
- Hand shut-off valves
- Hose & fittings
- Pressure regulating valves
- Refrigerant distributors
- Safety relief valves
- Solenoid valves
- Thermostatic expansion valves



HYDRAULICS

Key Markets

- Aerospace
- Aerial lift
- Agriculture
- Construction machinery
- Forestry
- Industrial machinery
- Mining
- Oil & gas
- Power generation & energy
- Truck hydraulics

Key Products

- Diagnostic equipment
- Hydraulic cylinders & accumulators
- Hydraulic motors & pumps
- Hydraulic systems
- Hydraulic valves & controls
- Power take-offs
- Rubber & thermoplastic hose & couplings
- Tube fittings & adapters
- Quick disconnects



PNEUMATICS

Key Markets

- Aerospace
- Conveyor & material handling
- Factory automation
- Life science & medical
- Machine tools
- Packaging machinery
- Transportation & automotive

Key Products

- Air preparation
- Brass fittings & valves
- Manifolds
- Pneumatic accessories
- Pneumatic actuators & grippers
- Pneumatic valves & controls
- Quick disconnects
- Rotary actuators
- Rubber & thermoplastic hose & couplings
- Structural extrusions
- Thermoplastic tubing & fittings
- Vacuum generators, cups & sensors

Parker



PROCESS CONTROL

Key Markets

- Chemical & refining
- Food, beverage & dairy
- Medical & dental
- Microelectronics
- Oil & gas
- Power generation

Key Products

- Analytical sample conditioning products & systems
- Fluoropolymer chemical delivery fittings, valves & pumps
- High purity gas delivery fittings, valves & regulators
- Instrumentation fittings, valves & regulators
- Medium pressure fittings & valves
- Process control manifolds



FILTRATION

Key Markets

- Food & beverage
- Industrial machinery
- Life sciences
- Marine
- Mobile equipment
- Oil & gas
- Power generation
- Process
- Transportation

Key Products

- Analytical gas generators
- Compressed air & gas filters
- Condition monitoring
- Engine air, fuel & oil filtration & systems
- Hydraulic, lubrication & coolant filters
- Process, chemical, water & microfiltration filters
- Nitrogen, hydrogen & zero air generators



FLUID & GAS HANDLING

Key Markets

- Aerospace
- Agriculture
- Bulk chemical handling
- Construction machinery
- Food & beverage
- Fuel & gas delivery
- Industrial machinery
- Mobile
- Oil & gas
- Transportation
- Welding

Key Products

- Brass fittings & valves
- Diagnostic equipment
- Fluid conveyance systems
- Industrial hose
- PTFE & PFA hose, tubing & plastic fittings
- Rubber & thermoplastic hose & couplings
- Tube fittings & adapters
- Quick disconnects



ELECTROMECHANICAL

Key Markets

- Aerospace
- Factory automation
- Life science & medical
- Machine tools
- Packaging machinery
- Paper machinery
- Plastics machinery & converting
- Primary metals
- Semiconductor & electronics
- Textile
- Wire & cable

Key Products

- AC/DC drives & systems
- Electric actuators
- Controllers
- Gantry robots
- Gearheads
- Human machine interfaces
- Industrial PCs
- Inverters
- Linear motors, slides and stages
- Precision stages
- Stepper motors
- Servo motors, drives & controls
- Structural extrusions



SEALING & SHIELDING

Key Markets

- Aerospace
- Chemical processing
- Consumer
- Energy, oil & gas
- Fluid power
- General industrial
- Information technology
- Life sciences
- Military
- Semiconductor
- Telecommunications
- Transportation

Key Products

- Dynamic seals
- Elastomeric o-rings
- EMI shielding
- Extruded & precision-cut, fabricated elastomeric seals
- Homogeneous & inserted elastomeric shapes
- High temperature metal seals
- Metal & plastic retained composite seals
- Thermal management

ENGINEERING YOUR SUCCESS.